

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

DRIVE TRANS OIL C4 SAE 10W DRIVE TRANS OIL C4 SAE 30

PRODUCT DESCRIPTION

Drive Trans Oil C4 SAE 10W and Drive Trans Oil C4 SAE 30 are blended from hydrocracked base stocks and carefully selected additive package to meet the requirements of General Motors Allison Division specifications for C4 heavy duty automatic and power shift transmission fluids. The products possess excellent oxidation stability, anti-wear, anti-rust & anti-foam characteristics.

Drive Trans Oil C4 fluids meet non-asbestos clutch friction tests & fluoroelastomer seal compatibility. The fluids are expected to provide trouble-free service & required drain period.

APPLICATION

Drive Trans Oil C4 SAE 10W and Drive Trans Oil C4 SAE 30 are recommended for use in all commercial power shift transmissions, & automatic transmissions for on-highway & off-highway service. Such hauling & cycling transmissions find wide applications in off-highway equipment such as dumpers, scrapers, crawler tractors, excavators, shovel loaders etc.

PERFORMANCE STANDARDS

**TES – 228 for Hydraulic Transmission Fluid
Type C4 of Detroit Diesel, Allison Division of
G.M., USA**

TYPICAL CHARACTERISTICS

SAE GRADE	10W	30
Kinematic Viscosity, cSt @ 40°C	37.23	90.67
Kinematic Viscosity, cSt @ 100°C	6.19	10.5
Viscosity Index	114	101
Flash Point, COC, °C, Min.	210	220
Pour Point, °C	-30	-24

Available Packs: Consult Your Valvoline Representative.

10/2021



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

