

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline GEO 15W40

PRODUCT DESCRIPTION

Valvoline GEO 15W40 has been specially formulated with premium quality base stocks and additive components to provide outstanding lubrication of engines running on Compressed Natural Gas (CNG) for vehicular applications. The ash content of the oil is optimized to control valve recession and reduce formation of 'hot-spots' that can lead to valve torching.

Valvoline GEO 15W40 also ensures excellent control on engine wear, deposits and enhanced protection to slider follower of valve train mechanism.

APPLICATIONS

Valvoline GEO 15W40 is approved by Cummins for use in Cummins B Series Gas Engines.

Also recommended for use in CNG engines of other makes for vehicular applications such as buses & trucks, delivery vans & other service fleets.

PERFORMANCE STANDARDS

CES 20074

API CF

PERFORMANCE BENEFITS:

- Excellent oxidation / nitration control.
- Enhanced protection to slider follower of valve train mechanism.

TYPICAL CHARACTERISTICS

Kinematic Viscosity, cSt @ 100°C	15.0
Viscosity Index	137
Flash Point, COC, °C	224
Pour Point, °C	-30
TBN, mg KOH/g	4.5

Available Packs: Consult Your Valvoline Representative.

01/2018



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

