

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline HLP 15

PRODUCT DESCRIPTION

Valvoline HLP 15 is specially formulated for use in hydraulic systems employing high performance pumps. It possesses excellent oxidation stability, water separation characteristics and high FZG rating. The product is further fortified with rust & foam inhibitors.

CHARACTERISTICS / APPLICATIONS

- Excellent film strength & anti-wear, properties to minimise wear in pumps, rings, valves, pistons, cylinders etc.
- Excellent water separation characteristics and air releasing property.
- Anti-foam properties ensure efficient functioning.
- High Viscosity index to ensure excellent viscosity characteristics under operating conditions.

Valvoline HLP 15 is recommended for use in hydraulic systems, high performance electro-hydraulic or numerically controlled systems, pumps & circulation oiling systems & enclosed gear boxes.

PERFORMANCE STANDARDS

DIN 51524 Part II

TYPICAL CHARACTERISTICS

Kinematic Viscosity@ 40°C,cSt	15.4
Viscosity Index	105
Flash Point, °C	180
Demulsibility Test, (40-40-0) ml, minutes	15

Available Pack: Consult your Valvoline Representative

03/2018



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

