

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Power Select Max 15W-40

PRODUCT DESCRIPTION

Valvoline Power Select Max 15W-40 Engine Oil is a blend of highly refined premium base oil with high viscosity index combined with a special additive package comprising of antioxidant, detergent and anti-wear agents. Unique boosters with premium Group II base oil accounts for excellent cold start protection minimizing valve train/pistons/ring liner wear and outstanding soot protection levels.

The Power Select Max Advantage

The advanced product technology offers a longer engine life, extended drain periods, advanced soot and deposit control ultimately taking engine durability to next level. The unique formulation offers good detergency and dispensability enabling excellent engine performance and greater load carrying ability.

PERFORMANCE PROFILE

- API CI-4/SL
- ACEA E7-08 Issue 2
- MB 228.3
- CES 20078
- Mack EO-M Plus
- Caterpillar ECF-2
- MAN 3275 & 271
- MTU Type 2
- Global DHD-1

APPLICATIONS

Valvoline Power Select Max 15W-40 Engine Oil is recommended for use in all naturally aspirated, Turbocharged (Incl EGR) diesel engines commissioned for Off-highway applications in construction and mining, marine, locomotive, fleet and long haul on-highway applications where API CI4 is the recommended grade.

TYPICAL CHARACTERISTICS

Kinematic Viscosity, cSt @ 40°C	114.0
Kinematic Viscosity, cSt @ 100°C	14.91
Viscosity Index	135
Flash Point, COC, °C	220
TBN, mg KOH/g	11.0
Pour Point, °C, max.	-33
CCS Viscosity @ -20°C, cP	6710

Available Packs: Consult your Valvoline Representative.

04/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

