

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Power Select Max Plus 15W-40

PRODUCT DESCRIPTION

Valvoline Power Select Max Plus 15W-40 Engine Oil is a blend of highly refined premium base oil to provide advanced lubricant performance in modern, low-emission diesel engines (Incl. EGR). Unique boosters with premium Group II base oil accounts for excellent cold start protection minimizing valve train/pistons/ring liner wear and class leading soot protection levels.

The Power Select Plus Advantage

The advanced product technology and state of the art additive chemistry strongly resists soot induced oil thickening and keeps the oil flow perfect for lubricating over longer periods. The formulation offers extended drain intervals, reduced oil filter restrictions, excellent thermo-oxidative stability and provides for outstanding performance even in extreme load conditions maximizing engine life.

PERFORMANCE PROFILE

- API CI-4 Plus/SL
- ACEA E7-08
- MB 228.3
- CES 20078
- Mack EO-M Plus
- Caterpillar ECF-2
- MAN 3275
- MTU Type 2
- Renault RLD-2
- Volvo VDS 3

APPLICATIONS

Valvoline Power Select Max Plus 15W-40 Engine Oil is recommended for use in all naturally aspirated, Turbocharged (Incl EGR) medium size and heavy duty diesel engines commissioned for Off-highway applications in construction and mining, marine, locomotive, fleet and long haul on-highway applications where API CI4 Plus is the recommended grade.

TYPICAL CHARACTERISTICS

Kinematic Viscosity, cSt @ 40°C	112.3
Kinematic Viscosity, cSt @ 100°C	15.00
Viscosity Index	135
Flash Point, COC, °C	226
TBN, mg KOH/g	11.4
Pour Point, °C, max.	-30
CCS Viscosity @ -20°C, cP	6550

Available Packs: Consult your Valvoline Representative.

04/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

