

# PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

## Valvoline Spindle Oil 12

### PRODUCT DESCRIPTION

Valvoline Spindle Oil 12 is a low viscosity lubricant blended from solvent extracted paraffinic base stock having inherent good oxidation stability. The product is further fortified with anti-oxidant, anti-wear, anti-rust and defoamant additives.

Valvoline Spindle Oil 12 has been specially developed for modern high speed spindles in machine tools & textile spinning machines.

### CHARACTERISTICS / APPLICATIONS

- Excellent rust and corrosion protection, wear resistance, oxidation resistance, demulsibility and anti-foam characteristics.
- Provides superior lubrication for use in high-speed textile and machine tool spindle bearings.
- Also recommended for use in hydraulic systems and other applications requiring low viscosity non-anti-wear lubricants.

### PERFORMANCE BENEFITS

- Reduce wear of components due to excellent load carrying capability.
- Longer service life because of improved oxidation stability.
- Excellent prevention against rust and corrosion.
- Because of low viscosity and good thermal stability maintains normal operating temperature.

### TYPICAL CHARACTERISTICS

|                                 |       |
|---------------------------------|-------|
| Specific Gravity @ 29.5 °C      | 0.853 |
| Kinematic Viscosity, cSt @ 40°C | 11.6  |
| Viscosity Index                 | 97    |
| Flash Point, COC, °C, min.      | 150   |
| Pour Point, °C                  | -15   |
| Rust Test D665, A&B, 24 hrs.    | Pass  |

**Available Pack:** Consult your Valvoline Representative

3/2017



Valvoline Cummins Pvt. Ltd.  
A Joint Venture Company of  
Valvoline International Inc., USA  
& Cummins India Ltd.  
3<sup>rd</sup> Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003  
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299  
Visit us at: [www.valvolinecummins.com](http://www.valvolinecummins.com)

