

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline WTGO Special 460

PRODUCT DESCRIPTION

Valvoline WTGO Special 460 is a high performance lubricating fluid specially designed for use in wind turbine gearboxes operating under wide range of operating conditions and extreme temperatures.

The combination of highly refined mineral base oils and selected additive chemistry makes Valvoline WTGO Special 460 capable of providing wear protection, clean gear and oxidation control. In addition, it also provides extended performance against corrosion, foam and micro-pitting.

CHARACTERISTICS / APPLICATIONS

Valvoline WTGO SPECIAL 460 is suitable for wind turbine transmissions designed by Winergy, Hansen, Eickoff, Bosch Rexroth Getriebetechnik (formerly Lohmann & Stolterfoth), Jahnel-Kestermann & Metso Drive.

PERFORMANCE STANDARDS

AGMA 9005-E02
US Steel 224
DIN 51517 Part 3

PERFORMANCE BENEFITS

- Consistently strong micropitting performance as specified by Flender AG and Winergy.
- Clean gear performance under conditions of high temperature and oxidation.
- Excellent phosphorus retention, ensuring extended wear protection.
- Low chlorine content
- Extended corrosion and foam performance.
- Resistance from bearing fatigue.

TYPICAL CHARACTERISTICS

ISO VG

Kinematic Viscosity, cSt @ 40°C
Kinematic Viscosity, cSt @ 100°C
Viscosity Index
Flash Point, COC, °C, min.
Pour Point, °C
Rust Test D665, A&B, 24 hrs.

460
459.58
30.58
95
268
-6
Pass

Available Pack: Consult Your Valvoline Representative.

7/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

