

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline BB EPL2 Grease

Product Description

Valvoline BB EPL2 Grease is a premium quality lithium base Grease suitable for lubrication over wide temperature range of 20°C to 120°C characterized by its high dropping point, excellent oxidation stability and very good EP characteristics. In addition Valvoline BB EPL2 Grease has good adhesion characteristics, high resistance to corrosion excellent chemical stability and good pumpability.

Performance Benefits

- ✓ Excellent water resistance
- ✓ Very good EP characteristics
- ✓ Good mechanical stability
- ✓ Low consumption as it stays longer
- ✓ Excellent Lubrication in both High and Low temperature conditions.

APPLICATIONS

Its good pumpability characteristics make it specially suitable for use in centralized lubrication systems of large industrial units. It is also recommended for wide range of industrial applications where high temperatures are encountered. It is ideal for steel plant applications such as continuous casters, coupling, oscillators, run out rolls, blowers etc. It is also suitable for mining industries for applications such as rock crushers, conveyor drilling machinery as well as rotary kiln in sponge iron industry. Also, ideal for applications where equipment comes in contact with water.

PERFORMANCE STANDARDS

Meets IS 7623, Lithium Base EP 2

Meets IPSS:1-09-005 Steel Plants

TYPICAL CHARACTERISTICS

NLGI Grade	2
Type of Soap	Lithium
Texture	Smooth & Buttery
Color	Dark Brown
Worked Penetration (60 Strokes) @ 25°C	280
Drop-Point, °C, min.	180
Rust Tests, D-1743	Pass
Four ball wear scar dia, mm, max.	0.6
Four ball wear load, Kg., min.	200
Timken OK Load, Kg., min.	20

Available Packs: Consult Your Valvoline Representative.

8/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

