
PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Koolant All Weather HD- RTU

Product description

Valvoline Koolant All Weather HD RTU coolant is a carboxylate formulation with a service life of up to five years or 3,00,000 Kms / 3000 Hrs. It incorporates state-of-the-art organic acid technology in an ethylene glycol base for protection of all cooling system metals including aluminum.

Valvoline Koolant – All Weather HD RTU is a balanced formulation developed specially for Indian condition that has both warm as well as moderately cold climate.

Valvoline Koolant - All Weather HD RTU contains no phosphates, silicates, borates, nitrates, amines and nitrites. Its universal formulation meets the phosphate-free requirements of European manufacturers and the silicate free requirement of Asian manufacturers.

Valvoline Koolant - All Weather protects modern engine components from boiling and provides excellent freeze protection. It contains a high quality defoamer and will not harm gaskets, hoses, plastics or original vehicle paint

Applications

Recommended for use in radiators of all On-Highway (commercial vehicles, tractors, passenger cars, MUVs and SUVs) and Off-Highway applications (Construction, Mining and Powergen).

Performance specifications

JIS K-2234 Class2

ASTM D3306

SAE J 1034, J814, J1941

TMC of ATA RP-302B

Performance Benefits

- Protection against corrosion to cooling system metals including aluminium.
- Prevents hot weather boil-overs and cold weather freez-ups.
- Does not harm non-metallic components like gaskets, hoses etc.
- Environmental friendly.

Directions for Use

- Drain and flush cooling system with water.
- Check system for leakages, if any.
- Top up periodically with Valvoline Koolant - All weather up to maximum mark on the expansion bottle.



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com



PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Typical Properties

Color	Green
Sp. Gravity @ 16° C	1.112
pH	8.6
Boiling Point, °C	108
Freeze Point, °C	-36

Aluminum Water Pump Tests		
ASTM D2809 Pump Cavitation (Extended Test)		
Test Period	Results	Specification
100 hours	9	8

ASTM cavitation corrosion rating: 10 - perfect 1 - perforated

Typical ASTM Corrosion Test Results			
Test	Weight Loss, Mg/Specimen		ASTM Method
	Maximum Limit	Actual	
Glassware Corrosion			D1384
Copper	10	2	
Solder	30	6	
Brass	10	3	
Steel	10	0	
Cast Iron	10	0	
Aluminum	30	0	
Simulated Service			D2570
Copper	20	2	
Solder	60	5	
Brass	20	1	
Steel	20	1	
Cast Iron	20	0	
Aluminium	60	0	
Hot Surface Corrosion			D4340
	mg/cm ² /wk		
Specimen weight loss	1	0.1	

Available Packs: Consult Your Valvoline Representative

8/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

