

44 GREASE

Silicone oil and special lithium soap based grease

Product Description

ASV®44 grease is based on a special highly heat stable silicone fluid and soap thickener along with additives to impart extreme pressure properties and prevent high temperature oxidation. This grease is capable of withstanding very high temperatures and maintains its consistency. It is inherently inert and possesses a high degree of shear stability and resistance to oxidation. It does not dry out, harden or melt even after long-term exposure to high temperatures and has very good resistance to water, steam, humid environments and chemicals. It is very effective for lubrication of bearings under light to moderate loads and metal and plastic surfaces.

Applications

For lubrication of rolling element bearings operating under light to moderate loads as in oven fans, exhaust motors, kiln pre-heaters, oil burners, textile slashers and driers, conveyors, washing machines, air conditioners, domestic appliances, data processing equipment, aircraft engines, radiator cooling fans, electrical motors, vacuum machines and plastic components.

Benefits

- Extremely wide service temperature range of -40°C to +204°C
- Exceptionally good oxidation resistance
- High shear stability
- Does not thin out at high temperatures
- Stable, chemically inactive and inherently more inert than petroleum based products
- Resistant to ageing, water, moisture, steam, humidity and corrosive environments
- Non toxic and non staining
- Low evaporation and does not volatilize at higher temperatures
- Safe for use on metal, plastic and rubber components (except those made of silicone)

Directions for Use

Use as supplied. Never dilute or mix with other oil or grease. Apply on all clean sliding surfaces by normal greasing methods i.e. by brush, grease gun or dispense via centralized lubrication systems.

44 GREASE

TECHNICAL PROPERTIES			
Parameter	Value	Unit	Standard
Type	Silicone & special lithium soap based grease		
Appearance	Smooth grease		
Base oil	Silicone		
Thickener	Lithium		
Color ¹	Light tan		
Penetration, worked	265-295	mm/10	ASTM 217
NLGI consistency	2	Class	DIN 51 818
Density, @ 25°C	0.95 - 1.05	g/cm ³	
Drop point	+ 210	°C	ASTM D 566
Service temperatures	-40 to + 204	°C	
SKF-Emcor method	0/0		DIN 51 802
Degree of corrosion	No corrosion		
Water resistance, static evaluation	0-90		DIN 51 807 pt.1
Oil separation, standard test, 168 h, 40° C	Lesser than 5 %		DIN 51 817
Rubber seal compatibility test	Pass, no swelling		
1. Minor color variation of the same product but of different batches could be possible. However the lubrication values remain unchanged.			

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Available Packaging

1 kg, 5 kg

Shelf Life

36 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE
PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.