

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Freez 68

PRODUCT DESCRIPTION

Valvoline Freez 68 is blended from specially selected lube base stocks to provide low pour point, good chemical stability & ready solubility in liquefied refrigerants.

These oils are straight mineral type having inherent resistance to oxidation and deposit formation.

APPLICATIONS

Valvoline Freez 68 is recommended for lubricant in wide range of compressors. The product can be used in conventional refrigerants, except sulphur dioxide, in both reciprocating & rotary compressors.

The product is also suitable in properly designed and maintained refrigeration systems when evaporator temperatures are lower than the pour point of the oil.

PERFORMANCE BENEFITS

- High fluidity at low temperature.
- Reduce deposit formation thus keeping compressor parts clean.
- Ensure high condenser efficiency.
- Longer service life due to good oxidation & thermal stability.

TYPICAL CHARACTERISTICS

ISO VG	68
Kinematic Viscosity, cSt @ 40°C	68
Flash Point, COC, °C	212
Pour Point, °C	-36

Available Packs: Consult your Valvoline Representative.

5/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

