

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline HVI Special Oils VG 68

PRODUCT DESCRIPTION

Valvoline HVI Special Oils are formulated from hydrocracked base stocks with inherent oxidation and thermal stability. The products are further fortified with antioxidant, antirust, antifoam and anti-wear additives, plus a special shear stable viscosity index improver which assists in maintaining viscosity under continuous use & severity of operation. The product has been specially designed for long drain intervals even at most severe operating conditions.

Tested in Indian operating conditions with proven reliability and long service life.

APPLICATIONS

Valvoline HVI Special Oils are recommended for all hydraulic applications including critical systems in industrial and mobile equipment using high pressure vane, gear & piston pumps. Valvoline HVI Special Oils are suitable for use in various types of earthmoving equipment.

Valvoline HVI Special Oils are recommended for all kinds of hydraulic systems & equipments working onsite which are subjected to extreme temperature variation.

Valvoline HVI Special Oils are specially recommended for Excavators and other civil engineering, agriculture, marine, transport and other industrial application.

PERFORMANCE STANDARDS

Dennison HF-0, HF-1, HF-2
Eaton Brochure 03-401-2010
DIN 51524 Part II
MAG IAS P-68, P-69, P-70
Bosch Rexroth 90240 Basic Level Approval
US Steel 127

PERFORMANCE BENEFITS

- A shear-stable viscosity modifier ensures correct viscosity at wide operating temperatures.
- Wide temperature range of operation.
- Excellent thermal stability to prevent formation of sludge even at high operating temperatures.
- Excellent protection against wear insuring maximum equipment life and lower down time.
- Excellent resistance to oxidation ensuring long service life of fluid.
- Good demulsibility ensuring rapid water separation.
- Good Anti-Foam & Air release properties
- Good protection against rust & corrosion.
- Long service life of equipment
- Extended drain intervals.

TYPICAL CHARACTERISTICS

ISO VG	68
Kinematic Viscosity, cSt @ 40°C	68
Viscosity Index	125
Flash Point, COC, °C, min.	220
Pour Point, °C, max.	-30
FZG Test, Pass Stages	12
Rust Test D665, A&B, 24 hrs.	Pass
Emulsion Test, D-1401, 40-37-3, minutes, max.	15

Available Pack: Consult Your Valvoline Representative.

12/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.

3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

