



**THE ORIGINAL
ENGINE OIL**

AMERICA'S FIRST MOTOR OIL BRAND



POWERING SEAMLESS OPERATIONS

Opal HT 220 Grease



© 2024 Valvoline Global Operations | TM Trademark, Valvoline Global Operations





VALVOLINE OPAL HT 220 GREASE

Valvoline OPAL HT 220 Grease is made from highly refined base oils and special additives. This grease is based on calcium sulphonate complex thickener and has high water resistance, high load carrying ability, high drop point and excellent mechanical, thermal, shear & oxidation stability. It possesses very good EP properties and improves component life due to low wear & tear.

Valvoline OPAL HT 220 Grease is suitable for use in centralized grease stations of steel plants and heavy engineering industries and rolling mills. It is also used in a wide variety of applications such as in paper mills, automotive, mining equipment, earth moving equipment and general machinery.

BENEFITS

- High load carrying capacity
- Excellent water resistance properties
- Superior thermal & oxidation stability
- Excellent mechanical and shear stability
- Extended re-lubrication period

APPLICATION

- For high load and slow speed applications in Steel Plants
- Sponge Iron Plants
- Kilns and Coolers
- Paper Mills
- Automotive, agricultural, construction & mining etc

TYPICAL CHARACTERISTICS

Test	Typical Values	Test Methods
Appearance	Smooth	Visual
Consistency, Penetration at 25+/-0.5°C	-	ASTM D 217
60 strokes	280-310	-
100K strokes	Difference not more than 20 units from 60 strokes	-
Color	Blue	Visual
Drop Point, °C, min	300	ASTM D 2265
Heat stability at 100°C for 30 hrs. loss of wt, max	3	ASTM D 6184
Resistance to water wash out at 80°C, % loss by mass, max	5	ASTM D 1264
Copper Strip Corrosion at 100°C for 24 hours	1b	ASTM D 4048
Four ball weld load, kg, min	315	ASTM D 2596
Type of soap	Calcium Sulphonate Complex	-

Available Packs: Consult Your Valvoline Representative.