

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Rock Drill 100

PRODUCT DESCRIPTION

Valvoline Rock Drill 100 specially formulated high performance lubricants for reciprocating and rotary pneumatic tools. These are blended from premium quality lube base stocks and are incorporated with anti-wear, extreme pressure and tackiness additives to provide load bearing, adhesiveness characteristics to the product.

The incorporation of special compounding agents ensures that the oil mixes with condensed moisture resulting in the formation of a tenacious oil-film without any obnoxious odour when operated in confined space. It has high load-carrying capacity to protect against wear and seizure of sliding metal surfaces under heavy or shock-load conditions.

APPLICATIONS

Valvoline Rock Drill 100 are recommended for the lubrication of pneumatically operated rock drills, jackhammers, riveters, chippers, pavement breakers, hoists, etc. These are also suitable for use in small in-plant pneumatic tools and motors such as grinders, filing tool, drills, tappers, screwdrivers and impact wrencher.

PERFORMANCE BENEFITS

- Good EP and anti-wear properties extend equipment life.
- Emulsifying and formation of tenacious protective film ensures lubrication even in presence of moist air.
- Protection against rust and corrosion.
- Good adhesiveness ensures reduced oil consumption.

TYPICAL CHARACTERISTICS

Kinematic Viscosity, cSt @ 40°C	98.78
Kinematic Viscosity, cSt @ 100°C	11.15
Viscosity Index	105
Flash Point, COC, °C, Min.	230
Pour Point, °C	-15
Rust Test (A&B, 24 hrs)	Pass

Available Packs: Consult your Valvoline Representative.

05/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector- 54, Gurgaon, Haryana – 122 003, India
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

