

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline ThermoSynth

PRODUCT DESCRIPTION

Valvoline ThermoSynth is synthetic base heat transfer fluid. It is fortified with selected chemical additives, which provide excellent thermal and oxidation stability to ensure longer life.

Valvoline ThermoSynth has wide operating range of -15°C to 305°C and in extreme cases at 310°C . Unlike mineral base products, it does not crack at high temperature forming carbon deposits and insoluble matter. Negligible deposits means better heat transfer rate. Insoluble matter/sludge is kept in fine dispersion, which increases the overall life of oil.

Valvoline ThermoSynth has low freezing point (below -20°C), which ensures good pumpability at low temperatures and smooth operations. Its low volatility reduces oil consumption during service. Due to special AFR (anti free radical) and minimum low boilers formation characteristics, Valvoline ThermoSynth has more life than conventional mineral base heat transfer oils.

APPLICATIONS

Valvoline ThermoSynth is recommended for well-designed indirect heat transfer system having high bulk operating temperatures. It gives excellent performance in high temperature heat transfer system. It has wide range of application in textile, pharmaceuticals, plywood, chemical and other processing industries, where there is indirect heating is an enclosed system.

PERFORMANCE BENEFITS

- High thermal and oxidation stability, less degradation, higher drain period.
- Improved heat transfer rate.
- Excellent overall stability.
- Low volatility results in less oil consumption.
- Non-corrosive, non-toxic.
- Ability to withstand at higher temperature.
- Low temperature pumpability and circulation.
- Overall reliable, cost effective performance even on continuous running.

TYPICAL CHARACTERISTICS

Appearance	Clear & Bright
Specific Gravity @ 29.5°C	0.862
% Water Content	< 0.01
Kinematic Viscosity @ 40°C , cSt	18.4
Copper Strip Corrosion @ 100°C , 3 Hrs.	1a
Pour Point, $^{\circ}\text{C}$	-36
Flash Point, COC, $^{\circ}\text{C}$	184
Fire Point, $^{\circ}\text{C}$, min.	200
Coefficient of thermal expansion	0.0096/ $^{\circ}\text{C}$

Available Packs: Consult your Valvoline Representative.

3/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector 54 – 122 003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

