

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

VALVOLINE OPAL HT 220 GREASE

PRODUCT DESCRIPTION

Valvoline OPAL HT 220 Grease is made from highly refined base oils and special additives. This grease is based on calcium sulphonate complex thickener and has high water resistance, high load carrying ability, high drop point and excellent mechanical, thermal, shear & oxidation stability. It possesses very good EP properties and improves component life due to low wear & tear.

Valvoline OPAL HT 220 Grease is suitable for use in centralized grease stations of steel plants and heavy engineering industries and rolling mills. Also, applicable for use in a wide variety of applications such as in paper mills, automotive, mining equipment, earth moving equipment and general machinery.

BENEFITS

- High Load carrying capacity
- Excellent water resistance properties
- Superior thermal & oxidation stability
- Excellent mechanical and shear stability
- Extended Re-Lubrication Period

APPLICATION

- For high load and slow speed applications in Steel Plants
- Sponge Iron Plants
- Kilns and Coolers
- Paper Mill applications
- Automotive, agricultural, construction & mining etc

TYPICAL CHARACTERISTICS

	Test	Typical values	Test Methods
1	Appearance	Smooth	Visual
2	Consistency, Penetration at 25+/-0.5 Deg C		ASTM D 217
	60 Strokes	280-310	
	100K Strokes	Difference not more than 20 units from 60 Strokes	
3	Color	Blue	Visual
4	Drop Point, Deg C, min	300	ASTM D 2265
7	Heat stability at 100°C FOR 30 Hrs. Loss of wt, max	3	ASTM D 6184
8	Resistance to water wash out at 80 deg C, % loss by mass, max	5	ASTM D 1264
9	Copper Strip Corrosion at 100°C for 24 hours	1b	ASTM D 4048
10	Four ball weld load, kg, min	315	ASTM D 2596
11	Type of Soap	Calcium Sulphonate Complex	

Available Packs: Consult Your Valvoline Representative.

8/2023



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

