

PRODUCT INFORMATION

A PRODUCT OF VALVOLINE CUMMINS PVT. LTD.



Valvoline AW EHVI 46 & 68

PRODUCT DESCRIPTION

Valvoline AW EHVI Oils are formulated from hydrocracked base stocks with inherent oxidation and thermal stability. The products are further fortified with antioxidant, antirust, antifoam and anti-wear additives, plus a special shear stable viscosity index improver which assists in maintaining viscosity under continuous use & severity of operation.

APPLICATIONS

Valvoline AW EHVI Oils are recommended for all hydraulic applications including critical systems in industrial and mobile equipment using high pressure vane, gear & piston pumps.

Valvoline AW EHVI Oils are suitable for use in various types of earthmoving equipment and are recommended for all kinds of equipment working onsite which are subjected to extreme temperature variation.

Valvoline AW EHVI Oils are specially recommended for Excavators, other civil engineering, agriculture, marine, transport and other industrial applications.

PERFORMANCE STANDARDS

- Dennison HF-0, HF-1, HF-2
- Eaton Brochure 03-401-2010
- DIN 51524 Part III
- MAG IAS P-68, P-69, P-70
- Bosch Rexroth RDE90240 Basic Level Approval
- US Steel 126,127,136
- ISO 11158 HM

PERFORMANCE BENEFITS

- A shear-stable viscosity modifier ensures correct viscosity at operating temperatures.
- Wide temperature range of operation.
- Excellent anti-wear properties.
- Excellent resistance to oxidation.
- Good demulsibility.
- Good protection against rust & corrosion.
- Long service life.

TYPICAL CHARACTERISTICS

VALVOLINE AW EHVI OILS- ISO VG GRADE:	46	68
Kinematic Viscosity, @ 40°C cSt	46	68
Viscosity Index, min	152	151
Flash Point, COC, °C	224	210
Pour Point, °C	-33	-33
FZG Test, Pass Stages	11	12
Rust Test D665, A&B, 24 hrs.	Pass	Pass
Emulsion Test, D-1401, 40-40-0, minutes	15	15

Available Packs: Consult Your Valvoline Representative.

04/2019



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of Valvoline International Inc., USA & Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.co

