

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline XLD Plus 10W

PRODUCT DESCRIPTION

Valvoline XLD Plus 10W is blended from high refined base stocks incorporating carefully selected detergent, dispersant and anti-oxidant additives to give the desired performance.

APPLICATION

Valvoline XLD Plus 10W is recommended for use in naturally aspirated and turbo-charged heavy duty diesel engines of heavy vehicles, earthmoving equipments operating under low ambient temperatures. The product is also recommended as hydraulic fluid type C2 specification of Detroit Diesel, Allison Division of General Motors, Komatsu and Caterpillar transmission systems.

PERFORMANCE STANDARDS

API	CD
BIS	13656 : 1993, E-DL2
US Military	MIL-L-45199B
Caterpillar	Series III
General Motors	
Allison Division,	C2 Type Fluids

TYPICAL CHARACTERISTICS

Kinematic Viscosity @ 100°C, cSt	6.4
Viscosity Index	105
Flash Point, COC, °C, Min.	210
Pour Point, °C	-30
TBN, mg KOH/g	7.0

Available Packs: Consult Your Valvoline Representative.

7/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

