

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

ZEREX NF EX LIFE COOLANT RTU

Zerex NF EX Life coolant RTU contains unique Valvoline patented technology* and is specially developed for heavy duty engines. It incorporates organic acid technology to protect diesel engines from liner pitting and hard water scale deposits. The silicate and nitrite free extended life chemistry protects all cooling system metals from corrosion including aluminum. It is pre-diluted (50:50) and ready to use glycol-based coolant. **Zerex NF EX Life coolant RTU** can also be used in gasoline engines, stationary power, marine, natural gas and light duty applications.

Zerex NF EX Life coolant RTU provides up to 10 years / 1,000,000 Kms / 20,000 hours of service without the need for extenders due to non-depleting organic acid technology. It is backward compatible for all cooling systems using OAT coolants. **Zerex NF EX Life coolant RTU** offers enhanced protection for aluminum cooling system components.

Zerex NF EX Life coolant RTU is compatible with major long life and conventional brands of ethylene glycol-based coolant. However, long life characteristics may be diminished by mixing with light duty or conventional fully formulated coolants. Valvoline recommends filling and always topping off **Zerex NF EX Life coolant RTU**.

Zerex NF EX Life coolant RTU is an approved formula for the following specifications:

ASTM D6210	Cummins CES 14603 Registered
Jenbacher Technical Instruction 1000-0200	Cummins CES 14439 Registered
(All engine types and all versions)	Deutz DQC-CB14

Zerex NF EX Life coolant RTU is formulated to meet or exceed the following specifications:

ASTM D3306	Isuzu	Paccar
ASTM D6210	JIS K 2234	Peterbilt
Case New Holland	John Deere	Scania
CAT EC-1	Komatsu	Siemens Wind Turbines
Detroit Diesel DFS93K217ELC	Link Belt	Terex
Federal Spec A-A-970a	Mack Man 324 SNF	Thermo King
Fiat Chrysler MS 12106	Mercedes-Benz DBL 7700	TMC OF ATA RP-329B
Ford Europe WSS-M97B44-D	MTU	TMC OF ATA RP-338
Ford WSS-M97B57-A1 and A2	Navistar MPAPS B-1 Type IIIA	Volvo Construction Equipment
Freightliner 48-22880	Nitrite Free European OEMs	VW

*US Patent 9328278 and Foreign Patents Pending

Characteristics	ASTM Method	Typical values
Color	-	Yellow
Density at 20 °C, g/cc	D4052	1.076
Freezing point, °C	D1177	-36
Boiling point, °C	D1120	128**
pH at 25°C	D1287	9.4
Reserve alkalinity, ml	D1121	7.1

**Boiling point shown using conventional 15 psi radiator cap.



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com



PRODUCT INFORMATION

A Product of Valvoline Cummins Pvt. Ltd.



Typical ASTM Corrosion Test Results			
	Weight Loss, Mg/Specimen		
Test	Maximum Limit	Actual	ASTM Method
Glassware Corrosion			D1384
Copper	10	1	
Solder	30	3	
Brass	10	1	
Steel	10	1	
Cast Iron	10	0	
Aluminum	30	1	
Simulated Service			D2570
Copper	20	-1	
Solder	60	-1	
Brass	20	0	
Steel	20	0	
Cast Iron	20	0	
Aluminium	60	-1	
Hot Surface Corrosion			D4340
mg/cm²/wk			
Specimen weight loss	1	0.1	
John Deere Coolant Cavitation	SRI Test 66-39-0302-5	Passed	D7583

Zerex NF EX Life coolant RTU		
Aluminum Water Pump Tests		
ASTM D2809 Pump Cavitation (Extended Test)		
Test Period	Results	Specification
100 hours	10	8

ASTM cavitation corrosion rating: 10 - perfect 1 - perforated

Available Packs: Consult Your Valvoline Representative

3/2022



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

