

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline AGMA EP Gear Oil 150 / 220 / 320 / 460

PRODUCT DESCRIPTION

Valvoline AGMA EP Gear Oils are lead-free extreme pressure type industrial gear lubricants. The oils are blended from high quality base stocks & contain special sulphur-phosphorus compounds to impart antiwear and extreme pressure properties.

CHARACTERISTICS / APPLICATIONS

- Extreme pressure gear oil formulated for use in industrial gear drives operating under high load, shock load and other severe service conditions.
- Excellent high temperature stability.
- Good water separation characteristics makes these gear oils an excellent choice for use in gear lubrication systems where high water ingress is encountered.
- Provides high temperature oil film thickness, rust and corrosion control, shear stability, viscosity control and lubricity.
- Also recommended for lubrication of oil lubricated flexible couplings, heavily loaded bearings and chains.

PERFORMANCE STANDARDS

AISE 224
DIN 51517 Part 3
ISO 12925-1 Type CKD
AGMA 9005-E02 (EP)
David Brown S1.53.101 E

PERFORMANCE BENEFITS

- High load carrying ability.
- Excellent prevention against rust & corrosion.
- Reduced tendency to foam.
- Resistance to deposit & germ formation.
- Non-corrosive to ferrous & non-ferrous metals at elevated temperatures.

TYPICAL CHARACTERISTICS

ISO VG

Kinematic Viscosity, cSt @ 40°C

Viscosity Index

Flash Point, COC

Pour Point, °C

FZG Test, Pass Stages

Rust Test D665, A&B, 24 hrs.

VALVOLINE AGMA EP GEAR OILS

150	220	320	460
150	220	320	460
95	95	97	96
232	238	240	246
-21	-18	-12	-12
12	12	12	12
Pass	Pass	Pass	Pass

Available Packs: Consult your Valvoline Representative.

1/2020



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

