

Castrol Hyspin VG Range

Hydraulic Oils

Description

The Castrol Hyspin™ VG hydraulic oil range is based upon highly refined mineral oil enhanced with rust and oxidation inhibitors.

Application

Castrol Hyspin VG has been specially formulated to provide outstanding protection against rust and oxidation while demonstrating good lubricity. Castrol Hyspin VG is also referred to as a "R & O" (Rust and Oxidation) hydraulic oil. This range is designed for use in hydraulic systems which do not need anti-wear performance but where a degree of rust and oxidation resistance is desirable. It is also suitable for pumps which contain silver-plated components. The Hyspin VG range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers.

Hyspin VG is classified as follows:

- DIN 51502 classification - HL
- ISO 6743/4 - Hydraulic Oils Type HL

Advantages

- Good thermal and oxidative stability leads to longer operating life, reduction in lubricant costs and minimises deposit formation giving a cleaner system.
- Good protection of yellow metal and ferrous components helps maintain and prolong equipment life.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.

Typical Characteristics

Name	Method	Units	32	46	68
ISO Viscosity Grade	-	-	32	46	68
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	870	880	880
Kinematic Viscosity @ 40°C / 104°	ISO 3104 / ASTM D445	mm ² /s	32	46	68
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	5.4	6.8	8.7
Viscosity Index	ISO 2909 / ASTM D2270	-	95	95	>95
Pour Point	ISO 3016 / ASTM D97	°C/°F	-30 / -22	-30 / -22	-24 / -11
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	220 / 428	240 / 464	240 / 464
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	30/0	30/0	30/0
Air Release @ 50°C / 122°F	ISO 9120 / ASTM D3427	min	2	3	5

Subject to usual manufacturing tolerances.

Castrol Hyspin VG Range

14 May 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd Technopolis Knowledge Park PO Box. 19411, 1st Floor Mahakali Caves Road Mumbai - 400 093 India
Toll Free: 1800 222100 / 1800 2098100, 022-27839800 Email: customer-care.india@castrol.com
www.castrol.com/industrial