

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline HLP 32 / 46 / 68

PRODUCT DESCRIPTION

Valvoline HLP 32 / 46 / 68 are specially formulated for use in hydraulic systems employing high performance pumps. They possess excellent oxidation, demulsibility characteristics & high FZG rating. The products are further fortified with rust & foam inhibitors.

CHARACTERISTICS / APPLICATIONS

- Valvoline HLP oils have good filterability
- Excellent film strength & anti-wear, properties to minimize wear in pumps, rings, valves, pistons, cylinders etc.
- High demulsibility.
- Anti-foam properties ensure efficient functioning.
- High Viscosity index to ensure excellent viscosity characteristics under varied operating conditions.

Valvoline HLP 32 / 46 / 68 are recommended for use in hydraulic systems, high performance electro-hydraulic or numerically controlled systems, pumps & circulation oiling systems & enclosed gear boxes.

PERFORMANCE STANDARDS

Dennison HF-0, HF-1, HF-2
Eaton Brochure 03-401-2010
DIN 51524 Part II
MAG IAS P-68, P-69, P-70
Bosch Rexroth RDE90240 Basic Level Approval
US Steel 126, 127, 136
ISO 11158 HM
David Brown

TYPICAL CHARACTERISTICS

ISO VG

Kinematic Viscosity, cSt @ 40°C

Viscosity Index

Flash Point, COC, °C

Pour Point, °C

FZG Test, Pass Stages

Rust Test D665, A&B, 24 hrs.

Emulsion Test, D-1401, 40-40-0, minutes

VALVOLINE HLP OILS

32	46	68
32	46	68
105	105	103
214	218	232
-24	-24	-24
10	10	12
Pass	Pass	Pass
10	10	15

Available Pack: Consult your Valvoline Representative

03/2018



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

