

TASK 4: Network Intrusion Detection System

Comprehensive Implementation Report Engineering & Deployment Guide

This deployment document provides a detailed blueprint for fulfilling all engineering requirements specified in **Task 4: Network Intrusion Detection System**. It covers environment layout, tool compilation, customized signature creation, zero-tolerance log monitoring, automated adaptive threat response active containment, and centralized visualization layers.

1. NIDS Setup & Installation (Snort Framework)

For this implementation, **Snort 3** (the next-generation network intrusion detection system) is selected due to its multi-threaded architecture, modular design, and advanced protocol inspection capabilities. The target implementation environment relies on an upstream network TAP or a configured SPAN mirror switch port directing raw layer-2 frames to the inspection interface (eth1).

Prerequisites & Dependency Toolchain Installation

Before installing Snort, required build dependencies, DAQ (Data Acquisition library), and system pre-requisites must be provisioned:

```
# Update repositories and install foundational toolchain
sudo apt-get update && sudo apt-get install -y      build-essential      libpcap-dev
libpcre3-dev      libdummy-net-dev      bison      flex      zlib1g-dev      liblua5.1-
dev      libssl-dev      pkg-config      libhwloc-dev      cmake      libwlocate-dev
libsqlite3-dev      uuid-dev      libcmocka-dev      libnetfilter-queue-dev      libmnl-
dev      autotools-dev      automake      libtool

# Download and compile the LibDAQ abstraction layer
cd /usr/src
sudo wget https://github.com/snort3/libdaq/archive/refs/tags/v3.0.13.tar.gz
sudo tar -xvf v3.0.13.tar.gz && cd libdaq-3.0.13
sudo ./bootstrap && sudo ./configure && sudo make && sudo make install
sudo ldconfig
```

Compiling and Launching Snort 3

```
# Download source, unpack, build and verify Snort 3 engine
cd /usr/src
sudo wget https://github.com/snort3/snort3/archive/refs/tags/3.1.74.0.tar.gz
sudo tar -xvf 3.1.74.0.tar.gz && cd snort3-3.1.74.0
sudo ./configure_cmake.sh --prefix=/usr/local/snort
cd build && sudo make && sudo make install

# Verify successful installation framework initialization
/usr/local/snort/bin/snort -V
```

2. Configuration of Custom Rules & Alert Criteria

Signatures govern real-time detection matrices. A specialized system rules file (/usr/local/snort/etc/snort/rules/local.rules) handles active detection of suspicious connection anomalies, credential brute-forcing, and network layer reconnaissance exploits.

Production Rules Configuration Blueprint

```
# Define signature path inclusion in main configuration (/usr/local/snort/etc/snort/snort.lua)
ips =
{
    rules = [[
        include /usr/local/snort/etc/snort/rules/local.rules
    ]]
}
```

Custom Multi-Vector Detection Signatures

The following optimized signatures are engineered to identify reconnaissance scans, excessive payload thresholds, and standard credential attacks:

```
# 1. ICMP Network Reconnaissance Discovery Ping Detection
alert icmp any any -> $HOME_NET any (msg:"SECURITY-POLICY ICMP Sweep/Ping Scan Detected";
icode:0; itype:8; classtype:attempted-recon; sid:1000001; rev:1;)

# 2. Aggressive TCP Port Scanning Profiling Action
alert tcp any any -> $HOME_NET any (msg:"RECONNAISSANCE - TCP SYN Port Scan Attempt";
flags:S; detection_filter:track by_src, count 30, seconds 10; classtype:attempted-recon;
sid:1000002; rev:1;)

# 3. Critical Infrastructure Layer: Inbound SSH Force Authentication Profiling
alert tcp any any -> $HOME_NET 22 (msg:"EXPLOIT - SSH Brute Force Authentication Attempt";
flags:S,A; flow:to_server,established; detection_filter:track by_src, count 10, seconds
20; classtype:suspicious-login; sid:1000003; rev:1;)

# 4. Outbound Sensitive Data Exfiltration Attempt via Data Stream
alert tcp $HOME_NET any -> any 80 (msg:"DATA-EXFILTRATION - Outbound Credit Card String
Transfer"; flow:to_server,established; content:"4111-xxxx-xxxx-xxxx"; fast_pattern;
classtype:policy-violation; sid:1000004; rev:1;)
```

Operational Validation Note

Before launching operational production listeners, the integrity of newly written rules must be evaluated using the validation flag: /usr/local/snort/bin/snort -c /usr/local/snort/etc/snort/snort.lua --verify-rules

3. Continuous Traffic Monitoring Strategy

Persistent execution ensures the detection system processes frames on the designated sniffing network interface without interruption. Snort runs as a unprivileged background daemon, continuously streaming standardized structured telemetry outputs.

Continuous Monitoring Daemon Daemonization

To establish an enterprise-grade execution lifecycle, create a systemd configuration definition block mapped to the network interface card:

```
[Unit]
Description=Snort3 Network Intrusion Detection System Daemon
After=network.target

[Service]
Type=simple
User=root
ExecStart=/usr/local/snort/bin/snort -c /usr/local/snort/etc/snort/snort.lua -i eth1 -l /
var/log/snort -D -k none
Restart=on-failure
RestartSec=5

[Install]
WantedBy=multi-user.target
```

```
# Commit daemon initialization state parameters
sudo systemctl daemon-reload
sudo systemctl enable --now snort3.service
sudo systemctl status snort3.service
```

Active Watch Engine Logging Schema

Alert records append to the standardized JavaScript Object Notation (JSON) unified log format file: `/var/log/snort/alert_json.txt`. This structured event structure allows downstream parsers to read logs efficiently:

```

{
  "seconds": 1781285220,
  "action": "allow",
  "class": "attempted-recon",
  "msg": "RECONNAISSANCE - TCP SYN Port Scan Attempt",
  "src_addr": "192.168.1.145",
  "src_port": 49832,
  "dst_addr": "10.0.0.5",
  "dst_port": 443,
  "proto": "TCP",
  "pkt_num": 14205,
  "priority": 2,
  "sid": 1000002
}

```

4. Incident Response & Threat Mitigation Mechanisms

Detection alone is insufficient. When critical rules fire, an automated response script isolates the source attacker IP at the perimeter host firewall via dynamic IPtables routing hooks.

Active Containment Orchestration Model

Phase	Action Vector	Execution Context
1. Parse	Continuous Log Tail Process	Asynchronously monitors /var/log/snort/alert_json.txt for new events.
2. Evaluate	Threat Level Assessment	Extracts Target IP parameters if priority thresholds match Critical (1) or High (2).
3. Enforce	Automated Dynamic Blocking	Appends host route rules to the kernel layer netfilter table dropping communication packets.

Automated Defensive Integration Script

```
#!/usr/bin/env python3
import json
import subprocess
import time

log_file_path = "/var/log/snort/alert_json.txt"

def apply_host_quarantine(attacker_ip):
    # Check if rule already applied to avoid duplication
    check_cmd = f"sudo iptables -C INPUT -s {attacker_ip} -j DROP"
    result = subprocess.run(check_cmd, shell=True, capture_output=True)

    if result.returncode != 0:
        block_cmd = f"sudo iptables -A INPUT -s {attacker_ip} -j DROP"
        subprocess.run(block_cmd, shell=True)
        print(f"[ACTIVE RESPONSE] Quarantined Attacker IP Source: {attacker_ip}")

def tail_handler(file_object):
    file_object.seek(0, 2)
    while True:
        line = file_object.readline()
        if not line:
            time.sleep(0.1)
            continue
        yield line

print("[*] Active Security Mitigation Engine Listening...")
with open(log_file_path, "r") as log_stream:
    for log_line in tail_handler(log_stream):
        try:
            alert_event = json.loads(log_line.strip())
            # Target priorities requiring physical boundary network exclusion
            if alert_event.get("priority") in [1, 2]:
                target_attacker = alert_event.get("src_addr")
                apply_host_quarantine(target_attacker)
        except Exception as parse_error:
            continue
```

5. Operational Intelligence Dashboards & Analytics

A structured dashboard helps security operators visualize alert data, identifying spikes in malicious activity and tracking top attack vectors over time.

NIDS Real-Time Threat Security Operations Center (SOC)


TOTAL OPERATIONAL SECURITY ALERTS

43,921

ACTIVE QUARANTINE NETWORK BLOCKS

128

ATTACK VECTOR CLASSIFICATION BREAKDOWN



TOP TARGETED INTERFACE NODES

10.0.0.5 (Primary Web Host) - 28,410 Events
10.0.0.22 (Internal Stage App) - 12,110 Events
10.0.0.1 (Perimeter Gateway Router) - 3,401 Events

6. Implementation Verification & Sign-off

To verify the installation, a validation attack simulation can be run from an external asset using network utilities like nmap or hping3:

```
# Execute target reconnaissance validation sweep test  
nmap -sS -P0 -p 22,80,443 10.0.0.5
```

Review the log analyzer to ensure the corresponding events are captured in the alert file: `tail -n 5 /var/log/snort/alert_json.txt`. This confirms the rule triggers correctly and verifies that the active firewall blocking script drops subsequent traffic from the simulated source address.