OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

Program did not output anything!

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       UPPER(Student_Name) AS Uppercase_Name
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+----------------+
| Student_Name | Uppercase_Name |
+--------------+----------------+
| Rahul        | RAHUL          |
| Priya        | PRIYA          |
| Amit         | AMIT           |
| Sneha        | SNEHA          |
| Rohit        | ROHIT          |
+--------------+----------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       LOWER(Student_Name) AS Lowercase_Name
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+----------------+
| Student_Name | Lowercase_Name |
+--------------+----------------+
| Rahul        | rahul          |
| Priya        | priya          |
| Amit         | amit           |
| Sneha        | sneha          |
| Rohit        | rohit          |
+--------------+----------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       LENGTH(Student_Name) AS Name_Length
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+-------------+
| Student_Name | Name_Length |
+--------------+-------------+
| Rahul        |           6 |
| Priya        |           6 |
| Amit         |           5 |
| Sneha        |           6 |
| Rohit        |           6 |
+--------------+-------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT CONCAT(Student_Name, ' - Class ', Class) AS Student_Details
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------------+
| Student_Details    |
+--------------------+
| Rahul  - Class 10A |
| Priya  - Class 10A |
| Amit  - Class 10B  |
| Sneha  - Class 10B |
| Rohit  - Class 10A |
+--------------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       SUBSTRING(Student_Name, 1, 5) AS First_Five_Characters
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+-----------------------+
| Student_Name | First_Five_Characters |
+--------------+-----------------------+
| Rahul        | Rahul                 |
| Priya        | Priya                 |
| Amit         | Amit                  |
| Sneha        | Sneha                 |
| Rohit        | Rohit                 |
+--------------+-----------------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Marks,
       ROUND(Marks * 1.05) AS Bonus_Marks
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+-------+-------------+
| Student_Name | Marks | Bonus_Marks |
+--------------+-------+-------------+
| Rahul        |    20 |          21 |
| Priya        |    92 |          97 |
| Amit         |    76 |          80 |
| Sneha        |    98 |         103 |
| Rohit        |    60 |          63 |
+--------------+-------+-------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Marks / 10.0 AS Marks_Value,
       CEIL(Marks / 10.0) AS Rounded_Up
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

Student_Name	Marks_Value	Rounded_Up
Rahul	2.0000	2
Priya	9.2000	10
Amit	7.6000	8
Sneha	9.8000	10
Rohit	6.0000	6

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Marks / 10.0 AS Marks_Value,
       FLOOR(Marks / 10.0) AS Rounded_Down
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

Student_Name	Marks_Value	Rounded_Down
Rahul	2.0000	2
Priya	9.2000	9
Amit	7.6000	7
Sneha	9.8000	9
Rohit	6.0000	6

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Marks,
       MOD(Marks, 10) AS Remainder
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+-------+-----------+
| Student_Name | Marks | Remainder |
+--------------+-------+-----------+
| Rahul        |    20 |         0 |
| Priya        |    92 |         2 |
| Amit         |    76 |         6 |
| Sneha        |    98 |         8 |
| Rohit        |    60 |         0 |
+--------------+-------+-----------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Marks,
       ABS(Marks - 80) AS Difference_From_80
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+-------+--------------------+
| Student_Name | Marks | Difference_From_80 |
+--------------+-------+--------------------+
| Rahul        |    20 |                 60 |
| Priya        |    92 |                 12 |
| Amit         |    76 |                  4 |
| Sneha        |    98 |                 18 |
| Rohit        |    60 |                 20 |
+--------------+-------+--------------------+
```

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Date_of_Birth,
       YEAR(Date_of_Birth) AS Birth_Year
FROM STUDENT;
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

Student_Name	Date_of_Birth	Birth_Year
Rahul	2008-05-20	2008
Priya	2008-11-20	2008
Amit	2009-02-10	2009
Sneha	2008-08-25	2008
Rohit	2009-01-30	2009

OneCompiler Upgrade AI MySQL Run Save

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Date_of_Birth,
       MONTH(Date_of_Birth) AS Birth_Month
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+---------------+-------------+
| Student_Name | Date_of_Birth | Birth_Month |
+--------------+---------------+-------------+
| Rahul        | 2008-05-20    |           5 |
| Priya        | 2008-11-20    |          11 |
| Amit         | 2009-02-10    |           2 |
| Sneha        | 2008-08-25    |           8 |
| Rohit        | 2009-01-30    |           1 |
+--------------+---------------+-------------+
```

OneCompiler Upgrade AI MySQL Run Save

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Date_of_Birth,
       DAY(Date_of_Birth) AS Birth_Day
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+--------------+---------------+-----------+
| Student_Name | Date_of_Birth | Birth_Day |
+--------------+---------------+-----------+
| Rahul        | 2008-05-20    |        20 |
| Priya        | 2008-11-20    |        20 |
| Amit         | 2009-02-10    |        10 |
| Sneha        | 2008-08-25    |        25 |
| Rohit        | 2009-01-30    |        30 |
+--------------+---------------+-----------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Student_Name,
       Date_of_Birth,
       TIMESTAMPDIFF(YEAR, Date_of_Birth, CURDATE()) AS Age
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

Student_Name	Date_of_Birth	Age
Rahul	2008-05-20	18
Priya	2008-11-20	17
Amit	2009-02-10	17
Sneha	2008-08-25	18
Rohit	2009-01-30	17

Ready

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT CURDATE() AS Today;
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
+------------+
| Today      |
+------------+
| 2026-09-04 |
+------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT Class,
       COUNT(*) AS Total_Students,
       AVG(Marks) AS Average_Marks
FROM STUDENT
GROUP BY Class;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

```
+-------+----------------+---------------+
| Class | Total_Students | Average_Marks |
+-------+----------------+---------------+
| 10A   |              3 |       57.3333 |
| 10B   |              2 |       87.0000 |
+-------+----------------+---------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT SUM(Marks) AS Total_Marks
FROM STUDENT;

```

I/O AI Agent

STDIN

Input for the program (Optional

Output:

```
+-------------+
| Total_Marks |
+-------------+
|         346 |
+-------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT AVG(Marks) AS Average_Marks
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (O

Output:

```
+---------------+
| Average_Marks |
+---------------+
|       69.2000 |
+---------------+
```

OneCompiler Upgrade AI MySQL Run

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT MAX(Marks) AS Highest_Marks
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optiona

Output:

```
+---------------+
| Highest_Marks |
+---------------+
|            98 |
+---------------+
```

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT MIN(Marks) AS Lowest_Marks
FROM STUDENT;
```

I/O | AI Agent

STDIN

Input for the program (Opt

Output:

```
+--------------+
| Lowest_Marks |
+--------------+
|           20 |
+--------------+
```

OneCompiler Upgrade AI MySQL Run Save

queries.sql

```sql
CREATE TABLE STUDENT (
    Student_ID INT,
    Student_Name VARCHAR(50),
    Class VARCHAR(10),
    Marks INT,
    Fee_Paid DECIMAL(10,2),
    Date_of_Birth DATE,
    Admission_Date DATE
);
INSERT INTO STUDENT VALUES
(101, 'Rahul ', '10A', 20, 10000, '2008-05-20', '2025-06-27'),
(102, 'Priya ', '10A', 92, 50000, '2008-11-20', '2024-06-12'),
(103, 'Amit ', '10B', 76, 65000, '2009-02-10', '2026-06-11'),
(104, 'Sneha ', '10B', 98, 48000, '2008-08-25', '2021-06-15'),
(105, 'Rohit ', '10A', 60, 26000, '2009-01-30', '2022-06-13');

SELECT
    UPPER(Student_Name) AS Student_Name,
    Class,
    Marks,
    ABS(Marks - 80) AS Difference_From_Target,
    YEAR(Date_of_Birth) AS Birth_Year
FROM STUDENT;
```

I/O AI Agent

STDIN

Input for the program (Optional)

Output:

Student_Name	Class	Marks	Difference_From_Target	Birth_Year
RAHUL	10A	20	60	2008
PRIYA	10A	92	12	2008
AMIT	10B	76	4	2009
SNEHA	10B	98	18	2008
ROHIT	10A	60	20	2009