



Harshitha S 250701234-2025-CSE ▾

H2**Started on** Friday, 9 October 2026, 3:11 PM**State** Finished**Completed on** Friday, 9 October 2026, 3:19 PM**Time taken** 7 mins 33 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int compareAsc(const void *a, const void *b) {
5      int x = *(const int *)a;
6      int y = *(const int *)b;
7      return (x > y) - (x < y);
8  }
9
10 int compareDesc(const void *a, const void *b) {
11     return compareAsc(b, a);
12 }
13
14 int main() {
15     int n;
16     scanf("%d", &n);
17
18     int a[n], b[n];
19
20     for (int i = 0; i < n; i++)
21         scanf("%d", &a[i]);
22
23     for (int i = 0; i < n; i++)
24         scanf("%d", &b[i]);
25
26     qsort(a, n, sizeof(int), compareAsc);
27     qsort(b, n, sizeof(int), compareDesc);
28
29     long long sum = 0;
30
31     for (int i = 0; i < n; i++)
32         sum += (long long)a[i] * b[i];
33
34     printf("%lld\n", sum);
35
36     return 0;
37 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)