

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  int main() {
4      int n;
5      scanf("%d", &n);
6
7      int A[n], B[n];
8
9      for(int i = 0; i < n; i++) {
10         scanf("%d", &A[i]);
11     }
12
13     for(int i = 0; i < n; i++) {
14         scanf("%d", &B[i]);
15     }
16
17     for(int i = 0; i < n; i++) {
18         for(int j = i + 1; j < n; j++) {
19             if(A[i] > A[j]) {
20                 int temp = A[i];
21                 A[i] = A[j];
22                 A[j] = temp;
23             }
24         }
25     }
26
27     for(int i = 0; i < n; i++) {
28         for(int j = i + 1; j < n; j++) {
29             if(B[i] < B[j]) {
30                 int temp = B[i];
31                 B[i] = B[j];
32                 B[j] = temp;
33             }
34         }
35     }
36
37     int sum = 0;
38
39     for(int i = 0; i < n; i++) {
40         sum += A[i] * B[i];
41     }
42
43     printf("%d", sum);
44
45     return 0;
46 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.



[Back to Course](#)