

Create table and insert

```
mysql> use AT3
Database changed
mysql> CREATE TABLE Customer (
  ->     CustomerID INT PRIMARY KEY,
  ->     CustomerName VARCHAR(50),
  ->     City VARCHAR(30)
  -> );
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> INSERT INTO Customer
  -> VALUES
  -> (1, 'Rahul', 'Chennai'),
  -> (2, 'Priya', 'Bangalore'),
  -> (3, 'Arun', 'Hyderabad'),
  -> (4, 'Sneha', 'Mumbai'),
  -> (5, 'Kiran', 'Delhi');
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM Customer;
```

CustomerID	CustomerName	City
1	Rahul	Chennai
2	Priya	Bangalore
3	Arun	Hyderabad
4	Sneha	Mumbai
5	Kiran	Delhi

```
5 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE Orders (
  ->     OrderID INT PRIMARY KEY,
  ->     ProductName VARCHAR(50),
  ->     Amount DECIMAL(10,2),
  ->     CustomerID INT,
  ->     FOREIGN KEY (CustomerID) REFERENCES Customer(CustomerID)
  -> );
Query OK, 0 rows affected (0.06 sec)
```

```
mysql> INSERT INTO Orders
  -> VALUES
  -> (101, 'Laptop', 65000.00, 1),
  -> (102, 'Mobile', 25000.00, 2),
  -> (103, 'Headphones', 3000.00, 1),
  -> (104, 'Keyboard', 1500.00, 5),
  -> (105, 'Mouse', 800.00, 3);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM Orders;
```

OrderID	ProductName	Amount	CustomerID
101	Laptop	65000.00	1
102	Mobile	25000.00	2
103	Headphones	3000.00	1
104	Keyboard	1500.00	5
105	Mouse	800.00	3

```
5 rows in set (0.00 sec)
```

INNER JOIN

```
mysql> SELECT Customer.CustomerID,  
-> Customer.CustomerName,  
-> Orders.OrderID,  
-> Orders.ProductName,  
-> Orders.Amount  
-> FROM Customer  
-> INNER JOIN Orders  
-> ON Customer.CustomerID = Orders.CustomerID;
```

CustomerID	CustomerName	OrderID	ProductName	Amount
1	Rahul	101	Laptop	65000.00
1	Rahul	103	Headphones	3000.00
2	Priya	102	Mobile	25000.00
3	Arun	105	Mouse	800.00
5	Kiran	104	Keyboard	1500.00

5 rows in set (0.00 sec)

```
mysql> SELECT Customer.CustomerID,  
-> Customer.CustomerName,  
-> Orders.OrderID,  
-> Orders.ProductName,  
-> Orders.Amount  
-> FROM Customer  
-> INNER JOIN Orders  
-> ON Customer.CustomerID = Orders.CustomerID;
```

CustomerID	CustomerName	OrderID	ProductName	Amount
1	Rahul	101	Laptop	65000.00
1	Rahul	103	Headphones	3000.00
2	Priya	102	Mobile	25000.00
3	Arun	105	Mouse	800.00
5	Kiran	104	Keyboard	1500.00

5 rows in set (0.00 sec)

LEFT JOIN

```
mysql> SELECT Customer.CustomerID,  
->         Customer.CustomerName,  
->         Orders.OrderID,  
->         Orders.ProductName  
-> FROM Customer  
-> LEFT JOIN Orders  
-> ON Customer.CustomerID = Orders.CustomerID;
```

CustomerID	CustomerName	OrderID	ProductName
1	Rahul	101	Laptop
1	Rahul	103	Headphones
2	Priya	102	Mobile
3	Arun	105	Mouse
4	Sneha	NULL	NULL
5	Kiran	104	Keyboard

6 rows in set (0.00 sec)

RIGHT JOIN

```
mysql> SELECT Customer.CustomerID,  
->         Customer.CustomerName,  
->         Orders.OrderID,  
->         Orders.ProductName  
-> FROM Customer  
-> RIGHT JOIN Orders  
-> ON Customer.CustomerID = Orders.CustomerID;
```

CustomerID	CustomerName	OrderID	ProductName
1	Rahul	101	Laptop
2	Priya	102	Mobile
1	Rahul	103	Headphones
5	Kiran	104	Keyboard
3	Arun	105	Mouse

5 rows in set (0.00 sec)

CROSS JOIN

```
mysql> SELECT Customer.CustomerName,  
->      Orders.ProductName  
-> FROM Customer  
-> CROSS JOIN Orders;
```

CustomerName	ProductName
Kiran	Laptop
Sneha	Laptop
Arun	Laptop
Priya	Laptop
Rahul	Laptop
Kiran	Mobile
Sneha	Mobile
Arun	Mobile
Priya	Mobile
Rahul	Mobile
Kiran	Headphones
Sneha	Headphones
Arun	Headphones
Priya	Headphones
Rahul	Headphones
Kiran	Keyboard
Sneha	Keyboard
Arun	Keyboard
Priya	Keyboard
Rahul	Keyboard
Kiran	Mouse
Sneha	Mouse
Arun	Mouse
Priya	Mouse
Rahul	Mouse

25 rows in set (0.00 sec)