

KARNAM HARSHITH 192511384

```
mysql> use cs;
Database changed
mysql> CREATE TABLE Student (
  ->     SID INT PRIMARY KEY,
  ->     SName VARCHAR(50),
  ->     Marks INT
  -> );
Query OK, 0 rows affected (0.09 sec)

mysql> INSERT INTO Student VALUES
  -> (101, 'Rahul', 85),
  -> (102, 'Priya', 45),
  -> (103, 'Arun', 92);
Query OK, 3 rows affected (0.03 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM Student;
+-----+-----+-----+
| SID | SName | Marks |
+-----+-----+-----+
| 101 | Rahul | 85    |
| 102 | Priya | 45    |
| 103 | Arun  | 92    |
+-----+-----+-----+
3 rows in set (0.01 sec)
```

IF

```
mysql>
mysql> CREATE PROCEDURE CheckPass(IN m INT)
  -> BEGIN
  ->     IF m >= 50 THEN
  ->         SELECT 'PASS' AS Result;
  ->     END IF;
  -> END //
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL CheckPass(75);
+-----+
| Result |
+-----+
| PASS   |
+-----+
1 row in set (0.01 sec)

Query OK, 0 rows affected (0.01 sec)
```

IF ELSE

```
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE CheckResult(IN m INT)
  -> BEGIN
  ->     IF m >= 50 THEN
  ->         SELECT 'PASS' AS Result;
  ->     ELSE
  ->         SELECT 'FAIL' AS Result;
  ->     END IF;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL CheckResult(45);
+-----+
| Result |
+-----+
| FAIL   |
+-----+
1 row in set (0.00 sec)
```

IF ELSE IF ELSE

```
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE GetGrade(IN m INT)
  -> BEGIN
  ->     IF m >= 90 THEN
  ->         SELECT 'A Grade' AS Grade;
  ->
  ->     ELSEIF m >= 75 THEN
  ->         SELECT 'B Grade' AS Grade;
  ->
  ->     ELSEIF m >= 50 THEN
  ->         SELECT 'C Grade' AS Grade;
  ->
  ->     ELSE
  ->         SELECT 'FAIL' AS Grade;
  ->
  ->     END IF;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql> CALL GetGrade(85);
+-----+
| Grade |
+-----+
| B Grade |
+-----+
1 row in set (0.00 sec)
```

CASE

```
mysql> DELIMITER //
```

```
mysql>
```

```
mysql> CREATE PROCEDURE CheckGradeCase(IN m INT)
```

```
    -> BEGIN
```

```
    ->     CASE
```

```
    ->         WHEN m >= 90 THEN
```

```
    ->             SELECT 'A Grade' AS Grade;
```

```
    ->
```

```
    ->         WHEN m >= 75 THEN
```

```
    ->             SELECT 'B Grade' AS Grade;
```

```
    ->
```

```
    ->         WHEN m >= 50 THEN
```

```
    ->             SELECT 'C Grade' AS Grade;
```

```
    ->
```

```
    ->         ELSE
```

```
    ->             SELECT 'FAIL' AS Grade;
```

```
    ->     END CASE;
```

```
    -> END //
```

```
Query OK, 0 rows affected (0.01 sec)
```



```
mysql>
```

```
mysql> DELIMITER ;
```

```
mysql> CALL CheckGradeCase(92);
```

```
+-----+
```

```
| Grade |
```

```
+-----+
```

```
| A Grade |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```



```
Query OK, 0 rows affected (0.00 sec)
```