

Create and insert data

```
mysql> create table student (
  -> studentID int primary key, name varchar (50), age int , departmenr varchar(30), marks int );
Query OK, 0 rows affected (0.05 sec)

mysql> INSERT INTO Student
  -> VALUES
  -> (101, 'Rahul', 20, 'CSE', 85),
  -> (102, 'Priya', 19, 'ECE', 78),
  -> (103, 'Arun', 21, 'CSE', 92),
  -> (104, 'Kiran', 20, 'IT', 67),
  -> (105, 'Sneha', 22, 'ECE', 88),
  -> (106, 'Rohit', 21, 'MECH', 74),
  -> (107, 'Anjali', 19, 'CSE', 95),
  -> (108, 'Vikram', 22, 'IT', 81);
Query OK, 8 rows affected (0.02 sec)
Records: 8 Duplicates: 0 Warnings: 0

mysql> select * from student;
```

studentID	name	age	departmenr	marks
101	Rahul	20	CSE	85
102	Priya	19	ECE	78
103	Arun	21	CSE	92
104	Kiran	20	IT	67
105	Sneha	22	ECE	88
106	Rohit	21	MECH	74
107	Anjali	19	CSE	95
108	Vikram	22	IT	81

```
8 rows in set (0.01 sec)
```

SELECT CLAUSES – BETWEEN

```
mysql> select * from student where marks between 70 and 90 ;
```

studentID	name	age	departmenr	marks
101	Rahul	20	CSE	85
102	Priya	19	ECE	78
105	Sneha	22	ECE	88
106	Rohit	21	MECH	74
108	Vikram	22	IT	81

```
5 rows in set (0.00 sec)
```

IN

```
mysql> select * from student where departmenr in ('ECE','IT');
+-----+-----+-----+-----+-----+
| studentID | name   | age  | departmenr | marks |
+-----+-----+-----+-----+-----+
| 102      | Priya  | 19   | ECE        | 78    |
| 104      | Kiran  | 20   | IT         | 67    |
| 105      | Sneha  | 22   | ECE        | 88    |
| 108      | Vikram | 22   | IT         | 81    |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

AGGREGATE FUNCTIONS – Count

```
mysql> select count(*) as total_students from student;
+-----+
| total_students |
+-----+
| 8              |
+-----+
1 row in set (0.01 sec)
```

SUM

```
mysql> select sum(studentID) as no_of_id from student;
+-----+
| no_of_id |
+-----+
| 836      |
+-----+
1 row in set (0.00 sec)
```

AVG

```
mysql> select avg(age) as avg_age from student;
+-----+
| avg_age |
+-----+
| 20.5000 |
+-----+
1 row in set (0.00 sec)
```

MAX

```
mysql> select max(marks) as 1st_mark from student;
+-----+
| 1st_mark |
+-----+
|      95 |
+-----+
1 row in set (0.00 sec)
```

MIN

```
mysql> select min(marks) as last_marks from student;
+-----+
| last_marks |
+-----+
|      67 |
+-----+
1 row in set (0.00 sec)
```

AGGREGATE FUNCTIONS WITH WHERE CLAUSES

```
mysql> select avg(marks) as avg_marks_IT from student where departmenr = 'IT';
+-----+
| avg_marks_IT |
+-----+
|    74.0000 |
+-----+
1 row in set (0.00 sec)
```