

# COL 352 Introduction to Automata and Theory of Computation


Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

March 22, 2023

Lecture 24: Turing Machines: Variants, CT Thesis (Part 3)

# Enumerators



- ▶ Turing machine with an attached printer.
- ▶ **Exercise:** Formally define it.
- ▶ An enumerator  $E$  starts with a blank input on its work tape.
- ▶ If the enumerator doesn't halt, it may print an infinite list of strings.
- ▶ The language enumerated by  $E$  is the collection of all the strings that it eventually prints out.
- ▶  $E$  may generate the strings of the language in any order, possibly with repetitions.

# Enumerators vs Recognizers

## *Theorem*

*A language is Turing-recognizable if and only if some enumerator enumerates it.*

## *Proof.*

# Enumerators vs Recognizers

## *Theorem*

*A language is Turing-recognizable if and only if some enumerator enumerates it.*

## *Proof.*

( $\Rightarrow$ ) On input  $w$ :

- 1 Run  $E$ . Every time that  $E$  outputs a string, compare it with  $w$ .
- 2 If  $w$  ever appears in the output of  $E$ , accept.

( $\Leftarrow$ )

# Enumerators vs Recognizers

## *Theorem*

*A language is Turing-recognizable if and only if some enumerator enumerates it.*

## *Proof.*

( $\Rightarrow$ ) On input  $w$ :

- ➊ Run  $E$ . Every time that  $E$  outputs a string, compare it with  $w$ .
- ➋ If  $w$  ever appears in the output of  $E$ , accept.

( $\Leftarrow$ ) Ignore the input. Repeat the following for  $i = 1, 2, 3, \dots$

# Enumerators vs Recognizers

## *Theorem*

*A language is Turing-recognizable if and only if some enumerator enumerates it.*

## *Proof.*

( $\Rightarrow$ ) On input  $w$ :

- 1 Run  $E$ . Every time that  $E$  outputs a string, compare it with  $w$ .
- 2 If  $w$  ever appears in the output of  $E$ , accept.

( $\Leftarrow$ ) Ignore the input. Repeat the following for  $i = 1, 2, 3, \dots$

- 1 Run  $M$  for  $i$  steps on each input,  $s_1, s_2, \dots, s_i$ .
- 2 If any computations accepts, print out the corresponding  $s_j$ .



**Remark:** Turing Recognizable = Recursively Enumerable languages.

# Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.

# Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.



# Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.
- ▶ Each write operation (called a push) adds a symbol to the left-hand end of the queue.

# Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.
- ▶ Each write operation (called a push) adds a symbol to the left-hand end of the queue.
- ▶ Each read operation (called a pull) reads and removes a symbol at the right-hand end.

# Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.
- ▶ Each write operation (called a push) adds a symbol to the left-hand end of the queue.
- ▶ Each read operation (called a pull) reads and removes a symbol at the right-hand end.
- ▶ **Initial condition:** the input tape contains a cell with a blank symbol following the input, to detect end of the input.
- ▶ **Computation:** Acceptance by entering a special accept state at any time.

**Note:** As with a PDA, the input of a DQA is placed on a separate read-only input tape, and the head on the input tape can move only from left to right

# Queues are more powerful than stacks

## *Theorem*

*Language can be recognized by a DQA, iff it is Turing-recognizable*

## *Proof Sketch.*

**Idea:** Show any DQA  $Q$  can be simulated with a 2-tape TM  $M$ .

# Queues are more powerful than stacks

## *Theorem*

*Language can be recognized by a DQA, iff it is Turing-recognizable*

## *Proof Sketch.*

**Idea:** Show any DQA  $Q$  can be simulated with a 2-tape TM  $M$ . Show that any single-tape deterministic TM  $D$  can be simulated by a DQA  $Q$ . □

# Simulating a DQA by a TM

- ▶ The first tape of  $M$  holds the input, second tape holds the queue.
- ▶ To simulate reading  $Q$ 's next input symbol,  $M$  reads the symbol under the first head and moves to the right.

# Simulating a DQA by a TM

- ▶ The first tape of  $M$  holds the input, second tape holds the queue.
- ▶ To simulate reading  $Q$ 's next input symbol,  $M$  reads the symbol under the first head and moves to the right.
- ▶ To simulate a *push*  $a$ ,  $M$  writes  $a$  on the leftmost blank cell of the second tape.

# Simulating a DQA by a TM

- ▶ The first tape of  $M$  holds the input, second tape holds the queue.
- ▶ To simulate reading  $Q$ 's next input symbol,  $M$  reads the symbol under the first head and moves to the right.
- ▶ To simulate a *push*  $a$ ,  $M$  writes  $a$  on the leftmost blank cell of the second tape.
- ▶ To simulate a *pull*,  $M$  reads the rightmost symbol on the second tape and shifts the tape one symbol leftward.



# Simulating a TM by DQA

$$M = (S_M, \Sigma, \Gamma_M, \delta_M, q_0^M, q_a^M, q_r^M)$$

$$Q = (S_Q, \Sigma, \Gamma_M \cup \hat{\Gamma}_M, \delta_Q, q_0^Q, \{q_a^M, q_r^M\})$$

# Simulating a TM by DQA

$$M = (S_M, \Sigma, \Gamma_M, \delta_M, q_0^M, q_a^M, q_r^M)$$

$$Q = (S_Q, \Sigma, \Gamma_M \cup \hat{\Gamma}_M, \delta_Q, q_0^Q, \{q_a^M, q_r^M\})$$

- ▶ For each symbol  $c \in \Gamma_M$ ,  $Q$  also has the corresponding  $\hat{c}$  to denote the head.
- ▶ Let  $Q$  also have an end of tape marker \$.

# Simulating a TM by DQA

$$M = (S_M, \Sigma, \Gamma_M, \delta_M, q_0^M, q_a^M, q_r^M)$$

$$Q = (S_Q, \Sigma, \Gamma_M \cup \hat{\Gamma}_M, \delta_Q, q_0^Q, \{q_a^M, q_r^M\})$$

- ▶ For each symbol  $c \in \Gamma_M$ ,  $Q$  also has the corresponding  $\hat{c}$  to denote the head.
- ▶ Let  $Q$  also have an end of tape marker \$.
- ▶  $Q$  simulates  $M$  by maintaining a copy of  $M$ 's tape in the queue.
- ▶  $Q$  can scan the tape from right to left by pulling symbols from the right-hand end of the queue and pushing them back on the left-hand end side, until \$ is seen.
- ▶ When a  $\hat{c}$  symbol is encountered,  $Q$  can determine  $M$ 's next move, because  $Q$  can record  $M$ 's current state in its control.

# Computation Simulation

- ▶ If  $M$ 's tape head moves leftwards, the updating of the queue is done by writing the new symbol  $c$  instead of the old  $\hat{c}$  and moving the  $\hat{\phantom{c}}$  one symbol left.

# Computation Simulation

- ▶ If  $M$ 's tape head moves leftwards, the updating of the queue is done by writing the new symbol  $c$  instead of the old  $\hat{c}$  and moving the  $\hat{\phantom{c}}$  one symbol left.
- ▶ Formally, if current configuration is  $u\hat{a}b^{\wedge}tv$  and  $\delta(q, b) = (q', c, L)$  then the next configuration is  $u\hat{a}ctv$  and is obtained by:

# Computation Simulation

- ▶ If  $M$ 's tape head moves leftwards, the updating of the queue is done by writing the new symbol  $c$  instead of the old  $\hat{c}$  and moving the  $\hat{c}$  one symbol left.
- ▶ Formally, if current configuration is  $u\hat{a}b\hat{t}v$  and  $\delta(q, b) = (q', c, L)$  then the next configuration is  $u\hat{a}c\hat{t}v$  and is obtained by:
  - ▶ *pull  $v$ ; push  $v$ ;*
  - ▶ *pull  $t$ ; push  $t$ ;*
  - ▶ *pull  $\hat{b}$ ; push  $c$ ; pull  $a$ ; push  $\hat{a}$ ;*
  - ▶ *pull  $u$ ; push  $u$ ;*

# Computation Simulation

- ▶ If  $M$ 's tape head moves leftwards, the updating of the queue is done by writing the new symbol  $c$  instead of the old  $\hat{c}$  and moving the  $\hat{\phantom{c}}$  one symbol left.
- ▶ Formally, if current configuration is  $u\hat{a}b\hat{t}v$  and  $\delta(q, b) = (q', c, L)$  then the next configuration is  $u\hat{a}c\hat{t}v$  and is obtained by:
  - ▶ *pull  $v$ ; push  $v$ ;*
  - ▶ *pull  $t$ ; push  $t$ ;*
  - ▶ *pull  $\hat{b}$ ; push  $c$ ; pull  $a$ ; push  $\hat{a}$ ;*
  - ▶ *pull  $u$ ; push  $u$ ;*
- ▶ How about move right? (Exercise!)

## 2 stacks?

- ▶ Same as the regular PDA but now you have two stacks




## 2 stacks?


- ▶ Same as the regular PDA but now you have two stacks
- ▶ As powerful as TMs.

## 2 stacks?

- ▶ Same as the regular PDA but now you have two stacks
- ▶ As powerful as TMs.



is simulated by



# Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

# Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

# Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

- ▶ Computation performed by a NTM is a tree whose branches correspond to different possibilities for the machine

# Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

- ▶ Computation performed by a NTM is a tree whose branches correspond to different possibilities for the machine
- ▶ If some branch of the computation tree leads to the accept state, the machine accepts the input
- ▶ Can nondeterministic Turing machines compute more functions than deterministic Turing machines?

# Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

- ▶ Computation performed by a NTM is a tree whose branches correspond to different possibilities for the machine
- ▶ If some branch of the computation tree leads to the accept state, the machine accepts the input
- ▶ Can nondeterministic Turing machines compute more functions than deterministic Turing machines?

## *Theorem*

*Every nondeterministic Turing machine,  $N$  has an equivalent deterministic Turing machine  $D$ .*

# Example: Finding Integer roots of Polynomials

- ▶ Given polynomial

$$p(x) = a_1x^n + a_2x^{n-1} + \cdots + a_nx + a_{n+1}$$

where  $a_i \in \mathbb{Z}$ , find an integer root.



# Example: Finding Integer roots of Polynomials

- ▶ Given polynomial

$$p(x) = a_1x^n + a_2x^{n-1} + \cdots + a_nx + a_{n+1}$$

where  $a_i \in \mathbb{Z}$ , find an integer root.

- ▶ **Exercise:** Let there be a root at  $x = x_0$  and  $a_{max}$  be the largest absolute value of a  $a_i$ . Show that

$$|x_0| < (n+1) \frac{a_{max}}{|a_1|}$$

# Proof of $L(N) = L(D)$

*Proof Idea.*

Show that a NTM  $N$  can be simulated with a DTM  $D$ .

# Proof of $L(N) = L(D)$

## *Proof Idea.*

Show that a NTM  $N$  can be simulated with a DTM  $D$ . In this simulation  $D$  tries all possible branches of  $N$ 's computation. If  $D$  ever finds the accept state on one of these branches then it accepts. Otherwise  $D$ 's simulation will not terminate.

- ▶  $N$ 's computation on an input  $w$  is a tree,  $N(w)$ .
- ▶ Each branch of  $N(w)$  represents one of the branches of the nondeterminism.

# Proof of $L(N) = L(D)$

## *Proof Idea.*

Show that a NTM  $N$  can be simulated with a DTM  $D$ . In this simulation  $D$  tries all possible branches of  $N$ 's computation. If  $D$  ever finds the accept state on one of these branches then it accepts. Otherwise  $D$ 's simulation will not terminate.

- ▶  $N$ 's computation on an input  $w$  is a tree,  $N(w)$ .
- ▶ Each branch of  $N(w)$  represents one of the branches of the nondeterminism.
- ▶ Each node of  $N(w)$  is a configuration of  $N$ .
- ▶ The root of  $N(w)$  is the start configuration.

# Proof of $L(N) = L(D)$

## *Proof Idea.*

Show that a NTM  $N$  can be simulated with a DTM  $D$ . In this simulation  $D$  tries all possible branches of  $N$ 's computation. If  $D$  ever finds the accept state on one of these branches then it accepts. Otherwise  $D$ 's simulation will not terminate.

- ▶  $N$ 's computation on an input  $w$  is a tree,  $N(w)$ .
- ▶ Each branch of  $N(w)$  represents one of the branches of the nondeterminism.
- ▶ Each node of  $N(w)$  is a configuration of  $N$ .
- ▶ The root of  $N(w)$  is the start configuration.
- ▶  $D$  searches  $N(w)$  for an accepting configuration.



# A tempting bad idea

- ▶ Design  $D$  to explore the tree  $N(w)$  using DFS.
- ▶

## A tempting bad idea

- ▶ Design  $D$  to explore the tree  $N(w)$  using DFS.
- ▶ A depth-first search goes all the way down on one branch before backing up to explore next branch. Hence,  $D$  could go forever down on an infinite branch and miss an accepting configuration on an other branch.

# A better idea

- ▶ Design  $D$  to explore the tree by using a breadth-first search
- ▶ This strategy explores all branches at the same depth before going to explore any branch at the next depth.
- ▶ Hence, this method guarantees that  $D$  will visit every node of  $N(w)$  until it encounters an accepting configuration.

*Proof.*

$D$  has three tapes:

- ▶ Tape 1 always contains the input and is never altered
- ▶ Tape 2 (called the simulation tape) maintains a copy of  $N$ 's tape on some branch of its nondeterministic computation
- ▶ Tape 3 (called address tape) keeps track of  $D$ 's location in  $N$ 's nondeterministic computation tree





# Other variants

- ▶ Multi-dimensional tapes.

# Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines

# Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines
- ▶ Your favorite programming language ("Turing-completeness")

# Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines
- ▶ Your favorite programming language ("Turing-completeness")
- ▶ Cellular automata

# Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines
- ▶ Your favorite programming language ("Turing-completeness")
- ▶ Cellular automata
- ▶ ...
- ▶ ...

# What is computation?



- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.

# What is computation?



- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.
- ▶ 10th problem: Devise an algorithm (a process doable using a finite no. of operations) to test if a (multivariate) polynomial has integral roots.

# What is computation?



## "HILBERT's TENTH PROBLEM"

a book written by [Yuri MATTYASEVICH](#)



Russian original:

**Десятая проблема Гильберта**

Наука, Москва, 1993



English translation:

**Hilbert's Tenth Problem**

[The MIT Press](#), Cambridge, London, 1993

The Publisher's [page of the book](#)



Traduction française:

- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.
- ▶ 10th problem: Devise an algorithm (a process doable using a finite no. of operations) to test if a (multivariate) polynomial has integral roots.



# What is computation?



## "HILBERT's TENTH PROBLEM"

a book written by [Yuri MATTYASEVICH](#)



Russian original:

**Десятая проблема Гильберта**

Наука, Москва, 1993



English translation:

**Hilbert's Tenth Problem**

[The MIT Press](#), Cambridge, London, 1993

The Publisher's [page of the book](#)

Traduction française:

- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.
- ▶ 10th problem: Devise an algorithm (a process doable using a finite no.of operations) to test if a (multivariate) polynomial has integral roots.
- ▶ Now we know that no such algorithm exists. But how to prove this without a mathematical definition of an algorithm?

# Church-Turing thesis



Alonso Church  
(1903–1995)



Alan Turing  
(1912–1954)

# Turing's paper

230

A. M. TURING

[Nov. 12,

## ON COMPUTABLE NUMBERS, WITH AN APPLICATION TO THE ENTSCHEIDUNGSPROBLEM

*By* A. M. TURING.

[Received 28 May, 1936.—Read 12 November, 1936.]

The “computable” numbers may be described briefly as the real numbers whose expressions as a decimal are calculable by finite means. Although the subject of this paper is ostensibly the computable *numbers*, it is almost equally concerned with the definition and investigation of the computable *functions*.