

# COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

February 23, 2023

Lecture 15: Pushdown Automata

# Recap

## Definition

A 2DFA  $A = (Q, \Sigma \cup \{\#, \$\}, \delta, q_0, q_{\text{acc}}, q_{\text{rej}})$ , where

$Q$ : set of states,  $\Sigma$ : input alphabet

$\#$ : left endmarker  $\$$ : right endmarker

$q_0$ : start state

$q_{\text{acc}}$ : accept state  $q_{\text{rej}}$ : reject state

$\delta: Q \times (\Sigma \cup \{\#, \$\}) \rightarrow Q \times \{L, R\}$

The following conditions are forced:

$\forall q \in Q, \exists q', q'' \in Q$  s.t.  $\delta(q, \#) = (q', R)$  and  $\delta(q, \$) = (q'', L)$ .

# Recap

## Definition

A 2DFA  $A = (Q, \Sigma \cup \{\#, \$\}, \delta, q_0, q_{\text{acc}}, q_{\text{rej}})$ , where

$Q$ : set of states,  $\Sigma$ : input alphabet

$\#$ : left endmarker  $\$$ : right endmarker

$q_0$ : start state

$q_{\text{acc}}$ : accept state  $q_{\text{rej}}$ : reject state

$\delta: Q \times (\Sigma \cup \{\#, \$\}) \rightarrow Q \times \{L, R\}$

The following conditions are forced:

$\forall q \in Q, \exists q', q'' \in Q$  s.t.  $\delta(q, \#) = (q', R)$  and  $\delta(q, \$) = (q'', L)$ .

**Exercise:** Come up with a suitable definition of 2-NFA. Redo closure properties of regular languages, but now using 2-DFA/2-NFA.

# Power of 2DFAs

## *Lemma*

*The class of language recognized by 2DFAs is regular.*

## *Proof.*

Let  $T_x : Q \cup \{\bowtie\} \rightarrow Q \cup \{\perp\}$ , which is defined as follows:

$T_x(p) := q$  if whenever  $A$  enters  $x$  on  $p$   
it leaves  $x$  on  $q$ .

$T_x(\bowtie) := q$   $q$  is the state in which  $A$  emerges  
on  $x$  the first time.

$T_x(q) := \perp$  if  $A$  loops on  $x$  forever.



# Power of 2DFAs

## *Lemma*

*The class of language recognized by 2DFAs is regular.*

## *Proof.*

Let  $T_x : Q \cup \{\bowtie\} \rightarrow Q \cup \{\perp\}$ , which is defined as follows:

$T_x(p) := q$  if whenever  $A$  enters  $x$  on  $p$   
it leaves  $x$  on  $q$ .

$T_x(\bowtie) := q$   $q$  is the state in which  $A$  emerges  
on  $x$  the first time.

$T_x(q) := \perp$  if  $A$  loops on  $x$  forever.

Total number of functions of the type

$$T_x \leq (|Q| + 1)^{(|Q|+1)}$$

# Power of 2DFAs

## *Lemma*

*The class of language recognized by 2DFAs is regular.*

## *Proof.*

Let  $T_x : Q \cup \{\bowtie\} \rightarrow Q \cup \{\perp\}$ , which is defined as follows:

$T_x(p) := q$  if whenever  $A$  enters  $x$  on  $p$   
it leaves  $x$  on  $q$ .

$T_x(\bowtie) := q$   $q$  is the state in which  $A$  emerges  
on  $x$  the first time.

$T_x(q) := \perp$  if  $A$  loops on  $x$  forever.

Total number of functions of the type

$$T_x \leq (|Q| + 1)^{(|Q|+1)}$$

$T_x = T_y \Rightarrow \forall z (xz \in F \Leftrightarrow yz \in F)$ . Prove this.

# Power of 2DFAs

## *Lemma*

*The class of language recognized by 2DFAs is regular.*

## *Proof.*

Let  $T_x : Q \cup \{\bowtie\} \rightarrow Q \cup \{\perp\}$ , which is defined as follows:

$T_x(p) := q$  if whenever  $A$  enters  $x$  on  $p$   
it leaves  $x$  on  $q$ .

$T_x(\bowtie) := q$   $q$  is the state in which  $A$  emerges  
on  $x$  the first time.

$T_x(q) := \perp$  if  $A$  loops on  $x$  forever.

Total number of functions of the type

$$T_x \leq (|Q| + 1)^{(|Q|+1)}$$

$T_x = T_y \Rightarrow \forall z (xz \in F \Leftrightarrow yz \in F)$ . Prove this.

$$T_x = T_y \Leftrightarrow x \equiv_A y$$



# Moving on

How to we add expressive power to DFA/NFA so that we can compute more functions?



# Pushdown automata

# Pushdown automata

- ▶  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

# Pushdown automata

- ▶  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .
- ▶  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

# Pushdown automata

- ▶  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .
- ▶  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

# Pushdown automata

- ▶  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .
- ▶  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

NFA needs more memory to solve them.

# Pushdown automata

- ▶  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .
- ▶  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

NFA needs more memory to solve them. What if the NFA had a stack?

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$$

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where



# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ : set of states

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ : set of states       $\Sigma$ : input alphabet

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ : set of states       $\Sigma$ : input alphabet

$\Gamma$ : stack alphabet

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ : set of states       $\Sigma$ : input alphabet

$\Gamma$ : stack alphabet       $q_0$ : start state

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ : set of states       $\Sigma$ : input alphabet

$\Gamma$ : stack alphabet     $q_0$ : start state

$\perp$ : start symbol

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

# Pushdown automata: formal definition

## *Definition*

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

# Pushdown automata: formal definition

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

Understanding  $\delta$

For  $q \in Q, a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,



# Pushdown automata: formal definition

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

## Understanding $\delta$

For  $q \in Q$ ,  $a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,  
then  $p$  is the new state and  $\gamma$  replaces  $X$  in the stack.

# Pushdown automata: formal definition

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

## Understanding $\delta$

For  $q \in Q, a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,  
then  $p$  is the new state and  $\gamma$  replaces  $X$  in the stack.  
if  $\gamma = \epsilon$  then  $X$  is popped.

# Pushdown automata: formal definition

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

## Understanding $\delta$

For  $q \in Q, a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,  
then  $p$  is the new state and  $\gamma$  replaces  $X$  in the stack.

if  $\gamma = \epsilon$  then  $X$  is popped.

if  $\gamma = X$  then  $X$  stays unchanged on the top of the stack.

# Pushdown automata: formal definition

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

## Understanding $\delta$

For  $q \in Q$ ,  $a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,  
then  $p$  is the new state and  $\gamma$  replaces  $X$  in the stack.

if  $\gamma = \epsilon$  then  $X$  is popped.

if  $\gamma = X$  then  $X$  stays unchanged on the top of the stack.

if  $\gamma = \gamma_1\gamma_2 \dots \gamma_k$  then  $X$  is replaced by  $\gamma_k$

# Pushdown automata: formal definition

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ :	set of states	$\Sigma$ :	input alphabet
$\Gamma$ :	stack alphabet	$q_0$ :	start state
$\perp$ :	start symbol	$F$ :	set of final states

$$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*.$$

## Understanding $\delta$

For  $q \in Q, a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,  
then  $p$  is the new state and  $\gamma$  replaces  $X$  in the stack.

if  $\gamma = \epsilon$  then  $X$  is popped.

if  $\gamma = X$  then  $X$  stays unchanged on the top of the stack.

if  $\gamma = \gamma_1\gamma_2 \dots \gamma_k$  then  $X$  is replaced by  $\gamma_k$

and  $\gamma_1\gamma_2 \dots \gamma_{k-1}$  are pushed on top of that.

# Pushdown automata

Example:

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .



# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

$$\delta(q_0, a, B) = (q_0, B)$$

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

$\delta(q_0, a, B) = (q_0, B)$  *push B while reading a on  $q_0$*

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

$$\delta(q_0, a, B) = (q_0, B) \text{ push } B \text{ while reading } a \text{ on } q_0$$

$$\delta(q_0, b, B) = (q_1, \epsilon)$$

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$\delta(q_0, a, \perp) = (q_0, B \perp)$

$\delta(q_0, a, B) = (q_0, B)$  *push B while reading a on  $q_0$*

$\delta(q_0, b, B) = (q_1, \epsilon)$  *move to  $q_1$  on seeing b*

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

$$\delta(q_0, a, B) = (q_0, B) \text{ push } B \text{ while reading } a \text{ on } q_0$$

$$\delta(q_0, b, B) = (q_1, \epsilon) \text{ move to } q_1 \text{ on seeing } b$$

$$\delta(q_1, b, B) = (q_1, \epsilon)$$

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$\delta(q_0, a, \perp) = (q_0, B \perp)$

$\delta(q_0, a, B) = (q_0, B)$  *push B while reading a on  $q_0$*

$\delta(q_0, b, B) = (q_1, \epsilon)$  *move to  $q_1$  on seeing b*

$\delta(q_1, b, B) = (q_1, \epsilon)$  *pop B while reading b on  $q_1$*

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

$$\delta(q_0, a, B) = (q_0, B) \text{ push } B \text{ while reading } a \text{ on } q_0$$

$$\delta(q_0, b, B) = (q_1, \epsilon) \text{ move to } q_1 \text{ on seeing } b$$

$$\delta(q_1, b, B) = (q_1, \epsilon) \text{ pop } B \text{ while reading } b \text{ on } q_1$$

$$\delta(q_1, b, \perp) = (q', \perp)$$



# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$\delta(q_0, a, \perp) = (q_0, B \perp)$

$\delta(q_0, a, B) = (q_0, B)$  *push B while reading a on  $q_0$*

$\delta(q_0, b, B) = (q_1, \epsilon)$  *move to  $q_1$  on seeing b*

$\delta(q_1, b, B) = (q_1, \epsilon)$  *pop B while reading b on  $q_1$*

$\delta(q_1, b, \perp) = (q', \perp)$  *extra b in the input then go to some state  $q'$*

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = (q_0, B \perp)$$

$$\delta(q_0, a, B) = (q_0, B) \text{ push } B \text{ while reading } a \text{ on } q_0$$

$$\delta(q_0, b, B) = (q_1, \epsilon) \text{ move to } q_1 \text{ on seeing } b$$

$$\delta(q_1, b, B) = (q_1, \epsilon) \text{ pop } B \text{ while reading } b \text{ on } q_1$$

$$\delta(q_1, b, \perp) = (q', \perp) \text{ extra } b \text{ in the input then go to some state } q'$$

$$\delta(q_1, \epsilon, \perp) = (q_2, \perp)$$

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$\delta(q_0, a, \perp) = (q_0, B \perp)$

$\delta(q_0, a, B) = (q_0, B)$  *push B while reading a on  $q_0$*

$\delta(q_0, b, B) = (q_1, \epsilon)$  *move to  $q_1$  on seeing b*

$\delta(q_1, b, B) = (q_1, \epsilon)$  *pop B while reading b on  $q_1$*

$\delta(q_1, b, \perp) = (q', \perp)$  *extra b in the input then go to some state  $q'$*

$\delta(q_1, \epsilon, \perp) = (q_2, \perp)$  *else go to accepting state  $q_2$*

# Pushdown automata

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{B\}, q_0, F = \{q_2\})$ .

$\delta(q_0, a, \perp) = (q_0, B \perp)$

$\delta(q_0, a, B) = (q_0, B)$  *push B while reading a on  $q_0$*

$\delta(q_0, b, B) = (q_1, \epsilon)$  *move to  $q_1$  on seeing b*

$\delta(q_1, b, B) = (q_1, \epsilon)$  *pop B while reading b on  $q_1$*

$\delta(q_1, b, \perp) = (q', \perp)$  *extra b in the input then go to some state  $q'$*

$\delta(q_1, \epsilon, \perp) = (q_2, \perp)$  *else go to accepting state  $q_2$*

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

$$\delta(q_0, a, A) = \{(q_0, AA), (q_1, AA)\}, \delta(q_0, a, B) = \{(q_0, AB), (q_1, AB)\}$$



# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

$$\delta(q_0, a, A) = \{(q_0, AA), (q_1, AA)\}, \delta(q_0, a, B) = \{(q_0, AB), (q_1, AB)\}$$

$$\delta(q_0, b, A) = \{(q_0, BA), (q_1, BA)\},$$

$$\delta(q_0, b, B) = \{(q_0, BB), (q_1, BB)\}$$

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

$$\delta(q_0, a, A) = \{(q_0, AA), (q_1, AA)\}, \delta(q_0, a, B) = \{(q_0, AB), (q_1, AB)\}$$

$$\delta(q_0, b, A) = \{(q_0, BA), (q_1, BA)\},$$

$$\delta(q_0, b, B) = \{(q_0, BB), (q_1, BB)\}$$

$$\delta(q_1, a, A) = (q_1, \epsilon)$$

$$\delta(q_1, b, B) = (q_1, \epsilon)$$

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

$$\delta(q_0, a, A) = \{(q_0, AA), (q_1, AA)\}, \delta(q_0, a, B) = \{(q_0, AB), (q_1, AB)\}$$

$$\delta(q_0, b, A) = \{(q_0, BA), (q_1, BA)\},$$

$$\delta(q_0, b, B) = \{(q_0, BB), (q_1, BB)\}$$

$$\delta(q_1, a, A) = (q_1, \epsilon)$$

$$\delta(q_1, b, B) = (q_1, \epsilon)$$

$$\delta(q_1, a, B) = (q', \epsilon)$$

$$\delta(q_1, b, A) = (q', \epsilon)$$

$$\delta(q_1, a, \perp) = (q', \epsilon)$$

$$\delta(q_1, b, \perp) = (q', \epsilon)$$

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

$$\delta(q_0, a, A) = \{(q_0, AA), (q_1, AA)\}, \delta(q_0, a, B) = \{(q_0, AB), (q_1, AB)\}$$

$$\delta(q_0, b, A) = \{(q_0, BA), (q_1, BA)\},$$

$$\delta(q_0, b, B) = \{(q_0, BB), (q_1, BB)\}$$

$$\delta(q_1, a, A) = (q_1, \epsilon)$$

$$\delta(q_1, b, B) = (q_1, \epsilon)$$

$$\delta(q_1, a, B) = (q', \epsilon)$$

$$\delta(q_1, b, A) = (q', \epsilon)$$

$$\delta(q_1, a, \perp) = (q', \epsilon)$$

$$\delta(q_1, b, \perp) = (q', \epsilon)$$

$$\delta(q_1, \epsilon, \perp) = (q_2, \perp)$$

# Nondeterministic pushdown automata

Example:  $PAL = \{w \cdot w^R \mid w \in \Sigma^*\}$ .

$N = (Q = \{q_0, q_1, q_2, q'\}, \Sigma = \{a, b\}, \Gamma = \{A, B\}, q_0, F = \{q_2\})$ .

$$\delta(q_0, a, \perp) = \{(q_0, A \perp), (q_1, A \perp)\}$$

$$\delta(q_0, b, \perp) = \{(q_0, B \perp), (q_1, B \perp)\}$$

$$\delta(q_0, a, A) = \{(q_0, AA), (q_1, AA)\}, \delta(q_0, a, B) = \{(q_0, AB), (q_1, AB)\}$$

$$\delta(q_0, b, A) = \{(q_0, BA), (q_1, BA)\},$$

$$\delta(q_0, b, B) = \{(q_0, BB), (q_1, BB)\}$$

$$\delta(q_1, a, A) = (q_1, \epsilon)$$

$$\delta(q_1, b, B) = (q_1, \epsilon)$$

$$\delta(q_1, a, B) = (q', \epsilon)$$

$$\delta(q_1, b, A) = (q', \epsilon)$$

$$\delta(q_1, a, \perp) = (q', \epsilon)$$

$$\delta(q_1, b, \perp) = (q', \epsilon)$$

$$\delta(q_1, \epsilon, \perp) = (q_2, \perp)$$