

COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420
Indian Institute of Technology, Delhi
nbalaji@cse.iitd.ac.in

April 9, 2023

Lecture 28: Reductions 3

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings

Universality of CFG

Lemma

$ALL_{CFG} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*)

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w , and

$N_{M,w}$ rejects at least one string if M does not accept w .

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w , and

$N_{M,w}$ rejects at least one string if M does not accept w .

Formally,

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w , and

$N_{M,w}$ rejects at least one string if M does not accept w .

Formally,

Input $(M, w) \longrightarrow N_{M,w}$

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w , and

$N_{M,w}$ rejects at least one string if M does not accept w .

Formally,

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w , and

$N_{M,w}$ rejects at least one string if M does not accept w .

Formally,

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Universality of CFG

Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

For a TM M and input w we create a PDA $N_{M,w}$ such that

$N_{M,w}$ accepts all strings (i.e. accepts Σ^*) if M accepts w , and

$N_{M,w}$ rejects at least one string if M does not accept w .

Formally,

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Filling in the details

The following two details need to be addressed.

Q_1 How should we design $N_{M,w}$?

Filling in the details

The following two details need to be addressed.

Q_1 How should we design $N_{M,w}$?

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Input $(M, w) \longrightarrow N_{M,w}$

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that ALL_{CFL} is decidable.

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that ALL_{CFL} is decidable.

C be the TM deciding it.

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Design A as follows:

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an M, w pair,
create $N_{M,w}$.

Assume that ALL_{CFL} is decidable.

C be the TM deciding it.

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Design A as follows:

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an M, w pair,
create $N_{M,w}$.

Feed $\langle N_{M,w} \rangle$ to
 C .

Assume that ALL_{CFL} is decidable.

C be the TM deciding it.

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Design A as follows:

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an M, w pair,
create $N_{M,w}$.

Feed $\langle N_{M,w} \rangle$ to
 C .

Assume that ALL_{CFL} is decidable.

C be the TM deciding it.

If C accepts then
reject;

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Design A as follows:

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an M, w pair,
create $N_{M,w}$.

Feed $\langle N_{M,w} \rangle$ to
 C .

Assume that ALL_{CFL} is decidable.

C be the TM deciding it.

If C accepts then
reject;

else accept.

Details for Q_2

Q_2 If such an $N_{M,w}$ is designed then why have we proved that ALL_{CFL} is undecidable?

Design A as follows:

Input $(M, w) \longrightarrow N_{M,w}$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an M, w pair,
create $N_{M,w}$.

Feed $\langle N_{M,w} \rangle$ to
 C .

Assume that ALL_{CFL} is decidable.

C be the TM deciding it.

If C accepts then
reject;

else accept.

Details for Q_1 : reduction via computation history

Q_1 How should we design $N_{M,w}$?

Details for Q_1 : reduction via computation history

Q_1 How should we design $N_{M,w}$?

Main idea

Use computational history of M on w .

Details for Q_1 : reduction via computation history

Q_1 How should we design $N_{M,w}$?

Main idea

Use computational history of M on w .

Accepting computation history is a sequence of configurations:
 C_1, C_2, \dots, C_ℓ such that

Details for Q_1 : reduction via computation history

Q_1 How should we design $N_{M,w}$?

Main idea

Use computational history of M on w .

Accepting computation history is a sequence of configurations:
 C_1, C_2, \dots, C_ℓ such that

C_1 is a start configuration.

C_ℓ is an accepting configuration.

for each $1 \leq i \leq \ell$, C_i yields C_{i+1} .

Rejecting computation history is a sequence of configurations:
 C_1, C_2, \dots, C_ℓ such that

Details for Q_1 : reduction via computation history

Q_1 How should we design $N_{M,w}$?

Main idea

Use computational history of M on w .

Accepting computation history is a sequence of configurations:
 C_1, C_2, \dots, C_ℓ such that

C_1 is a start configuration.

C_ℓ is an accepting configuration.

for each $1 \leq i \leq \ell$, C_i yields C_{i+1} .

Rejecting computation history is a sequence of configurations:
 C_1, C_2, \dots, C_ℓ such that

C_1 is a start configuration.

C_ℓ is a rejecting configuration.

for each $1 \leq i \leq \ell$, C_i yields C_{i+1} .

Universality of CFLs is undecidable!

- Interpret input x to $N_{M,w}$ as a computational history of M on w .

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, but C_ℓ is not an accepting configuration

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, but C_ℓ is not an accepting configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, C_ℓ is an accepting configuration, but there exists an i s.t. $1 \leq i \leq \ell - 1$ and C_i does not yield C_{i+1} .

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, but C_ℓ is not an accepting configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, C_ℓ is an accepting configuration, but there exists an i s.t. $1 \leq i \leq \ell - 1$ and C_i does not yield C_{i+1} .
- ▶ If M accepts w , let \tilde{x} be a accepting computation history of M on w .

$N_{M,w}$ will reject \tilde{x}

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, but C_ℓ is not an accepting configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, C_ℓ is an accepting configuration, but there exists an i s.t. $1 \leq i \leq \ell - 1$ and C_i does not yield C_{i+1} .
- ▶ If M accepts w , let \tilde{x} be a accepting computation history of M on w .

$N_{M,w}$ will reject \tilde{x} , i.e. $\tilde{x} \notin L(N_{M,w})$.

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, but C_ℓ is not an accepting configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, C_ℓ is an accepting configuration, but there exists an i s.t. $1 \leq i \leq \ell - 1$ and C_i does not yield C_{i+1} .
- ▶ If M accepts w , let \tilde{x} be a accepting computation history of M on w .
 $N_{M,w}$ will reject \tilde{x} , i.e. $\tilde{x} \notin L(N_{M,w})$.
- ▶ If M does not accept w , then
no matter what x is, $N_{M,w}$ will accept x

Universality of CFLs is undecidable!

- ▶ Interpret input x to $N_{M,w}$ as a computational history of M on w .
- ▶ Design $N_{M,w}$ s.t. it accepts x if any of the following conditions holds:
 - ▶ x does not have the pattern of a computational history of x OR
 - ▶ x is a computational history, but C_1 is not a start configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, but C_ℓ is not an accepting configuration OR
 - ▶ x is a computational history, C_1 is a start configuration, C_ℓ is an accepting configuration, but there exists an i s.t. $1 \leq i \leq \ell - 1$ and C_i does not yield C_{i+1} .
- ▶ If M accepts w , let \tilde{x} be a accepting computation history of M on w .
 $N_{M,w}$ will reject \tilde{x} , i.e. $\tilde{x} \notin L(N_{M,w})$.
- ▶ If M does not accept w , then
no matter what x is, $N_{M,w}$ will accept x , i.e. $L(N_{M,w}) = \Sigma^*$.

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists.

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Example: Consider the lists $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$ and $B = \langle \text{110110}, \text{00}, \text{110} \rangle$.

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Example: Consider the lists $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$ and $B = \langle \text{110110}, \text{00}, \text{110} \rangle$. **Solution:** There is a sequence $i = 2, 3, 1$ such that $s_2 s_3 s_1 = t_2 t_3 t_1$,

Witness: $s_2 s_3 s_1 = \text{00110110110}$ and $t_2 t_3 t_1 = \text{00110110110}$

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Example: Consider the lists $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$ and $B = \langle \text{110110}, \text{00}, \text{110} \rangle$. **Solution:** There is a sequence $i = 2, 3, 1$ such that $s_2 s_3 s_1 = t_2 t_3 t_1$,

Witness: $s_2 s_3 s_1 = \text{00110110110}$ and $t_2 t_3 t_1 = \text{00110110110}$

- ▶ What about $A = \{0011, 11, 1101\}$ and $B = \{101, 1, 110\}$?

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Example: Consider the lists $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$ and $B = \langle \text{110110}, \text{00}, \text{110} \rangle$. **Solution:** There is a sequence $i = 2, 3, 1$ such that $s_2 s_3 s_1 = t_2 t_3 t_1$,

Witness: $s_2 s_3 s_1 = \text{00110110110}$ and $t_2 t_3 t_1 = \text{00110110110}$

- ▶ What about $A = \{0011, 11, 1101\}$ and $B = \{101, 1, 110\}$?
- ▶ What about $A = \{100, 0, 1\}$ and $B = \{1, 100, 0\}$?

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Example: Consider the lists $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$ and $B = \langle \text{110110}, \text{00}, \text{110} \rangle$. **Solution:** There is a sequence $i = 2, 3, 1$ such that $s_2 s_3 s_1 = t_2 t_3 t_1$,

Witness: $s_2 s_3 s_1 = \text{00110110110}$ and $t_2 t_3 t_1 = \text{00110110110}$

- ▶ What about $A = \{0011, 11, 1101\}$ and $B = \{101, 1, 110\}$?
- ▶ What about $A = \{100, 0, 1\}$ and $B = \{1, 100, 0\}$? (Shortest solution length = 75)

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists.

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Can you design an algorithm to solve this problem? A semi-algorithm?

A String Matching Problem

String List Matching Problem

Given two lists $A = \langle s_1, s_2, \dots, s_n \rangle$ and $B = \langle t_1, t_2, \dots, t_n \rangle$ of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence $1 \leq i_1, i_2, \dots, i_m \leq n$ (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Can you design an algorithm to solve this problem? A semi-algorithm?

Theorem

There is no algorithm for the string-list matching problem. In other words, this problem is undecidable.

Post's Correspondence Problem

A Domino game

Given a collection of dominos $\begin{bmatrix} b \\ ca \end{bmatrix}$ $\begin{bmatrix} a \\ ab \end{bmatrix}$ $\begin{bmatrix} ca \\ a \end{bmatrix}$ $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.

Post's Correspondence Problem

A Domino game

Given a collection of dominos $\begin{bmatrix} b \\ ca \end{bmatrix}$ $\begin{bmatrix} a \\ ab \end{bmatrix}$ $\begin{bmatrix} ca \\ a \end{bmatrix}$ $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.
- ▶ Does this collection of dominos have a match?

Post's Correspondence Problem

A Domino game

Given a collection of dominos $\begin{bmatrix} b \\ ca \end{bmatrix}$ $\begin{bmatrix} a \\ ab \end{bmatrix}$ $\begin{bmatrix} ca \\ a \end{bmatrix}$ $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.
- ▶ Does this collection of dominos have a match?
- ▶ Same as the string matching problem

Post's Correspondence Problem

A Domino game

Given a collection of dominos $\begin{bmatrix} b \\ ca \end{bmatrix}$ $\begin{bmatrix} a \\ ab \end{bmatrix}$ $\begin{bmatrix} ca \\ a \end{bmatrix}$ $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.
- ▶ Does this collection of dominos have a match?
- ▶ Same as the string matching problem
- ▶ Called Post's Correspondence Problem or PCP.

Theorem

PCP is undecidable.

- ▶ Encode TM computation histories!
- ▶ Each transition as a domino!
- ▶ Simulate the run using the dominos.

Proof of Undecidability of PCP

Simplifying assumptions

Proof of Undecidability of PCP

Simplifying assumptions

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.

Proof of Undecidability of PCP

Simplifying assumptions

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If $w = \varepsilon$, then use \sqcup instead of w .

Proof of Undecidability of PCP

Simplifying assumptions

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If $w = \varepsilon$, then use \sqcup instead of w .
- ▶ $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

Proof of Undecidability of PCP

Simplifying assumptions

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If $w = \varepsilon$, then use \sqcup instead of w .
- ▶ $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

We define a reduction from A_{TM} to (M)PCP.

Proof of Undecidability of PCP

Simplifying assumptions

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If $w = \varepsilon$, then use \sqcup instead of w .
- ▶ $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

We define a reduction from A_{TM} to (M)PCP. Let an instance of A_{TM} be

- ▶ $M = (Q, \Sigma, \Gamma, \delta, q_0, q_f, q_r)$
- ▶ $w = w_1 \dots w_n$

Proof of Undecidability of PCP

Simplifying assumptions

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If $w = \varepsilon$, then use \sqcup instead of w .
- ▶ $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

We define a reduction from A_{TM} to (M)PCP. Let an instance of A_{TM} be

- ▶ $M = (Q, \Sigma, \Gamma, \delta, q_0, q_f, q_r)$
- ▶ $w = w_1 \dots w_n$

We build instance P' of MPCP in several steps.

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every $a, b, c \in \Gamma$ and every $q, q' \in Q$, $q \neq q_r$,
 - ▶ If $\delta(q, a) = (q', b, R)$, then add domino to P'

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every $a, b, c \in \Gamma$ and every $q, q' \in Q$, $q \neq q_r$,
 - ▶ If $\delta(q, a) = (q', b, R)$, then add domino to P'

$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every $a, b, c \in \Gamma$ and every $q, q' \in Q$, $q \neq q_r$,
 - ▶ If $\delta(q, a) = (q', b, R)$, then add domino to P'
$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$
 - ▶ If $\delta(q, a) = (q', b, L)$, then add domino to P'

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every $a, b, c \in \Gamma$ and every $q, q' \in Q$, $q \neq q_r$,

- ▶ If $\delta(q, a) = (q', b, R)$, then add domino to P'

$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$

- ▶ If $\delta(q, a) = (q', b, L)$, then add domino to P'

$$\begin{bmatrix} cqa \\ q'cb \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in P'

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.

- ▶ For every $a, b, c \in \Gamma$ and every $q, q' \in Q$, $q \neq q_r$,

- ▶ If $\delta(q, a) = (q', b, R)$, then add domino to P'

$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$

- ▶ If $\delta(q, a) = (q', b, L)$, then add domino to P'

$$\begin{bmatrix} cqa \\ q'cb \end{bmatrix}$$

- ▶ add all dominos (i.e, for all $a \in \Gamma \cup \{\#\}$) to P' .

$$\begin{bmatrix} a \\ a \end{bmatrix} \quad \begin{bmatrix} \# \\ \sqcup\# \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos

Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
 - ▶ For every $a \in \Gamma$, we add all dominos to P'

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
 - ▶ For every $a \in \Gamma$, we add all dominos to P'

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
 - ▶ For every $a \in \Gamma$, we add all dominos to P'

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

- ▶ Step 4: Complete the match

$$\begin{bmatrix} q_a \# \# \\ \# \end{bmatrix}$$

Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
 - ▶ For every $a \in \Gamma$, we add all dominos to P'

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

- ▶ Step 4: Complete the match

$$\begin{bmatrix} q_a \# \# \\ \# \end{bmatrix}$$

- ▶ This completes the reduction, i.e., map from instance of A_{TM} to PCP.
- ▶ M accepts w if and only if P' gives a solution to PCP.

Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
 - ▶ For every $a \in \Gamma$, we add all dominos to P'

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

- ▶ Step 4: Complete the match

$$\begin{bmatrix} q_a \# \# \\ \# \end{bmatrix}$$

- ▶ This completes the reduction, i.e., map from instance of A_{TM} to PCP.
- ▶ M accepts w if and only if P' gives a solution to PCP.
- ▶ MPCP to PCP?