

# COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

January 29, 2023

Lecture 8: Regular Expressions

# Recap

## Definition (Pattern)

A pattern  $\alpha$  is a string of symbols of a certain form representing a (possibly infinite) set of strings in  $\Sigma^*$ .

$$L(\alpha) = \{x \in \Sigma^* \mid x \text{ matches } \alpha\}$$

# Recap: Atomic and Compound Patterns

- 1  $a \in \Sigma, L(a) = \{a\}$
- 2  $\varepsilon, L(\varepsilon) = \{\varepsilon\}$
- 3  $\emptyset, L(\emptyset) = \emptyset$
- 4  $\Sigma$ , matching any alphabet
- 5  $\Sigma^*$ , matching any finite string
- 6  $x$  matches  $\alpha + \beta$  if  $L(\alpha + \beta) = L(\alpha) \cup L(\beta)$
- 7  $x$  matches  $\alpha \cap \beta$  if  $L(\alpha \cap \beta) = L(\alpha) \cap L(\beta)$
- 8  $x$  matches  $\alpha\beta$  if  $x = yz$  where  $L(\alpha\beta) = L(\alpha)L(\beta)$
- 9  $x$  matches  $\overline{\alpha}$  if  $L(\overline{\alpha}) = \overline{L(\alpha)} = \Sigma^* \setminus L(\alpha)$
- 10  $x$  matches  $\alpha^*$  if  $x$  can be expressed as zero or more of strings that match  $\alpha$ , i.e.,  $L(\alpha^*) = L(\alpha)^*$
- 11  $x$  matches  $\alpha^+$  if  $x$  can be expressed as one or more of strings that match  $\alpha$ , i.e.,  $L(\alpha^+) = L(\alpha)^+$

## *Recap:* DFA to regular expression

### **Lemma**

Any regular language can be specified by a regular expression

## Recap: DFA to regular expression

### Lemma

Any regular language can be specified by a regular expression

**Want:** Given any DFA, convert it into a regular expression.

### Lemma

Given any DFA  $A$ , we can obtain a regular expression, say  $R_A$ , such that  $L(A) = L(R_A)$ .

## Recap: Computing with labelled graphs

### Lemma

Any regular language can be specified by a regular expression

**Want:** Given any DFA, convert it into a regular expression.

### Lemma

Given any DFA  $A$ , we can obtain a regular expression, say  $R_A$ , such that  $L(A) = L(R_A)$ .

# Regular expressions

For a regular expression  $E$  we write  $L(E)$  for its language. The set of valid regular expressions  $RegEx$  can be defined recursively as the following:

	Syntax	Semantics
Empty String	$\epsilon$	$L(\epsilon) = \{\epsilon\}$
Empty Set	$\emptyset$	$L(\emptyset) = \emptyset$
Single Letter	$a$	$L(a) = \{a\}$
Union	$E + F$	$L(E + F) = L(E) \cup L(F)$
Concatenation	$E.F$	$L(E.F) = L(E) \circ L(F)$
Kleene Star	$E^*$	$L(E)^*$

# NFA to regular expressions



# NFA to regular expressions

## Theorem

Let  $A = (Q, \Sigma, \delta, q_0, F)$  be a DFA, then there is an RE  $R$  such that  $L(R) = L(A)$ .

# NFA to regular expressions

## Theorem

Let  $A = (Q, \Sigma, \delta, q_0, F)$  be a DFA, then there is an RE  $R$  such that  $L(R) = L(A)$ .

# NFA to regular expressions

## Theorem

Let  $A = (Q, \Sigma, \delta, q_0, F)$  be a DFA, then there is an RE  $R$  such that  $L(R) = L(A)$ .

## Proof.

Let us assign states in  $Q = \{q_1, \dots, q_n\}$  an arbitrary order, where  $q_0 = q_1$  and  $q_1 < \dots < q_n$ .

# NFA to regular expressions

## Theorem

Let  $A = (Q, \Sigma, \delta, q_0, F)$  be a DFA, then there is an RE  $R$  such that  $L(R) = L(A)$ .

## Proof.

Let us assign states in  $Q = \{q_1, \dots, q_n\}$  an arbitrary order, where  $q_0 = q_1$  and  $q_1 < \dots < q_n$ .

Each path on a DFA corresponds to a word.

# NFA to regular expressions

## Theorem

Let  $A = (Q, \Sigma, \delta, q_0, F)$  be a DFA, then there is an RE  $R$  such that  $L(R) = L(A)$ .

## Proof.

Let us assign states in  $Q = \{q_1, \dots, q_n\}$  an arbitrary order, where  $q_0 = q_1$  and  $q_1 < \dots < q_n$ .

Each path on a DFA corresponds to a word.

We will incrementally consider longer and longer paths.

# NFA to regular expressions (contd)

## Proof. (contd.)

# NFA to regular expressions (contd)

**Proof. (contd.)** Let us define the following set of paths.

# NFA to regular expressions (contd)

**Proof. (contd.)** Let us define the following set of paths.


$p(i, j, k) :=$  the set of paths from  $q_i$  to  $q_j$  that do not have intermediate states that are greater than  $q_k$ .



# NFA to regular expressions (contd)

**Proof. (contd.)** Let us define the following set of paths.


$p(i, j, k) :=$  the set of paths from  $q_i$  to  $q_j$  that do not have intermediate states that are greater than  $q_k$ .



# NFA to regular expressions (contd)

**Proof. (contd.)** Let us define the following set of paths.

$p(i, j, k) :=$  the set of paths from  $q_i$  to  $q_j$  that do not have intermediate states that are greater than  $q_k$ .




Note that  $q_i$  and  $q_j$  **need not** be smaller than  $q_k$ .

# NFA to regular expressions (contd)

**Proof. (contd.)** Let us define the following set of paths.

$p(i, j, k) :=$  the set of paths from  $q_i$  to  $q_j$  that do not have intermediate states that are greater than  $q_k$ .



Note that  $q_i$  and  $q_j$  **need not** be smaller than  $q_k$ .

Let  $R(i, j, k)$  be the regular expression that defines the set of words along the paths in  $p(i, j, k)$ .

# NFA to regular expressions (contd)

## Proof. (contd.)

# NFA to regular expressions (contd)

## Proof. (contd.)

Let us define  $R(i, j, k)$  by induction over  $k$ .


# NFA to regular expressions (contd)

## Proof. (contd.)

Let us define  $R(i, j, k)$  by induction over  $k$ .

**Base case:** Let  $\{a_1, \dots, a_r\} = \{a \mid \delta(q_i, a) = q_j\}$ , i. e., letters that take  $q_i$  to  $q_j$ .

$$R(i, j, 0) := \begin{cases} a_1 + \dots + a_r, & i \neq j \\ a_1 + \dots + a_r + \varepsilon & \text{Otherwise} \end{cases}$$




# NFA to regular expressions (contd)

## Proof. (contd.)

Let us define  $R(i, j, k)$  by induction over  $k$ .

**Base case:** Let  $\{a_1, \dots, a_r\} = \{a \mid \delta(q_i, a) = q_j\}$ , i. e., letters that take  $q_i$  to  $q_j$ .

$$R(i, j, 0) := \begin{cases} a_1 + \dots + a_r, & i \neq j \\ a_1 + \dots + a_r + \varepsilon & \text{Otherwise} \end{cases}$$




## NFA to regular expressions (contd)

**Induction step:** By induction hypothesis, we have regular expressions for the paths upto  $k - 1$ . Let us consider the paths that also go via state  $q_k$ .




## NFA to regular expressions (contd)

**Induction step:** By induction hypothesis, we have regular expressions for the paths upto  $k - 1$ . Let us consider the paths that also go via state  $q_k$ .




## NFA to regular expressions (contd)

**Induction step:** By induction hypothesis, we have regular expressions for the paths upto  $k - 1$ . Let us consider the paths that also go via state  $q_k$ .




## NFA to regular expressions (contd)

**Induction step:** By induction hypothesis, we have regular expressions for the paths upto  $k - 1$ . Let us consider the paths that also go via state  $q_k$ .




## NFA to regular expressions (contd)

**Induction step:** By induction hypothesis, we have regular expressions for the paths upto  $k - 1$ . Let us consider the paths that also go via state  $q_k$ .



## NFA to regular expressions (contd)

**Induction step:** By induction hypothesis, we have regular expressions for the paths upto  $k - 1$ . Let us consider the paths that also go via state  $q_k$ .




$$R(i, j, k) := R(\textcolor{red}{i}, \textcolor{red}{j}, \textcolor{red}{k} - 1) + R(\textcolor{green}{i}, \textcolor{green}{k}, \textcolor{green}{k} - 1)R(\textcolor{blue}{k}, \textcolor{blue}{k}, \textcolor{blue}{k} - 1)^* R(\textcolor{brown}{k}, \textcolor{brown}{j}, \textcolor{brown}{k} - 1)$$

# NFA to regular expressions (contd)

Let  $F = \{q_{j1}, \dots, q_{js}\}$


# NFA to regular expressions (contd)

Let  $F = \{q_{j_1}, \dots, q_{j_s}\}$



## NFA to regular expressions (contd)

Let  $F = \{q_{j_1}, \dots, q_{j_s}\}$




The following regular expression will recognize  $L(A)$


$$R(1, j_1, n) + \dots + R(1, j_s, n)$$



# Examples




# Examples



**Base Cases:**

$$R(1, 1, 0) = \varepsilon + 1$$

# Examples




**Base Cases:**

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$

# Examples




**Base Cases:**

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

# Examples



## Base Cases:


$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$


$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$R(1, 2, 1) = R(1, 2, 0) +$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$


$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$R(1, 2, 1) = R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0)$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$


$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + \end{aligned}$$



# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$


$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + (\varepsilon + 1)(\varepsilon + 1)^*0 \end{aligned}$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$


$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + (\varepsilon + 1)(\varepsilon + 1)^*0 = 1 * 0 \end{aligned}$$

## Examples



### Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$


$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + (\varepsilon + 1)(\varepsilon + 1)^*0 = 1 * 0 \end{aligned}$$

$$R(2, 2, 1) = R(2, 2, 0) + R(2, 1, 0)R(1, 1, 0)^*R(1, 2, 0)$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$


$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + (\varepsilon + 1)(\varepsilon + 1)^*0 = 1 * 0 \end{aligned}$$

$$\begin{aligned} R(2, 2, 1) &= R(2, 2, 0) + R(2, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= \varepsilon + 0 + 1 + \end{aligned}$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$


$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + (\varepsilon + 1)(\varepsilon + 1)^*0 = 1 * 0 \end{aligned}$$

$$\begin{aligned} R(2, 2, 1) &= R(2, 2, 0) + R(2, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= \varepsilon + 0 + 1 + \emptyset(\varepsilon + 1)^*0 \end{aligned}$$

# Examples



## Base Cases:

$$R(1, 1, 0) = \varepsilon + 1$$

$$R(2, 2, 0) = \varepsilon + 0 + 1$$

$$R(1, 2, 0) = 0$$

$$R(2, 1, 0) = \emptyset$$

$$\begin{aligned} R(1, 2, 1) &= R(1, 2, 0) + R(1, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= 0 + (\varepsilon + 1)(\varepsilon + 1)^*0 = 1 * 0 \end{aligned}$$

$$\begin{aligned} R(2, 2, 1) &= R(2, 2, 0) + R(2, 1, 0)R(1, 1, 0)^*R(1, 2, 0) \\ &= \varepsilon + 0 + 1 + \emptyset(\varepsilon + 1)^*0 = \varepsilon + 0 + 1 \end{aligned}$$

## Examples (Contd.)

$$\begin{aligned}L(A) &= R(1, 2, 2) \\&= R(1, 2, 1) + R(1, 2, 1)R(2, 2, 1)^*R(2, 2, 1) \\&= 1^*0 + 1^*0(\varepsilon + 0 + 1)^*(\varepsilon + 0 + 1) \\&= 1^*0(0 + 1)^*\end{aligned}$$

# Limitations of Finite Automata



## Limitations of Finite Automata

$$L_{0,1} = \{0^n 1^n \mid n \geq 0\}$$

[illegible]

# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

## *Proof.*

- ▶ Suppose there was a DFA accepting  $L_{0,1}$ .

# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

## *Proof.*

- ▶ Suppose there was a DFA accepting  $L_{0,1}$ . By Pigeon Hole Principle,  $\exists i, j \in \mathbb{N}$  such that  $i \neq j$

# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

## *Proof.*

- ▶ Suppose there was a DFA accepting  $L_{0,1}$ . By Pigeon Hole Principle,  $\exists i, j \in \mathbb{N}$  such that  $i \neq j$ , automaton reaches the same state after reading both  $0^i, 0^j$ .

# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

## *Proof.*

- ▶ Suppose there was a DFA accepting  $L_{0,1}$ . By Pigeon Hole Principle,  $\exists i, j \in \mathbb{N}$  such that  $i \neq j$ , automaton reaches the same state after reading both  $0^i, 0^j$ .
- ▶ Then  $0^i \cdot 1^j$  and  $0^j \cdot 1^j$  are both accepted or both rejected

# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

## *Proof.*

- ▶ Suppose there was a DFA accepting  $L_{0,1}$ . By Pigeon Hole Principle,  $\exists i, j \in \mathbb{N}$  such that  $i \neq j$ , automaton reaches the same state after reading both  $0^i, 0^j$ .
- ▶ Then  $0^i \cdot 1^j$  and  $0^j \cdot 1^j$  are both accepted or both rejected, which is a contradiction.


# Proving that $L_{0,1}$ is not a regular language

## *Lemma*

*There is no finite state automaton accepting  $L_{0,1}$*

## *Proof.*

- ▶ Suppose there was a DFA accepting  $L_{0,1}$ . By Pigeon Hole Principle,  $\exists i, j \in \mathbb{N}$  such that  $i \neq j$ , automaton reaches the same state after reading both  $0^i, 0^j$ .
- ▶ Then  $0^i \cdot 1^j$  and  $0^j \cdot 1^j$  are both accepted or both rejected, which is a contradiction.





# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

*Proof.*

By Pigeon Hole Principle.

# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

## *Proof.*

By Pigeon Hole Principle.

Suppose  $\exists x, y \in \Sigma^n$  such that  $x \neq y$

# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

## *Proof.*

By Pigeon Hole Principle.

Suppose  $\exists x, y \in \Sigma^n$  such that  $x \neq y$ ,  
automaton reaches the same state after reading both  $x, y$ .

# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

## *Proof.*

By Pigeon Hole Principle.

Suppose  $\exists x, y \in \Sigma^n$  such that  $x \neq y$ ,  
automaton reaches the same state after reading both  $x, y$ .  
Then  $x \cdot x^R$  and  $y \cdot x^R$  are both accepted or both rejected

# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

## *Proof.*

By Pigeon Hole Principle.

Suppose  $\exists x, y \in \Sigma^n$  such that  $x \neq y$ ,  
automaton reaches the same state after reading both  $x, y$ .  
Then  $x \cdot x^R$  and  $y \cdot x^R$  are both accepted or both rejected,  
which is a contradiction.

# Proving that PAL is not a regular language

## Lemma

$\forall n \in \mathbb{N}$  let  $PAL_n = \{w \cdot w^R \mid w \in \Sigma^*, |w| = n\}$ . Any automaton accepting  $PAL_n$  must have  $|\Sigma|^n$  states.

## *Proof.*

By Pigeon Hole Principle.

Suppose  $\exists x, y \in \Sigma^n$  such that  $x \neq y$ ,  
automaton reaches the same state after reading both  $x, y$ .  
Then  $x \cdot x^R$  and  $y \cdot x^R$  are both accepted or both rejected,  
which is a contradiction.



## *Corollary*

Let  $PAL = \cup_{n \geq 0} PAL_n$ .  $PAL$  is not regular.