

COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420
Indian Institute of Technology, Delhi
nbalaji@cse.iitd.ac.in

January 16, 2023

Lecture 6: Nondeterminism: Epsilon Transitions

Recap

- ▶ Languages, Decision problems.
- ▶ Finite State Automata - devices with finite memory.
- ▶ Deterministic Finite State Automata (DFA): From one state, reading an action we move to exactly one other state.
- ▶ Regular languages: L is regular if there exists some DFA A such that $L = L(A)$.
- ▶ Closed under Union, Intersection, Complement.

Recap

- ▶ Languages, Decision problems.
- ▶ Finite State Automata - devices with finite memory.
- ▶ Deterministic Finite State Automata (DFA): From one state, reading an action we move to exactly one other state.
- ▶ Regular languages: L is regular if there exists some DFA A such that $L = L(A)$.
- ▶ Closed under Union, Intersection, Complement.
- ▶ NFA: From one state, reading an action we move to a subset of states!

Recap

- ▶ Languages, Decision problems.
- ▶ Finite State Automata - devices with finite memory.
- ▶ Deterministic Finite State Automata (DFA): From one state, reading an action we move to exactly one other state.
- ▶ Regular languages: L is regular if there exists some DFA A such that $L = L(A)$.
- ▶ Closed under Union, Intersection, Complement.
- ▶ NFA: From one state, reading an action we move to a subset of states!
- ▶ Subset Construction: Every NFA has an equivalent DFA.

Recap



- ▶ Languages, Decision problems.
- ▶ Finite State Automata - devices with finite memory.
- ▶ Deterministic Finite State Automata (DFA): From one state, reading an action we move to exactly one other state.
- ▶ Regular languages: L is regular if there exists some DFA A such that $L = L(A)$.
- ▶ Closed under Union, Intersection, Complement.
- ▶ NFA: From one state, reading an action we move to a subset of states!
- ▶ Subset Construction: Every NFA has an equivalent DFA.
- ▶ Exponential blowup in state complexity unavoidable! NFAs indeed are very concise.

Recap

- ▶ Languages, Decision problems.
- ▶ Finite State Automata - devices with finite memory.
- ▶ Deterministic Finite State Automata (DFA): From one state, reading an action we move to exactly one other state.
- ▶ Regular languages: L is regular if there exists some DFA A such that $L = L(A)$.
- ▶ Closed under Union, Intersection, Complement.
- ▶ NFA: From one state, reading an action we move to a subset of states!
- ▶ Subset Construction: Every NFA has an equivalent DFA.
- ▶ Exponential blowup in state complexity unavoidable! NFAs indeed are very concise.
- ▶ Question: Can we always make sure a DFA has exactly one final/accepting state?



$$L = \{x \in \{a\}^* \mid |x| \text{ is divisible by 3 or 5}\}$$

$$L = \{x \in \{a\}^* \mid |x| \text{ is divisible by 3 or 5}\}$$



Epsilon Transitions

$$L = \{x \in \{a\}^* \mid |x| \text{ is divisible by 3 or 5}\}$$



Jump from a state to another without reading any letter.

Such transitions are called ϵ -transitions.

- ▶ How to define them formally?
- ▶ Are they more powerful than normal DFA/NFA?
- ▶ Usefulness?

Closure under union


Lemma

If L_1 and L_2 are regular then so is $L_1 \cup L_2$

Closure under union

Lemma

If L_1 and L_2 are regular then so is $L_1 \cup L_2$



Closure under concatenation

Lemma

If L_1 and L_2 are regular then so is $L_1 \circ L_2$


$$L_1 \circ L_2 = \{w_1w_2 \in \Sigma^* \mid w_1 \in L_1, w_2 \in L_2\}$$

Closure under concatenation

Lemma

If L_1 and L_2 are regular then so is $L_1 \circ L_2$

$$L_1 \circ L_2 = \{w_1w_2 \in \Sigma^* \mid w_1 \in L_1, w_2 \in L_2\}$$



Closure under Kleene star

Lemma

If L is regular then so is L^* .


$$L^* = \{w_1 w_2 \dots w_k \in \Sigma^* \mid k \geq 0 \ \forall i, w_i \in L\}$$

Closure under Kleene star

Lemma

If L is regular then so is L^* .

$$L^* = \{w_1 w_2 \dots w_k \in \Sigma^* \mid k \geq 0 \ \forall i, w_i \in L\}$$



Modelling epsilon transitions

Definition

An ε -nondeterministic finite-state automaton (ε -NFA) is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet, i.e., set of input symbols
- ▶ $\delta : Q \times (\Sigma \cup \varepsilon) \rightarrow 2^Q$ is a function that takes a state and input symbol and returns the set of possible next states,
- ▶ $q_0 \in Q$ is the start/initial state
- ▶ $F \subseteq Q$ is the set of final/accepting states.

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S .

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S . Inductive definition of $EClose(S)$:

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S . Inductive definition of $EClose(S)$:

- ▶ For all $q \in S$, $q \in EClose(S)$

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S . Inductive definition of $EClose(S)$:

- ▶ For all $q \in S$, $q \in EClose(S)$
- ▶ If $q \in EClose(S)$ and $q' \in \delta(q, \varepsilon)$, then $q' \in EClose(S)$.

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S . Inductive definition of $EClose(S)$:

- ▶ For all $q \in S$, $q \in EClose(S)$
- ▶ If $q \in EClose(S)$ and $q' \in \delta(q, \varepsilon)$, then $q' \in EClose(S)$.

Extended Transition Relation

Let $\hat{\delta} : Q \times \Sigma^* \rightarrow 2^Q$ be defined as:

- ▶ $\hat{\delta}(q, \varepsilon) = EClose(\{q\})$

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S . Inductive definition of $EClose(S)$:

- ▶ For all $q \in S$, $q \in EClose(S)$
- ▶ If $q \in EClose(S)$ and $q' \in \delta(q, \varepsilon)$, then $q' \in EClose(S)$.

Extended Transition Relation

Let $\hat{\delta} : Q \times \Sigma^* \rightarrow 2^Q$ be defined as:

- ▶ $\hat{\delta}(q, \varepsilon) = EClose(\{q\})$
- ▶ $\hat{\delta}(q, wa) = \bigcup_{q' \in \hat{\delta}(q, w)} EClose(\delta(q', a))$

Epsilon Closure

Definition

Let $(Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. For each set $S \subseteq Q$, $EClose(S)$ is the set of states reachable via ε -transitions from S . Inductive definition of $EClose(S)$:

- ▶ For all $q \in S$, $q \in EClose(S)$
- ▶ If $q \in EClose(S)$ and $q' \in \delta(q, \varepsilon)$, then $q' \in EClose(S)$.

Extended Transition Relation

Let $\hat{\delta} : Q \times \Sigma^* \rightarrow 2^Q$ be defined as:

- ▶ $\hat{\delta}(q, \varepsilon) = EClose(\{q\})$
- ▶ $\hat{\delta}(q, wa) = \bigcup_{q' \in \hat{\delta}(q, w)} EClose(\delta(q', a))$

Acceptance: An ε -NFA A accepts w iff $\hat{\delta}(q_0, w) \cap F \neq \emptyset$.

How Powerful are Epsilon Transitions

Question: Do ϵ transitions add expressive power to NFAs?

How Powerful are Epsilon Transitions

Question: Do ε transitions add expressive power to NFAs?

Answer: No!

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.

Removing Epsilon Transitions


Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.




Removing ϵ and adding transitions from EClose .

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.



Removing ϵ and adding transitions from $EClose$.

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.

Proof.

Let $A = (Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. Then, we construct NFA $A' = (Q', \Sigma, \delta', q'_0, F')$ s.t.,

- ▶ $Q' = Q$
- ▶ Σ is the same but no ε -transitions are used now.
- ▶ $\delta'(q, a) = EClose(\delta(q, a))$.
- ▶ $q'_0 = q_0$
- ▶ $F' = F$

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.

Proof.

Let $A = (Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. Then, we construct NFA $A' = (Q', \Sigma, \delta', q'_0, F')$ s.t.,

- ▶ $Q' = Q$
- ▶ Σ is the same but no ε -transitions are used now.
- ▶ $\delta'(q, a) = EClose(\delta(q, a))$.
- ▶ $q'_0 = q_0$
- ▶ $F' = F$

Correctness: $\forall w \in \Sigma^*$, w accepted by A' iff w is accepted by A .

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.

Proof.

Let $A = (Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. Then, we construct NFA $A = (Q', \Sigma, \delta', q'_0, F')$ s.t.,

- ▶ $Q' = Q$
- ▶ Σ is the same but no ε -transitions are used now.
- ▶ $\delta'(q, a) = EClose(\delta(q, a))$.
- ▶ $q'_0 = q_0$
- ▶ $F' = F$

Correctness: $\forall w \in \Sigma^*$, w accepted by A' iff w is accepted by A . Is this always true?

Removing Epsilon Transitions

Theorem

For any ε -NFA A , there exists an NFA A' (without ε -transitions) such that $L(A) = L(A')$.


Proof.

Let $A = (Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. Then, we construct NFA $A = (Q', \Sigma, \delta', q'_0, F')$ s.t.,



- ▶ $Q' = Q$
- ▶ Σ is the same but no ε -transitions are used now.
- ▶ $\delta'(q, a) = EClose(\delta(q, a))$.
- ▶ $q'_0 = q_0$
- ▶ $F' = F$

Correctness: $\forall w \in \Sigma^*$, w accepted by A' iff w is accepted by A . Is this always true? What if there are ε -transitions to start or final state? □


Removing Epsilon Transitions: A Caveat





Removing Epsilon Transitions: A Caveat



Removing Epsilon Transitions: A Caveat



Removing Epsilon Transitions: A Caveat



Removing Epsilon Transitions: Fix

- ▶ What went wrong?

Removing Epsilon Transitions: Fix

- ▶ What went wrong?
- ▶ Base case was handled incorrectly!
- ▶ Need to distinguish between first visit and subsequent visits of q_0 .

Proof.

Let $A = (Q, \Sigma, \delta, q_0, F)$ be an ε -NFA. Then, we construct NFA $A = (Q', \Sigma, \delta', q'_0, F')$ s.t.,

- ▶ $Q' = Q \cup \{\tilde{q}_0\}$
- ▶ Σ is the same but no ε -transitions are used now.
- ▶ $q'_0 = \tilde{q}_0$
- ▶ $F' = F \cup \{\tilde{q}_0\}$ (if $EClose(\{q_0\}) \cap F \neq \emptyset$) and F (otherwise)
- ▶ $\delta'(q, a) = EClose(\delta(EClose(q_0, a)))$ (if $q = \tilde{q}_0$), otherwise $EClose(\delta(q, a))$.



Handling Epsilon moves: The Algorithm

Lemma

For any NFA A with ϵ transitions, there is another NFA, say B , such that B has no ϵ transitions and $L(A) = L(B)$.

Handling Epsilon moves: The Algorithm

Lemma

For any NFA A with ϵ transitions, there is another NFA, say B , such that B has no ϵ transitions and $L(A) = L(B)$.

Proof Idea.

Construction in 3 steps:

- 1 **Saturate:** repeatedly add shortcuts that make ϵ -transitions redundant.
- 2 **Fix final states:** if some state reachable from initial state by ϵ -transitions is final, then make initial state as final!
- 3 **Remove** ϵ -transitions.