VulnSuite

VulnSuite is an internal security platform that finds and prioritises vulnerabilities, monitors servers for intrusion and coordinates approved response. It connects assessment findings with operational evidence while keeping responsibility, review and deployment requirements visible.

What the suite does

- Finds vulnerabilities across code, cloud, containers, hosts and APIs
- Scores and prioritises them by business risk
- Monitors Linux and Windows servers for intrusion
- Coordinates investigation and approved response

How it is governed

- Identity-provider login, four least-privilege roles
- Tenant isolation enforced inside PostgreSQL
- Immutable audit trail of every API action
- Passive by default; scans need explicit authorisation

Introducing VulnSuite | Built for Indian BFSI: RBI Cyber Security Framework and CERT-In obligations are embedded in every finding.

What the suite addresses

Security teams need a clear path from identifying exposure to deciding what action is justified. VulnSuite supports that process by linking findings, suspicious activity and investigation records, helping analysts prioritise work and document their decisions.

Reduce exposure

- Find vulnerable software and unsafe configurations
- Assess exposed services, APIs, TLS and cloud posture
- Turn thousands of raw CVEs into a short P0–P4 queue
- Track remediation, acceptance and false positives

Investigate and respond

- Connect host alerts with vulnerability findings
- Assign incidents, review evidence and track action
- Approve bounded containment and inspect receipts
- Answer auditors from one evidence trail

Selected detection signals support investigation; coverage is not equivalent to a complete EDR platform.

Platform coverage

Different assets expose different kinds of risk, from vulnerable libraries to unsafe cloud settings and suspicious host activity. VulnSuite brings assessment and monitoring into a common operational context, with coverage determined by configured tools and telemetry sources.

Assessment modules

- SCA, secrets and static code analysis
- Network, cloud, containers and asset discovery
- IaC, Kubernetes and external attack surface
- API testing and software supply-chain checks

Protection and operations

- Linux audit and Windows event adapters
- Access, process, malware and integrity signals
- SOC console, investigations and agent lifecycle
- Signed notifications and approved response plans

Assessment and protection services retain separate persistence and deployment boundaries.

Risk prioritisation and compliance

A single risk engine scores every finding, whichever tool produced it, so one queue replaces twenty tool-specific reports. Regulatory context travels with the finding: the RBI clause it maps to, and for critical items the CERT-In incident record needed within six hours.

One score, five buckets

- Every finding scored on exploit likelihood and asset context
- P0 ≥ 7.0 starts the CERT-In six-hour clock automatically
- Cross-tool corroboration recorded for auditors
- AI advisory signals never alter the deterministic score

Regulatory mapping

- RBI CSF Annex-I clause cited on each finding
- CERT-In incident JSON generated for every P0
- CIS, ISO 27001, NIST 800-53 and OWASP via scanner packs
- Tamper-evident PDF reports with SHA-256 footer

Missing CVSS falls back to severity; missing EPSS uses a configured floor so nothing is silently dropped.

Software and supply-chain risk

Applications inherit risk from their own code, third-party dependencies and build artifacts. These checks help teams understand what software contains, identify known weaknesses and retain supporting evidence so remediation and software release decisions can be reviewed.

Code and dependencies

- Trivy, pip-audit and OSV-Scanner collectors
- Semgrep and Bandit static analysis
- Gitleaks and TruffleHog secret detection, values redacted
- Checkov and Trivy infrastructure-as-code checks

Build and artifact evidence

- Syft software bill of materials
- Cosign signature and SLSA attestation checks
- VEX statements applied as documented downgrades
- Air-gap verification with a pinned public key

Coverage depends on configured targets, installed tools and available advisory data.

Infrastructure and API assessment

Exposed services, weak configurations and application interfaces can create paths into an organisation. Assessment collectors identify these conditions across selected targets, giving teams evidence to prioritise fixes and confirm which systems need closer investigation.

Infrastructure

- Passive nmap service discovery, aggressive modes refused
- testssl.sh TLS hygiene checks
- Kubescape cluster posture and runtime image scans
- Dockle container hardening checks

Applications and APIs

- Nuclei and OWASP ZAP assessment collectors
- Dynamic testing off by default, three independent gates
- External discovery with Subfinder and httpx
- Enumerated hosts filtered to authorised domains

Assessment scans complement host monitoring and inline WAF enforcement.

Cloud posture and discovery

Cloud estates change daily. Discovery keeps the asset inventory current across Azure, AWS and GCP, and posture benchmarks run under credentials that an administrator has explicitly bound to the tenant, so a scan can never reach further than the account it was approved for.

Posture and inventory

- Prowler Azure, AWS and GCP configuration benchmarks
- Azure Resource Graph, AWS and gcloud asset discovery
- Kubernetes context enumeration and domain discovery
- Nightly scheduled discovery per tenant

Credential discipline

- Each cloud account bound to one tenant by an admin
- Bindings hold references only; secrets are rejected
- Collectors run under the bound account, ambient keys stripped
- Unbound accounts fail closed, never widen scope

Read-only cloud roles are expected; VulnSuite never requests write permissions in the target accounts.

Scan authorisation and target safety

A scanning platform is itself a risk if it can be pointed at systems the organisation does not own. VulnSuite scans private networks freely but requires an administrator to attest ownership of public domains and ranges, and validates every target before it reaches a scanner.

Who may scan what

- Private address space scannable by definition
- Public hosts need an admin-approved domain or network scope
- Hostnames resolved before the check, no literal-only bypass
- Rules enforced in the API and again in the worker

Safe inputs

- Every target field validated for format and shell safety
- Repository paths confined to a workspace root
- Scanner binaries receive targets after an explicit separator
- Rejected requests recorded as denied in the audit trail

A bypassed API check is still caught at worker time; defence in depth is deliberate.

Verified identity and tenant isolation

Security operations involve sensitive evidence and actions that can interrupt services. Verified identity and explicit permissions establish who may act, while PostgreSQL enforces tenant boundaries itself, so an application bug cannot expose another organisation’s data.

Authentication and roles

- Verify token signature, issuer, audience and expiry
- Require signed tenant and explicit role claims
- Admin, analyst, auditor and viewer rights
- Sign-in and MFA follow identity-provider policy

Database boundaries

- Forced row-level security on all five tenant tables
- Tenant bound to every transaction from the token
- Schema owner separated from the runtime database role
- Runtime role cannot alter policies or audit rows

JWT verification and RLS controls are implemented; live IdP integration and database-role enforcement need staging.

Audit trail and analyst triage

Auditors and incident reviewers need to know who did what, when, and why a risk was accepted. Every authenticated API call is recorded in a table nobody can rewrite, and analyst decisions carry a justification, an owner and an expiry that the platform enforces.

Immutable API audit trail

- Actor, tenant, action, outcome and client IP per call
- Request IDs echoed back for log correlation
- Handler detail: targets requested, triage changes made
- Insert-only table guarded by a database trigger

Triage workflow

- Open, triaged, accepted and false-positive states
- Justification required for acceptance and false positive
- Acceptances expire within 365 days and reopen automatically
- Re-scans never silently close analyst-owned findings

A finding is auto-closed only when the tool that reported it completed cleanly and no longer reports it.

Unified operations console

An analyst investigating an alert needs to understand the affected host, its known weaknesses and any response already underway. The console brings that context together, helping teams coordinate investigation while making unavailable information visible.

Shared investigation view

- View intrusion alerts and vulnerability findings
- Inspect agent health, sensor status and version drift
- Create and assign incidents from selected alerts
- Review response plans before approval

Operational safeguards

- Apply the same API role checks to console actions
- Keep access tokens in browser-tab memory
- Report unavailable upstream sources explicitly
- Retrieve findings through a fixed HTTPS connector

The console shows bounded recent lists; it is not an exhaustive cross-platform evidence search.

Windows and Linux monitoring

Server monitoring depends on collecting useful activity from the operating system and making gaps visible. Windows event sources and Linux audit records provide investigation evidence, while sensor health indicators help teams distinguish quiet systems from missing telemetry.

Windows monitoring

- Security log authentication and network logons
- RDP and SMB evidence where source events support it
- Sysmon process-creation records
- Selected fields without raw command-line capture

Linux monitoring

- Event-driven audit execution records
- Linux /proc process polling
- SSH access, API denials and file-integrity signals
- Sensor health and missing-telemetry indicators

Windows and Linux support monitoring and approved containment. Native enforcement and recovery require staging validation.

Process and malware detection

Selected process patterns and reviewed malware indicators provide clues that warrant investigation. A known-bad hash match supplies specific file evidence; analysts can review its context before approving action, while missing scanners or telemetry remain visible as coverage limitations.

Suspicious activity

- Recognised web-server parent spawning a shell
- Execution from writable temporary locations
- Deleted executable signals on Linux
- Event records for short-lived processes

Malware evidence

- Known-bad SHA256 matches on selected targets
- Optional Linux selected-file ClamAV scans
- Path, signature and hash retained for review
- Unavailable scanners surface degraded coverage

Coverage excludes complete memory scanning and full-disk protection. File quarantine does not terminate a running process.

Lateral-movement signals

Activity that appears ordinary on one server can become suspicious when repeated across several hosts. Correlating authentication events helps analysts recognise possible account misuse or movement between systems, while retaining context needed to assess legitimate administrative activity.

Correlated patterns

- Password spraying across multiple hosts
- Same-user successful-login fan-out
- Suspected pivots from already flagged hosts
- Remote-access evidence from supported event sources

Investigation context

- Administrator-defined host-to-IP ownership
- Time-bounded correlation with retained evidence
- Retry, out-of-order and restart handling
- Expiring exceptions for reviewed false positives

NAT, shared accounts and legitimate automation need review; protocol labels require supporting source evidence.

WAF integration

Web application firewalls provide an enforcement point for traffic reaching protected applications. Connecting their signals with investigations helps teams understand attempted abuse and review scoped blocking decisions, with tuning and deployment checks needed to avoid disrupting legitimate requests.

On-premises or proxy WAF

- Nginx / ModSecurity and OWASP CRS templates
- Sanitised serial-JSON rule-match collection
- DetectionOnly starting configuration
- No request-body or credential export

Cloudflare response connector

- Use a configured zone and custom-ruleset scope
- Apply an approved source-IP block
- Embed fixed expiry in the provider rule
- Retry cleanup without extending the deadline

Rule ordering, provider permissions, propagation and real traffic enforcement remain staging checks.

Reviewed containment and response

Containment can interrupt business services, so response decisions need clear evidence and accountability. VulnSuite places file quarantine, process termination, host isolation, identity and WAF response behind separate approval and local policy checks, with recorded outcomes and reviewed recovery paths.

On the host

- Quarantine with approved path and SHA256 evidence
- Process termination after an identity re-check
- Isolation with kernel or scheduled-task expiry
- Restore and release as separately approved rollbacks

In the identity provider and WAF

- Entra ID session revocation, one shot
- Entra ID account disable for a fixed window
- Cloudflare block with provider-evaluated expiry
- Protected users, domains and executables enforced twice

Containment is disabled by default. Every action needs a second administrator; pre-approved isolation exists only for ransomware with dual opt-in.

Ransomware and log-tamper signals

Attackers encrypt data and erase their tracks. Decoy files, change-rate and entropy signals give the SOC minutes of warning on a share, while tamper signals, sequence numbers and a hash chain show when logs or stored evidence were altered, by which process and when.

Ransomware early warning

- Canary documents nothing legitimate touches
- Mass rename, rewrite and deletion thresholds
- High-entropy rewrites sampled from changed files
- Critical alert; optional pre-approved isolation

Log and record integrity

- Truncated, deleted or replaced log files reported
- auditd watch records with executable, PID and uid
- Windows log cleared and audit policy changes
- Sequence numbers and a hash chain with SIEM checkpoints

Encryption is detected at the next poll, not prevented; backups decide the outcome. The chain proves alteration, the off-host copy is the protection.

How the components fit

The assessment service evaluates exposure; the protection service handles telemetry, investigations and response. Their separate responsibilities help teams plan access, storage, maintenance and integration around the requirements of each service.

Assessment service

- FastAPI service, Celery workers and nightly scheduler
- PostgreSQL with tenant policies, Redis broker and cache
- Canonical findings, dedup and deterministic risk scoring
- Read-only findings feed into the operations console

Protection service

- Authenticated Linux and Windows agents
- One organisation per SQLite operational store
- Detection, incidents, policies and response history
- Independent delivery and cloud-response worker

SQLite protection persistence is not a horizontally scalable or highly available PostgreSQL backend.

Central agent lifecycle

Host monitoring depends on knowing which agents are enrolled, authorised and reporting correctly. Central lifecycle controls help maintain that inventory, replace credentials, withdraw access and identify policy or version differences that require administrator attention.

Credential management

- Issue expiring, one-time enrollment credentials
- Store hashes of enrolled host credentials
- Rotate keys and revoke agent access centrally
- Cancel unexecuted responses after revocation

Inventory and policy

- Track platform, agent version and queue health
- Record administrator policy-version history
- Flag drift from the desired software version
- Keep privileged response enablement local to hosts

Agent software installation and upgrades use an administrator-controlled rollout.

Incident and notification workflows

Investigations often involve several people and external operational systems. Incident records preserve ownership and decisions, while signed notifications carry relevant information to organisation-operated integrations, helping teams coordinate work and recover delivery after temporary service failures.

Investigation workflow

- Link alerts to owned incident cases
- Track status, notes and evidence timelines
- Protect concurrent edits with case versions
- Review alerts and add scoped, expiring exceptions

SIEM and ticketing bridges

- Send signed JSON to fixed HTTPS endpoints
- Persist delivery state, leases and retry attempts
- Attach stable keys for receiver deduplication
- Audit outcomes without storing upstream secrets

Webhooks support organisation-operated adapters; native Jira, ServiceNow or Splunk connectors are not implied.

Reliable delivery and retention

Network interruptions and growing evidence volumes can affect security operations. Persistent queues and acknowledgement checks support recovery after outages, while backup and retention controls help teams manage stored evidence according to investigation needs and operational requirements.

Telemetry continuity

- Keep events until exact acknowledgement
- Replay retained events after service outages
- Pause collection visibly when the queue is full
- Archive older events without fresh containment

Evidence maintenance

- Create consistent SQLite backups and verify restore
- Preview retention cleanup before applying it
- Preserve incident and response-linked evidence
- Create offline-agent and stale-sensor alerts

Schedule maintenance explicitly and measure capacity, recovery objectives and backup security in the target environment.

Hardened deployment

A security tool that downloads twenty scanners is a supply-chain target. Every binary in the image is pinned to a known checksum and verified at build time, the containers run unprivileged, and the whole stack can operate without internet access using locally mirrored vulnerability data.

Build integrity

- Every scanner download SHA-256 pinned and verified
- No pipe-to-shell, no floating "latest" versions
- Containers run as an unprivileged user
- Hash-locked Python dependencies

Runtime posture

- Redis authenticated; browser origins explicit, never wildcard
- No scanner telemetry egress
- Full offline mode with local vulnerability databases
- Secrets injected from a vault, never baked into images

Tests fail the build if any download lacks a pin or the runtime user is removed.

Validation evidence

The validation results demonstrate exercised code paths and selected native file behaviours. They provide evidence for technical review, while full containment effectiveness, host compatibility and operational performance require testing in the intended environment.

486 automated tests passed

- Access, roles, tenant and database-role boundaries
- Target safety, scopes, cloud bindings and audit trail
- Triage, scan lifecycle and deployment pinning
- Detection, enrollment, incident and response workflows

7 native Windows file checks passed

- Disposable file-operation contract fixtures
- Pinned-handle relative rename behavior
- File-sharing and junction-race checks
- Full ACL and firewall workflows require staging

Automated tests and narrow native file checks do not establish live containment efficacy or production readiness.

Required staging validation

Deployment conditions determine whether security controls work as intended. Staging should verify identity, database roles, telemetry, permissions, enforcement and recovery together, including how containment behaves during service interruptions and host restarts.

Identity and data

- IdP issuance, token lifetime and revocation behavior
- PostgreSQL policies with both deployed database roles
- Container image build and scanner compatibility
- Existing-database migration rehearsal

Hosts and enforcement

- Windows Security/Sysmon and Linux audit collection
- Cloudflare permissions, expiry and rule ordering
- Linux/Windows isolation, expiry and rollback
- False positives, overhead, backlog and recovery

Validate native Windows ACLs, firewall enforcement, scheduled-task expiry and reboot recovery before enabling containment.

Evaluating fit for your organisation

A suitable deployment starts with clear asset scope, accountable owners and measurable acceptance criteria. These decisions help teams assess coverage, operational impact, recovery expectations and the conditions under which approved response should be enabled.

Scope and ownership

- Select applications, APIs, cloud accounts and servers
- Identify incident owners and response approvers
- Approve the domains and networks in scope
- Agree retention and recovery requirements

Acceptance criteria

- Measure detection coverage and false positives
- Verify roles and separate-actor approval
- Exercise containment, expiry and restoration
- Measure host overhead and service recovery

Production deployment requires environment-specific validation and an approved operating procedure.