

Offline Facial Recognition & Liveness

Secure field-personnel authentication for zero-network zones

NHAI / MORTH — Hackathon 7.0

Fully offline · React Native (Android + iOS) · $\approx$ 10 MB models · CPU-only

The problem

Field personnel must be authenticated in **remote, zero-network** locations on **standard mid-range phones**, and it must drop into the existing **Datalake 3.0** React Native app.

Requirements:

- **Offline** face recognition + **liveness** (anti-spoofing)
- Lightweight model (**target ≤ 20 MB**), **< 1 s** recognition
- Android 8.0+ / iOS 12+, 3 GB RAM, **no GPU**
- **Open-source only**; sync + **purge** to server when network returns

Solution at a glance

```
Camera --> MediaPipe FaceMesh --> Liveness gate --> 112x112 crop
      --> MobileFaceNet (TFLite, FP16) --> 512-d embedding
      --> cosine match vs encrypted on-device template --> ✓ / ✗
                    |
                    v
auth event --> encrypted offline queue --> (on reconnect) sync --> purge
```

- **100% on-device** authentication — no network needed to enroll or verify
- Edge AI: **MobileFaceNet + ArcFace**, FP16, **6.5 MB**
- Liveness: **blink (EAR)** + **head-turn**, both offline
- **Sync & purge** audit lifecycle to an AWS-deployable backend

Innovation — edge model & compression

Asset	Size
MobileFaceNet/ArcFace (WebFace600K), FP16	6.5 MB
Total footprint	≈ 10.1 MB — ~50% of the 20 MB budget

- **ArcFace** angular-margin embeddings → robust across **diverse Indian demographics** and outdoor lighting (model family reports >99% on LFW-style).
- **FP16 quantization** halves size with negligible accuracy loss.
- **512-d, L2-normalized** → stable cosine matching; multi-frame **centroid** enrollment (front/left/right) for pose/lighting robustness.

Offline liveness (anti-spoofing)

Two **scale-invariant** signals from FaceMesh — pass by **blink OR head-turn**:

- **Blink** = Eye-Aspect-Ratio dips closed (≤ 0.19) then opens (≥ 0.27) across frames. A photo/screen holds constant EAR $\rightarrow$ **fails**.
- **Head-turn** = nose offset / eye-distance ≥ 0.07 .

The match is gated — login refuses to run recognition until liveness passes, defeating the photo/replay attack. Logic is **pure & unit-tested**.

Feasibility — speed < 1 s, easy integration

- **In-app Benchmark screen** times `detect → crop → infer → match` over 20 runs and shows a per-stage table + a **< 1 s** verdict on the **core** compute (measured live on-device; Home → Benchmark).
- **CPU-only** (`default` TFLite delegate) — no GPU; runs on mid-range hardware.
- **Drop-in SDK**: `src/faceAuth/sdk` exposes `embed/match/liveness/enroll/sync` without our screens. See `docs/INTEGRATION.md` for the Datalake-3.0 guide.

Scalability & Sustainability — Sync & Purge

Offline events are durably queued (encrypted), then on reconnect:

1. `POST /sync/events` → server confirms `acceptedEventIds`
2. `POST /sync/purge-ack` → server marks **PURGED** (kept for audit)
3. Device **deletes the local row** — **ACK-before-purge**
 - Triggers: **NetInfo reconnect**, retry interval, app-foreground
 - Visible live on the **Sync & Purge** screen ("Synced & purged" counter)
 - Backend: Go + MongoDB, **AWS-deployable** (ECS/EC2 + DocumentDB)

Architecture

Layer	Tech
Mobile app	React Native 0.80 (TS), VisionCamera
	<code>react-native-fast-tflite</code>
Geometry/liveness	MediaPipe Face Landmarker (478 pts)
Backend	Go + Gin + MongoDB, Ed25519-signed profiles, JWT

Cross-platform: native modules for **both Android (Kotlin) and iOS (Swift)**.

Open-source & compliance

- **MobileFaceNet/ArcFace** — InsightFace, **MIT**
- **MediaPipe Face Landmarker** — Google, **Apache-2.0**
- TFLite, VisionCamera, React Native, NetInfo — **MIT / Apache-2.0**
- **No additional licenses required.** Full attribution in `THIRD_PARTY_LICENSES.md`.

Meets: Android 8.0+/iOS 12+ · 3 GB RAM · no GPU · ≤ 20 MB · offline.

Roadmap

- Add smile (mouth-aspect-ratio) as a third selectable liveness challenge
- On-device FAR/FRR study across demographics & lighting
- Native iOS TFLite delegate tuning (Core ML) for extra headroom
- Hard-delete purged events server-side after a retention window

Thank you

Offline. Lightweight. Secure. Cross-platform.

Source + docs: `README.md` · `docs/TECHNICAL_DOCUMENTATION.md` ·
`docs/INTEGRATION.md`