

Order

(1) OrderType

What kind of order is this?

orderTypeId* → Sales-order, Purchase-order
 parentTypeId → For sub-type (Self-referential hierarchy)
 hasTable → whether a detail table exists for this table
 description → Human-readable label

connects to : OrderHeader (one OrderType → many OrderHeader)

(2) OrderHeader

The master record of every order.

orderId → unique internal order ID (eg → 10001)
 orderTypeId → Sales-order
 orderName → HCDDEV# 3344 (Shopify-order-name)
 externalId → 5916412870909 (Shopify-order-id)
 SaleschannelEnumId → Web, Sale-Pos, Phone
 orderDate → When customer placed the order
 entryDate → When order entered the system.
 statusId → Order completed (current status)
 createdBy → Harsh Mahajan (user login who create the order)
 grandTotal → 1000 (Total order value)

(3) OrderItemType

orderItemTypeId → Bill-order-item, Work-order-item, Purchase-specific
 parentTypeId → purchase-specific
 hasTable → N
 description → This is PO: Inventory.

(4) OrderItem

Each line item in Order

PK: OrderId, OrderItemSeqId

OrderId → 1001

OrderItemSeqId → 1001, 1002

ExternalId → Shopify order Id

OrderItemTypeId → Product_Order-Item

ProductId → 10010

quantity → 70 (actual selling price per unit)

unit price → 100 (original price before discount)

ShipGroupSeqId → 101

StatusId → Item-Approved (current status)

Cancelquantity → 1

eg →

Order-Id	Order-ItemSeq-Id	Ship-Group-Seq-Id	Shipment Method TYPE-id
1001	101	0001	BoPIS
1001	102	0002	Standard
1001	103	0003	Third Day

(5) OrderRole

who is involved in this order?

PK: OrderId, PartyId, RoleTypeId

OrderId* → The order → 1084

PartyId* → The person or org → 10059 → id se PartyTypeId

RoleTypeId* → What role they play → Bill-to-customer

Order-Id	Party-id	Role-type-id
1001	10053	Bill-to-customer
1001	10053	Ship-to-customer
1001	10533	Bill-from-Vendor

Role types in oms:

Ship-To-Customer → the delivery recipient
 Bill-To-Customer → who gets the invoice
 Placing-customer → who placed the order
 End User-Customer → actual end user
 Supplier-Agent → dropship vendor

(6) OrderStatus

Audit trail of every status change

OrderStatusId → Auto-generated
 StatusId → What status was set
 OrderId → The order Id
 OrderItemSeqId → id for items

OrderStatusId	Status Id	Order Id	Order seq Id	Time
100	Order created	10035	null	10
101	Item-Created	10035	101	11
102	Payment-authorized	10035	null	12
103	Order approved	10035	null	1
104	Item-approved	10035	101	2

Order Status lifecycle:

Order-created → Order-Approved → Order-processing →
 → Order-complete
 → Order-cancelled
 → Order-rejected

Item-Created → Item-approved → Item-cancelled
 → Pick/Pack/Ship → Item-Complete

(7) Order-Adjustment

Discount, taxes, shipping charges.

OrderAdjustedId	→ Unique Id
OrderAdjustmentTypeId	→ Sales Tax, Promotion, Shipping-charges, GST+Tax, appeasement
OrderId	→ FK
OrderItemSeqId	→ item level adjustment
ShipGroupSeqId	→ 1 st item → Standard → shipping charges; 2 nd item → BOPIS
Amount	→ adjustment value

Note :- VAT-Tax is include in price

OAI	OATI	OI	OISI	SHSI	Amount
1	Sales Tax	100	101	11	100
2	FEE	100	102	12	20
3	Shipping charges	100	102	12	50
4	Promotion	100	102	12	100

(8) OrderItemShipGroup :

A shipping package/group from this order.

FK :- OrderId, ShipGroupSeqId

↳ (shipping-charges inc in here)
hai to all new build bang

OrderId → 101

ShipGroupSeqId → 101, 102, 103

ShipmentMethodTypeId → BOPIS, FEDEX, Two-Day, Standard.

FacilityId → which store/warehouse will fulfill

ContactMechId → FK (10010)

CarrierPartyId → FK the carrier company

CarrierRateTypeId → Carrier

Note :- FacilityId here is set by the brokering engine. It represents the fulfillment location assigned to fulfill these items.

(9) OrderItemShipGroupAssoc
Which item go in which ship group?
PK: OrderId, OrderItemSeqId, ShipGroupSeqId

(10) OrderPaymentPreference
How is the order being paid?
PK: OrderPaymentPreferenceId

OrderPaymentPreferenceId	OT	Payment-Method-Type-Id
1001	101	EXT-SHOP-VISA
1002	102	EXT-SHOP-PAYPAL
1003	103	Cash-ON-DELIVERY
1004	103	EXT-SHOP-OTHER

maxAmount → max amount to charge against this method.
StatusId → current status (Payment - Authorized, Received, cancelled)

(11) OrderContactMech
Address associated with the order

OrderId* → 1001
ContactMechPurposeTypeId* → Primary-Email, Primary-Mobile, Shipping-Location
ContactMechId* → 1001 (F31)

(12) OrderShipment
Link an order item to a physical shipment.

OrderId* → 100 ShipGroupSeqId → 10001
OrderItemSeqId* → 101, 102
ShipmentId* → 1
ShipmentItemSeqId* → 1001
Quantity → 10

I ordered itemA, itemE, itemZ, itemO
(101 102 103 104)

§1

item 1	101
item 0	102
item	
item 0	104

82

itemD
itemE 102
itemN

83

itemx
itemy
itemz 103

Ek shipment me apne 2 items thi ho sakte hai, uske humne ship ^{from} ~~from~~ _{to}
 thi change. to identify specific item in same shipment.

Case $\rightarrow$ Same item ke different shipmentID ho sakta hai. example
more ex order me 5 item bulay same quantity = 5.

Matlab orderItemSeqId same hogi bas quantity = 5.

for ~~over~~ 2-quantity + 2 quantity ¹ day ¹ day facility so
puffball has to 2 shipment longer means 2 shipment Id.

This is the bridge between OMS and the shipment fulfillment system.

(13) Credit Billing

impl order form to invoices

orderId*, orderItemSeqId*, InvoiceId*, invoiceItemSeqId*

hum ye ~~stare~~ machi karte

(14) OrderItemChange

Audit log of item mutations

PK: OrderItemChangeId

Ye table Data Model Book me nahi hai.

OrderItemChangeId → unique log entry (1001)

orderId → orderId (100)

OrderItemSeqId → Sequence Id of order (1001, 1002)

ChangeTypeEnumId → ord-item-update

Quantity → 10

ReasonEnumId → Reason code (changed-Mind)

ChangeTypeEnumId

- Item-delivery-date-chngd

- Ord-item-append

- Ord-item-cancel

- Ord-item-update

ReasonEnumId

- Auto-cancel

- cheaper-alternative

- OICR-Micro-order-item

- Bad review

- Not required

- other reason

- changed-Mind

- OICR-chang-Mind

- Shopping-cancellation

(15) OrderItemShipRes

Inventory Reservations

orderId * → 101

Ship-group-seq-Id * → 101, 102

Order-item-seq-Id * → 1, 2

Inventory-item-id * → 10001 (PK)

reserve-order-enum-Id → INV-REC

↳ Inv-RES-order

(16) Order Attribute

Custom Key-value data on an order.

orderId*	attrName*	attrValue*	attrDescription
101	Shopify-UserId	770019569	user id
101	Order type	regular	Regular

↑ Source: Ob Biz-Framework / application / datamodel / entitydef / order-entitymodel.xml

Detail Order: Return Entities:-

(1) ReturnHeaderType

What kind of return is this?

ReturnHeaderTypeId* → Customer-Return, Vendor-Return, Trade-In, Appliance
parentTypeId → id hierarchical parent type
description → Human readable label

(2) ReturnHeader

The master record of a return.

returnId → 1000
returnHeaderTypeId → Customer-Return
statusId → Return-Completed
fromPartyId → 105 (who is returning (the customer))
toPartyId → 106 (who receives the return (the company))
destinationFacilityId → which Warehouse/store receives the returned goods
needsInventoryReceive → 4 = returned good must be received into inventory.
Case → Sometimes item is not returned in order return.
Example → Protein Powder.
return-channel-enumId → Ecom-RTN-channel, POS-RTN-channel.

(3) ReturnItem

Each product line in the system;

returnId* → id (FK → returnHeader)

returnItemSeqId* → sequence within system

orderId → id (FK → orderHeader)

orderItemSeqId → id FK → orderItem

productId → id (FK → Product) Product being return

returnTypeId → RTN-Credit → store credit

RTN-Refund → refund

RTN-Repair-Replacement → repair replacement

RTN Replace → replacement

RTN-CSReplace → cross-ship replacement

returnItemTypeId → return digital good item

return finished good item

return non-product item

return service product item

(4) ReturnReason

Why is the customer returning?

returnReasonId*

description, SequenceId

Return-Reason-Id

- Color
- defective
- Miscellaneous
- other
- not met want
- Size too large
- Size too small

returnType → what does the customer want back?

returnItemType → what kind of thing is being returned?

(5) ReturnItemMap

Auto-mapping order item → return item type

returnItemMapKey* → Source type Id (productId, orderAdjustmentType)

returnHeaderType* → Type of return this mapping applies to (customer)

returnItemId → what returnType to use for this mapping

(6) ReturnAdjustment

ReturnAdjustments (taxes, shipping, promos)

returnAdjustmentId → id (PK)

returnTypeId → id (FK → returnAdjustmentType)

returnId → id (FK → returnHeader)

returnAdjustmentTypeId → id (FK → returnAdjustmentType)

returnItemSeqId → optional

amount → adjustment value

orderAdjustmentId → original order adjustment being reversed.
orderId?

RAI	RATI	RI	RISI	RTI
1000	SalesTax	1	101	refund
1001	replacement	1	102	refund

AdjustmentType : - RET_Promotion_Adj → reversal of a promotional Adjustment
- RET_Shipping_Adj → refund of shipping charges
- RET_SalesTax_Adj → tax refund
- RET_Discount_Adj → discount reversal

(7) ReturnStatus

returnStatusId* → id (PK) auto generated
 statusId → which status was set.
 returnId → the return
 statusDateTime → date-time

(8) ReturnItemResponse

What was actually done to resolve the return?
 Records the outcome of the return - was it refund payment,
 A store credit, or new replacement order?

(9) ReturnItemShipment

The physical inbound return shipment

returnId*	RISI*	shipmentId*	SISI*	quantity
1	1	101	11	2
1	2	101	12	1
1	3	102	11	3

(10) CommunicationEventReturn

communication tied to a return

returnId* → id (FK → returnHeader)
 communicationEventId* → id (FK → communicationEvent)