

DEPARTMENT OF COMPUTER SCIENCE & TECHNOLOGY

"T2 Examination, MARCH-2020"

Semester: 4th

Subject: Operating System

Programme: CSE

Course Type: Core

Time: 90 Minutes

Max.Marks: 30

Date of Exam: 24/03/2020

Subject Code: CSH206B-T

Session: (II) 1:00AM-3:30PM

Course Nature: Hard

Branch: CSE

Signature: HOD/Associate HOD:

PART A (All questions are compulsory)

Q1. Answer the following:

(a) Mention which scheduling algorithm would be used in following situations: [5]

- (i) The process needs to be scheduled in order of its arrival in a non-preemptive manner.
- (ii) Front end processes need to be scheduled first followed by back end processes.
- (iii) The processes need to be scheduled in ascending order of burst time in a non-preemptive manner.
- (iv) The processes need to be scheduled in ascending order of burst time in a preemptive manner
- (v) This scheduling algorithm allocates time quantum to each process for fair CPU utilization.

(b) Answer the following as to how would you achieve the following with justification:[5]

- (i) To solve the problem of starvation through scheduling algorithm for processes that have aged in the system.
- (ii) The synchronization tool used for successful critical section execution of n number of cooperating processes.
- (iii) Deadlock management conditions to ensure that the system will never enter a deadlock state.
- (iv) Deadlock algorithm to ensure deadlock avoidance when there are multiple instances of resource types.
- (v) To solve the issue of race condition.

PART B (Attempt all questions. Each question carries 10 marks)

Q2. (a) Following is a scenario where P represents process and R represents a resource type. There are 2 instances of R1 and two instances of R2 available in the system. Determine if the system is in 'safe' state. Justify your answer with a resource allocation graph. [5]

Allocation:

- P1 is allocated one instance of R2.
- P2 is allocated one instance of R1.
- P3 is allocated one instance of R1.
- P4 is allocated one instance of R2.

Request: P3 is requesting one instance of R2.

(b) Consider the following snapshot of a system:

Process	Allocation				Max				Available			
	A	B	C	D	A	B	C	D	A	B	C	D
P0	2	0	0	1	4	2	1	2	3	3	2	1
P1	3	1	2	1	5	2	5	2				
P2	2	1	0	3	2	3	1	6				
P3	1	3	1	2	1	4	2	4				
P4	1	4	3	2	3	6	6	5				

Answer the following questions using banker's algorithm:

- What will be the contents of the need matrix? [2]
- Whether the system is in safe state? if yes, then what is the safe sequence. [1]
- If a request for process P1 arrives for (1,1,0,0), can the request be granted immediately? [1]
- If a request for process P4 arrives for (0,0,2,0), can the request be granted immediately? [1]

Q3. (a) Consider the set of 5 processes whose arrival time and burst time are given below- If the CPU scheduling policy is Round Robin with time quantum = 2 units, Draw a Gantt chart and calculate the average waiting time and average turnaround time. [5]

Process	Arrival Time	Execution Time
P1	0	5
P2	1	3
P3	2	1
P4	3	2
P5	4	3

- Apply SRTF on 3 processes with their arrival times zero, and having burst time ten, twenty & thirty units respectively. Each process undergoes input/output for first twenty percent of time, & next seventy percent of time is spent on execution and last ten percent time is again consumed on input/output. New process gets scheduled either when the running process gets blocked on input/output or when the running process finishes its burst. Assuming all input/output can be overlapped as much as possible, draw the Gantt chart & calculate for what percentage of time does the CPU remain idle? [2.5]
- A Counting Semaphore was initialized to 12. then 10 P (wait) and then 4 V (Signal) operations were computed on this semaphore. What is the result? [2.5]