



<b>Experiment No.7</b>
Implement Circular Linked List ADT.
Name: Harsh Naik
Roll No: 32
Date of Performance: 12/09/23
Date of Submission: 26/09/23
Marks:
Sign:

### **Experiment No. 7: Circular Linked List Operations**

#### **Aim: Implementation of Circular Linked List ADT Objective:**

In circular linked list last node is connected to first node. On other hand circular linked list can be used to implement traversal along web pages.

#### **Theory:**

In a circular linked list, the last node contains a pointer to the first node of the list. We can have a circular singly linked list as well as a circular doubly linked list. While traversing a circular linked list, we can begin at any node and traverse the list in any one direction, forward or backward, until we reach the same node where we started. Thus, a circular linked list has no beginning and no ending.

#### **Inserting a New Node in a Circular Linked List**

Case 1: The new node is inserted at the beginning.



Case 2: The new node is inserted at the end.

Deleting a Node from a Circular Linked List Case

1: The first node is deleted.

Case 2: The last node is deleted.

Insertion and Deletion after or before a given node is same as singly linked list.

### Algorithm

Algorithm to insert a new node at the beginning

Step 1: IF AVAIL = NULL

Write OVERFLOW

Go to Step 9 [END OF IF]

Step 2: SET NEW\_NODE = AVAIL

Step 3: SET AVAIL = AVAIL → NEXT

Step 4: SET NEW\_NODE → DATA = VAL

Step 5: SET PTR = START

Repeat Step 6 while PTR NEXT != START

Step 6: SET PTR = PTR NEXT [END OF LOOP]

Step 7: SET NEW\_NODE → NEXT = START

Step 8: SET PTR → NEXT = START

Step 9: SET START = NEW\_NODE

Step 10: EXIT

Algorithm to insert a new node at the end

Step 1: IF AVAIL = NULL

Write OVERFLOW

Go to Step 11 [END OF IF]

Step 2: SET NEW\_NODE = AVAIL



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

Step 3: SET AVAIL = AVAIL--> NEXT  
Step 4: SET NEW\_NODE -->DATA = VAL  
Step 5: SET NEW\_NODE-->NEXT = START  
Step 6: SET PTR = START  
Step 7: Repeat Step 8 while PTR--> NEXT != START  
Step 8: SET PTR = PTR -->NEXT [END OF LOOP]  
Step 9: SET PTR -->NEXT = NEW\_NODE  
Step 10: EXIT

Algorithm to delete the first node

Step 1: IF START = NULL  
    Write UNDERFLOW  
    Go to Step 6 [END OF IF]  
Step 2: SET PTR = START  
Step 3: Repeat Step 4 while PTR--> NEXT != START  
Step 4: SET PTR = PTR -->NEXT [END OF LOOP]  
Step 4: SET PTR □ NEXT = START -->NEXT  
Step 5: FREE START  
Step 6: EXIT

Algorithm to delete the last node

Step 1: IF START = NULL  
    Write UNDERFLOW  
    Go to Step 7 [END OF IF]  
Step 2: SET PTR = START [END OF LOOP]  
Step 3: Repeat Step 4 and Step 5 while PTR -->NEXT != START  
Step 4: SET PREPTR = PTR  
Step 5: SET PTR = PTR -->NEXT  
Step 6: SET PREPTR-->NEXT = START



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

Step 7: FREE PTR

Step 8: EXIT

### Code:

```
#include <stdio.h>

#include <conio.h>

#include <malloc.h> struct
node
{
    int data; struct
    node *next;
};

struct node *start = NULL; struct node
*create_cll(struct node *); struct node
*display(struct node *); struct node
*insert_beg(struct node *); struct node
*insert_end(struct node *); struct node
*delete_beg(struct node *); struct node
*delete_end(struct node *); struct node
*delete_after(struct node *); struct node
*delete_list(struct node *); int main()
{
    int option; clrscr();

    do
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
{  
printf("\n\n **MAIN MENU **");  
printf("\n 1: Create a list"); printf("\n 2: Display  
the list"); printf("\n 3: Add a node at the  
beginning"); printf("\n 4: Add a node at the  
end"); printf("\n 5: Delete a node from the  
beginning"); printf("\n 6: Delete a node from the  
end"); printf("\n 7: Delete a node after a given  
node"); printf("\n 8: Delete the entire list");  
printf("\n 9: EXIT"); printf("\n\n Enter your  
option : "); scanf("%d", &option); switch(option)  
{  
case 1: start = create_cll(start); printf("\n  
CIRCULAR LINKED LIST CREATED"); break;  
case 2: start = display(start); break; case 3:  
start = insert_beg(start); break; case 4: start  
= insert_end(start);  
  
break; case 5: start = delete_beg(start);  
break; case 6: start = delete_end(start);  
break; case 7: start = delete_after(start);  
break; case 8: start = delete_list(start);  
printf("\n CIRCULAR LINKED LIST DELETED");  
break;
```



```
}  
  
}while(option !=9);  
  
getch();  
  
return 0;  
  
}  
  
struct node *create_cll(struct node *start)  
{  
  
    struct node *new_node, *ptr;  
  
    int num; printf("\n Enter -1 to  
end"); printf("\n Enter the  
data : "); scanf("%d", &num);  
  
    while(num!=-1)  
    {  
  
        new_node = (struct node*)malloc(sizeof(struct node));  
  
        new_node -> data = num; if(start == NULL)  
        {  
  
            new_node -> next = new_node; start  
= new_node;  
        }  
  
        else { ptr = start;  
while(ptr -> next != start)  
  
ptr = ptr -> next; ptr ->  
  
next = new_node;  
  
new_node -> next = start;
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
}

printf("\n Enter the data : ");

scanf("%d", &num);

}

return start;

}

struct node *display(struct node *start)

{

struct node *ptr;

ptr=start; while(ptr->

next != start) { printf("\t

%d", ptr->data); ptr =

ptr->next;

}

printf("\t %d", ptr->data); return

start;

}

struct node *insert_beg(struct node *start)

{

struct node *new_node, *ptr; int num; printf("\n Enter

the data : "); scanf("%d", &num); new_node = (struct

node *)malloc(sizeof(struct node)); new_node->data

= num;
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
ptr = start; while(ptr ->
next != start) ptr = ptr ->
next; ptr -> next =
new_node; new_node ->
next = start; start =
new_node; return start;
}

struct node *insert_end(struct node *start)
{
struct node *ptr, *new_node; int num; printf("\n Enter
the data : "); scanf("%d", &num); new_node = (struct
node *)malloc(sizeof(struct node)); new_node -> data
= num;
ptr = start; while(ptr ->
next != start) ptr = ptr ->
next; ptr -> next =
new_node; new_node ->
next = start; return start;
}

struct node *delete_beg(struct node *start)
{
struct node *ptr; ptr =
start; while(ptr -> next !=
start) ptr = ptr -> next;
```





# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
ptr -> next = start -> next;
```

```
free(start); start = ptr ->
```

```
next; return start;
```

```
}
```

```
struct node *delete_end(struct node *start)
```

```
{
```

```
struct node *ptr, *preptr;
```

```
ptr = start; while(ptr ->
```

```
next != start)
```

```
{
```

```
preptr = ptr; ptr
```

```
= ptr -> next;
```

```
}
```

```
preptr -> next = ptr -> next;
```

```
free(ptr); return start;
```

```
}
```

```
struct node *delete_after(struct node *start)
```

```
{
```

```
struct node *ptr, *preptr; int val; printf("\n Enter the value after
```

```
which the node has to deleted : "); scanf("%d", &val); ptr = start;
```

```
preptr = ptr; while(preptr -> data != val)
```

```
{
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
preptr = ptr; ptr
= ptr -> next;
}
preptr -> next = ptr -> next;
if(ptr == start) start =
preptr -> next; free(ptr);
return start;
}
struct node *delete_list(struct node *start)
{
struct node *ptr; ptr =
start; while(ptr -> next !=
start) start =
delete_end(start);
free(start); return start;
}
```

**Output:**



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
**MAIN MENU **
1: Create a list
2: Display the list
3: Add a node at the beginning
4: Add a node at the end
5: Delete a node from the beginning
6: Delete a node from the end
7: Delete a node after a given node
8: Delete the entire list
9: EXIT
```

Enter your option : 1

Enter -1 to end

Enter the data : 2

Enter the data : 3

Enter the data : -1\_

```
1: Create a list
2: Display the list
3: Add a node at the beginning
4: Add a node at the end
5: Delete a node from the beginning
6: Delete a node from the end
7: Delete a node after a given node
8: Delete the entire list
9: EXIT
```

Enter your option : 2

2 3

```
**MAIN MENU **
1: Create a list
2: Display the list
3: Add a node at the beginning
4: Add a node at the end
5: Delete a node from the beginning
6: Delete a node from the end
7: Delete a node after a given node
8: Delete the entire list
9: EXIT
```

Enter your option : \_



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

```
1: Create a list
2: Display the list
3: Add a node at the beginning
4: Add a node at the end
5: Delete a node from the beginning
6: Delete a node from the end
7: Delete a node after a given node
8: Delete the entire list
9: EXIT
```

Enter your option : 2

1 2 3

**\*\*MAIN MENU \*\***

```
1: Create a list
2: Display the list
3: Add a node at the beginning
4: Add a node at the end
5: Delete a node from the beginning
6: Delete a node from the end
7: Delete a node after a given node
8: Delete the entire list
9: EXIT
```

Enter your option :

### Conclusion:

1) Write an example of insertion and deletion in the circular linked list while traversing the web pages?

- The provided code is a C program that implements a menu-driven system for creating, displaying, inserting, and deleting nodes in a circular linked list. It provides various options to manipulate the circular linked list.

However, there is an issue with the code related to the 'clrscr()' and 'getch()' functions, which appear to be from the old Borland C compiler and may not be compatible with modern compilers or environments. Additionally, the code uses the '<conio.h>' and '<malloc.h>' headers, which are not part of the standard C library and are specific to certain compilers.

Regarding your question about a circular linked list example related to web page traversal, here's a conceptual example:

Assume you want to implement a browser history using a circular linked list. Each node in the list represents a web page, and the 'next' pointer connects the current page to the next page you visit.



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

---

1.     \*Insertion\*: When you visit a new web page, you would insert it into the circular linked list. The 'insert\_end' function in the code could be used for this purpose. It appends the new page to the end of the list, making it the next page in the browsing history.
2.     \*Deletion\*: When you want to go back to the previous page, you can delete the last page you visited. The 'delete\_end' function in the code could be used for this. It removes the last page, effectively taking you back in your browsing history.

By using this circular linked list, you can easily navigate forward and backward through the web pages you've visited, making it a suitable data structure for managing browser history. However, in a real web browser, you would need to store more information about each web page, such as the page URL, title, etc. The code you provided mainly deals with the 'data' field in the nodes, which could be expanded to include more information for a practical implementation.