

Atlas X200 Product Manual

Overview

The Atlas X200 is a rugged, industrial-grade wireless access point designed for use in harsh environments. It features a compact, fanless design, making it suitable for indoor and outdoor applications. The device supports both 2.4GHz and 5GHz Wi-Fi, providing high throughput and low latency. It is the default configuration for the Atlas X200. The device is supplied with a standard power supply and a mounting bracket, providing a platform for integration into various systems.

Specifications

The Atlas X200 is a rugged, industrial-grade wireless access point. It features a compact, fanless design, making it suitable for indoor and outdoor applications. The device supports both 2.4GHz and 5GHz Wi-Fi, providing high throughput and low latency. It is the default configuration for the Atlas X200. The device is supplied with a standard power supply and a mounting bracket, providing a platform for integration into various systems.

Installation

Mount the device in a secure location, ensuring adequate clearance for ventilation. The device supports PoE (Power over Ethernet) and can be configured via a web interface or command line. Device initialization is required, including setting the IP address and password. The device will initialize and will initialize.

Networking

The Atlas X200 is a rugged, industrial-grade wireless access point. It features a compact, fanless design, making it suitable for indoor and outdoor applications. The device supports both 2.4GHz and 5GHz Wi-Fi, providing high throughput and low latency. It is the default configuration for the Atlas X200. The device is supplied with a standard power supply and a mounting bracket, providing a platform for integration into various systems.

Wireless Configuration

The Atlas X200 is a rugged, industrial-grade wireless access point. It features a compact, fanless design, making it suitable for indoor and outdoor applications. The device supports both 2.4GHz and 5GHz Wi-Fi, providing high throughput and low latency. It is the default configuration for the Atlas X200. The device is supplied with a standard power supply and a mounting bracket, providing a platform for integration into various systems.

Error Codes

Error code

powered on
checksum
Error code
code E-22
recommend
interface.

LED Indicators

A solid green
booting or
error code
traffic. The
when nego

Maintenance

Inspect the
days in du
recessed re
before any
every five y

Troubleshooting

If the device
fully seated
channel is
that hardw
unreachabl
codes.

Security

Administrat
authenticat
timestamp.
image is r
deployment

Error Code Reference

The followi
down. E-10
address po
configurati
mismatch.
blocked. E

temperature
below its r
expired. E-
module wa

Frequently Asked Questions

How do I re
which resto
Yes, but on
does not su
of VPN tun
4000 lease
uses SKU-

Compliance and Power

The Atlas
adapter is
millisecond
eMMC bef
ambient.

Warranty

The Atlas
purchase.
unauthorize
the device
business d