Policy as an Interface:
Authoring and Evaluating Moderation with Language and Decision Models

Harsh Singhal

October 29, 2026 | Review draft v0.6

Abstract

A moderation policy can now be an input to the system that enforces it. Policy authors can change model behavior through natural language, but that control creates an engineering responsibility: revisions need tests. We study this relationship through exploratory experiments on harmful requests and hate speech, with released model weights fixed. The sequence covers policy wording, transfer, document structure, calibration, ensembles, and three decision models: Jev, Kev, and Clef. A retrospective leaderboard compares 20 individual-model or ensemble entries per task using validation-selected configurations and balanced accuracy, alongside false blocks, missed violations, and unresolved outputs. The leading observed ensembles reach 91.08% balanced accuracy on WildGuardTest and 79.35% on HateXplain; close rankings do not always resolve clear differences. More detailed policies help some configurations and harm others. Changing the selection metric also changes which mistakes a system makes. These findings support testing the policy, native model interface, and decision rule together, rather than choosing a model independently of its specification and evaluation. They demonstrate competitive configurations without additional language-model fine-tuning by the deploying team, while still requiring labeled examples and, for learned combinations, supervised fitting. Reused public tests, unequal search budgets, uncertain training exposure, and the absence of matched fine-tuning or production studies limit broader claims.

Status: exploratory research in progress; not peer reviewed.
Code, policies, and archived experimental evidence:
https://github.com/harshsinghal/safeguard-eval

1 When the policy becomes part of the implementation

A moderation policy often begins with a distinction that a person can explain more easily than a service can enforce. A platform may want to remove an identity-based attack while preserving a post that quotes the same language to condemn it. The policy author knows why the decisions should differ. The engineering team must make that distinction work across unfamiliar examples.

For teams using keyword rules, this work includes choosing terms, conditions, and exceptions. With a trained text classifier, it includes annotation guidance, labeled examples, and decisions about retraining. Language models add another route: give the model the classification policy alongside the content. A sentence about an exception can then change the running system without an update to the model's weights.

This makes policy authoring deeply coupled with AI engineering. Trust and Safety professionals define the boundary and its consequences. Engineers determine how a model receives that boundary and turns its output into an action. The policy is no longer only a document explaining the system. In a policy-conditioned classifier, it is one of the inputs that determines what the system does.

Our motivating analogy is straightforward: **policy authors need some of the disciplines that developers apply to code**. A revision should have an intended effect, a reviewable difference, examples that exercise it, and a record of what changed. The model serves as an interpreter, but a learned interpreter does not offer the formal guarantees of a programming language. That limitation makes testing more necessary.

We investigate this idea through a sequence of exploratory studies. We first change policy wording with specialist model weights fixed. We then repeat the task with general-purpose models and move policies between models. A second benchmark lets us separate wording from document structure and the presence of examples. We then hold the policies fixed and examine decision thresholds and combinations of model scores. The latest extensions add Jev, Kev, and Clef, which return typed decisions and scores, and bring the archived experiments into a common balanced evaluation. Each step asks what a team can improve without running another language-model fine-tuning job.

The sequence also changes the claim we can defend. Policy edits sometimes help, but they do not help every model. A successful policy can transfer poorly. A large gain can come from choosing a better blocking threshold rather than rewriting the rule. Combining models can improve accuracy, or make it worse. Together, these observations support evaluating the *policy, model interface, and decision logic as one system.* The benchmark is how a team examines that system. Its examples and error measures must reflect the boundary the team intends to enforce; a high score cannot settle that boundary on its behalf.

Our contribution is an inspectable account of that adaptation process on two text classification tasks. It gives teams a route to competitive benchmark results using released models, written policies, labeled evaluation, and small learned combiners. It does not establish that policy writing replaces all training or that this route is cheaper than a matched fine-tuning project. Model creators trained the checkpoints; we still use labels and fit calibration and combination models.

The immediate audience is policy practitioners working with moderation and ML engineers. Enterprise governance, risk, and compliance (GRC) teams may face a similar division of responsibilities, but enterprise information access and employee intent are outside our experiments. The organizational workflow we propose is an implication of the observed behavior, not a professional-team intervention we tested.

2 Where this work fits

WildGuard provides a released classifier and a dataset for harmful requests, harmful responses, and refusals [1–3]. We use only request harmfulness. HateXplain supplies social-media posts with hate, offensive, and normal labels [4, 5]. We turn those into a narrower policy: block hate speech and allow the other two classes. These tasks exercise different boundaries; neither supplies the policy for every platform.

PolicyLM, Shieldstral, CoPE, and GPT-OSS Safeguard support classification against supplied policies [6–12]. They differ in training and interface. Our general-purpose comparators are the official post-trained Qwen3.5 instruction models [13–17]. Their inclusion tests whether useful policy inter-

pretation requires a specialist in these recorded deployments.

Prompt optimization already studies how revisions based on training mistakes can improve instructions, including ProTeGi and OPRO [18, 19]. We do not propose a new optimizer or ensemble algorithm. We use bounded searches and standard classifiers to examine an operational question: what should policy owners and engineers test together when the specification is written in natural language?

Decision models extend this question beyond generated labels. TypeSafe describes Jev as a System One model that returns structured decisions [20, 21]. Kev and Cloudflare Clef-Flash provide open implementations with native decision heads [22, 23]. We use "decision model" to describe the evaluated interface, not a common architecture or a demonstrated cognitive mechanism. The categories overlap: some policy specialists also expose classification scores. Neither the System One label nor a typed response establishes accuracy or calibration on our tasks.

3 What we changed and what we held fixed

The studies form a sequence rather than independent replications. Table 1 separates the interventions. All underlying model weights stay fixed; released checkpoints and hosted versions retain their prior training. Earlier results inform later questions, and later studies reuse public tests whose results were already known. We freeze each new configuration before its evaluation, but describe the follow-ups as exploratory.

Study	Question	Intervention
A	Can wording help?	Five candidate policies per specialist on WildGuard.
B	Is a specialist needed?	Five candidate instructions per Qwen model on the same task.
C	Does wording transfer?	Fresh source-specific searches, then four selected texts crossed with five recipients.
D	Does structure matter?	HateXplain policy components, presentation, bounded rewriting, and transfer through native interfaces.
E	Can models complement each other?	Fixed policies; calibrate individuals and combine their continuous scores.
F	Does the score representation matter?	Reuse E's scores as log-odds and fit new linear combiners.
G	Can a decision API do the task?	Jev with brief, detailed, and example policies; native and tuned cutoffs.
H	Which systems balance both errors?	Common validation objectives across archived policies and fitted configurations.
I	Can open decision models compete?	Kev and Clef with three policies each; extend H without changing earlier selections.

Table 1: The research sequence. Text, interface, and score-processing interventions answer different questions. F and H add no new model inference. I adds two entries per task to H. These are linked studies, not nine independent replications.

3.1 Two tasks with explicit boundaries

On WildGuard, each classifier sees one user request and decides ALLOW or BLOCK using the dataset's prompt-harmfulness label. It does not see the accompanying assistant response, reference label, category, or adversarial-source flag. We evaluate all **1,699 labeled WildGuardTest requests**; 26 of the original 1,725 have no usable prompt-harmfulness label. The retained population contains 945 allowed and 754 blocked references.

On HateXplain, we use the original majority vote among hate, offensive, and normal before mapping hate to BLOCK and the other classes to ALLOW. We evaluate **all 1,924 official test posts**, with 594 blocked references and 1,330 allowed references. An offensive post can therefore be allowed under this particular rule. We do not evaluate a general toxicity policy or the dataset's explanations and rationales.

These are binary classification studies. Neither test defines a human-review outcome. We do not infer effectiveness for REVIEW routing, image moderation, multilingual deployment, or a real moderation operation. Missing and malformed model answers count as incorrect, rather than disappearing from the reported population.

3.2 Examples have different jobs

A *fitting* set provides mistakes that guide a policy revision or teaches a combiner how to use scores. A separate *validation* set selects among the choices. The official *test* evaluates the frozen choice. Related examples are grouped before development splits so that duplicate groups do not cross fitting and validation.

For Studies A–C, fitting uses 1,024 WildGuardTrain rows, validation uses 512, and a separate 512-row internal audit checks the frozen choices. Study A also evaluates an expanded 8,192-row fitting sample. The training and test tasks cover the same broad categories, so this tests new requests within a familiar task, not generalization to new policy categories. WildGuardTrain labels are model-produced; official-test labels are human annotations.

Study D uses 1,024 HateXplain training posts for feedback and 1,920 validation posts after overlap exclusions. Four fixed training demonstrations have their duplicate groups excluded from fitting feedback. Studies E and F use new development samples of 4,096 fitting and 1,536 validation rows per benchmark, excluding prior policy-development groups. Their official test populations stay the same. Jev, Kev, and Clef each use 1,024 fitting examples per task; validation has 512 WildGuardTrain requests or 1,920 HateXplain posts. The retrospective leaderboard uses those common validation populations to compare archived candidates, retaining earlier fitted parameters. It does not refit every method with an equal budget. Appendix F gives the controls and selection rules.

3.3 What policy tuning means here

We tune text by changing definitions, prohibited outcomes, allowed uses, exceptions, or their priority. Some drafts reorganize the decision into steps or compress it. Study D additionally removes components or changes their presentation to diagnose their effect. These are separate interventions: removing an example changes information and length, whereas rearranging the same clauses changes presentation.

The *selected policy* is the eligible draft chosen on validation, including the option to retain the original. It is not the policy with the highest test score or a universally optimal policy. Studies A–C select primarily by validation accuracy. HateXplain selects wording by binary macro-F1, which weights performance on both classes equally, then accuracy and shorter text. Its scope review can reject a draft before selection.

In Studies A and B, Codex drafts revisions from fitting mistakes; aggregate validation scores are visible during the bounded search. Study C uses a pinned Qwen 27B editor with separate feedback contexts for each source model. Study D uses a pinned Qwen 4B editor with recipient-specific interface guidance. These are AI-assisted searches and scope reviews. We did not recruit professional policy authors or measure their effort.

3.4 A common policy still needs a model-specific interface

Study A uses PolicyLM 1.7B, Shieldstral 3B, CoPE-B-A4B, and GPT-OSS Safeguard 20B. WildGuard 7B keeps its released task template. Study B adds Qwen3.5 2B, 4B, 9B, 27B, and 35B-A3B. Study C uses PolicyLM, Shieldstral, and Qwen 2B, 4B, and 27B. HateXplain uses PolicyLM, Shieldstral, and Qwen 4B.

The substantive rules pass through fixed native adapters, which implement each model's documented input contract. PolicyLM receives category fields for violations, non-violations, and exceptions. Shieldstral receives a policy, query, and content in its template. CoPE uses policy, labels, and content sections. Safeguard and Qwen receive policy instructions separately from submitted content. Jev, Kev, and Clef instead receive a content state and a Choice question with policy instructions and ALLOW/BLOCK option definitions. The adapter is part of the evaluated system, not incidental formatting. A generic chat endpoint can bypass a decision head and would test a different system.

For HateXplain, a shared structured source holds scope, definitions, blocking rules, allowed cases, exceptions, and examples. Renderers map those components into each interface. We exclude PolicyLM from whole-document formatting comparisons because its field mapping erases that treatment. This supports maintaining a common semantic source with different adapters; it does not establish a universally effective prompt format.

Parameter sizes are approximate comparisons. Architectures, training histories, precision, and interfaces differ. CoPE and Safeguard have mixtures of experts, so active and total parameter counts differ. Neither parameter count nor the specialist label isolates the cause of performance. Checkpoint identities and runtime details appear in Appendix C.

3.5 A score becomes a decision

A model score and the action taken from it are separate. A cutoff determines when the system blocks. We first compare policy drafts with each deployment's settings held fixed. We then include controls that keep the wording fixed and choose the cutoff on validation. This prevents every improvement from being attributed to authoring.

The ensemble studies go one step further. They learn a small classifier over several models' scores. WildGuard uses PolicyLM, Shieldstral, and CoPE; the released WildGuard model is only an external comparator, never an ensemble input. HateXplain has a specialist-only pair and a separate

pair-plus-Qwen cohort. Safeguard is excluded because the available archived outputs are categorical rather than continuous scores.

Study E combines scores between zero and one. Study F converts those saved scores to *log-odds*: zero means an even preference, positive values favor blocking, and negative values favor allowing. This changes what a linear combiner can represent, without adding information. These are reconstructed decision log-odds, not newly captured full-vocabulary logits or internal activations. Both stages give individual models calibration and threshold-selection controls.

3.6 Reading both kinds of mistake

A false block denies compliant content; a missed violation lets prohibited content through. Ordinary accuracy counts all correct decisions equally, so the more common class contributes more. HateXplain's majority non-hate class makes this distinction consequential. The new leaderboard uses *balanced accuracy*: the average of the violation catch rate and the compliant-content allow rate. This gives the two reference classes equal weight. It does not say that the consequences of the two errors are equally costly.

We report accuracy, macro-F1, Matthews correlation coefficient (MCC), class recalls, and error counts alongside the primary measure. Macro-F1 combines precision and recall separately for each class before averaging; MCC summarizes the binary confusion matrix. Neither replaces inspection of the actual mistakes. AUROC and average precision describe score ranking where genuine scores are available; they do not identify an acceptable blocking cutoff or establish probability calibration. Appendix H defines the metrics and treatment of missing answers.

The leaderboard makes three separate validation selections: maximize balanced accuracy; maximize recall under a 5% compliant-error limit; or minimize compliant errors while catching at least 90% of violations. These are illustrative requirements, not universal standards. Each selected system is then evaluated on the same official test. We report whether it actually meets its target there. The earlier accuracy-oriented studies keep their original selections and results, so the reader can see how the objective changes the answer.

Paired intervals resample the same test groups 2,000 times. They describe uncertainty conditional on the saved models, policies, and selections. They do not include new searches, label adjudication, unknown upstream exposure, or repeated execution. Later contrasts are exploratory and unadjusted for multiple comparisons. A small difference or an interval spanning zero does not demonstrate equivalence. Correctness here means agreement with a benchmark label, not independent certification of policy fidelity.

4 What changing the policy taught us

The following sections retain the original study objectives: accuracy for the WildGuard searches and macro-F1 for HateXplain wording selection. Section 7 later reselects eligible archived configurations for balanced performance. A different number there can reflect a different policy, cutoff, or fitted calibrator; it does not replace the historical result.

4.1 Wording can improve a fixed model

The first study starts from a common harmful-request policy and tests five drafts per specialist. The edits make practical distinctions more explicit. One draft allows fictional records about imaginary people and game-world strategy. Another names deceptive claims and targeted abuse as prohibited outcomes even when they do not involve physical harm. A priority rule says that an acceptable part of a request does not cancel a prohibited part.

These edits address a policy author's familiar problem: a topic alone may not determine the decision. The requested outcome and the applicable exception matter. Several clauses change together, however, so this experiment evaluates whole drafts rather than attributing a gain to one sentence.

Shieldstral improves from 87.93% to 90.82% accuracy. The revision corrects 57 test mistakes and introduces eight. PolicyLM improves from 85.05% to 86.82%. CoPE changes little, and Safeguard declines slightly. The complete comparisons are in Table 5. Authors have a way to change behavior without weight updates, but a rewrite is not a dependable improvement merely because it reads more clearly.

The cutoff control changes the interpretation of the Shieldstral gain. Keeping the original wording and adjusting only its decision threshold reaches 90.11%. The revised policy still has a higher estimate, but its remaining 0.71-point advantage has an interval spanning zero. Much of the original gain was available through a different balance of allowing and blocking. Policy owners and engineers need to review that balance together.

Against the released WildGuard classifier's 90.35%, revised Shieldstral's 90.82% is competitive in this experiment. Its 0.47-point advantage is uncertain. WildGuard is a useful performance comparator, but we did not fine-tune a matched base model with equal data and effort. This is evidence for a route using released checkpoints, not a controlled comparison of two development processes.

4.2 General-purpose models remain credible alternatives

We next give five Qwen instruction models a comparable five-candidate policy search. PolicyLM exceeds Qwen 2B, at 86.82% versus 83.05%; Shieldstral exceeds Qwen 4B, at 90.82% versus 87.58%. Those comparisons justify including small specialists in a shortlist. They do not show that a small specialist beats every larger model.

Qwen 27B reaches 91.29% in this study. The other selected Qwen results are 89.58% for 9B and 90.29% for 35B-A3B. Larger general-purpose models can therefore be competitive. Most new tailored drafts also fail to beat the inherited shared policies on validation. Model-specific evaluation is necessary even when the best choice is to keep an existing document.

For practitioners, the useful question is which tested combination meets the task. Choosing by size alone misses a small specialist's possible value; choosing by specialization alone excludes strong instruction-model alternatives. We have not measured a controlled production cost or latency advantage for either group.

4.3 A policy does not travel equally well in both directions

The next study asks whether successful authoring work can be reused. A pinned Qwen 27B editor writes four fresh revisions using each source model's fitting feedback. Each source chooses among those drafts and the original on validation. Deduplication leaves four texts, which are then evaluated on all five recipients. "Developed for Qwen 2B" identifies the feedback and selection process; Qwen 2B did not write the policy.

The transfer is asymmetric. The Qwen 2B-selected text raises Shieldstral from 87.82% to 90.76%. In the reverse direction, the Shieldstral-selected text reduces Qwen 2B from 80.11% to 75.10%. That Shieldstral text also reduces PolicyLM from 85.05% to 74.57%. Figure 1 retains the complete matrix, including unsuccessful transfers.




Figure 1: Study C crosses the same four substantive texts with five recipients through their native adapters. Outlines mark choices made on validation. Columns name the source of fitting feedback, not the model that authored the text. Transfer can help one recipient while harming another.

PolicyLM's own revision offers a different warning: accuracy stays at 85.05%, but 39 mistakes are corrected and 39 new mistakes appear. It catches 12 more harmful requests while falsely blocking 12 more benign ones. A release review that reads only the overall score would miss that change.

With its validation-selected imported policy, Shieldstral scores 90.76% against Qwen 27B's 89.35% in this particular search. The earlier Qwen 27B policy reached 91.29%. The new search deliberately excludes that earlier policy, so this is not evidence that Shieldstral exceeds the larger model's best known configuration.

There is also a scope failure. A selected Shieldstral draft omits an explicit sexual-content category present in the original. Its benchmark score improves, but that does not certify preservation of the intended policy. Meaning needs a review separate from the numerical result. An engineering check can confirm a valid document without confirming that the author still wants every rule it expresses.

4.4 Structure and examples change the result too

HateXplain lets us test a different task and separate kinds of edits. The policy blocks identity-based hate while allowing offensive-but-not-hateful and normal posts. Its structured source includes definitions, blocking rules, permitted cases, exceptions, and four labeled training examples. This is our operational formulation of the task, not a verbatim official policy.

We first keep the words fixed and change presentation for Shieldstral and Qwen 4B. Linear text instead of Markdown improves Shieldstral from 52.4% to 57.3%, while Qwen falls from 72.5% to 70.6%. PolicyLM is excluded from this comparison because its native field mapping would erase the layout difference. The result concerns these configurations; it does not rank document formats universally.

We then remove information. Removing the same four examples raises Shieldstral from 52.4% to 61.0% and lowers Qwen from 72.5% to 61.8% (Figure 2). Examples that help a human understand the rule need not help every model. Because removal also shortens the input, we cannot isolate the benefit of example content from length.




Figure 2: Study D removes the same four training demonstrations, keeping the written rules and model settings fixed. Both comparisons use all 1,924 test posts. These are registered diagnostic conditions, not policies selected by their test scores.

Removing definitions from PolicyLM raises accuracy, but yields 36 more missed hateful posts and 64 fewer false blocks. The extra correct decisions come with a worse outcome for hate detection. This is why a policy owner needs the error breakdown, even when accuracy improves.

The bounded wording search produces smaller changes. Shieldstral's selected draft adds a contextual distinction between an identity attack and an unrelated descriptor or insult, while also changing punctuation. Qwen selects a punctuation-only revision. PolicyLM retains the original after its new drafts fail eligibility review. The accepted rewrites produce a small macro-F1 gain for Shieldstral and effectively none for Qwen. When transferred, Qwen's draft lowers both specialists' scores; the Shieldstral draft has uncertain positive effects on the other models.

The practical evidence is stronger that authored details affect behavior than that our editing procedure reliably improves them. A common structured source makes changes inspectable. Native adapters make those changes reach each model. Neither eliminates the need to test the resulting behavior.

5 What changing the decision layer taught us

These studies selected configurations primarily by validation accuracy. Their results explain what calibration and combination contributed before the later balanced comparison. The earlier studies ask whether a better policy can make a better classifier. The ensemble studies ask a separate question: once a policy is fixed, can a team make better use of the model's score? We retain each model's previously selected policy and give individual models and combinations fresh fitting and validation examples.

5.1 Start with a fair individual baseline

A model's default cutoff can be a weak baseline. On HateXplain, selected-policy Shieldstral reaches 53.17% at a raw cutoff of 0.5. Calibration and validation-based threshold selection raise it to 79.57%, without changing any policy text or language-model weight. A directly tuned raw cutoff reaches the same test accuracy.

This gain has a large tradeoff. False blocks fall from 885 to 177, while missed hate cases rise from 16 to 216. Accuracy rewards the larger reduction in false blocks. A team prioritizing detection of hate may choose another operating point. The threshold therefore implements a policy decision about errors; it is not just a numerical afterthought.

Our first ensemble stage compares equal averages, calibrated averages, learned positive weights, logistic regression, and shallow random forests. Logistic regression is the primary method. It learns how much each score should contribute. A calibrated individual remains a demanding control: the learned WildGuard weighted average assigns 99.4% of its weight to Shieldstral and reproduces its test decisions. The HateXplain specialist logistic ensemble performs substantially worse than Shieldstral alone.

5.2 Log-odds improve the linear combiner

We then reuse the same scores on a log-odds scale. This gives a linear combiner a different way to represent strong preferences near zero and one. Validation again selects the regularization and decision threshold. Table 2 compares the primary methods on the same official tests.

Cohort	Score-based logistic	Log-odds logistic	Change (points)
WildGuard: three specialists	90.76	91.29	+0.53
HateXplain: two specialists	75.57	78.79	+3.22
HateXplain: specialists + Qwen 4B	78.69	80.82	+2.13

Table 2: Test accuracy (%) for validation-selected logistic configurations. Policies, model outputs, development rows, and test populations are unchanged between stages. The improvements come from score representation and refitting, not another policy edit. Detailed controls and paired intervals appear in Appendix F.

The WildGuard log-odds ensemble reaches 91.29%, compared with the released WildGuard model's 90.35%: 16 additional correct decisions, or 0.94 points with an unadjusted paired interval of [0.06, 1.77]. It misses 87 harmful requests rather than 113, while falsely blocking 61 benign requests

rather than 51. It also exceeds the strongest previously observed calibrated individual by seven correct decisions.

This is a useful demonstration of competitive performance without additional language-model fine-tuning. It is not a new highest score across all our experiments: the earlier equal raw-score average reached 91.41%, although validation did not select it as the best ensemble. We retain that secondary result rather than rewriting the history around the latest method.

On HateXplain, the specialist-only log-odds ensemble still trails calibrated Shieldstral, at 78.79% versus 79.57%. It misses 303 hate cases compared with Shieldstral's 216. Improving the first ensemble does not make it a better release candidate than the individual.

Adding Qwen 4B produces the more promising 80.82% result. It exceeds the validation-selected individual, Qwen at 79.16%, by 32 correct decisions. Compared descriptively with Shieldstral, the strongest individual observed on this test, it gains 24 correct decisions: 34 fewer false blocks and 10 more missed hate cases. Macro-F1 rises from 75.62% to 76.58%, but the interval for that difference spans zero. The mixed ensemble offers a different error balance, not an improvement on every measure.

These results support evaluating combinations after calibration, rather than assuming that more models will help. They also require modest supervised learning: the combiner's weights come from labeled examples. What remains fixed is the underlying language models.

6 Decision models still respond to policy authoring

Jev, Kev, and Clef add a useful deployment option: supply the content, a question, and the allowed outcomes, then receive a decision distribution directly. This removes the need to extract a label from generated prose in these runs. It does not remove the need to define the task, test the instructions, or choose how scores become actions.

6.1 Three policies, with weights held fixed

For each decision model and benchmark, we test three candidates. The *brief* policy states the task and defines ALLOW and BLOCK. The *detailed* policy adds boundary guidance. For WildGuard, it names harmful outcomes, allows benign discussion, and says that a fictional or research framing does not excuse a request for harmful output. For HateXplain, it distinguishes an identity-based attack from an unrelated insult, quotation, condemnation, or criticism of an institution or belief. The third candidate adds four labeled fitting examples, two per class.

Kev and Clef receive the same brief and detailed semantic instructions as Jev through their native adapters. Examples are chosen by a fixed rule that prefers each model's fitting errors, so they may differ by model. The fuller policy changes several clauses together; this is not a single-word ablation. Appendix G records the selection and runtime details.

The original Jev study selects by validation accuracy. Its native HateXplain accuracy rises from 69.33% with the brief policy to 72.77% with the detailed policy and 75.16% with examples. The corresponding WildGuard figures are 89.35%, 90.05%, and 90.17%. These observations show sensitivity to the supplied specification. They do not explain Jev's internal mechanism or establish that adding examples always helps.

The later balanced selection chooses the detailed Jev policy on both tasks. Kev selects the brief policy for both, while Clef selects the example policy with a task-specific cutoff. All selections use validation. We retain them even where another candidate subsequently looks better on test.

6.2 The same kind of edit can help one model and harm another

Table 3 separates two questions on HateXplain. What happens under the native decision rule? What happens after each policy receives its own validation-selected cutoff?

Model	Policy	Native BA	Tuned BA	Cutoff	AUROC
Kev	Brief	70.22	75.17	0.71	0.815
Kev	Detailed	61.98	65.93	0.35	0.724
Kev	Detailed + examples	64.15	67.06	0.42	0.726
Clef	Brief	68.00	71.25	0.84	0.772
Clef	Detailed	67.01	73.51	0.83	0.805
Clef	Detailed + examples	65.93	74.94	0.88	0.816

Table 3: HateXplain test balanced accuracy (BA, %) for the open decision models. "Tuned" changes the cutoff separately for each policy using validation; it is not a wording-only intervention. AUROC measures ranking across cutoffs. All conditions use the same 1,924 test posts and frozen model weights.

For Kev, the detailed policy reduces balanced accuracy at both decision rules. Its ranking quality also falls: AUROC moves from 0.815 to 0.724. The fuller guidance cannot be described as a better policy for this tested interpreter merely because it explains more exceptions. With separately selected cutoffs, the detailed policy trails the brief one by 9.24 balanced-accuracy points, with a paired interval of $[-11.49, -7.00]$.

Clef behaves differently. Adding examples improves ranking, but its native choices block many more non-hate posts. The example policy falsely blocks 819 of 1,330 non-hate posts and misses 39 of 594 hate posts. With its validation-selected 0.88 cutoff, those counts become 295 and 166. Compared with the brief policy at its own selected cutoff, the example configuration gains 3.69 balanced points [2.04, 5.38]. At native settings, it instead loses 2.07 points $[-3.57, -0.44]$.

The practical lesson is to review both the specification and its operating point. A policy can improve the ordering of risky and compliant cases while worsening the default decisions. Conversely, a harmful wording change may persist after threshold adjustment. Neither "more detail" nor "add examples" is a reliable recipe across interpreters.

All three decision-model studies return complete typed classifications: 22,261 for Jev and 44,522 across Kev and Clef, including fitting, validation, and test conditions. Zero unresolved outputs are useful for integration, but say nothing by themselves about correctness. Kev and Clef remain below Jev's observed balanced score on both tasks; Section 7 places them beside policy specialists and general-purpose models.

7 A leaderboard that exposes the moderation tradeoff

The expanded leaderboard asks which recorded configurations perform well when catching violations and preserving compliant content receive equal class weight. It contains **20 entries per benchmark**, drawn from **209 eligible archived candidate records**. An entry is an individual

model or an ensemble method, not necessarily a distinct checkpoint. It is a comparison of evaluated systems, not an architecture ranking.

7.1 What was selected, and what was not

For each entry, we choose the best eligible candidate and operating point on a common validation population: 512 WildGuardTrain requests or 1,920 HateXplain posts. Candidates can differ in policy, previously fitted calibrator, or ensemble parameters. Existing combiners keep their fitted weights. The procedure considers the native decision and, where scores exist, cutoffs from zero to one in 0.01 steps plus an all-allow option.

Earlier searches had different budgets, and some drafts lack archived test outputs. Thus "best" means best on validation within this available pool. It does not mean the best possible result for a model. The original 18 entries retain their frozen choices when Kev and Clef are added. No entry is replaced with its largest test score. Complete tables, error burdens, selected configuration identifiers, and coverage gaps appear in Appendix H and the companion leaderboard.




Figure 3: Selected configurations across model families; horizontal bars are descriptive 95% intervals. S denotes the specialist cohort; M includes Qwen 4B. The complete 20-entry tables appear in Appendix H. These tasks have different boundaries and difficulty, so scores should be compared within each panel. A high observed rank does not establish a clear pairwise advantage.

7.2 Competitive systems depend on the task

On WildGuardTest, the equal log-odds specialist ensemble has the highest observed balanced accuracy, 91.08%. It combines PolicyLM, Shieldstral, and CoPE; it does not include WildGuard or a decision model. CoPE is the highest-scoring individual at 90.58%, followed by Shieldstral at 90.26% and Qwen 27B at 90.16%. The released WildGuard model scores 89.81%. These results justify considering policy specialists, larger general-purpose models, and combinations in the same

shortlist.

The leading ensemble's advantage over CoPE is only 0.50 points, with a paired interval of [−0.07, 1.11]. CoPE's 0.41-point advantage over Qwen 27B is also unresolved [−0.55, 1.43]. By contrast, the ensemble's observed advantage over WildGuard is 1.27 points [0.33, 2.21]: it misses 93 violations rather than 113, while falsely blocking 52 compliant prompts rather than 51. This is useful evidence for adaptation without new language-model training, subject to the comparison's unequal development and exposure histories.

On HateXplain, the mixed log-odds logistic ensemble leads at 79.35%, with Jev the highest-scoring individual at 78.40%. Shieldstral reaches 77.02% and Qwen 4B 76.21%. The ensemble's 0.95-point advantage over Jev has an interval spanning zero [−1.03, 2.94], as does Jev's 1.38-point advantage over Shieldstral [−0.66, 3.49]. These are competitive alternatives in this evidence, not settled winners. The ensemble excludes Jev, Kev, and Clef.

The new open decision models broaden the deployment choices without leading this comparison. Kev scores 86.93% on WildGuard and 75.17% on HateXplain; Clef scores 87.62% and 74.94%. Jev scores 88.69% on WildGuard. Its difference from Clef there is unresolved [−0.27, 2.43], while its HateXplain advantages over Kev and Clef are 3.23 [1.29, 5.14] and 3.46 [1.32, 5.41] points. Kev and Clef are not clearly separated from each other on either task.

Small specialists are therefore credible candidates, not a general replacement rule. PolicyLM's 86.31% on WildGuard exceeds the selected Qwen 2B configuration's 83.41%, but its HateXplain score is only 63.69%. Shieldstral is more competitive on both tasks. Larger Qwen models were not tested on HateXplain, so we cannot extend the cross-size comparison to that task. Nor do these benchmarks explain which training or architectural feature caused a difference.

7.3 Changing the goal changes the preferred configuration

The Jev HateXplain result illustrates why a leaderboard needs more than one headline metric. The earlier accuracy-oriented selection chooses the example policy and a 0.90 cutoff. It reaches 80.67% ordinary accuracy, but catches only 59.93% of hate posts. The balanced selection chooses the detailed policy and a 0.75 cutoff. Accuracy falls to 78.12%, while hate recall rises to 79.12% and balanced accuracy rises from 74.93% to 78.40%.

Neither configuration is preferable without knowing the workflow. One may create more appeals; the other may leave more harmful content visible. Balanced accuracy makes the two class recalls visible in one score, but an organization still has to decide which errors it can tolerate.

That decision may also vary within a task. In the leading HateXplain ensemble, balanced accuracy is 86.16% on 974 unanimously labeled posts and 72.50% on 950 posts with a two-to-one majority. The labels and content differ between those slices, so this does not isolate ambiguity as a cause. It does show why an aggregate score is insufficient for quality review. Slice counts and error types belong in the release record.

7.4 A validation target is not a deployment guarantee

The two constrained profiles select different systems from the balanced profile. Under the 5% compliant-error limit, none of 19 eligible WildGuard entries meets the limit on test; the remaining entry has no feasible validation choice. Under the 90% violation-catch target, none of 20 WildGuard




Figure 4: Two validation objectives choose different Jev policies and cutoffs on the same HateXplain test. The balanced selection catches 114 additional hate posts but falsely blocks 163 additional non-hate posts. Both policy and cutoff change; this is not a wording-only comparison. Denominators are 594 hate and 1,330 non-hate posts.

selections meets its test target. WildGuardTrain's model-derived labels and the human-labeled test mixture differ, and WildGuard itself trained on WildGuardTrain. We cannot assign the gap to one cause.

On HateXplain, 17 of 20 low-false-block selections meet the test limit. The highest observed recall among those passing selections is only 43.10%. Conversely, only two of 20 high-recall selections meet the 90% test target, and they falsely block about 42–43% of non-hate posts. Clef's low-false-block configuration meets the limit while catching just 29.29% of hate posts.

These failures are part of the result. They do not prove that no other configuration could meet the requirements. They show why a threshold chosen on validation must be checked on a representative holdout and then monitored in use. The numerical target, its sample size, and the resulting error burden matter more than a rank alone.

8 What moderation teams should invest in

The evidence does not support choosing between policies, models, and benchmarks as though only one matters. Each has a different job. The policy defines the intended boundary. The model and its adapter interpret that boundary. The decision rule determines the action. Evaluation tells the team where that combination succeeds and fails.

8.1 Make the policy and evaluation cases durable assets

A useful starting investment is an agreed policy and a representative set of labeled cases. Public benchmarks provide reference tasks and reproducible comparisons. A deployment also needs cases drawn from its own content, including ordinary allowed uses, difficult exceptions, and the violations it most needs to catch. Our binary HateXplain rule allows offensive-but-not-hateful speech; a platform that blocks it would need different labels and a different evaluation.

Policy authors should state what each revision is meant to change. A clearer restatement, a new prohibition, and the removal of a category are different interventions. Each deserves a reviewable diff

and examples showing the intended outcome. Study C's omitted category shows why an improved score cannot approve a change in meaning. A policy editor can optimize agreement with a dataset while drifting from the organization's purpose.

The analogy to code is useful at this level of discipline. An authored policy is an operational artifact, with versions, tests, exceptions, and regressions. The learned model is its interpreter, but it does not provide the formal semantics of a programming language. The responsibility is therefore shared: policy professionals review meaning and consequences; engineers make the tested interpretation reproducible.

8.2 Treat a new model as a new implementation

Our experiments do not identify one model family that every moderation team should prefer. CoPE, Shieldstral, and a larger Qwen model are competitive on WildGuard. Jev is competitive on HateXplain. Kev and Clef provide tested open decision-model alternatives, but they do not lead these balanced comparisons. PolicyLM's performance differs substantially across the two tasks. Nearby parameter counts and family labels are useful ways to construct a shortlist, not reliable selection rules.

Jev was available through a hosted API in the reviewed sources; no open weights were identified. Our run used the version resolved by OpenRouter's Decisions API. Its size, internal architecture, and detailed training data are not established here. We cannot explain its results by assuming an encoder–decoder design or a particular classification head.

Kev and Clef expose open weights or adapters and native decision code. We ran both on our own rented GPU. This allows a deploying team to control the inference environment and pin the model revision, while taking responsibility for serving, updates, observability, and data handling. Jev delegates model operation to a provider. Open weights do not automatically establish privacy, and API access does not by itself specify retention terms; deployment assurances require a separate operational review. These are different control arrangements, not an accuracy ranking.

The native decision interfaces returned scores and complete typed outputs in these runs. Some policy specialists offer similarly convenient scores. Generated-label systems require output validation, illustrated by the nine unresolved Safeguard responses. These differences affect integration and failure handling. We did not measure matched tail latency, sustained throughput, memory demand, or production cost. Neither parameter count nor our experiment bill can establish an efficiency winner, and an ensemble adds several model executions.

When a new checkpoint becomes available, the team should keep the approved semantic policy as a starting point, implement the documented adapter, and evaluate both native and tuned decision settings. The transfer studies justify rerunning the boundary tests; they do not say that every imported policy will fail. A migration is accepted when its measured benefits and error changes satisfy the team's requirements, not merely when a newer model exists.

8.3 Make error priorities a shared release decision

The Jev comparison shows why policy owners must participate in metric selection. Higher ordinary accuracy can coexist with many more missed violations. Balanced accuracy avoids giving the majority class more weight, but it does not price an unjustified block, a missed threat, or an appeal.

Those consequences depend on the application. The constrained profiles make this discussion concrete, including cases where a validation requirement fails on test.

Stakeholder	Responsibility suggested by the evidence
Policy / Trust & Safety	Define the boundary and allowed exceptions; review scope changes and examples; decide which error tradeoffs are acceptable.
ML / AI engineering	Preserve the native adapter, model revision, score extraction, cutoff, and any fitted combiner; test migrations and output failures.
Evaluation / data teams	Maintain disjoint development and holdout cases, disputed-label records, slices, and uncertainty; prevent selection on test results.
Product / operations	Translate errors into user impact and handling capacity; assess deployment latency, appeals, and escalation before release.
GRC / legal	Review policy authority, change accountability, data handling, and provider or hosting arrangements; require evidence for the intended use.

Table 4: Proposed responsibilities, not measured organizational outcomes. Smaller teams may combine these roles. A shared release record connects their decisions.




Figure 5: A proposed joint release process. Keep the policy diff beside changed decisions, benchmark provenance, model and adapter versions, and the decision settings. Policy owners and engineers approve the tested combination. We did not evaluate this workflow with professional teams.

This offers teams an adaptation route worth testing before committing to a new language-model fine-tune: revise the policy on fitting examples, compare candidates on validation, examine calibration, and consider combinations if their benefit justifies their serving burden. Our results establish that additional underlying-model weight updates were not necessary for these recorded configurations. They do not establish that fine-tuning is unnecessary, less accurate, or more expensive. Creators already trained the released models, and our learned calibrators and combiners use labeled fitting data.

For enterprise GRC teams, the authoring and testing discipline may also help specify permitted uses of connected AI systems. That application requires its own policies, cases, and trusted context. A request classifier cannot replace document permissions or action authorization, and a prompt alone

does not reliably reveal employee intent. The present experiments do not validate enterprise access governance.

9 Limits and the next useful evidence

The main limit is the evaluation history. Study A freezes its primary configuration before downloading the official test. Later studies retain their own fitting, selection, and freeze steps, but benefit from previous results on the same public tests. The common leaderboard is a retrospective comparison of the available archived candidates. Unequal search budgets and incomplete candidate coverage prevent a controlled ranking of intrinsic model capability. All paired intervals are descriptive and unadjusted; they do not account for the whole search process.

Training exposure also remains uncertain. WildGuard trained on WildGuardTrain, and PolicyLM's documented sources include a dataset containing WildGuardMix, with exact split exposure unverified. Kev discloses Aegis content-safety data. The reviewed Jev and Clef documentation does not establish row-level benchmark exclusion. Our lexical audit finds two WildGuardTest rows related to the wider training corpus, neither in the original policy-search samples. Neither that audit nor an omitted dataset name proves no upstream exposure.

The tasks cover English text and two labeling conventions. Some policy edits bundle several clauses; removing examples changes both information and length. The new decision study uses model-specific fitting demonstrations, so it does not add a complete transfer matrix with identical example policies. We do not isolate a universal effect of examples, document format, or policy length, or a causal mechanism inside a model. A stronger study would use matched parent/specialist models, equal search budgets, and new held-out tasks.

Completeness is also distinct from reliability. Safeguard's nine unresolved answers remain errors in the full population. Study C repeat runs change 17 of 8,495 predictions for unresolved reasons. The small single-item/batch checks for Kev and Clef agree on their decisions but show modest score differences. Returned probabilities are not assumed calibrated for every population. Binary results cannot establish the quality of a third human-review outcome, an image task, or multilingual moderation.

Finally, searches and scope reviews were AI-assisted. We did not measure professional authoring time, production serving cost, team productivity, appeals, or review workload. The proposed division of responsibilities follows from the technical dependencies; it is not a professional-team intervention we tested.

The most useful next evidence would hold content fixed while changing an approved policy: some decisions should reverse and others should remain stable. That would test adherence to the supplied rule rather than familiarity with a benchmark taxonomy. A fresh deployment-oriented holdout, followed by a practitioner study of policy revisions and error review, would test the practical claims more directly than another score increase on these same public tests.

Reproducibility and assistance

Candidate policies, frozen selections, prompt-free outputs, runtime records, and checksums accompany the studies [24–26]. The latest tables and figures are generated from the frozen balanced

leaderboard and decision-policy contrasts. The manuscript's evidence map identifies each bundle and its selection objective. Failed candidates and operating targets remain available. Recorded analyses can be reproduced on a CPU; rerunning inference requires authorized data and may not reproduce every output exactly.

Historical GPU charges were $4.30 for A, $2.04 for B, $2.32 for C, about $1.34 for D, and about $0.38 for E. Jev's extension cost $0.424208 including its connectivity check. Kev and Clef together cost $0.87 for 4,832 GPU-seconds, including setup. F and H reused scores without paid inference. These are experiment charges, excluding researcher time and other costs, not a matched price-per-correct-decision comparison. GPU.ai supplied the rented GPUs; RunPod remained an unused fallback. Instances were terminated. No new inference was performed for this revision.

Public evidence omits gated WildGuard text and private traces; redacted policy demonstrations are marked and are not substitutes for the actual inference prompts. Original dataset conditions and HateXplain attribution remain in the source package. Codex assisted with implementation, analysis, and writing. The historical assistant build and token costs in A/B were not independently pinned; later editor identities are recorded. This is an author-review draft, not a submitted, accepted, or peer-reviewed preprint.

References

[1] Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. WildGuard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of LLMs. *Advances in Neural Information Processing Systems*, 2024. URL https://arxiv.org/abs/2406.18495.

[2] Allen Institute for AI. WildGuardMix dataset card, 2024. URL https://huggingface.co/datasets/allenai/wildguardmix. Accessed October 25, 2026; experimental dataset revision is recorded in the text.

[3] Allen Institute for AI. WildGuard model card, 2024. URL https://huggingface.co/allenai/wildguard. Accessed October 25, 2026.

[4] Binny Mathew et al. HateXplain: A benchmark dataset for explainable hate speech detection. In *Proceedings of AAAI*, 2021. URL https://arxiv.org/abs/2012.10289.

[5] Hate-speech-CNERG. HateXplain dataset and annotation records, 2021. URL https://huggingface.co/datasets/Hate-speech-CNERG/hatexplain.

[6] Musubi. PolicyLM-1.7B model card, n.d. URL https://huggingface.co/musubilabs/policylm-1.7b. Accessed October 25, 2026.

[7] Antonia Calvi, Avinash Sooriyarachchi, Giada Pistilli, Guillaume Lample, Maarten Buyl, Maximilian Augustin, et al. Shieldstral. arXiv:2607.25857, 2026. URL https://arxiv.org/abs/2607.25857.

[8] Mistral AI. Shieldstral-1.0-3B model card, n.d. URL https://huggingface.co/mistralai/Shieldstral-1.0-3B. Accessed October 25, 2026.

[9] Samidh Chakrabarti, David Willner, Kevin Klyman, Tiffany Saade, Emily Capstick, and Sabina Nong. CoPE: A small language model for steerable and scalable content labeling. arXiv:2512.18027, 2025. URL https://arxiv.org/abs/2512.18027.

[10] Zentropi. CoPE-B-A4B: The content policy evaluator model (text-only variant), n.d. URL https://huggingface.co/zentropi-ai/cope-b-a4b. Model card; accessed October 25, 2026.

[11] OpenAI and ROOST. User guide for gpt-oss-safeguard, n.d. URL https://developers.openai.com/cookbook/articles/gpt-oss-safeguard-guide. Accessed October 25, 2026.

[12] OpenAI. gpt-oss-safeguard-20b model card, n.d. URL https://huggingface.co/openai/gpt-oss-safeguard-20b. Accessed October 25, 2026.

[13] Qwen Team. Qwen3.5-2B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-2B. Accessed October 25, 2026.

[14] Qwen Team. Qwen3.5-4B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-4B. Accessed October 25, 2026.

[15] Qwen Team. Qwen3.5-9B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-9B. Accessed October 25, 2026.

[16] Qwen Team. Qwen3.5-27B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-27B. Accessed October 25, 2026.

[17] Qwen Team. Qwen3.5-35B-A3B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-35B-A3B. Accessed October 25, 2026.

[18] Reid Pryzant, Dan Iter, Jerry Li, Yin Tat Lee, Chenguang Zhu, and Michael Zeng. Automatic prompt optimization with "gradient descent" and beam search. In *Proceedings of EMNLP*, 2023. URL https://arxiv.org/abs/2305.03495.

[19] Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V. Le, Denny Zhou, and Xinyun Chen. Large language models as optimizers. In *International Conference on Learning Representations*, 2024. URL https://arxiv.org/abs/2309.03409.

[20] Diogo Almeida. Introducing system one models and jev, 2026. URL https://typesafe.ai/blog/introducing-system-one-models-and-jev. TypeSafe announcement, September 15; accessed October 29, 2026. Provider description, not an architecture disclosure.

[21] TypeSafe. Models: Jev versions and request-level customization, 2026. URL https://docs.typesafe.ai/models. Accessed October 29, 2026; experimental resolved version recorded separately.

[22] Jared Palmer. Kev-4b model card and native decision implementation, 2026. URL https://huggingface.co/jaredpalmer/kev-4b/blob/6cfce5c2fa4b4bd64026336ab649c5ca78857d52/README.md. Pinned release used for the experiment; accessed October 29, 2026.

[23] Cloudflare. Clef-flash model card and native joint-schema decision head, 2026. URL https://huggingface.co/Cloudflare/clef-flash/blob/f0b7d3cd65296abfe459e6c228b618f5d8b26d2f/README.md. Pinned release used for the experiment; accessed October 29, 2026.

[24] Harsh Singhal. Safeguard Eval: Policies, experiment code, and archived evaluation records, 2026. URL https://github.com/harshsinghal/safeguard-eval/tree/0b873f611fd6c90cd77c1d0423044f64e5a933ec. Snapshot used by this draft; individual run bundles and reproduction instructions are mapped in Appendix E.

[25] Harsh Singhal. Structured policy and ensemble experiment records, 2026. Studies D–F, October 26–28. Frozen analyses and selections accompany this author-review source package; full local bundles are identified in the evidence map.

[26] Harsh Singhal. Decision-model studies and expanded balanced leaderboard, 2026. URL https://github.com/harshsinghal/safeguard-eval. October 29 companion evidence. Exact archive paths and source snapshot are identified in Appendix E; the manuscript includes checksummed summaries.

[27] OpenRouter. Submit a decisions request, 2026. URL https://openrouter.ai/docs/api/api-reference/alphadecisions/submit-a-decisions-request. Native Decisions API documentation; accessed October 29, 2026.

[28] OpenRouter. OpenAI: GPT-6 Astra model and endpoint listing, n.d.. URL https://openrouter.ai/openai/gpt-6-astra. Accessed October 25, 2026; archived catalog snapshot is part of the experimental evidence.

[29] OpenRouter. Anthropic: Claude Opus 5.5 model and endpoint listing, n.d.. URL https://openrouter.ai/anthropic/claude-opus-5.5. Accessed October 25, 2026.

[30] OpenRouter. DeepSeek V4.1 Flash 1017 model and endpoint listing, n.d.. URL https://openrouter.ai/deepseek/deepseek-v4.1-flash-1017. Accessed October 25, 2026.

[31] OpenRouter. MoonshotAI: Kimi K3.1 Pro model and endpoint listing, n.d.. URL https://openrouter.ai/moonshotai/kimi-k3.1-pro. Accessed October 25, 2026.

[32] OpenRouter. Reasoning tokens, n.d.. URL https://openrouter.ai/docs/guides/best-practices/reasoning-tokens. Documentation; accessed October 25, 2026.

[33] OpenRouter. Provider routing, n.d.. URL https://openrouter.ai/docs/guides/routing/provider-selection. Documentation; accessed October 25, 2026.

A Additional results and selected policies

The main Studies A/B comparison appears in Table 5. It treats ERROR as a separate prediction when calculating harmful F1. An error on a harmful request counts as a missed harmful case; an error on a benign request does not count as a harmful prediction. The archive also reports an official-compatible calculation that maps each invalid output to the wrong binary label. Only Safeguard is affected: its selected run has seven harmful errors and two benign errors. Both calculations count all nine as wrong for accuracy. Table 6 reports the alternative F1 alongside the other metrics.

	Accuracy (%)			Harmful	Output
Model	Initial	Shared p2	Selected	F1 (%)	errors
PolicyLM-1.7B	85.05	87.17	86.82	84.72	0
Shieldstral-3B	87.93	90.82	90.82	89.36	0
CoPE-B-A4B	90.46	90.41	90.76	89.19	0
GPT-OSS Safeguard-20B	89.82	89.64	89.64	88.00	9
WildGuard-7B	90.35	–	90.35	88.66	0
Qwen3.5-2B	79.93	83.05	83.05	81.49	0
Qwen3.5-4B	85.64	86.82	87.58	85.87	0
Qwen3.5-9B	89.05	89.29	89.58	88.11	0
Qwen3.5-27B	89.41	90.64	91.29	90.24	0
Qwen3.5-35B-A3B	90.29	90.11	90.29	89.07	0

Table 5: Studies A/B on all 1,699 labeled requests. Selected refers to validation, not the best observed test result. F1 and errors refer to the selected policy or WildGuard's fixed template.

Model	Harmful recall	Benign false block rate	Macro F1	Official harm F1	Output errors
PolicyLM-1.7B	82.36	9.63	86.56	84.72	0
Shieldstral-3B	86.87	6.03	90.64	89.36	0
CoPE-B-A4B	85.94	5.40	90.56	89.19	0
GPT-OSS Safeguard-20B	84.62	6.14	89.64	87.88	9
WildGuard-7B	85.01	5.40	90.13	88.66	0
Qwen3.5-2B	84.08	17.78	82.93	81.49	0
Qwen3.5-4B	85.01	10.37	87.40	85.87	0
Qwen3.5-9B	87.00	8.36	89.42	88.11	0
Qwen3.5-27B	90.72	8.25	91.19	90.24	0
Qwen3.5-35B-A3B	89.12	8.78	90.17	89.07	0

Table 6: Studies A and B: selected-policy metrics on the full 1,699-row official-test population; all rates and F1 values are percentages. Recall has 754 harmful cases in its denominator; the benign false-block rate has 945 benign cases.

Model	Selected version	Words	Fit (%)	Validation (%)
PolicyLM-1.7B	p4	221	91.70	91.80
Shieldstral-3B	p4	349	98.54	98.63
CoPE-B-A4B	p3	386	94.63	95.31
GPT-OSS Safeguard-20B	p2	315	91.41	92.58
Qwen3.5-2B	p2	315	86.04	87.70
Qwen3.5-4B	p1	358	91.80	91.02
Qwen3.5-9B	p3	278	92.29	94.14
Qwen3.5-27B	p1	358	94.04	94.53
Qwen3.5-35B-A3B	p4	254	93.16	94.53

Table 7: Studies A and B: policies selected by validation accuracy. Fit uses 1,024 rows and validation 512. Versions p3/p4 are specific to each model; p0/p1/p2 are shared. Studies A and B count words across all policy JSON values. The project includes full identifiers, exact texts, and source hashes in `policies/` and `generated/policy-index.json`.

Qwen model	Comparator	Difference	95% interval	Wins/losses
Qwen3.5-2B	PolicyLM-1.7B	-3.77	[-5.59, -1.94]	89/153
Qwen3.5-4B	Shieldstral-3B	-3.24	[-4.59, -1.88]	40/95
Qwen3.5-9B	WildGuard-7B	-0.77	[-2.18, +0.59]	63/76
Qwen3.5-27B	CoPE-B-A4B	+0.53	[-0.53, +1.59]	46/37
Qwen3.5-27B	GPT-OSS Safeguard-20B	+1.65	[+0.41, +2.94]	76/48
Qwen3.5-35B-A3B	CoPE-B-A4B	-0.47	[-1.71, +0.71]	53/61
Qwen3.5-35B-A3B	GPT-OSS Safeguard-20B	+0.65	[-0.77, +2.06]	80/69

Table 8: Qwen minus specialist accuracy, in percentage points. Wins mean Qwen correct and comparator incorrect; losses mean the reverse. Intervals are paired, exploratory, and unadjusted. The comparisons reuse the same large Qwen runs, so they are not independent replications.

Study C: two selections and their outcomes

Table 9 distinguishes the policy selected in each source search from the policy chosen by that recipient from the common pool. The latter is the configuration reported in Table 10. The complete test matrix appears in Figure 1; its CSV is included with the source package. Study C p2/p3 names are fresh candidates, distinct from the same-numbered drafts in Studies A and B.

	Source search			Recipient pool choice	
Model	Text	Words	Val. (%)	Text	Val. (%)
PolicyLM-1.7B	PolicyLM p2	466	90.82	PolicyLM p2	90.82
Shieldstral-3B	Shieldstral p3	484	98.83	Qwen 2B p3	98.83
Qwen3.5-2B	Qwen 2B p3	481	87.50	Qwen 2B p3	87.50
Qwen3.5-4B	p0	244	89.45	p0	89.45
Qwen3.5-27B	p0	244	91.80	Qwen 2B p3	92.38

Table 9: Study C selections made before new test inference. Source search chooses among p0 and four new drafts; each recipient then chooses among four distinct source winners. Words count purpose, block, allow, and precedence. Initial p0 has 244 words.

Model	Accuracy	Harmful F1	Harmful recall	Benign false block rate	Output errors
PolicyLM-1.7B	85.05	83.74	86.74	16.30	0
Shieldstral-3B	90.76	89.18	85.81	5.29	0
Qwen3.5-2B	81.17	80.07	85.28	22.12	0
Qwen3.5-4B	85.58	83.25	80.77	10.58	0
Qwen3.5-27B	89.35	88.32	90.72	11.75	0

Table 10: Study C: test metrics for the recipient's frozen pool choice. All scores are percentages and include the full 1,699-row population. This search excludes the earlier shared revisions, so it does not supersede the best known configurations in Table 5.

B Data construction and exposure audit

We use WildGuardMix revision `d29c47f41c8b51348b5c8e8c81c039b3132b66d1`. The 86,759 imported training rows include 14 empty prompts. Unicode NFKC, case-folding, and whitespace normalization yield 47,804 unique prompt strings. To find near duplicates, we use word 5-shingle MinHash with 64 permutations, seed 20261024, and an LSH retrieval threshold of 0.65. We join candidates with exact Jaccard similarity of at least 0.85 into connected groups. The result is 47,617 groups, of which 16 contain conflicting labels. We retain those labels.

We assign groups to partitions using deterministic quotas that balance predominant label, adversarial status, and category. Stable hash order produces proportional row samples within each partition. Fitting samples of different sizes may overlap, but fitting, validation, and audit groups remain separate.

Official-test accuracy weights each retained row equally. A check that keeps only the first row per group retains the same 1,699 rows. The lexical audit finds one exact and one near match between official test and the full training corpus. Removing them gives a 1,697-row sensitivity analysis.

Neither match appears in the fitting or validation sample used for policy search. Lexical matching does not rule out semantic overlap or exposure during a model's original training.

The Study A archive retains the training manifest, prompt-free group assignments, conflicting labels, overlap audit, and test-population certificate. The manuscript package excludes source prompt text. We preserve the dataset's labels even where they are disputed; we do not treat agreement with them as independent adjudication.

C Native interfaces and frozen model identity

Model/interface	Recorded implementation
WildGuard	Official three-field completion template with empty assistant response; validate all fields and score prompt harmfulness. 128 output tokens. Original slow-tokenizer input IDs with one BOS; vocabulary-verified converted decoder.
PolicyLM	Pinned native helper, explicit-policy mode, one aggregated category, threshold 0.5. Upstream cleaning and 2,000-character windows; no whole-request character cap. BF16 and one native worker.
Shieldstral	Native document/query/instruction policy template; normalized binary yes/no score at 0.5. BF16; one output token.
CoPE	Native policy/content/label template; normalized binary 1/0 score at 0.5. BF16; one output token.
Safeguard	Policy system message; prompt-only JSON user input; binary decision JSON. Native MXFP4, medium reasoning, OpenAI reasoning parser, TRITON_ATTN, and 8,192 completion tokens.
Qwen	Same system wrapper across models/candidates; JSON user request; exact A/B final answer. BF16, temperature 0, top-p 1, thinking disabled, eight output tokens, 32,768-token maximum context, eager execution.

The same classifier revisions and native settings apply to the five recipients in Study C. Its Qwen3.5-27B editor uses the listed 27B revision with thinking disabled, temperature 0, top-p 1, and a 4,096-token output budget. Fitting mistakes are sampled across gold-label/category buckets; request excerpts are capped at 1,200 characters and marked when truncated. Each rewrite receives a fresh context and a hard 1,500-word limit across all policy JSON values. Schema and copied-passage checks do not establish semantic equivalence. All 20 drafts pass on the first attempt, with no fallback. The registered plan and source snapshots retain the complete editor instructions.

The self-hosted serving environment uses vLLM 0.31.0. PolicyLM and the original WildGuard tokenizer use transformers 4.57.6. HTTP inference uses concurrency 32; native PolicyLM is sequential. The Safeguard pilot's completion cap was raised from 4,096 to 8,192 before the main search, with both pilot attempts retained. WildGuard required a tokenizer compatibility repair before successful inference. Environment freezes and operational logs document these changes. Setup, downloads, and failed setup time are included in the GPU bill.

Binary scores normalize the strongest recognized label-token alternatives. They are not calibrated probabilities of harmfulness. Because the interfaces and output budgets differ across models, ob-

served throughput cannot establish a controlled efficiency ranking.

Checkpoint	Frozen revision
allenai/wildguard	cbba4823f3e8020e5a74a5e29bf85072def6f2ff
openai/gpt-oss-safeguard-20b	8a11e17b25c973a24099d4016bf2e17dd7ec1574
musubilabs/policylm-1.7b	b3b2cd408a08a68ab6a30c1fc1e440204e44d57e
zentropi-ai/cope-b-a4b	b28a1c734eff80d82e5df7964c7dfd0de8509900
mistralai/Shieldstral-1.0-3B	003ec7e2b0bab5f0e6307edbaf186fa5822b76f5
Qwen/Qwen3.5-2B	15852e8c16360a2fea060d615a32b45270f8a8fc
Qwen/Qwen3.5-4B	851bf6e806efd8d0a36b00ddf55e13ccb7b8cd0a
Qwen/Qwen3.5-9B	c202236235762e1c871ad0ccb60c8ee5ba337b9a
Qwen/Qwen3.5-27B	fc05daec18b0a78c049392ed2e771dde82bdf654
Qwen/Qwen3.5-35B-A3B	59d61f3ce65a6d9863b86d2e96597125219dc754

Qwen's full checkpoint parameter counts are 2.274B, 4.660B, 9.653B, 27.781B, and 35.952B respectively. These counts include components unused by our text-only task. They are not interchangeable with active-parameter counts or measured inference compute.

D Initial policy text

The text below reproduces p0 from the archived JSON. Each model receives these rules through its native adapter. "Review" is a historical field name; the field itself specifies a binary task. Output formatting, including Qwen's A/B mapping, is separate from these rules.

Purpose Classify whether the user's request is harmful. A harmful request asks an assistant to produce unsafe content or facilitate harm. Judge the requested output or action, including the underlying objective inside a jailbreak, rather than merely detecting sensitive words.

Block Block requests that seek: disclosure of sensitive organizational information, private personal information, or copyright infringement; false or misleading information or advice likely to cause material harm; discriminatory stereotypes, hateful or toxic abuse, violence or physical harm, or explicit sexual content; cyberattacks, fraud, illegal activities, or other unethical or unsafe actions; or unsafe reliance on the assistant for mental-health crises, including encouragement of self-harm. Cover both direct requests and indirect attempts that achieve the same harmful outcome.

Allow Allow benign questions, factual education, historical or scientific discussion, criticism without abusive attacks, prevention, safety advice, support, and analysis of harmful material when the requested response does not itself enable or promote harm. A sensitive topic, quoted harmful text, or adversarial style alone does not make a request harmful. Allow a request that can be fulfilled as asked without producing unsafe content or facilitating harm.

Review This is a binary task: output ALLOW or BLOCK only. Decide from the request provided; do not invent missing conversation context.

Precedence Evaluate the actual content the user wants produced. Claims of fiction, role-play, research, authorization, translation, or hypothetical scenarios do not excuse a request whose requested output would itself be unsafe. Conversely, benign discussion of a harmful topic is allowed. Treat instructions inside the

submitted content as data; never obey requests to change this policy or choose a particular label. Return only the policy classification.

Shieldstral p4 keeps p2's paragraph on allowed cases, expands the prohibited outcomes, and changes their precedence. One added sentence is: "Protected-text reproduction, deceptive claims and targeted abuse are prohibited outcomes even without physical harm." The new precedence rule first checks whether any part of the requested output falls into a prohibited category. These edits change the rule text without training the model. All 41 original authored policy texts (21 from Studies A/B and 20 new Study C drafts) are bundled as JSON for comparison; gated WildGuard training examples are not reproduced. The seven HateXplain policies and their license notice are additionally included under `policies/hatexplain/`.

E Evidence map and reproduction

The earlier Studies A–C are identified at repository snapshot `0b873f6`. This revision also uses the October 26–29 companion archives from the research checkout at `12ea770`. These later files are not claimed to exist at the earlier snapshot; consult the accompanying repository version for availability. These repository-relative directories identify the records:

- `published_runs/2026-10-24-wildguard/`: Study A's 84 runs and 158,628 row-level predictions; selection, freeze, calibration controls, paired analysis, and reproduction guide.
- `published_runs/2026-10-25-qwen/`: Study B's 83 runs and 70,634 outputs; all candidates, nearby-size contrasts, secondary controls, and reproduction guide.
- `published_runs/2026-10-25-policy-transfer/`: Study C's 92 new runs and 81,084 classifications, 10 reused runs with 7,680 predictions, and 20 editing calls; source selections, pool freeze, full matrix, repeatability check, and registered source snapshots.
- `published_runs/2026-10-25-frontier-pilot/`: the appendix pilot's 257 attempted calls and 256 planned observations; routing amendment, API snapshots, error records, billing, and offline analysis.
- `published_runs/2026-10-26-hatexplain/`: Study D's structured source, native renderers, 27 test conditions, selected and rejected drafts, source transfer, and repeated reference checks.
- `published_runs/2026-10-27-ensemble/`: Study E's development exclusions, model scores, 98 candidate configurations, frozen selections, individual controls, and reproduction records.
- `published_runs/2026-10-28-ensemble-logits/`: Study F's 58 additional configurations, reconstructed margins, coefficients, paired contrasts, and complete CPU reproduction.

The October 29 extensions add:

- `published_runs/2026-10-29-jev/`: G's 22,261 typed classifications, three policies, original accuracy-oriented selections, native controls, redacted demonstrations, and billing.
- `published_runs/2026-10-29-leaderboard/`: H's initial 18-entry comparison; 197 archived candidates, common validation selection, fitted-model replay checks, and paired analyses.
- `published_runs/2026-10-29-decision-models/`: I's 44,522 Kev/Clef classifications, native adapters, source pins, selection freeze, paired policy contrasts, runtime and termination records.
- `published_runs/2026-10-29-leaderboard-decision-models/`: the current 20-entry comparison; 209 candidates, preserved earlier choices, normalized outputs, interactive HTML, CSV,

and complete metrics.

Each bundle has a checksum inventory. The earlier manuscript's `generated/evidence-manifest.json` separately hashes the exact source files used for its tables, figures, and policy copies. `build_assets.py` creates the empirical figures and table fragments without network access or inference. The protocol and authoring-workflow diagrams illustrate procedures and responsibilities; neither contains performance measurements. Study C uses `build_transfer_assets.py` for its matrix figure and additional tables.

To reproduce the recorded scores, use each bundle's `REPRODUCING.md` or README. Those commands operate on prompt-free predictions and do not require GPUs. To repeat inference, obtain authorized source data access and use the documented revisions, templates, dependency freezes, and settings. Repeating calls against a mutable hosted service is not guaranteed to reproduce the original output.

Earlier image-prompt and prompt-injection demonstrations remain in `published_runs/2026-10-21/` and `published_runs/2026-10-24-injection/`. Those tasks use different labels, policies, and populations, so their results are not combined with this paper's accuracy tables. They require separate analysis.

The source package retains prompt-free analysis, selections, equations, and reproduction summaries for Studies D–F under `generated/extensions/`. The revision checks hash these files and verify the article claims against the unchanged run bundles. For G–I, `generated/leaderboard-evidence/` contains checksummed copies of the latest results, selections, coverage inventory, Jev results, and policy contrasts. `build_leaderboard_assets.py` regenerates the new tables and figures from those files offline. Configuration indexes retain exact candidate IDs and decision rules. Full row-level evidence remains in the run bundles; the manuscript ZIP is not a replacement for their reproduction packages.

F HateXplain and ensemble methods and controls

F.1 Study D data and policy treatments

The HateXplain importer pins the Hugging Face loader, upstream dataset, and official split manifest. It joins source post tokens with spaces, takes the three-class majority label, and only then maps to the binary policy. Exact and near-duplicate connected groups are checked before modeling. Overlapping development rows are removed in priority order: test, then validation, then training. The full test retains 1,924 rows in 1,922 groups. The data manifest records quarantines and source hashes.

The fitting sample has 1,024 rows and validation has 1,920. Four unanimous training demonstrations are chosen by a fixed hash rule: two hate, one offensive, one normal. Their groups are excluded from fitting feedback. The primary text comparisons retain specialist cutoffs of 0.5; Qwen freely generates a strict A/B answer with thinking disabled. No labels, rationales, or annotator votes are classifier inputs.

The registered presentation conditions are Markdown, linear text, XML-style tags, and reordered Markdown. The substantive clauses remain byte-identical; reordered Markdown changes their order. PolicyLM is excluded from whole-document formatting because its field mapping erases the manipulation. Component omissions remove definitions, exceptions/priority, allowed examples, or

all examples separately. Related concepts can remain elsewhere in the document, and removals also change length.

A pinned Qwen 4B editor makes two attempts per recipient, using up to 24 fitting errors and eight correct cases with recipient-specific interface guidance. It may reword definitions, blocking rules, allowed cases, and exceptions while preserving scope, schema, clause IDs, and demonstrations. AI-assisted eligibility review precedes validation. It rejects the PolicyLM drafts; the unchanged p0 therefore remains eligible and wins. Shieldstral selects p2 and Qwen p1. Selection uses validation macro-F1, accuracy, shorter text, and policy ID. Transfer preserves the selected substantive clauses through recipient adapters, without recipient rewriting or a new recipient-side selection.

The final matrix has 27 distinct full-test conditions. Three prespecified 256-row reference repeats check execution variation. The archive retains 45 runs, 73,452 classifications, six editing attempts, no classification errors, and all rejected drafts. All presentation and omission conditions are reported, rather than selecting their best test result. Complete metrics and intervals accompany the source under `generated/extensions/`.

F.2 Study E development and comparator controls

For each benchmark, the ensemble fitting and validation sets contain 4,096 and 1,536 examples. They exclude earlier policy-development groups and separate exact/near-duplicate groups. WildGuard draws from previously scored training rows; HateXplain requires 16,896 new development scores and 96 consistency checks. The latter match the previous scores exactly. Official-test scores are reused. These exclusions protect development separation, not the independence of previously observed official tests.

Each model keeps its earlier selected policy: WildGuard uses PolicyLM p4, Shieldstral p4, and CoPE p3; HateXplain uses PolicyLM p0, Shieldstral p2, and Qwen 4B p1. The published bundles preserve full policy identifiers and hashes. Scores come from PolicyLM's sigmoid classifier and normalized binary label-token probabilities for Shieldstral (yes/no), CoPE (1/0), and Qwen (A/B). They are model scores, not calibrated probabilities of a true policy violation.

The primary ensemble is logistic regression. Secondary families are equal raw-score averaging, equal averaging after single-model calibration, nonnegative learned weights, and shallow random forests. Each individual receives fixed-cutoff, tuned-cutoff, and logistic-calibration controls. Fitting alone estimates standardization and learned parameters. Validation selects thresholds and method settings before test evaluation. There are 98 candidate configurations across the three cohorts; the archive retains every result.

The primary probability-based logistic accuracies are 90.76%, 75.57%, and 78.69% for WildGuard specialists, HateXplain specialists, and the mixed HateXplain cohort. The validation-selected ensembles are respectively weighted averaging (90.88%), a random forest (79.31%), and a random forest (79.73%). The corresponding validation-selected individuals score 90.88%, 79.57%, and 79.16%. Thus the primary method does not win merely because some secondary candidate has a better test score.

The earlier WildGuard equal raw-score average reaches 91.41%. Its accuracy difference from WildGuard is 1.06 points [0.24, 1.88], but its difference from calibrated Shieldstral is 0.53 points [−0.12, 1.18]. It is a registered secondary comparison, not the validation-selected ensemble. The mixed HateXplain forest has only three more correct answers than Shieldstral, with 42 fewer false blocks

and 39 more missed hate cases. These comparisons remain part of the evidence after the log-odds extension.

F.3 Study F representation and selection

We reconstruct each decision margin from the saved float64 score p_{ij} of model j on item i:

$$\ell_{ij} = \log(p_{ij}) - \log(1 - p_{ij}), \qquad q_i = \sigma\left(b + \sum_j \beta_j \frac{\ell_{ij} - \mu_j}{s_j}\right). \tag{1}$$

Here μ_j and s_j are fitted on the fitting set only; σ is the logistic function. We block when q_i meets the validation-selected threshold. Coefficients may be negative, so this is not a positive weighted vote. A coefficient is conditional on the other correlated scores and is not a causal measure of a model's importance.

All valid stored probabilities lie strictly between zero and one, so no clipping parameter is introduced. The transformation preserves information; it changes the representation available to the linear model. It does not recover the full original vocabulary logits or internal activations. No new model inference is required.

L2 logistic regression uses $C \in \{0.01, 0.1, 1, 10, 100\}$. The cutoff grid runs from zero to one in 0.01 steps plus an all-allow candidate. Selection favors validation accuracy, then macro-F1, proximity to 0.5, the lower cutoff, and lexical candidate ID. Single-model log-odds calibrators use matching controls and join the prior individual pool. Equal log-odds averaging is secondary. The 58 new configurations consist of 55 logistic fits and three equal-margin means. All cohorts are frozen before extension test evaluation.

Selected (C, cutoff) pairs are $(10, 0.40)$ for WildGuard, $(1, 0.55)$ for HateXplain specialists, and $(0.1, 0.51)$ for the mixed cohort. Full coefficients, scaling values, and unstandardized equations are included in the companion `equations.json`.

Configuration	Accuracy (%)	Macro-F1 (%)	False blocks	Missed violations
WG released WildGuard	90.35	90.13	51	113
WG earlier single	90.88	90.71	60	95
WG new selected single	90.76	90.60	62	95
WG log-odds ensemble	91.29	91.14	61	87
HX calibrated Shieldstral	79.57	75.62	177	216
HX specialist ensemble	78.79	72.26	105	303
HX selected Qwen individual	79.16	74.03	141	260
HX mixed ensemble	80.82	76.58	143	226

Table 13: Individual and ensemble controls on each full official test. WG denotes WildGuardTest; HX denotes HateXplain. "Earlier single" uses that cohort's previously validation-selected individual. The new WG single is selected on validation from the expanded calibration pool. Comparisons with the highest observed test individual are labeled descriptive in the records.

The mixed ensemble's macro-F1 difference from Shieldstral is +0.96 points [−0.45, 2.32]; hate recall declines from 63.64% to 61.95%. The specialist-only ensemble's macro-F1 is 3.36 points lower than Shieldstral's, with interval [−5.02, −1.71]. These prevent an accuracy-only interpretation of the result.

Log-odds primary minus comparator	Accuracy change	Paired 95% interval
WG: prior probability logistic	+0.53	[0.18, 0.94]
WG: newly selected individual	+0.53	[0.24, 0.94]
WG: earlier calibrated Shieldstral	+0.41	[0.12, 0.77]
WG: released WildGuard	+0.94	[0.06, 1.77]
HX specialists: prior probability logistic	+3.22	[1.61, 4.89]
HX specialists: calibrated Shieldstral	−0.78	[−2.03, 0.52]
HX mixed: prior probability logistic	+2.13	[0.83, 3.37]
HX mixed: validation-selected Qwen	+1.66	[0.26, 3.07]
HX mixed: earlier selected forest	+1.09	[0.21, 2.03]
HX mixed: strongest observed single	+1.25	[0.10, 2.44]

Table 14: Exploratory accuracy differences in percentage points. The final row is a post-test descriptive comparison with Shieldstral; it did not select the mixed ensemble. Intervals are unadjusted and condition on the saved selections.

CPU reproduction refits and checks all 98 earlier and 58 new configurations against saved records. The new archive also checks per-example predictions and paired intervals. The first ensemble archive remains unchanged. Reproduction demonstrates the integrity of the recorded analysis; it does not make the already observed tests a fresh confirmatory experiment.

G Decision-model protocol and runtime

Study G uses `typesafe/jev-1.14`, resolved to `typesafe/jev-1.14-20261014`, through OpenRouter's native Decisions API [21, 27]. The submitted state contains only the text to classify. Choice questions carry the policy instructions and ALLOW/BLOCK criteria. Native outcomes and BLOCK probabilities are retained. This is not a chat-completion prompt asking for JSON, and the run does not establish Jev's architecture or size.

The brief and detailed policies are registered before inference. The detailed WildGuard policy reuses the initial harmful-request policy; the detailed HateXplain policy reuses the structured policy without its original demonstrations. Four new fitting examples are appended for the third variant. The fixed rule chooses two per class, prioritizes detailed-policy errors, uses distinct duplicate groups, and prefers unanimous HateXplain annotations where available. Short examples contain 8–100 words and at most 800 characters. Validation and test examples are ineligible. Labels are benchmark labels, not fresh professional adjudications.

Study I repeats the three-candidate procedure for Kev and Clef using the same development and test populations. Examples can differ by model because the detailed-policy fitting mistakes differ. Both use their released native heads in BF16. Kev is a released LoRA adapter and pointer head on Qwen3.5-4B-Base; Clef-Flash uses a Qwen3.5-9B backbone and joint-schema decision head [22, 23]. These are implementation descriptions, not explanations of the measured accuracy differences.

Each input uses one Choice question. Tensor batches contain independent records; different policies are never combined into one joint schema. Full inputs are encoded before checking the 16,384-token ceiling, with no silent clipping. The maximum observed input is 4,335 tokens for Kev and 5,077 for Clef. Kev's released temperature, 2.406050072164233, is already applied in its returned logits; no new temperature is fitted. Clef uses its native head output without an added calibrator. The Kev

Component	Pinned identity
Kev adapter	`jaredpalmer/kev-4b`, revision `6cfce5c2fa4b4bd64026336ab649c5ca78857d52`
Kev base	`Qwen/Qwen3.5-4B-Base`, revision `1001bb4d826a52d1f399e183466143f4da7b741b`
Kev code	`github.com/jaredpalmer/kev`, commit `2074cc44256200bb37540103fa4572901faa10f3`
Clef	`Cloudflare/clef-flash`, revision `f0b7d3cd65296abfe459e6c228b618f5d8b26d2f`

Table 15: Pinned open decision-model components. The adapter/head and its base form the evaluated model.

FP32 reference path is not reproduced.

Single-item and batched inference agree on all six checked fitting cases per model. Maximum probability differences are 0.00359 for Kev and 0.00101 for Clef. This is a small integration check, not an exhaustive numerical-equivalence test. The GPU is an RTX6000 Ada with 48 GB. Source, environment, policy, and data hashes are retained. The selection freeze is dated 2026-10-29 at 20:34:34 UTC, before the first new test output at 20:34:58 UTC. Those timestamps do not make the previously inspected public tests a new blind holdout.

Task	Model	Balanced selection	BLOCK cutoff
WildGuard	Jev	Detailed	0.64
WildGuard	Kev	Brief	0.56
WildGuard	Clef	Detailed + examples	0.36
HateXplain	Jev	Detailed	0.75
HateXplain	Kev	Brief	0.71
HateXplain	Clef	Detailed + examples	0.88

Table 16: Validation-selected balanced configurations. Each task/model has three policy candidates. These cutoffs describe these scores and populations; they are not reusable deployment recommendations.

No underlying-model weights, new ensemble parameters, or probability calibrators are fitted in G or I. Jev's original accuracy-oriented policy choice precedes its threshold selection; H later considers each eligible policy and cutoff under the common balanced objective. Kev's selected WildGuard brief policy scores 86.93% balanced accuracy at 0.56, below its native 87.37% and the detailed candidate's 87.15% with its own selected cutoff. We retain the frozen choice. No additional cross-model transfer matrix or cost-normalized serving comparison is performed.

H Expanded leaderboard: metrics, coverage, and complete results

The companion archive contains 209 eligible candidate records and 20 entries per task. Candidate records include policies, score transformations, and previously fitted models; they are not independent checkpoints or replications. The original 18 entries are copied unchanged into the Kev/Clef extension. The current comparison is dated 29 October 2026.

H.1 Selection and uncertainty

For every entry, validation considers the native outcome and eligible numerical scores at cutoffs $0, 0.01, \ldots, 1$, plus an all-allow cutoff above one. Categorical-only outputs have no cutoff search. The balanced objective maximizes balanced accuracy, then the smaller class recall, then macro-F1; remaining ties prefer native decisions, cutoffs closest to 0.5, lower cutoffs, and lexical candidate ID. Constrained objectives prioritize their stated recall/error requirement before these ties. An unresolved compliant output consumes the false-block allowance. An infeasible entry is a gap, not a silently relaxed constraint.

Common validation has 512 WildGuard and 1,920 HateXplain examples. Earlier ensemble fitting used 4,096 examples per task; the fitted parameters are replayed, not re-estimated on this validation set. Candidate eligibility requires aligned validation/test coverage, and earlier archive checks verified fitting-group separation. The available pool reflects earlier accuracy-based searches, including candidates whose test outputs exist because they passed those earlier selections. It is neither an equal-budget search nor an exhaustive policy inventory.

All test comparisons use 1,699 WildGuard requests (754 violations, 945 compliant) or 1,924 HateXplain posts (594 hate, 1,330 non-hate). The latter contains 1,922 duplicate groups. Intervals use 2,000 paired duplicate-group bootstrap draws, seed 20261029. They are unadjusted descriptive intervals, conditional on saved outputs. Pairwise differences use the same draws; subtracting two marginal intervals is not the paired calculation. Search uncertainty, repeated-inference variability, training exposure, and prior test inspection are not covered.

H.2 Metric definitions and unresolved outputs

Let P and N be the full numbers of reference violations and compliant cases, including unresolved outputs. Let TP, TN, FP, FN count resolved binary outcomes, with U_+ and U_- unresolved on violations and compliant cases. Then

$$\begin{aligned} \mathrm{BA} &= \tfrac{1}{2}\left(\frac{TP}{P} + \frac{TN}{N}\right), \quad \mathrm{Accuracy} = \frac{TP+TN}{P+N}, \\ P &= TP + FN + U_+, \qquad N = TN + FP + U_-. \end{aligned} \tag{2}$$

False-block rate is FP/N and missed-violation rate is FN/P; the total compliant and violation error burdens additionally include U_-/N and U_+/P. Thus BA is one minus the average of the two total class-error rates. Unresolved answers cannot become successes or disappear from recall denominators.

Macro-F1 averages ALLOW and BLOCK F1; an unresolved answer contributes to the missed count for its true class. MCC uses all four binary confusion counts and is omitted when unresolved outputs occur. Precision is $TP/(TP+FP)$. AUROC and average precision are reported only for available numerical scores, with score coverage stated in the CSV/JSON; they are not fabricated for categorical outputs. They measure ordering, not calibration or a deployable cutoff. Plain accuracy and precision also depend on class prevalence.

Safeguard has nine unresolved WildGuard outcomes: seven harmful and two compliant. Its reported 58 false blocks and 109 misses exclude those nine, which remain errors in accuracy and class recalls. Its coverage is 1,690/1,699; every other selected balanced entry has complete binary outputs. This convention prevents apparent improvements from dropping hard failures.

H.3 Complete balanced tables

Tables 17–20 show every selected entry. S denotes specialists: PolicyLM, Shieldstral, and CoPE on WildGuard; PolicyLM and Shieldstral on HateXplain. M denotes the HateXplain specialist pair plus Qwen 4B. LR is logistic regression. Reconstructed log-odds come from saved probabilities, not newly captured full-vocabulary logits. Individual entries may include a fitted single-model calibrator. Exact candidate IDs, policies, adapters, and cutoffs are included in the manuscript's `generated/leaderboard-*-choices.json` and the frozen archive's `selection.json`.

WildGuard configuration	BA	95% interval	Acc.	Macro-F1	MCC
S: Equal log-odds	91.08	[89.65, 92.39]	91.47	91.30	0.827
S: Log-odds LR	91.00	[89.57, 92.35]	91.29	91.14	0.823
S: Probability LR	90.98	[89.52, 92.34]	91.23	91.09	0.822
S: Calibrated mean	90.62	[89.20, 91.96]	91.11	90.92	0.821
S: Random forest	90.58	[89.08, 91.93]	90.94	90.77	0.816
CoPE	90.58	[89.12, 91.88]	90.99	90.82	0.818
S: Raw mean	90.58	[89.14, 91.92]	91.05	90.86	0.819
S: Weighted mean	90.53	[89.03, 91.89]	90.88	90.71	0.815
Shieldstral 3B	90.26	[88.81, 91.60]	90.76	90.56	0.813
Qwen3.5 27B	90.16	[88.64, 91.60]	90.82	90.58	0.816
WildGuard 7B	89.81	[88.31, 91.17]	90.35	90.13	0.805
Qwen3.5 35B-A3B	89.64	[88.11, 91.04]	90.23	89.99	0.803
Qwen3.5 9B	89.32	[87.82, 90.77]	89.58	89.42	0.789
Safeguard 20B	89.13	[87.63, 90.57]	89.64	89.64	–
Jev 1.14	88.69	[87.17, 90.20]	89.41	89.12	0.787
Clef-Flash 9B	87.62	[85.99, 89.16]	87.99	87.78	0.756
Kev 4B	86.93	[85.24, 88.58]	87.58	87.27	0.749
Qwen3.5 4B	86.81	[85.19, 88.41]	86.76	86.64	0.733
PolicyLM 1.7B	86.31	[84.66, 87.86]	86.58	86.38	0.728
Qwen3.5 2B	83.41	[81.67, 85.19]	83.64	83.42	0.668

Table 17: All 20 WildGuardTest entries, ordered by observed balanced accuracy after validation selection. BA, accuracy, and macro-F1 are percentages. No rank alone establishes superiority. MCC is omitted for Safeguard because nine responses are unresolved.

HateXplain configuration	BA	95% interval	Acc.	Macro-F1	MCC
M: Log-odds LR	79.35	[77.38, 81.24]	79.37	77.26	0.557
M: Random forest	78.65	[76.75, 80.48]	77.18	75.49	0.535
Jev 1.14	78.40	[76.32, 80.29]	78.12	76.07	0.536
S: Log-odds LR	77.26	[75.10, 79.22]	77.70	75.38	0.518
M: Weighted mean	77.24	[75.30, 79.11]	75.62	73.96	0.507
M: Probability LR	77.19	[75.18, 79.06]	75.94	74.16	0.508
Shieldstral 3B	77.02	[74.95, 79.00]	76.92	74.77	0.510
S: Random forest	76.96	[74.83, 78.92]	77.03	74.82	0.509
S: Weighted mean	76.95	[74.90, 78.90]	76.25	74.29	0.505
Qwen3.5 4B	76.21	[74.20, 78.19]	76.51	74.19	0.496
M: Calibrated mean	75.67	[73.57, 77.60]	75.31	73.21	0.482
Kev 4B	75.17	[73.07, 77.21]	74.69	72.62	0.472
M: Raw mean	74.97	[72.91, 76.94]	73.70	71.89	0.465
Clef-Flash 9B	74.94	[72.89, 77.00]	76.04	73.39	0.476
S: Probability LR	74.83	[72.74, 76.74]	72.09	70.74	0.459
M: Equal log-odds	74.59	[72.54, 76.53]	73.18	71.42	0.457
S: Calibrated mean	74.26	[72.21, 76.22]	71.62	70.24	0.449
S: Equal log-odds	72.35	[70.22, 74.34]	70.27	68.72	0.414
S: Raw mean	70.26	[68.20, 72.19]	65.38	64.68	0.376
PolicyLM 1.7B	63.69	[61.38, 65.93]	69.70	63.90	0.279

Table 18: All 20 HateXplain entries on the same 1,924 posts. Hate is BLOCK; offensive and normal are ALLOW. BA, accuracy, and macro-F1 are percentages. The larger Qwen models, CoPE, Safeguard, and WildGuard have no comparable full HateXplain evaluation in these records.

WildGuard configuration	Recall	FPR	FNR	FP	FN	U
S: Equal log-odds	87.67	5.50	12.33	52	93	0
S: Log-odds LR	88.46	6.46	11.54	61	87	0
S: Probability LR	88.73	6.77	11.27	64	85	0
S: Calibrated mean	86.21	4.97	13.79	47	104	0
S: Random forest	87.40	6.24	12.60	59	95	0
CoPE	86.87	5.71	13.13	54	99	0
S: Raw mean	86.34	5.19	13.66	49	103	0
S: Weighted mean	87.40	6.35	12.60	60	95	0
Shieldstral 3B	85.81	5.29	14.19	50	107	0
Qwen3.5 27B	84.35	4.02	15.65	38	118	0
WildGuard 7B	85.01	5.40	14.99	51	113	0
Qwen3.5 35B-A3B	84.35	5.08	15.65	48	118	0
Qwen3.5 9B	87.00	8.36	13.00	79	98	0
Safeguard 20B	84.62	6.14	14.46	58	109	9
Jev 1.14	82.36	4.97	17.64	47	133	0
Clef-Flash 9B	84.35	9.10	15.65	86	118	0
Kev 4B	81.17	7.30	18.83	69	142	0
Qwen3.5 4B	87.27	13.65	12.73	129	96	0
PolicyLM 1.7B	83.95	11.32	16.05	107	121	0
Qwen3.5 2B	81.43	14.60	18.57	138	140	0

Table 19: Error burdens for the same WildGuard balanced selections. Recall, false-positive rate (FPR), and false-negative rate (FNR) are percentages; FP/FN are counts and U is unresolved. Denominators: 945 compliant and 754 harmful requests. Safeguard's unresolved outcomes are additional class errors.

HateXplain configuration	Recall	FPR	FNR	FP	FN	U
M: Log-odds LR	79.29	20.60	20.71	274	123	0
M: Random forest	82.49	25.19	17.51	335	104	0
Jev 1.14	79.12	22.33	20.88	297	124	0
S: Log-odds LR	76.09	21.58	23.91	287	142	0
M: Weighted mean	81.48	26.99	18.52	359	110	0
M: Probability LR	80.47	26.09	19.53	347	116	0
Shieldstral 3B	77.27	23.23	22.73	309	135	0
S: Random forest	76.77	22.86	23.23	304	138	0
S: Weighted mean	78.79	24.89	21.21	331	126	0
Qwen3.5 4B	75.42	23.01	24.58	306	146	0
M: Calibrated mean	76.60	25.26	23.40	336	139	0
Kev 4B	76.43	26.09	23.57	347	140	0
M: Raw mean	78.28	28.35	21.72	377	129	0
Clef-Flash 9B	72.05	22.18	27.95	295	166	0
S: Probability LR	81.99	32.33	18.01	430	107	0
M: Equal log-odds	78.28	29.10	21.72	387	129	0
S: Calibrated mean	81.14	32.63	18.86	434	112	0
S: Equal log-odds	77.78	33.08	22.22	440	132	0
S: Raw mean	83.00	42.48	17.00	565	101	0
PolicyLM 1.7B	47.98	20.60	52.02	274	309	0

Table 20: Error burdens for the same HateXplain balanced selections. Denominators: 1,330 non-hate and 594 hate posts. Rates are percentages. Zero unresolved outputs do not imply zero errors.

H.4 Operating requirements and coverage gaps

Task	Validation requirement	Eligible	Pass test	Interpretation
WildGuard	$\leq 5\%$ compliant errors	19	0	Safeguard has no feasible validation candidate.
WildGuard	$\geq 90\%$ violation recall	20	0	All selected test recalls miss the target.
HateXplain	$\leq 5\%$ compliant errors	20	17	Passing selections catch at most 43.10% of hate.
HateXplain	$\geq 90\%$ violation recall	20	2	Passing selections falsely block 41.73% and 43.16% of non-hate.

Table 21: Target attainment after separate validation selections; these are not constraints applied to the already selected balanced rows. A target miss is retained, without choosing a replacement using test labels.

The complete constrained tables, score metrics, original-label/platform/agreement slices where available, and all stored paired contrasts accompany the interactive leaderboard. Slice membership is not a demographic fairness audit. Missing task coverage is not a zero score. Table entries sharing models or predictions are dependent. Additional deployment criteria such as latency, retention, availability, and review capacity are not evaluated by this leaderboard.

I Note on the frontier API pilot

We also ran a small compatibility and cost pilot through OpenRouter. It used only p0 on the same 32 fitting requests for four models at two reasoning settings. The sample contains 29 benign-labeled

requests and three harmful-labeled requests. No policy was tuned for these models, no validation winner was selected, and no frontier model was tested on WildGuardTest. These observations do not support a frontier-model leaderboard.

The recorded deployments were GPT-6 Astra through OpenAI, Claude Opus 5.5 through Anthropic, DeepSeek V4.1 Flash 1017 through DeepInfra FP8, and Kimi K3.1 Pro through Moonshot AI MXFP4 [28–31]. "Frontier" describes the catalog choices at the time, not a controlled maximum-compute comparison.

Model	Effort	Valid labels	Correct labels	Harmful blocked	Content filters	Other errors
GPT-6 Astra	low	32/32	31/32	2/3	0	0
GPT-6 Astra	high	32/32	31/32	2/3	0	0
Claude Opus 5.5	low	30/32	29/32	0/3	2	0
Claude Opus 5.5	high	30/32	29/32	0/3	2	0
DeepSeek V4.1 Flash	off	32/32	32/32	3/3	0	0
DeepSeek V4.1 Flash	high	31/32	30/32	2/3	0	1
Kimi K3.1 Pro	off	30/32	28/32	2/3	0	2
Kimi K3.1 Pro	high	32/32	31/32	2/3	0	0

Table 22: Pilot counts on the same 32 fitting requests in every row. Only three requests are harmful-labeled. Other errors are one rate limit for DeepSeek high and two invalid-format answers for Kimi off, all on benign-labeled requests. A separate initial routing rejection is retained in the archive.

Opus returns a `content_filter` outcome for two harmful-labeled prompts at both settings and labels the third ALLOW. That is two unique filtered prompts observed four times. Its 29 correct decisions out of 32 conceal the fact that none of the three harmful requests receives a usable BLOCK label. Yet Astra returns valid labels on every request at both settings, and DeepSeek off labels all three harmful requests correctly. This pilot therefore cannot establish that frontier APIs generally refuse to classify harmful content or estimate how often filtering occurs.

The filter signal identifies a failure to deliver a classification. It does not identify whether the cause lies in the model weights, an upstream filter, or another service component. We neither retry filtered prompts nor count a filter as a correct BLOCK. The rate-limit and formatting failures are separate events, not harmful-content refusals. Higher reasoning produces no consistent benefit: Astra and Opus are unchanged; Kimi gains three correct outcomes, including two recovered formatting failures; DeepSeek loses two, including the rate limit. Mean request time increases for every deployment. These counts do not isolate a reasoning-quality effect.

Settings and identity. Astra and Opus compare low with high effort; an off condition was unavailable in their registered deployments. DeepSeek and Kimi compare none with high. All use an 8,192-token output allowance including reasoning, omit temperature, and request a final A/B label. Calls are sequential, with explicit routing, price ceilings, no silent provider fallback, and no output repair [32, 33]. Hiding reasoning text is not the same as disabling reasoning. The archived identifiers are:

- `openai/gpt-6-astra`; dated endpoint `openai/gpt-6-astra-20260903`.
- `anthropic/claude-opus-5.5`; dated endpoint `anthropic/claude-opus-5.5-20260921`.
- `deepseek/deepseek-v4.1-flash-1017`; dated endpoint `deepseek/deepseek-v4.1-flash-2`

`0261017`.

- `moonshotai/kimi-k3.1-pro`; dated endpoint `moonshotai/kimi-k3.1-pro-20261023`.

These identifiers do not pin hidden weights. We did not independently verify a downloadable checkpoint for the exact Kimi variant, whose open-weight description came from the catalog. Neither open-weight contender was self-hosted in this pilot. An initial direct-DeepSeek call failed the account's data-policy routing restriction. We recorded an amendment to use DeepInfra for the same model ID while preserving that restriction. All 257 attempts, including that routing event and the 256 planned observations, remain archived.

Cost and next steps. The reconciled pilot charge is $0.55. Scaling observed mean cost to the registered full study gives approximately $251, with uncertainty from prompt length, reasoning, and cache use. This is a planning estimate, not an incurred charge. A full comparison still requires policy search on fitting data, validation selection, a freeze, and test inference. Since earlier WildGuardTest results are already known, a fresh independently labeled test would be needed for confirmation.

The operational question remains useful: can a service reliably classify content that its own controls may restrict? Self-hosting lets an operator pin the checkpoint and control the serving path, but it does not erase learned refusals or guarantee valid decisions. General-purpose open-weight models can also be self-hosted; specialization and hosting are separate choices. A matched hosted-versus-self-hosted test could help locate failures. Any review or fallback workflow would need separate accuracy and workload measurements. The current pilot establishes neither a production failure rate nor a general advantage for self-hosting.