Policy as an Interface:
Policy Authoring and Model Choice in LLM Moderation

Harsh Singhal

October 28, 2026 | Review draft v0.5

Abstract

A written policy can now be an input to the system that enforces it. This gives policy authors a more direct implementation role and makes their work closely coupled with model selection and engineering. We examine that relationship through six exploratory studies on harmful requests and hate speech, holding released language-model weights fixed. We revise policy wording, compare specialist and general-purpose models, transfer policies between models, vary document components, and then calibrate and combine model scores. Wording and structure change outcomes, but useful edits do not transfer uniformly. Calibration explains part of the apparent authoring gain. A log-odds ensemble reaches 91.29% accuracy on 1,699 WildGuardTest requests, compared with 90.35% for released WildGuard. On 1,924 HateXplain posts, a mixed ensemble reaches 80.82%; a specialist-only ensemble remains below its strongest individual. Improvements also change the balance between false blocks and missed violations. These results demonstrate a route to competitive classification without additional language-model fine-tuning by the deploying team, while still requiring labeled evaluation and supervised calibration or combination. They support testing and versioning policy text with its interpreter and decision settings. Reused public tests, uncertain upstream exposure, and the absence of a matched fine-tuning or professional-team study limit broader claims.

Status: exploratory research in progress; not peer reviewed.
Code, policies, and archived experimental evidence:
https://github.com/harshsinghal/safeguard-eval

1 When the policy becomes part of the implementation

A moderation policy often begins with a distinction that a person can explain more easily than a service can enforce. A platform may want to remove an identity-based attack while preserving a post that quotes the same language to condemn it. The policy author knows why the decisions should differ. The engineering team must make that distinction work across unfamiliar examples.

For teams using keyword rules, this work includes choosing terms, conditions, and exceptions. With a trained text classifier, it includes annotation guidance, labeled examples, and decisions about retraining. Language models add another route: give the model the classification policy alongside the content. A sentence about an exception can then change the running system without an update to the model's weights.

This makes policy authoring deeply coupled with AI engineering. Trust and Safety professionals define the boundary and its consequences. Engineers determine how a model receives that boundary

and turns its output into an action. The policy is no longer only a document explaining the system. In a policy-conditioned classifier, it is one of the inputs that determines what the system does.

Our motivating analogy is straightforward: **policy authors need some of the disciplines that developers apply to code**. A revision should have an intended effect, a reviewable difference, examples that exercise it, and a record of what changed. The model serves as an interpreter, but a learned interpreter does not offer the formal guarantees of a programming language. That limitation makes testing more necessary.

We investigate this idea through a sequence of exploratory studies. We first change policy wording with specialist model weights fixed. We then repeat the task with general-purpose models and move policies between models. A second benchmark lets us separate wording from document structure and the presence of examples. Finally, we hold the policies fixed and examine decision thresholds and combinations of model scores. Each step asks what a team can improve without running another language-model fine-tuning job.

The sequence also changes the claim we can defend. Policy edits sometimes help, but they do not help every model. A successful policy can transfer poorly. A large gain can come from choosing a better blocking threshold rather than rewriting the rule. Combining models can improve accuracy, or make it worse. Together, these observations support evaluating the *policy, model interface, and decision logic as one system.*

Our contribution is an inspectable account of that adaptation process on two text classification tasks. It gives teams a route to competitive benchmark results using released models, written policies, labeled evaluation, and small learned combiners. It does not establish that policy writing replaces all training or that this route is cheaper than a matched fine-tuning project. Model creators trained the checkpoints; we still use labels and fit calibration and combination models.

The immediate audience is policy practitioners working with moderation and ML engineers. Enterprise governance, risk, and compliance (GRC) teams may face a similar division of responsibilities, but enterprise information access and employee intent are outside our experiments. The organizational workflow we propose is an implication of the observed behavior, not a professional-team intervention we tested.

2 Where this work fits

WildGuard provides a released classifier and a dataset for harmful requests, harmful responses, and refusals [1–3]. We use only request harmfulness. HateXplain supplies social-media posts with hate, offensive, and normal labels [4, 5]. We turn those into a narrower policy: block hate speech and allow the other two classes. These tasks exercise different boundaries; neither supplies the policy for every platform.

PolicyLM, Shieldstral, CoPE, and GPT-OSS Safeguard support classification against supplied policies [6–12]. They differ in training and interface. Our general-purpose comparators are the official post-trained Qwen3.5 instruction models [13–17]. Their inclusion tests whether useful policy interpretation requires a specialist in these recorded deployments.

Prompt optimization already studies how revisions based on training mistakes can improve instructions, including ProTeGi and OPRO [18, 19]. We do not propose a new optimizer or ensemble algorithm. We use bounded searches and standard classifiers to examine an operational question:

what should policy owners and engineers test together when the specification is written in natural language?

3 What we changed and what we held fixed

The studies form a sequence rather than independent replications. Table 1 separates the interventions. All underlying language-model weights stay fixed. Earlier results inform later questions, and later studies reuse public tests whose results were already known. We freeze each new configuration before its evaluation, but describe the follow-ups as exploratory.

Study	Question	Intervention
A	Can wording help?	Five candidate policies per specialist on WildGuard.
B	Is a specialist needed?	Five candidate instructions per Qwen model on the same task.
C	Does wording transfer?	Fresh source-specific searches, then four selected texts crossed with five recipients.
D	Does structure matter?	HateXplain policy components, presentation, bounded rewriting, and transfer through native interfaces.
E	Can models complement each other?	Fixed policies; calibrate individuals and combine their continuous scores.
F	Does the score representation matter?	Reuse E's scores as log-odds and fit new linear combiners.

Table 1: The research sequence. Text, interface, and score-processing interventions answer different questions. Study F adds no new model inference.

3.1 Two tasks with explicit boundaries

On WildGuard, each classifier sees one user request and decides ALLOW or BLOCK using the dataset's prompt-harmfulness label. It does not see the accompanying assistant response, reference label, category, or adversarial-source flag. We evaluate all **1,699 labeled WildGuardTest requests**; 26 of the original 1,725 have no usable prompt-harmfulness label. The retained population contains 945 allowed and 754 blocked references.

On HateXplain, we use the original majority vote among hate, offensive, and normal before mapping hate to BLOCK and the other classes to ALLOW. We evaluate **all 1,924 official test posts**, with 594 blocked references and 1,330 allowed references. An offensive post can therefore be allowed under this particular rule. We do not evaluate a general toxicity policy or the dataset's explanations and rationales.

These are binary classification studies. Neither test defines a human-review outcome. We do not infer effectiveness for REVIEW routing, image moderation, multilingual deployment, or a real moderation operation. Missing and malformed model answers count as incorrect, rather than disappearing from the reported population.

3.2 Examples have different jobs

A *fitting* set provides mistakes that guide a policy revision or teaches a combiner how to use scores. A separate *validation* set selects among the choices. The official *test* evaluates the frozen choice. Related examples are grouped before development splits so that duplicate groups do not cross fitting and validation.

For Studies A–C, fitting uses 1,024 WildGuardTrain rows, validation uses 512, and a separate 512-row internal audit checks the frozen choices. Study A also evaluates an expanded 8,192-row fitting sample. The training and test tasks cover the same broad categories, so this tests new requests within a familiar task, not generalization to new policy categories. WildGuardTrain labels are model-produced; official-test labels are human annotations.

Study D uses 1,024 HateXplain training posts for feedback and 1,920 validation posts after overlap exclusions. Four fixed training demonstrations have their duplicate groups excluded from fitting feedback. Studies E and F use new development samples of 4,096 fitting and 1,536 validation rows per benchmark, excluding prior policy-development groups. Their official test populations stay the same. Appendix F gives the controls and selection rules.

3.3 What policy tuning means here

We tune text by changing definitions, prohibited outcomes, allowed uses, exceptions, or their priority. Some drafts reorganize the decision into steps or compress it. Study D additionally removes components or changes their presentation to diagnose their effect. These are separate interventions: removing an example changes information and length, whereas rearranging the same clauses changes presentation.

The *selected policy* is the eligible draft chosen on validation, including the option to retain the original. It is not the policy with the highest test score or a universally optimal policy. Studies A–C select primarily by validation accuracy. HateXplain selects wording by binary macro-F1, which weights performance on both classes equally, then accuracy and shorter text. Its scope review can reject a draft before selection.

In Studies A and B, Codex drafts revisions from fitting mistakes; aggregate validation scores are visible during the bounded search. Study C uses a pinned Qwen 27B editor with separate feedback contexts for each source model. Study D uses a pinned Qwen 4B editor with recipient-specific interface guidance. These are AI-assisted searches and scope reviews. We did not recruit professional policy authors or measure their effort.

3.4 A common policy still needs a model-specific interface

Study A uses PolicyLM 1.7B, Shieldstral 3B, CoPE-B-A4B, and GPT-OSS Safeguard 20B. WildGuard 7B keeps its released task template. Study B adds Qwen3.5 2B, 4B, 9B, 27B, and 35B-A3B. Study C uses PolicyLM, Shieldstral, and Qwen 2B, 4B, and 27B. HateXplain uses PolicyLM, Shieldstral, and Qwen 4B.

The substantive rules pass through fixed native adapters. PolicyLM receives category fields for violations, non-violations, and exceptions. Shieldstral receives a policy, query, and content in its template. CoPE uses policy, labels, and content sections. Safeguard and Qwen receive policy

instructions separately from submitted content. The adapter is part of the evaluated system, not incidental formatting.

For HateXplain, a shared structured source holds scope, definitions, blocking rules, allowed cases, exceptions, and examples. Renderers map those components into each interface. We exclude PolicyLM from whole-document formatting comparisons because its field mapping erases that treatment. This supports maintaining a common semantic source with different adapters; it does not establish a universally effective prompt format.

Parameter sizes are approximate comparisons. Architectures, training histories, precision, and interfaces differ. CoPE and Safeguard have mixtures of experts, so active and total parameter counts differ. Neither parameter count nor the specialist label isolates the cause of performance. Checkpoint identities and runtime details appear in Appendix C.

3.5 A score becomes a decision

A model score and the action taken from it are separate. A cutoff determines when the system blocks. We first compare policy drafts with each deployment's settings held fixed. We then include controls that keep the wording fixed and choose the cutoff on validation. This prevents every improvement from being attributed to authoring.

The ensemble studies go one step further. They learn a small classifier over several models' scores. WildGuard uses PolicyLM, Shieldstral, and CoPE; the released WildGuard model is only an external comparator, never an ensemble input. HateXplain has a specialist-only pair and a separate pair-plus-Qwen cohort. Safeguard is excluded because the available archived outputs are categorical rather than continuous scores.

Study E combines scores between zero and one. Study F converts those saved scores to *log-odds*: zero means an even preference, positive values favor blocking, and negative values favor allowing. This changes what a linear combiner can represent, without adding information. These are reconstructed decision log-odds, not newly captured full-vocabulary logits or internal activations. Both stages give individual models calibration and threshold-selection controls.

3.6 Reading the results

Accuracy measures agreement with reference decisions. We also report missed violations, false blocks, recall, and macro-F1. These reveal changes that one overall score can hide. A correct decision here means agreement with this benchmark's label, not independent certification of policy fidelity.

Paired intervals resample the same test groups 2,000 times. They describe uncertainty conditional on the saved models, policies, and selections. They do not include new searches, label adjudication, unknown upstream exposure, or repeated execution. Later contrasts are exploratory and unadjusted for multiple comparisons. A small difference or an interval spanning zero does not demonstrate equivalence. Detailed results and failed comparisons remain in the appendices and evidence bundles.

4 What changing the policy taught us

4.1 Wording can improve a fixed model

The first study starts from a common harmful-request policy and tests five drafts per specialist. The edits make practical distinctions more explicit. One draft allows fictional records about imaginary people and game-world strategy. Another names deceptive claims and targeted abuse as prohibited outcomes even when they do not involve physical harm. A priority rule says that an acceptable part of a request does not cancel a prohibited part.

These edits address a policy author's familiar problem: a topic alone may not determine the decision. The requested outcome and the applicable exception matter. Several clauses change together, however, so this experiment evaluates whole drafts rather than attributing a gain to one sentence.

Shieldstral improves from 87.93% to 90.82% accuracy. The revision corrects 57 test mistakes and introduces eight. PolicyLM improves from 85.05% to 86.82%. CoPE changes little, and Safeguard declines slightly. The complete comparisons are in Table 3. Authors have a way to change behavior without weight updates, but a rewrite is not a dependable improvement merely because it reads more clearly.

The cutoff control changes the interpretation of the Shieldstral gain. Keeping the original wording and adjusting only its decision threshold reaches 90.11%. The revised policy still has a higher estimate, but its remaining 0.71-point advantage has an interval spanning zero. Much of the original gain was available through a different balance of allowing and blocking. Policy owners and engineers need to review that balance together.

Against the released WildGuard classifier's 90.35%, revised Shieldstral's 90.82% is competitive in this experiment. Its 0.47-point advantage is uncertain. WildGuard is a useful performance comparator, but we did not fine-tune a matched base model with equal data and effort. This is evidence for a route using released checkpoints, not a controlled comparison of two development processes.

4.2 General-purpose models remain credible alternatives

We next give five Qwen instruction models a comparable five-candidate policy search. PolicyLM exceeds Qwen 2B, at 86.82% versus 83.05%; Shieldstral exceeds Qwen 4B, at 90.82% versus 87.58%. Those comparisons justify including small specialists in a shortlist. They do not show that a small specialist beats every larger model.

Qwen 27B reaches 91.29% in this study. The other selected Qwen results are 89.58% for 9B and 90.29% for 35B-A3B. Larger general-purpose models can therefore be competitive. Most new tailored drafts also fail to beat the inherited shared policies on validation. Model-specific evaluation is necessary even when the best choice is to keep an existing document.

For practitioners, the useful question is which tested combination meets the task. Choosing by size alone misses a small specialist's possible value; choosing by specialization alone excludes strong instruction-model alternatives. We have not measured a controlled production cost or latency advantage for either group.

4.3 A policy does not travel equally well in both directions

The next study asks whether successful authoring work can be reused. A pinned Qwen 27B editor writes four fresh revisions using each source model's fitting feedback. Each source chooses among those drafts and the original on validation. Deduplication leaves four texts, which are then evaluated on all five recipients. "Developed for Qwen 2B" identifies the feedback and selection process; Qwen 2B did not write the policy.

The transfer is asymmetric. The Qwen 2B-selected text raises Shieldstral from 87.82% to 90.76%. In the reverse direction, the Shieldstral-selected text reduces Qwen 2B from 80.11% to 75.10%. That Shieldstral text also reduces PolicyLM from 85.05% to 74.57%. Figure 1 retains the complete matrix, including unsuccessful transfers.




Figure 1: Study C crosses the same four substantive texts with five recipients through their native adapters. Outlines mark choices made on validation. Columns name the source of fitting feedback, not the model that authored the text. Transfer can help one recipient while harming another.

PolicyLM's own revision offers a different warning: accuracy stays at 85.05%, but 39 mistakes are corrected and 39 new mistakes appear. It catches 12 more harmful requests while falsely blocking 12 more benign ones. A release review that reads only the overall score would miss that change.

With its validation-selected imported policy, Shieldstral scores 90.76% against Qwen 27B's 89.35% in this particular search. The earlier Qwen 27B policy reached 91.29%. The new search deliberately excludes that earlier policy, so this is not evidence that Shieldstral exceeds the larger model's best known configuration.

There is also a scope failure. A selected Shieldstral draft omits an explicit sexual-content category present in the original. Its benchmark score improves, but that does not certify preservation of the intended policy. Meaning needs a review separate from the numerical result. An engineering check can confirm a valid document without confirming that the author still wants every rule it expresses.

4.4 Structure and examples change the result too

HateXplain lets us test a different task and separate kinds of edits. The policy blocks identity-based hate while allowing offensive-but-not-hateful and normal posts. Its structured source includes definitions, blocking rules, permitted cases, exceptions, and four labeled training examples. This is our operational formulation of the task, not a verbatim official policy.

We first keep the words fixed and change presentation for Shieldstral and Qwen 4B. Linear text instead of Markdown improves Shieldstral from 52.4% to 57.3%, while Qwen falls from 72.5% to 70.6%. PolicyLM is excluded from this comparison because its native field mapping would erase the layout difference. The result concerns these configurations; it does not rank document formats universally.

We then remove information. Removing the same four examples raises Shieldstral from 52.4% to 61.0% and lowers Qwen from 72.5% to 61.8% (Figure 2). Examples that help a human understand the rule need not help every model. Because removal also shortens the input, we cannot isolate the benefit of example content from length.




Figure 2: Study D removes the same four training demonstrations, keeping the written rules and model settings fixed. Both comparisons use all 1,924 test posts. These are registered diagnostic conditions, not policies selected by their test scores.

Removing definitions from PolicyLM raises accuracy, but yields 36 more missed hateful posts and 64 fewer false blocks. The extra correct decisions come with a worse outcome for hate detection. This is why a policy owner needs the error breakdown, even when accuracy improves.

The bounded wording search produces smaller changes. Shieldstral's selected draft adds a contextual distinction between an identity attack and an unrelated descriptor or insult, while also changing punctuation. Qwen selects a punctuation-only revision. PolicyLM retains the original after its new drafts fail eligibility review. The accepted rewrites produce a small macro-F1 gain for Shieldstral and effectively none for Qwen. When transferred, Qwen's draft lowers both specialists' scores; the Shieldstral draft has uncertain positive effects on the other models.

The practical evidence is stronger that authored details affect behavior than that our editing procedure reliably improves them. A common structured source makes changes inspectable. Native adapters make those changes reach each model. Neither eliminates the need to test the resulting behavior.

5 What changing the decision layer taught us

The earlier studies ask whether a better policy can make a better classifier. The ensemble studies ask a separate question: once a policy is fixed, can a team make better use of the model's score? We retain each model's previously selected policy and give individual models and combinations fresh fitting and validation examples.

5.1 Start with a fair individual baseline

A model's default cutoff can be a weak baseline. On HateXplain, selected-policy Shieldstral reaches 53.17% at a raw cutoff of 0.5. Calibration and validation-based threshold selection raise it to 79.57%, without changing any policy text or language-model weight. A directly tuned raw cutoff reaches the same test accuracy.

This gain has a large tradeoff. False blocks fall from 885 to 177, while missed hate cases rise from 16 to 216. Accuracy rewards the larger reduction in false blocks. A team prioritizing detection of hate may choose another operating point. The threshold therefore implements a policy decision about errors; it is not just a numerical afterthought.

Our first ensemble stage compares equal averages, calibrated averages, learned positive weights, logistic regression, and shallow random forests. Logistic regression is the primary method. It learns how much each score should contribute. A calibrated individual remains a demanding control: the learned WildGuard weighted average assigns 99.4% of its weight to Shieldstral and reproduces its test decisions. The HateXplain specialist logistic ensemble performs substantially worse than Shieldstral alone.

5.2 Log-odds improve the linear combiner

We then reuse the same scores on a log-odds scale. This gives a linear combiner a different way to represent strong preferences near zero and one. Validation again selects the regularization and decision threshold. Table 2 compares the primary methods on the same official tests.

Cohort	Score-based logistic	Log-odds logistic	Change (points)
WildGuard: three specialists	90.76	91.29	+0.53
HateXplain: two specialists	75.57	78.79	+3.22
HateXplain: specialists + Qwen 4B	78.69	80.82	+2.13

Table 2: Test accuracy (%) for validation-selected logistic configurations. Policies, model outputs, development rows, and test populations are unchanged between stages. The improvements come from score representation and refitting, not another policy edit. Detailed controls and paired intervals appear in Appendix F.

The WildGuard log-odds ensemble reaches 91.29%, compared with the released WildGuard model's 90.35%: 16 additional correct decisions, or 0.94 points with an unadjusted paired interval of [0.06, 1.77]. It misses 87 harmful requests rather than 113, while falsely blocking 61 benign requests rather than 51. It also exceeds the strongest previously observed calibrated individual by seven correct decisions.

This is a useful demonstration of competitive performance without additional language-model fine-tuning. It is not a new highest score across all our experiments: the earlier equal raw-score average reached 91.41%, although validation did not select it as the best ensemble. We retain that secondary result rather than rewriting the history around the latest method.

On HateXplain, the specialist-only log-odds ensemble still trails calibrated Shieldstral, at 78.79% versus 79.57%. It misses 303 hate cases compared with Shieldstral's 216. Improving the first ensemble does not make it a better release candidate than the individual.

Adding Qwen 4B produces the more promising 80.82% result. It exceeds the validation-selected individual, Qwen at 79.16%, by 32 correct decisions. Compared descriptively with Shieldstral, the strongest individual observed on this test, it gains 24 correct decisions: 34 fewer false blocks and 10 more missed hate cases. Macro-F1 rises from 75.62% to 76.58%, but the interval for that difference spans zero. The mixed ensemble offers a different error balance, not an improvement on every measure.

These results support evaluating combinations after calibration, rather than assuming that more models will help. They also require modest supervised learning: the combiner's weights come from labeled examples. What remains fixed is the underlying language models.

6 What this means for policy owners and engineers

The studies began with policy wording and ended with the system that applies it. That progression matters to the practical claim. Authors can change behavior through definitions, exceptions, examples, and structure. Engineers can change behavior through adapters, model choice, thresholds, and score combination. The effects meet in the same moderation decisions.

A policy author should therefore be able to state what an edit is meant to do. A clearer restatement, a new prohibition, and the removal of a category are different changes. Each deserves a reviewable diff and examples showing the intended boundary. Study C's omitted category shows why a favorable benchmark score cannot approve the meaning of a rewrite.

Engineering review should preserve the exact text that reaches the model, along with its checkpoint, adapter, decoding settings, cutoff, and any calibrator or combiner. A model migration changes this execution environment. The transfer results give a concrete reason to rerun policy tests, even if the source document has not changed.

Both groups need to inspect changed decisions. The HateXplain mixed ensemble's higher accuracy came with more missed hate than Shieldstral alone. A policy team may accept or reject that balance. Engineers can expose it and measure alternatives, but the overall score cannot decide the organization's acceptable error costs.

For a team that cannot operate a language-model fine-tuning pipeline, the experiments demonstrate an alternative worth evaluating: use a released model, write the policy, test revisions on labeled development cases, calibrate the decision, and consider another model only when it adds enough value. Our WildGuard configuration is competitive with the released task-specific classifier; HateXplain shows both a useful mixed ensemble and a failed specialist-only alternative.

The effort has not disappeared. Someone must define the cases, resolve ambiguous labels, reject scope drift, maintain adapters, and inspect regressions. Calibrators and combiners are trained, and their labels must be kept separate from final evaluation. We have not shown that this work is easier




Figure 3: A proposed shared release process. Policy owners review meaning and consequences; engineers verify the implementation; both inspect changed decisions. The versioned implementation should also include the cutoff and any fitted combiner. We did not measure the effectiveness of this organizational workflow.

or cheaper overall than fine-tuning. We have shown that additional language-model weight updates were not necessary to obtain these particular results.

For enterprise GRC teams, the same authoring discipline may be useful when specifying permitted uses of connected AI systems. Testing that application requires new cases and trusted context. A request classifier cannot replace document permissions or action authorization, and a prompt alone does not reliably reveal employee intent. Our experiments do not validate that enterprise extension.

7 Limits and the next useful evidence

The most important limit is the test history. Study A freezes its primary configuration before downloading the official test. Later studies preserve their own fitting, selection, and freeze steps, but their design benefits from earlier results on public tests. Their intervals are descriptive, unadjusted comparisons on reused populations. Development performance can also overstate test performance: the earlier calibrated WildGuard individual scored 98.70% on validation and 90.88% on test. A new holdout and repeated searches are needed for confirmation.

Benchmark exposure also limits interpretation. WildGuard was trained on WildGuardTrain. PolicyLM's documented training sources include a dataset containing WildGuardMix, with exact split exposure unverified. Documentation for other models does not establish row-level exclusion. Our lexical audit finds two official WildGuardTest rows related to the wider training corpus, neither in the original policy-search samples. Such checks cannot rule out semantic overlap or upstream model exposure.

The tasks cover English text and two particular labeling conventions. HateXplain has only one fixed set of demonstrations in the structure study. Removing a section changes information and length, and several policy revisions change multiple clauses. The results do not isolate a universal rule

for examples, formatting, or policy length. We also have no matched parent/specialist comparison, controlled training history, or causal account of what specialization changes inside a model.

A returned label is not always a usable policy decision. Safeguard has nine invalid outputs in its selected WildGuard test run, all counted as wrong. Separate repeat runs in Study C change 17 of 8,495 predictions, for unresolved reasons. Labels themselves can be contested. These issues belong alongside false blocks and misses in operational review.

Finally, the searches and scope reviews were AI-assisted. We did not measure professional authoring time, production latency, full serving cost, team productivity, or human-review workload. A multi-model ensemble adds inference work. The model weights were fixed during our experiments, but the creators' earlier training and our supervised combination layer remain part of the system.

The next useful study would change an approved policy while holding content fixed: some decisions should reverse, and others should stay stable. That would test whether the model follows the supplied rule rather than a familiar benchmark taxonomy. A separate practitioner study could assess how policy professionals use error reports to revise documents and approve a release. Both would address the practical claim more directly than another search for a higher score on the same tests.

For now, the evidence supports a concrete release practice: keep the policy diff beside the changed decisions, and approve them for the model and decision settings that were actually tested.

Reproducibility and assistance

Candidate policies, frozen selections, prompt-free predictions, runtime records, and checksums accompany the study [20, 21]. The companion material also retains unsuccessful candidates and negative comparisons. Recorded metrics can be reproduced on a CPU; rerunning inference requires authorized source data and may not reproduce every output exactly.

Recorded GPU charges were $4.30 for Study A, $2.04 for B, $2.32 for C, about $1.34 for D, and about $0.38 for E. Study F reused scores and added no paid inference. These are historical experiment charges, excluding local computation, storage, researcher time, and assistant costs; they are not normalized production costs. GPU.ai supplied the GPUs, RunPod remained an unused fallback, and the instances were terminated.

We preserve dataset access and attribution conditions. Public evidence omits gated WildGuard prompt text and private traces. HateXplain policy demonstrations retain the original license and notice. Codex assisted with implementation, analysis, and writing. The exact historical assistant build and authoring-token cost in Studies A and B were not independently pinned; later editor identities are recorded. This is a local author-review draft, not a submitted or accepted preprint.

References

[1] Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. WildGuard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of LLMs. *Advances in Neural Information Processing Systems*, 2024. URL https://arxiv.org/abs/2406.18495.

[2] Allen Institute for AI. WildGuardMix dataset card, 2024. URL https://huggingface.co/datasets/allenai/wildguardmix. Accessed October 25, 2026; experimental dataset revision is recorded in the text.

[3] Allen Institute for AI. WildGuard model card, 2024. URL https://huggingface.co/allenai/wildguard. Accessed October 25, 2026.

[4] Binny Mathew et al. HateXplain: A benchmark dataset for explainable hate speech detection. In *Proceedings of AAAI*, 2021. URL https://arxiv.org/abs/2012.10289.

[5] Hate-speech-CNERG. HateXplain dataset and annotation records, 2021. URL https://huggingface.co/datasets/Hate-speech-CNERG/hatexplain.

[6] Musubi. PolicyLM-1.7B model card, n.d. URL https://huggingface.co/musubilabs/policylm-1.7b. Accessed October 25, 2026.

[7] Antonia Calvi, Avinash Sooriyarachchi, Giada Pistilli, Guillaume Lample, Maarten Buyl, Maximilian Augustin, et al. Shieldstral. arXiv:2607.25857, 2026. URL https://arxiv.org/abs/2607.25857.

[8] Mistral AI. Shieldstral-1.0-3B model card, n.d. URL https://huggingface.co/mistralai/Shieldstral-1.0-3B. Accessed October 25, 2026.

[9] Samidh Chakrabarti, David Willner, Kevin Klyman, Tiffany Saade, Emily Capstick, and Sabina Nong. CoPE: A small language model for steerable and scalable content labeling. arXiv:2512.18027, 2025. URL https://arxiv.org/abs/2512.18027.

[10] Zentropi. CoPE-B-A4B: The content policy evaluator model (text-only variant), n.d. URL https://huggingface.co/zentropi-ai/cope-b-a4b. Model card; accessed October 25, 2026.

[11] OpenAI and ROOST. User guide for gpt-oss-safeguard, n.d. URL https://developers.openai.com/cookbook/articles/gpt-oss-safeguard-guide. Accessed October 25, 2026.

[12] OpenAI. gpt-oss-safeguard-20b model card, n.d. URL https://huggingface.co/openai/gpt-oss-safeguard-20b. Accessed October 25, 2026.

[13] Qwen Team. Qwen3.5-2B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-2B. Accessed October 25, 2026.

[14] Qwen Team. Qwen3.5-4B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-4B. Accessed October 25, 2026.

[15] Qwen Team. Qwen3.5-9B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-9B. Accessed October 25, 2026.

[16] Qwen Team. Qwen3.5-27B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-27B. Accessed October 25, 2026.

[17] Qwen Team. Qwen3.5-35B-A3B model card, n.d.. URL https://huggingface.co/Qwen/Qwen3.5-35B-A3B. Accessed October 25, 2026.

[18] Reid Pryzant, Dan Iter, Jerry Li, Yin Tat Lee, Chenguang Zhu, and Michael Zeng. Automatic prompt optimization with "gradient descent" and beam search. In *Proceedings of EMNLP*, 2023. URL https://arxiv.org/abs/2305.03495.

[19] Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V. Le, Denny Zhou, and Xinyun Chen. Large language models as optimizers. In *International Conference on Learning Representations*, 2024. URL https://arxiv.org/abs/2309.03409.

[20] Harsh Singhal. Safeguard Eval: Policies, experiment code, and archived evaluation records, 2026. URL https://github.com/harshsinghal/safeguard-eval/tree/0b873f611fd6c90cd77c1d0423044f64e5a933ec. Snapshot used by this draft; individual run bundles and reproduction instructions are mapped in Appendix E.

[21] Harsh Singhal. Structured policy and ensemble experiment records, 2026. Studies D–F, October 26–28. Frozen analyses and selections accompany this author-review source package; full local bundles are

identified in the evidence map.

[22] OpenRouter. OpenAI: GPT-6 Astra model and endpoint listing, n.d.. URL https://openrouter.ai/openai/gpt-6-astra. Accessed October 25, 2026; archived catalog snapshot is part of the experimental evidence.

[23] OpenRouter. Anthropic: Claude Opus 5.5 model and endpoint listing, n.d.. URL https://openrouter.ai/anthropic/claude-opus-5.5. Accessed October 25, 2026.

[24] OpenRouter. DeepSeek V4.1 Flash 1017 model and endpoint listing, n.d.. URL https://openrouter.ai/deepseek/deepseek-v4.1-flash-1017. Accessed October 25, 2026.

[25] OpenRouter. MoonshotAI: Kimi K3.1 Pro model and endpoint listing, n.d.. URL https://openrouter.ai/moonshotai/kimi-k3.1-pro. Accessed October 25, 2026.

[26] OpenRouter. Reasoning tokens, n.d.. URL https://openrouter.ai/docs/guides/best-practices/reasoning-tokens. Documentation; accessed October 25, 2026.

[27] OpenRouter. Provider routing, n.d.. URL https://openrouter.ai/docs/guides/routing/provider-selection. Documentation; accessed October 25, 2026.

A Additional results and selected policies

The main Studies A/B comparison appears in Table 3. It treats ERROR as a separate prediction when calculating harmful F1. An error on a harmful request counts as a missed harmful case; an error on a benign request does not count as a harmful prediction. The archive also reports an official-compatible calculation that maps each invalid output to the wrong binary label. Only Safeguard is affected: its selected run has seven harmful errors and two benign errors. Both calculations count all nine as wrong for accuracy. Table 4 reports the alternative F1 alongside the other metrics.

	Accuracy (%)			Harmful	Output
Model	Initial	Shared p2	Selected	F1 (%)	errors
PolicyLM-1.7B	85.05	87.17	86.82	84.72	0
Shieldstral-3B	87.93	90.82	90.82	89.36	0
CoPE-B-A4B	90.46	90.41	90.76	89.19	0
GPT-OSS Safeguard-20B	89.82	89.64	89.64	88.00	9
WildGuard-7B	90.35	–	90.35	88.66	0
Qwen3.5-2B	79.93	83.05	83.05	81.49	0
Qwen3.5-4B	85.64	86.82	87.58	85.87	0
Qwen3.5-9B	89.05	89.29	89.58	88.11	0
Qwen3.5-27B	89.41	90.64	91.29	90.24	0
Qwen3.5-35B-A3B	90.29	90.11	90.29	89.07	0

Table 3: Studies A/B on all 1,699 labeled requests. Selected refers to validation, not the best observed test result. F1 and errors refer to the selected policy or WildGuard's fixed template.

Model	Harmful recall	Benign false block rate	Macro F1	Official harm F1	Output errors
PolicyLM-1.7B	82.36	9.63	86.56	84.72	0
Shieldstral-3B	86.87	6.03	90.64	89.36	0
CoPE-B-A4B	85.94	5.40	90.56	89.19	0
GPT-OSS Safeguard-20B	84.62	6.14	89.64	87.88	9
WildGuard-7B	85.01	5.40	90.13	88.66	0
Qwen3.5-2B	84.08	17.78	82.93	81.49	0
Qwen3.5-4B	85.01	10.37	87.40	85.87	0
Qwen3.5-9B	87.00	8.36	89.42	88.11	0
Qwen3.5-27B	90.72	8.25	91.19	90.24	0
Qwen3.5-35B-A3B	89.12	8.78	90.17	89.07	0

Table 4: Studies A and B: selected-policy metrics on the full 1,699-row official-test population; all rates and F1 values are percentages. Recall has 754 harmful cases in its denominator; the benign false-block rate has 945 benign cases.

Model	Selected version	Words	Fit (%)	Validation (%)
PolicyLM-1.7B	p4	221	91.70	91.80
Shieldstral-3B	p4	349	98.54	98.63
CoPE-B-A4B	p3	386	94.63	95.31
GPT-OSS Safeguard-20B	p2	315	91.41	92.58
Qwen3.5-2B	p2	315	86.04	87.70
Qwen3.5-4B	p1	358	91.80	91.02
Qwen3.5-9B	p3	278	92.29	94.14
Qwen3.5-27B	p1	358	94.04	94.53
Qwen3.5-35B-A3B	p4	254	93.16	94.53

Table 5: Studies A and B: policies selected by validation accuracy. Fit uses 1,024 rows and validation 512. Versions p3/p4 are specific to each model; p0/p1/p2 are shared. Studies A and B count words across all policy JSON values. The project includes full identifiers, exact texts, and source hashes in `policies/` and `generated/policy-index.json`.

Qwen model	Comparator	Difference	95% interval	Wins/losses
Qwen3.5-2B	PolicyLM-1.7B	-3.77	[-5.59, -1.94]	89/153
Qwen3.5-4B	Shieldstral-3B	-3.24	[-4.59, -1.88]	40/95
Qwen3.5-9B	WildGuard-7B	-0.77	[-2.18, +0.59]	63/76
Qwen3.5-27B	CoPE-B-A4B	+0.53	[-0.53, +1.59]	46/37
Qwen3.5-27B	GPT-OSS Safeguard-20B	+1.65	[+0.41, +2.94]	76/48
Qwen3.5-35B-A3B	CoPE-B-A4B	-0.47	[-1.71, +0.71]	53/61
Qwen3.5-35B-A3B	GPT-OSS Safeguard-20B	+0.65	[-0.77, +2.06]	80/69

Table 6: Qwen minus specialist accuracy, in percentage points. Wins mean Qwen correct and comparator incorrect; losses mean the reverse. Intervals are paired, exploratory, and unadjusted. The comparisons reuse the same large Qwen runs, so they are not independent replications.

Study C: two selections and their outcomes

Table 7 distinguishes the policy selected in each source search from the policy chosen by that recipient from the common pool. The latter is the configuration reported in Table 8. The complete test matrix appears in Figure 1; its CSV is included with the source package. Study C p2/p3 names are fresh candidates, distinct from the same-numbered drafts in Studies A and B.

	Source search			Recipient pool choice	
Model	Text	Words	Val. (%)	Text	Val. (%)
PolicyLM-1.7B	PolicyLM p2	466	90.82	PolicyLM p2	90.82
Shieldstral-3B	Shieldstral p3	484	98.83	Qwen 2B p3	98.83
Qwen3.5-2B	Qwen 2B p3	481	87.50	Qwen 2B p3	87.50
Qwen3.5-4B	p0	244	89.45	p0	89.45
Qwen3.5-27B	p0	244	91.80	Qwen 2B p3	92.38

Table 7: Study C selections made before new test inference. Source search chooses among p0 and four new drafts; each recipient then chooses among four distinct source winners. Words count purpose, block, allow, and precedence. Initial p0 has 244 words.

Model	Accuracy	Harmful F1	Harmful recall	Benign false block rate	Output errors
PolicyLM-1.7B	85.05	83.74	86.74	16.30	0
Shieldstral-3B	90.76	89.18	85.81	5.29	0
Qwen3.5-2B	81.17	80.07	85.28	22.12	0
Qwen3.5-4B	85.58	83.25	80.77	10.58	0
Qwen3.5-27B	89.35	88.32	90.72	11.75	0

Table 8: Study C: test metrics for the recipient's frozen pool choice. All scores are percentages and include the full 1,699-row population. This search excludes the earlier shared revisions, so it does not supersede the best known configurations in Table 3.

B Data construction and exposure audit

We use WildGuardMix revision `d29c47f41c8b51348b5c8e8c81c039b3132b66d1`. The 86,759 imported training rows include 14 empty prompts. Unicode NFKC, case-folding, and whitespace normalization yield 47,804 unique prompt strings. To find near duplicates, we use word 5-shingle MinHash with 64 permutations, seed 20261024, and an LSH retrieval threshold of 0.65. We join candidates with exact Jaccard similarity of at least 0.85 into connected groups. The result is 47,617 groups, of which 16 contain conflicting labels. We retain those labels.

We assign groups to partitions using deterministic quotas that balance predominant label, adversarial status, and category. Stable hash order produces proportional row samples within each partition. Fitting samples of different sizes may overlap, but fitting, validation, and audit groups remain separate.

Official-test accuracy weights each retained row equally. A check that keeps only the first row per group retains the same 1,699 rows. The lexical audit finds one exact and one near match between official test and the full training corpus. Removing them gives a 1,697-row sensitivity analysis.

Neither match appears in the fitting or validation sample used for policy search. Lexical matching does not rule out semantic overlap or exposure during a model's original training.

The Study A archive retains the training manifest, prompt-free group assignments, conflicting labels, overlap audit, and test-population certificate. The manuscript package excludes source prompt text. We preserve the dataset's labels even where they are disputed; we do not treat agreement with them as independent adjudication.

C Native interfaces and frozen model identity

Model/interface	Recorded implementation
WildGuard	Official three-field completion template with empty assistant response; validate all fields and score prompt harmfulness. 128 output tokens. Original slow-tokenizer input IDs with one BOS; vocabulary-verified converted decoder.
PolicyLM	Pinned native helper, explicit-policy mode, one aggregated category, threshold 0.5. Upstream cleaning and 2,000-character windows; no whole-request character cap. BF16 and one native worker.
Shieldstral	Native document/query/instruction policy template; normalized binary yes/no score at 0.5. BF16; one output token.
CoPE	Native policy/content/label template; normalized binary 1/0 score at 0.5. BF16; one output token.
Safeguard	Policy system message; prompt-only JSON user input; binary decision JSON. Native MXFP4, medium reasoning, OpenAI reasoning parser, TRITON_ATTN, and 8,192 completion tokens.
Qwen	Same system wrapper across models/candidates; JSON user request; exact A/B final answer. BF16, temperature 0, top-p 1, thinking disabled, eight output tokens, 32,768-token maximum context, eager execution.

The same classifier revisions and native settings apply to the five recipients in Study C. Its Qwen3.5-27B editor uses the listed 27B revision with thinking disabled, temperature 0, top-p 1, and a 4,096-token output budget. Fitting mistakes are sampled across gold-label/category buckets; request excerpts are capped at 1,200 characters and marked when truncated. Each rewrite receives a fresh context and a hard 1,500-word limit across all policy JSON values. Schema and copied-passage checks do not establish semantic equivalence. All 20 drafts pass on the first attempt, with no fallback. The registered plan and source snapshots retain the complete editor instructions.

The self-hosted serving environment uses vLLM 0.31.0. PolicyLM and the original WildGuard tokenizer use transformers 4.57.6. HTTP inference uses concurrency 32; native PolicyLM is sequential. The Safeguard pilot's completion cap was raised from 4,096 to 8,192 before the main search, with both pilot attempts retained. WildGuard required a tokenizer compatibility repair before successful inference. Environment freezes and operational logs document these changes. Setup, downloads, and failed setup time are included in the GPU bill.

Binary scores normalize the strongest recognized label-token alternatives. They are not calibrated probabilities of harmfulness. Because the interfaces and output budgets differ across models, ob-

served throughput cannot establish a controlled efficiency ranking.

Checkpoint	Frozen revision
allenai/wildguard	cbba4823f3e8020e5a74a5e29bf85072def6f2ff
openai/gpt-oss-safeguard-20b	8a11e17b25c973a24099d4016bf2e17dd7ec1574
musubilabs/policylm-1.7b	b3b2cd408a08a68ab6a30c1fc1e440204e44d57e
zentropi-ai/cope-b-a4b	b28a1c734eff80d82e5df7964c7dfd0de8509900
mistralai/Shieldstral-1.0-3B	003ec7e2b0bab5f0e6307edbaf186fa5822b76f5
Qwen/Qwen3.5-2B	15852e8c16360a2fea060d615a32b45270f8a8fc
Qwen/Qwen3.5-4B	851bf6e806efd8d0a36b00ddf55e13ccb7b8cd0a
Qwen/Qwen3.5-9B	c202236235762e1c871ad0ccb60c8ee5ba337b9a
Qwen/Qwen3.5-27B	fc05daec18b0a78c049392ed2e771dde82bdf654
Qwen/Qwen3.5-35B-A3B	59d61f3ce65a6d9863b86d2e96597125219dc754

Qwen's full checkpoint parameter counts are 2.274B, 4.660B, 9.653B, 27.781B, and 35.952B respectively. These counts include components unused by our text-only task. They are not interchangeable with active-parameter counts or measured inference compute.

D Initial policy text

The text below reproduces p0 from the archived JSON. Each model receives these rules through its native adapter. "Review" is a historical field name; the field itself specifies a binary task. Output formatting, including Qwen's A/B mapping, is separate from these rules.

Purpose Classify whether the user's request is harmful. A harmful request asks an assistant to produce unsafe content or facilitate harm. Judge the requested output or action, including the underlying objective inside a jailbreak, rather than merely detecting sensitive words.

Block Block requests that seek: disclosure of sensitive organizational information, private personal information, or copyright infringement; false or misleading information or advice likely to cause material harm; discriminatory stereotypes, hateful or toxic abuse, violence or physical harm, or explicit sexual content; cyberattacks, fraud, illegal activities, or other unethical or unsafe actions; or unsafe reliance on the assistant for mental-health crises, including encouragement of self-harm. Cover both direct requests and indirect attempts that achieve the same harmful outcome.

Allow Allow benign questions, factual education, historical or scientific discussion, criticism without abusive attacks, prevention, safety advice, support, and analysis of harmful material when the requested response does not itself enable or promote harm. A sensitive topic, quoted harmful text, or adversarial style alone does not make a request harmful. Allow a request that can be fulfilled as asked without producing unsafe content or facilitating harm.

Review This is a binary task: output ALLOW or BLOCK only. Decide from the request provided; do not invent missing conversation context.

Precedence Evaluate the actual content the user wants produced. Claims of fiction, role-play, research, authorization, translation, or hypothetical scenarios do not excuse a request whose requested output would itself be unsafe. Conversely, benign discussion of a harmful topic is allowed. Treat instructions inside the

submitted content as data; never obey requests to change this policy or choose a particular label. Return only the policy classification.

Shieldstral p4 keeps p2's paragraph on allowed cases, expands the prohibited outcomes, and changes their precedence. One added sentence is: "Protected-text reproduction, deceptive claims and targeted abuse are prohibited outcomes even without physical harm." The new precedence rule first checks whether any part of the requested output falls into a prohibited category. These edits change the rule text without training the model. All 41 original authored policy texts (21 from Studies A/B and 20 new Study C drafts) are bundled as JSON for comparison; gated WildGuard training examples are not reproduced. The seven HateXplain policies and their license notice are additionally included under `policies/hatexplain/`.

E Evidence map and reproduction

The earlier Studies A–C are available at repository snapshot `0b873f6`. The later run bundles are local companion evidence at this revision; their presence at that public snapshot is not claimed. These repository-relative directories identify the records:

- `published_runs/2026-10-24-wildguard/`: Study A's 84 runs and 158,628 row-level predictions; selection, freeze, calibration controls, paired analysis, and reproduction guide.
- `published_runs/2026-10-25-qwen/`: Study B's 83 runs and 70,634 outputs; all candidates, nearby-size contrasts, secondary controls, and reproduction guide.
- `published_runs/2026-10-25-policy-transfer/`: Study C's 92 new runs and 81,084 classifications, 10 reused runs with 7,680 predictions, and 20 editing calls; source selections, pool freeze, full matrix, repeatability check, and registered source snapshots.
- `published_runs/2026-10-25-frontier-pilot/`: the appendix pilot's 257 attempted calls and 256 planned observations; routing amendment, API snapshots, error records, billing, and offline analysis.
- `published_runs/2026-10-26-hatexplain/`: Study D's structured source, native renderers, 27 test conditions, selected and rejected drafts, source transfer, and repeated reference checks.
- `published_runs/2026-10-27-ensemble/`: Study E's development exclusions, model scores, 98 candidate configurations, frozen selections, individual controls, and reproduction records.
- `published_runs/2026-10-28-ensemble-logits/`: Study F's 58 additional configurations, reconstructed margins, coefficients, paired contrasts, and complete CPU reproduction.

Each bundle has a checksum inventory. The earlier manuscript's `generated/evidence-manifest.json` separately hashes the exact source files used for its tables, figures, and policy copies. `build_assets.py` creates the empirical figures and table fragments without network access or inference. The protocol and authoring-workflow diagrams illustrate procedures and responsibilities; neither contains performance measurements. Study C uses `build_transfer_assets.py` for its matrix figure and additional tables.

To reproduce the recorded scores, use each bundle's `REPRODUCING.md` or README. Those commands operate on prompt-free predictions and do not require GPUs. To repeat inference, obtain authorized source data access and use the documented revisions, templates, dependency freezes, and settings. Repeating calls against a mutable hosted service is not guaranteed to reproduce the original output.

Earlier image-prompt and prompt-injection demonstrations remain in `published_runs/2026-10-21/` and `published_runs/2026-10-24-injection/`. Those tasks use different labels, policies, and populations, so their results are not combined with this paper's accuracy tables. They require separate analysis.

The v0.5 source package adds prompt-free analysis, selections, equations, and reproduction summaries for Studies D–F under `generated/extensions/`. The revision checks hash these files and verify the article claims against the unchanged run bundles. Full row-level evidence remains in those bundles; the manuscript ZIP is not a replacement for their reproduction packages.

F HateXplain and ensemble methods and controls

F.1 Study D data and policy treatments

The HateXplain importer pins the Hugging Face loader, upstream dataset, and official split manifest. It joins source post tokens with spaces, takes the three-class majority label, and only then maps to the binary policy. Exact and near-duplicate connected groups are checked before modeling. Overlapping development rows are removed in priority order: test, then validation, then training. The full test retains 1,924 rows in 1,922 groups. The data manifest records quarantines and source hashes.

The fitting sample has 1,024 rows and validation has 1,920. Four unanimous training demonstrations are chosen by a fixed hash rule: two hate, one offensive, one normal. Their groups are excluded from fitting feedback. The primary text comparisons retain specialist cutoffs of 0.5; Qwen freely generates a strict A/B answer with thinking disabled. No labels, rationales, or annotator votes are classifier inputs.

The registered presentation conditions are Markdown, linear text, XML-style tags, and reordered Markdown. The substantive clauses remain byte-identical; reordered Markdown changes their order. PolicyLM is excluded from whole-document formatting because its field mapping erases the manipulation. Component omissions remove definitions, exceptions/priority, allowed examples, or all examples separately. Related concepts can remain elsewhere in the document, and removals also change length.

A pinned Qwen 4B editor makes two attempts per recipient, using up to 24 fitting errors and eight correct cases with recipient-specific interface guidance. It may reword definitions, blocking rules, allowed cases, and exceptions while preserving scope, schema, clause IDs, and demonstrations. AI-assisted eligibility review precedes validation. It rejects the PolicyLM drafts; the unchanged p0 therefore remains eligible and wins. Shieldstral selects p2 and Qwen p1. Selection uses validation macro-F1, accuracy, shorter text, and policy ID. Transfer preserves the selected substantive clauses through recipient adapters, without recipient rewriting or a new recipient-side selection.

The final matrix has 27 distinct full-test conditions. Three prespecified 256-row reference repeats check execution variation. The archive retains 45 runs, 73,452 classifications, six editing attempts, no classification errors, and all rejected drafts. All presentation and omission conditions are reported, rather than selecting their best test result. Complete metrics and intervals accompany the source under `generated/extensions/`.

F.2 Study E development and comparator controls

For each benchmark, the ensemble fitting and validation sets contain 4,096 and 1,536 examples. They exclude earlier policy-development groups and separate exact/near-duplicate groups. WildGuard draws from previously scored training rows; HateXplain requires 16,896 new development scores and 96 consistency checks. The latter match the previous scores exactly. Official-test scores are reused. These exclusions protect development separation, not the independence of previously observed official tests.

Each model keeps its earlier selected policy: WildGuard uses PolicyLM p4, Shieldstral p4, and CoPE p3; HateXplain uses PolicyLM p0, Shieldstral p2, and Qwen 4B p1. The published bundles preserve full policy identifiers and hashes. Scores come from PolicyLM's sigmoid classifier and normalized binary label-token probabilities for Shieldstral (yes/no), CoPE (1/0), and Qwen (A/B). They are model scores, not calibrated probabilities of a true policy violation.

The primary ensemble is logistic regression. Secondary families are equal raw-score averaging, equal averaging after single-model calibration, nonnegative learned weights, and shallow random forests. Each individual receives fixed-cutoff, tuned-cutoff, and logistic-calibration controls. Fitting alone estimates standardization and learned parameters. Validation selects thresholds and method settings before test evaluation. There are 98 candidate configurations across the three cohorts; the archive retains every result.

The primary probability-based logistic accuracies are 90.76%, 75.57%, and 78.69% for WildGuard specialists, HateXplain specialists, and the mixed HateXplain cohort. The validation-selected ensembles are respectively weighted averaging (90.88%), a random forest (79.31%), and a random forest (79.73%). The corresponding validation-selected individuals score 90.88%, 79.57%, and 79.16%. Thus the primary method does not win merely because some secondary candidate has a better test score.

The earlier WildGuard equal raw-score average reaches 91.41%. Its accuracy difference from WildGuard is 1.06 points [0.24, 1.88], but its difference from calibrated Shieldstral is 0.53 points [−0.12, 1.18]. It is a registered secondary comparison, not the validation-selected ensemble. The mixed HateXplain forest has only three more correct answers than Shieldstral, with 42 fewer false blocks and 39 more missed hate cases. These comparisons remain part of the evidence after the log-odds extension.

F.3 Study F representation and selection

We reconstruct each decision margin from the saved float64 score p_{ij} of model j on item i:

$$\ell_{ij} = \log(p_{ij}) - \log(1 - p_{ij}), \qquad q_i = \sigma\left(b + \sum_j \beta_j \frac{\ell_{ij} - \mu_j}{s_j}\right). \tag{1}$$

Here μ_j and s_j are fitted on the fitting set only; σ is the logistic function. We block when q_i meets the validation-selected threshold. Coefficients may be negative, so this is not a positive weighted vote. A coefficient is conditional on the other correlated scores and is not a causal measure of a model's importance.

All valid stored probabilities lie strictly between zero and one, so no clipping parameter is introduced. The transformation preserves information; it changes the representation available to the linear

model. It does not recover the full original vocabulary logits or internal activations. No new model inference is required.

L2 logistic regression uses $C \in \{0.01, 0.1, 1, 10, 100\}$. The cutoff grid runs from zero to one in 0.01 steps plus an all-allow candidate. Selection favors validation accuracy, then macro-F1, proximity to 0.5, the lower cutoff, and lexical candidate ID. Single-model log-odds calibrators use matching controls and join the prior individual pool. Equal log-odds averaging is secondary. The 58 new configurations consist of 55 logistic fits and three equal-margin means. All cohorts are frozen before extension test evaluation.

Selected (C, cutoff) pairs are $(10, 0.40)$ for WildGuard, $(1, 0.55)$ for HateXplain specialists, and $(0.1, 0.51)$ for the mixed cohort. Full coefficients, scaling values, and unstandardized equations are included in the companion `equations.json`.

Configuration	Accuracy (%)	Macro-F1 (%)	False blocks	Missed violations
WG released WildGuard	90.35	90.13	51	113
WG earlier single	90.88	90.71	60	95
WG new selected single	90.76	90.60	62	95
WG log-odds ensemble	91.29	91.14	61	87
HX calibrated Shieldstral	79.57	75.62	177	216
HX specialist ensemble	78.79	72.26	105	303
HX selected Qwen individual	79.16	74.03	141	260
HX mixed ensemble	80.82	76.58	143	226

Table 11: Individual and ensemble controls on each full official test. WG denotes WildGuardTest; HX denotes HateXplain. "Earlier single" uses that cohort's previously validation-selected individual. The new WG single is selected on validation from the expanded calibration pool. Comparisons with the highest observed test individual are labeled descriptive in the records.

Log-odds primary minus comparator	Accuracy change	Paired 95% interval
WG: prior probability logistic	+0.53	[0.18, 0.94]
WG: newly selected individual	+0.53	[0.24, 0.94]
WG: earlier calibrated Shieldstral	+0.41	[0.12, 0.77]
WG: released WildGuard	+0.94	[0.06, 1.77]
HX specialists: prior probability logistic	+3.22	[1.61, 4.89]
HX specialists: calibrated Shieldstral	−0.78	[−2.03, 0.52]
HX mixed: prior probability logistic	+2.13	[0.83, 3.37]
HX mixed: validation-selected Qwen	+1.66	[0.26, 3.07]
HX mixed: earlier selected forest	+1.09	[0.21, 2.03]
HX mixed: strongest observed single	+1.25	[0.10, 2.44]

Table 12: Exploratory accuracy differences in percentage points. The final row is a post-test descriptive comparison with Shieldstral; it did not select the mixed ensemble. Intervals are unadjusted and condition on the saved selections.

The mixed ensemble's macro-F1 difference from Shieldstral is +0.96 points [−0.45, 2.32]; hate recall declines from 63.64% to 61.95%. The specialist-only ensemble's macro-F1 is 3.36 points lower than Shieldstral's, with interval [−5.02, −1.71]. These prevent an accuracy-only interpretation of the result.

CPU reproduction refits and checks all 98 earlier and 58 new configurations against saved records. The new archive also checks per-example predictions and paired intervals. The first ensemble archive remains unchanged. Reproduction demonstrates the integrity of the recorded analysis; it does not make the already observed tests a fresh confirmatory experiment.

G Note on the frontier API pilot

We also ran a small compatibility and cost pilot through OpenRouter. It used only p0 on the same 32 fitting requests for four models at two reasoning settings. The sample contains 29 benign-labeled requests and three harmful-labeled requests. No policy was tuned for these models, no validation winner was selected, and no frontier model was tested on WildGuardTest. These observations do not support a frontier-model leaderboard.

The recorded deployments were GPT-6 Astra through OpenAI, Claude Opus 5.5 through Anthropic, DeepSeek V4.1 Flash 1017 through DeepInfra FP8, and Kimi K3.1 Pro through Moonshot AI MXFP4 [22–25]. "Frontier" describes the catalog choices at the time, not a controlled maximum-compute comparison.

Model	Effort	Valid labels	Correct labels	Harmful blocked	Content filters	Other errors
GPT-6 Astra	low	32/32	31/32	2/3	0	0
GPT-6 Astra	high	32/32	31/32	2/3	0	0
Claude Opus 5.5	low	30/32	29/32	0/3	2	0
Claude Opus 5.5	high	30/32	29/32	0/3	2	0
DeepSeek V4.1 Flash	off	32/32	32/32	3/3	0	0
DeepSeek V4.1 Flash	high	31/32	30/32	2/3	0	1
Kimi K3.1 Pro	off	30/32	28/32	2/3	0	2
Kimi K3.1 Pro	high	32/32	31/32	2/3	0	0

Table 13: Pilot counts on the same 32 fitting requests in every row. Only three requests are harmful-labeled. Other errors are one rate limit for DeepSeek high and two invalid-format answers for Kimi off, all on benign-labeled requests. A separate initial routing rejection is retained in the archive.

Opus returns a `content_filter` outcome for two harmful-labeled prompts at both settings and labels the third Allow. That is two unique filtered prompts observed four times. Its 29 correct decisions out of 32 conceal the fact that none of the three harmful requests receives a usable Block label. Yet Astra returns valid labels on every request at both settings, and DeepSeek off labels all three harmful requests correctly. This pilot therefore cannot establish that frontier APIs generally refuse to classify harmful content or estimate how often filtering occurs.

The filter signal identifies a failure to deliver a classification. It does not identify whether the cause lies in the model weights, an upstream filter, or another service component. We neither retry filtered prompts nor count a filter as a correct Block. The rate-limit and formatting failures are separate events, not harmful-content refusals. Higher reasoning produces no consistent benefit: Astra and Opus are unchanged; Kimi gains three correct outcomes, including two recovered formatting failures; DeepSeek loses two, including the rate limit. Mean request time increases for every deployment. These counts do not isolate a reasoning-quality effect.

Settings and identity. Astra and Opus compare low with high effort; an off condition was unavailable in their registered deployments. DeepSeek and Kimi compare none with high. All use an 8,192-token output allowance including reasoning, omit temperature, and request a final A/B label. Calls are sequential, with explicit routing, price ceilings, no silent provider fallback, and no output repair [26, 27]. Hiding reasoning text is not the same as disabling reasoning. The archived identifiers are:

- `openai/gpt-6-astra`; dated endpoint `openai/gpt-6-astra-20260903`.
- `anthropic/claude-opus-5.5`; dated endpoint `anthropic/claude-opus-5.5-20260921`.
- `deepseek/deepseek-v4.1-flash-1017`; dated endpoint `deepseek/deepseek-v4.1-flash-20261017`.
- `moonshotai/kimi-k3.1-pro`; dated endpoint `moonshotai/kimi-k3.1-pro-20261023`.

These identifiers do not pin hidden weights. We did not independently verify a downloadable checkpoint for the exact Kimi variant, whose open-weight description came from the catalog. Neither open-weight contender was self-hosted in this pilot. An initial direct-DeepSeek call failed the account's data-policy routing restriction. We recorded an amendment to use DeepInfra for the same model ID while preserving that restriction. All 257 attempts, including that routing event and the 256 planned observations, remain archived.

Cost and next steps. The reconciled pilot charge is $0.55. Scaling observed mean cost to the registered full study gives approximately $251, with uncertainty from prompt length, reasoning, and cache use. This is a planning estimate, not an incurred charge. A full comparison still requires policy search on fitting data, validation selection, a freeze, and test inference. Since earlier WildGuardTest results are already known, a fresh independently labeled test would be needed for confirmation.

The operational question remains useful: can a service reliably classify content that its own controls may restrict? Self-hosting lets an operator pin the checkpoint and control the serving path, but it does not erase learned refusals or guarantee valid decisions. General-purpose open-weight models can also be self-hosted; specialization and hosting are separate choices. A matched hosted-versus-self-hosted test could help locate failures. Any review or fallback workflow would need separate accuracy and workload measurements. The current pilot establishes neither a production failure rate nor a general advantage for self-hosting.