

HTML CHEATSHEET		references	<a href="https://www.quackit.com/html/html_cheat_sheet.cfm">https://www.quackit.com/html/html_cheat_sheet.cfm</a>	
	* = no attributes		<a href="http://www.simplehtmlguide.com/cheatsheet.php">http://www.simplehtmlguide.com/cheatsheet.php</a>	
	all tags have global attributes		<a href="https://digital.com/tools/html-cheatsheet/">https://digital.com/tools/html-cheatsheet/</a>	
Element	Description	Attributes	Code Example	New in HTML5?
<!--...-->	Specifies a comment	*	<!--lots of comments-->	
<!DOCTYPE>	Specifies the document type	*	<!doctype html>	
<a>	Specifies a hyperlink	href; target; download; rel; hreflang; type	<a href="url"> link text </a>	
<abbr>	Specifies an abbreviation		<abbr title="Hypertext Markup Language">HTML</abbr>	
<address>	Specifies an address element		<address>The Rashtrapati Bhavan President's Estate New Delhi India</address>	
<area>	Specifies an area inside an image map	alt; coords; shape; href; target; download; x	<map name="primary"> <area shape="circle" coords="200,250,25" href="another.htm" /> <area shape="default" nohref /> </map>	
<article>	Specifies an article		<article class="hehe"> <p>Some para</p> <footer> <p> Posted on <time datetime="2018-09-15 02:40">Sep 15</time> by Harsh. </p> </footer> </article>	NEW
<aside>	Specifies content aside from the page content		<body> <main><p>Some para</p></main> <aside> <p>Some unrelated text which could not make it to main</p> </aside> </body>	NEW
<audio>	Specifies sound content	src; crossorigin; preload; autoplay; mediagroup	<audio src="http://abcradio.org/music.ogg" autoplay> Your browser does not support the <code>audio</code> element. </audio>	NEW
<b>	Specifies bold text		<b>bold</b>	
<base>	Specifies a base URL for all the links in a page	href; target	<base href="https://w3.org/somefolder">	
<bdi>	For bi-directional text formatting		<p dir="ltr">This arabic word <bdi>ARABIC PLACEHOLDER</bdi> is automatically displayed right-to-left.</p>	NEW
<bdo>	Specifies the direction of text display		<p><bdo dir="rtl">This text will go right to left.</bdo></p>	
<blockquote>	Specifies a long quotation	cite	<blockquote cite="https://tutes.club">This is a quote taken from tutes club</blockquote>	
<body>	Specifies the body element	onafterprint; onbeforeprint; onbeforeunload; onafterprint; onbeforeprint; onbeforeunload;	<body>ALL THE UNIVERSE INSIDE ME</body>	
 	Inserts a single line break		 	
<button>	Specifies a push button	autofocus; disabled; form; formaction; formenctype	<button name="bbbtnt">Click me </button>	
<canvas>	Define graphics	width; height	<canvas id="whatever" width="300" height="200">Alternate text</canvas>	NEW
<caption>	Specifies a table caption		<table><caption>table caption</caption><tr><td>some table</td></tr></table>	
<cite>	Specifies a citation		<p><cite>Sholay</cite> by Ramesh Sippy released in 1975</p>	
<code>	Specifies computer code text		<code>int x=0;</code>	
<col>	Specifies attributes for table columns	span		
<colgroup>	Specifies groups of table columns	span		
<data>	Allows for machine-readable data to be provided	value	<p><data value="2323">tenty three twenty three</data></p>	NEW
<datalist>	Specifies an "autocomplete" dropdown list		<label>Choose a browser from this list: <input list="browsers" name="myBrowser" /> </label> <datalist id="browsers"> <option value="Chrome"> <option value="Firefox"> <option value="Internet Explorer"> <option value="Opera"> <option value="Safari"> <option value="Microsoft Edge"> </datalist>	NEW
<dd>	Specifies a definition description		refer dl	

<del>	Specifies deleted text	cite; datetime	<p><del>deleted</del><ins>inserted</ins></p>	
<details>	Specifies details of an element	open	<details open> <summary>Summary of text</summary> <p>lots of detailed text</p> </details>	NEW (HTML5.1)
<dfn>	Defines a definition term		<p><dfn>Internet</dfn> is a network of computers connected to world wide web</p>	
<dialog>	Specifies that part of an application is interactive.	open	<dialog open><p>Hello Everyone</p></dialog>	NEW
<div>	Specifies a section in a document		<div>...</div>	
<dl>	Specifies a definition list		<dl> <dt>HTML</dt> <dd>Hypertext Markup Language</dd> <dt>CSS</dt> <dd>Cascading Style Sheets</dd> </dl>	
<dt>	Specifies a definition term		refer dl	
<em>	Specifies emphasized text		<em>emphasized</em>	
<embed>	Specifies external application or interactive content	src; type; width; height;		NEW
<fieldset>	Specifies a fieldset	disabled; form; name	refer legend	
<figcaption>	Specifies caption for the figure element.		refer figure	NEW
<figure>	Specifies a group of media content, and their caption		<figure> <figcaption>Taj Mahal</figcaption> <img src=tajmahal.png alt="The Taj"> </figure>	NEW
<footer>	Specifies a footer for a section or page		<footer><p>copyright company</p></footer>	NEW
<form>	Specifies a form	accept-charset; action; autocomplete; enctype	<form action="page.php" method="post"> <input name="itt" type="text"> <input type="submit" value="fill form"> </form>	
<h1>	Specifies a heading level 1		<h1>...</h1>	
<h2>	Specifies a heading level 2		<h2>...</h2>	
<h3>	Specifies a heading level 3		<h3>...</h3>	
<h4>	Specifies a heading level 4		<h4>...</h4>	
<h5>	Specifies a heading level 5		<h5>...</h5>	
<h6>	Specifies a heading level 6		<h6>...</h6>	
<head>	Specifies information about the document		<head><title>Hello World</title></head>	
<header>	Specifies a group of introductory or navigational aids, including hgroup elements		<header><div id=logo>Company</div></header>	NEW
<hr>	Specifies a horizontal rule		<p>...</p><hr><p>...</p>	
<html>	Specifies an html document	manifest	<html></html>	
<i>	Specifies italic text		<i>italic</i>	
<iframe>	Specifies an inline sub window (frame)	src; srcdoc; name; sandbox; width; height	<iframe src="https://somepage.com/somepage" width="400" height="600"><p>iframe not supported</p></iframe>	
<img>	Specifies an image	alt; src; crossorigin; usemap; ismap; width;		
<input>	Specifies an input field	accept; alt; autocomplete; autofocus; checked	<input type="text" value="some value">	
<ins>	Specifies inserted text	cite; datetime	<p><del>deleted</del><ins>inserted</ins></p>	
<kbd>	Specifies keyboard text		<p><kbd>CTRL + C</kbd></p>	
<label>	Specifies a label for a form control	form; for	<label>Click and type<input type="text"></label>	
<legend>	Specifies a title in a fieldset		<form><fieldset><legend>Legend Text</legend></fieldset></form>	
<li>	Specifies a list item	value	<ul><li>list item</li></ul>	
<link>	Specifies a resource reference	href; crossorigin; rel; media; hreflang; type	<link rel="stylesheet" href="somefile.css">	
<main>	Specifies the main content area of an HTML document.		<main> <h1>heading</h1> <article><h3></h3></article> </main>	NEW
<map>	Specifies an image map	name	refer area	
<mark>	Specifies marked text		<mark>marked text</mark>	NEW
<meta>	Specifies meta information	name; http-equiv; content; charset	<meta charset="utf-8">	
<meter>	Specifies measurement within a predefined range	value; min; max; low; high; optimum	<p>Heat the oven to <meter min="100" max="400" value="350">350 degrees</meter>.</p>	NEW
<nav>	Specifies navigation links		<nav><ul><li>sitemap</li><li>contact us</li></ul></nav>	NEW

<noscript>	Specifies a noscript section		<noscript>please enable javascript</noscript>	
<object>	Specifies an embedded object	data; type; typemustmatch; name; usemap; form; width; height		
<ol>	Specifies an ordered list	reversed; start; type	<ol><li>ordered item1</li></ol>	
<optgroup>	Specifies an option group	disabled; label		
<option>	Specifies an option in a drop-down list	disabled; label; selected; value	refer select	
<output>	Specifies some types of output	for; form; name		NEW
<p>	Specifies a paragraph		<p>...</p>	
<param>	Specifies a parameter for an object	name; value		
<pre>	Specifies preformatted text		<pre>looks preformatted</pre>	
<progress>	Specifies progress of a task of any kind	value; max	<progress value="50" max="100">50% complete</progress>	NEW
<q>	Specifies a short quotation	cite	<p> Remember Teja? <q cite="https://www.imdb.com/title/tt0109117/">Mark idhar hai!!</q> </p>	
<s>	Indicates text that's no longer accurate or relevant.		<s>some old fact</s>	
<samp>	Specifies sample computer code		<samp>X is 4.</samp>	
<script>	Specifies a script	src; type; charset; async; defer; crossorigin	<script type="text/javascript">alert("sdfsdf");</script>	
<section>	Specifies a section		<section><div></div></section>	NEW
<select>	Specifies a selectable list	autofocus; disabled; form; multiple; name; re	<select name="select"><option value="value1">Value 1</option><option value="value2" selected>Value 2</option><option value="value3">Value 3</option></select>	
<small>	Specifies small text		<small>mini size</small>	
<source>	Specifies media resources	src; type; media	refer picture	NEW
<span>	Specifies a section in a document		<span>hoho</span>	
<strong>	Specifies strong text		<strong>important text</strong>	
<style>	Specifies a style definition	media; type	<style>#eye{color:white}</style>	
<sub>	Specifies subscripted text		C<sub>2</sub>H<sub>5</sub>OH	
<summary>	Specifies a summary / caption for the <details> element		refer details	NEW (HTML 5.1)
<sup>	Specifies superscripted text		<p>22<sup>nd</sup> September</p>	
<table>	Specifies a table		<table><thead><tr><th>heading</th><th>heading</th></tr></thead><tbody><tr><td>data</td><td>data</td></tr></tbody><tfoot><tr><td colspan="2">tfoot</td></tr></tfoot></table>	
<tbody>	Specifies a table body		refer table	
<td>	Specifies a table cell		refer table	
<template>	Declares HTML fragments that can be cloned and inserted in the document by script.			NEW
<textarea>	Specifies a text area	autofocus; cols; dirname; disabled; form; max	<form><textarea name="txtarr2" cols="40" rows="30"></textarea></form>	
<tfoot>	Specifies a table footer		refer table	
<th>	Specifies a table header	colspan; rowspan; headers; scope; abbr	refer table	
<thead>	Specifies a table header		refer table	
<time>	Specifies a date/time	datetime	<p>event will start at <time>22:00</time></p>	NEW
<title>	Specifies the document title		refer head	
<tr>	Specifies a table row		refer table	
<track>	Specifies a text track for media such as video and audio	default; kind; label; src; srclang		NEW
<u>	Specifies text with a non-textual annotation.		<u>underline</u>	
<ul>	Specifies an unordered list		<ul><li>list item</li></ul>	
<var>	Specifies a variable		<p><var>x</var> + <var>y</var> + 2</p>	
<video>	Specifies a video	src; crossorigin; poster; preload; autoplay;	<video src="some/file.webm" autoplay><p>Not supported</p></video>	NEW

`<wbr>`

Specifies a line break opportunity for very long words and strings of text with no spaces.

```
<p>some<wbr>really<wbr>really  
<wbr>long<wbr>word</p>
```

**NEW**