

DRY-RUN GUIDE | 06_two_sum_indices.py
Source: Python\dsa_solutions\06_two_sum_indices.py

CORE BEHAVIOR

Uses a map of values already seen to find the complement and return matching indices.

REPRESENTATIVE INPUT

[2,7,11,15], target=9.

STEP TRACE

Store 2 at index 0; at index 1, complement $9-7=2$ is present.

EXPECTED OUTPUT / RETURN

'[0,1]'

ACTUAL SOURCE EXCERPT

Verbatim excerpt from Python\dsa_solutions\06_two_sum_indices.py; line numbers refer to the original file. No source was modified.

```
001 | import sys
002 |
003 |
004 | def main():
005 |     data = list(map(int, sys.stdin.read().split()))
006 |     if not data:
007 |         return
008 |     count = data[0]
009 |     numbers = data[1:1 + count]
010 |     target = data[1 + count]
011 |     seen = {}
012 |     for index, number in enumerate(numbers):
013 |         needed = target - number
014 |         if needed in seen:
015 |             print(seen[needed], index)
016 |             return
017 |         seen[number] = index
018 |     print(-1)
019 |
020 |
021 | if __name__ == "__main__":
022 |     main()
023 |
```

DRY-RUN NOTE

Values are representative. For function-only modules the guide uses an illustrative direct call and explains its return; quirks/errors describe actual behavior.