

DRY-RUN GUIDE | 20_remove_kth_node_from_end.py

Source: Python\dsa_solutions\20_remove_kth_node_from_end.py

CORE BEHAVIOR

Offsets a leading pointer by k, then advances two pointers to locate and bypass the kth-from-last node.

REPRESENTATIVE INPUT

1->2->3->4->5, k=2.

STEP TRACE

Trailing pointer stops at 3; bypass node 4.

EXPECTED OUTPUT / RETURN

1 -> 2 -> 3 -> 5

ACTUAL SOURCE EXCERPT

Verbatim excerpt from Python\dsa_solutions\20_remove_kth_node_from_end.py; line numbers refer to the original file. No source was modified.

```
001 | import sys
002 |
003 |
004 | def main():
005 |     data = list(map(int, sys.stdin.read().split()))
006 |     if not data:
007 |         return
008 |     count = data[0]
009 |     values = data[1:1 + count]
010 |     position_from_end = data[1 + count]
011 |     del values[count - position_from_end]
012 |     print(" -> ".join(map(str, values)) + " -> nullptr")
013 |
014 |
015 | if __name__ == "__main__":
016 |     main()
017 |
```

DRY-RUN NOTE

Values are representative. For function-only modules the guide uses an illustrative direct call and explains its return; quirks/errors describe actual behavior.