

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Hide

Clear Response

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

☐ It keeps executing indefinitely.

5/5

+1 0

A learner changes the condition to `while n != 0:` and changes the update to `n = n - 6`, while keeping `n = 20`. What happens?

☐ The loop stops when `n` becomes `2`.

☐ The loop stops when `n` becomes `0`.

☐ The loop executes exactly four times and then stops.

☐ The loop continues because the update skips past `0`.

Clear Response

< Previous

Next >

Your camera feed, audio and screen are being proctored.

kalvium.community is sharing your screen.

Stop sharing

Hide

on 17 of 18

Instructions

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

Mark for review

+10

0

Transaction Filter

A payment dashboard receives transaction amounts and needs two kinds of information. First, it must count how many transactions belong to each spending band. Second, it must keep transactions from a chosen qualification range and create an adjusted version of those values for a reward calculation.

Write a program that reads the transaction amounts, stores them in a list, and processes them with a loop.

Classify every transaction into exactly one spending band:

- **Budget:** amount less than
- **Standard:** amount from to inclusive
- **Premium:** amount or greater

A transaction is **qualified** when its amount is from to inclusive. For every qualified transaction, keep its original amount in one new list and store in another new list called the adjusted list.

Your program must:

1. Read an integer , followed by integer transaction amounts.
2. Store all transaction amounts in a list in input order.
3. Use separate counters for Budget, Standard, and Premium transactions.
4. Classify each amount into exactly one band.

< Previous

Next >

Your camera feed, audio and screen are being proctored.

kakvium.community is sharing your screen.

Stop sharing
 Hide

1

Instructions

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

< Previous

Next >

A transaction is **qualified** when its amount is from to inclusive. For every qualified transaction, keep its original amount in one new list and store in another new list called the adjusted list.

Program must:

1. Read an integer , followed by integer transaction amounts.
2. Store all transaction amounts in a list in input order.
3. Use separate counters for Budget, Standard, and Premium transactions.
4. Classify each amount into exactly one band.
5. Build a Qualified list containing amounts from to inclusive.
6. Build an Adjusted list containing each qualified amount minus .
7. Preserve duplicates and original order in both new lists.

Input Format

- Line 1: integer , the number of transactions
- Next lines: one integer transaction amount per line

Output Format

Print exactly five lines:

```

Budget: <number of Budget transactions>
Standard: <number of Standard transactions>
Premium: <number of Premium transactions>
Qualified: <list of qualified amounts>
Adjusted: <list of qualified amounts after subtracting 100>
    
```

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Hide

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

Qualified: <list of qualified amounts>
Adjusted: <list of qualified amounts after subtracting 100>

both lists using Python list format, including brackets and commas. If no amount qualifies, print [] for both lists.

Example 1

Input

```
6
250
500
1200
1999
2000
3500
```

Output

```
Budget: 1
Standard: 3
Premium: 2
Qualified: [1200, 1999, 2000]
Adjusted: [1100, 1899, 1900]
```

Explanation

< Previous

Next >

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Hide

- Explanation
- 250 is below 500, so it increases the Budget count.
- 500, 1200, and 1999 fall from 500 to 1999, so the Standard count is 3.
- 2000 and 3500 are at least 2000, so the Premium count is 2.
 - 1200, 1999, and 2000 are also inside the separate qualification range from 1000 to 3000.
 - Subtracting 100 from those qualified amounts produces [1100, 1899, 1900].

Example 2

Input

```
3
100
400
4500
```

Output

```
Budget: 2
Standard: 0
Premium: 1
Qualified: []
Adjusted: []
```

< Previous

Next >

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

Instructions

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

Explanation

- 100

 and

400

 are Budget transactions, while

4500

 is Premium.
- 1000

 to amount is between

1000

 and

3000

 inclusive.
- Since nothing qualifies, no value is appended and both result lists remain empty.

Constraints

- 0 <= n <= 20
- 0 <= amount <= 5000
- The values

500

 and

1999

 belong to Standard.
- The value

2000

 belongs to Premium.
- The qualification boundaries

1000

 and

3000

 are included.
- Band classification and qualification are separate decisions. One amount belongs to one band and may also be qualified.
- Duplicate qualified amounts must appear repeatedly in both result lists.
- Read each input using plain `input()` with no prompt text.
- Use direct loop iteration, counters, `if/elif/else` combined conditions, and `.append()`.
- Do not use list comprehensions, `filter()`, `map()`, `.count()`, imports, or hardcoded outputs.

PYTHON

1

Use print() to print to the console

Your camera feed, audio
kalvium.community is sharing your screen.

Stop sharing

Hide

Mark for review

+10 0

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

Question 18 of 18

Score Statistics

A training platform records scores from a practice assessment. A raw list of scores is not enough for the trainer, so the platform must turn it into a useful report containing the total, lowest score, highest score, average, and number of students who scored above the group average.

Write a program that reads the number of scores followed by the scores themselves. Store the scores in a list and process them using accumulator patterns.

The report requires two passes through the list. In the first pass, calculate the count, sum, minimum, and maximum. After that pass, calculate the average. In the second pass, count how many scores are **strictly greater than** that average.

Your program must:

1. Read an integer , followed by integer scores.
2. Store all scores in a list in input order.
3. Calculate the count, sum, minimum, and maximum manually using a loop.
4. Calculate the average only after the first pass is complete.
5. Scan the list again and count scores strictly greater than the average.
6. Print when is , without indexing the empty list or dividing by zero.

Input Format

- Line 1: integer , the number of scores

< Previous

Next >

Your camera feed, audio and screen are being proctored.



Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

Input Format

- Line 1: integer the number of scores
- Next lines: one integer score per line

Output Format

If is greater than , print exactly six lines:

```
Count: <number of scores>
Sum: <sum of all scores>
Minimum: <smallest score>
Maximum: <largest score>
Average: <average shown to exactly 2 decimal places>
Above average: <number of scores strictly above the average>
```

If is , print exactly:

No scores

Example 1

Input

|| kalvium.community is sharing your screen.

Stop sharing

Hide

< Previous

Next >


 Your camera feed, audio and screen are being proctored.



1

Instructions

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

|| kalvium.community is sharing your screen.

Stop sharing
 [Hide](#)

Example 1

Input

```
5
82
45
91
67
58
```

Output

```
Count: 5
Sum: 343
Minimum: 45
Maximum: 91
Average: 68.60
Above average: 2
```

Explanation

- Five scores are read and stored: [82, 45, 91, 67, 58].
- The first pass gives a sum of [343], a minimum of [45], and a maximum of [91].
- The average is [343 / 5 = 68.6] displayed as [68.60].
- In the second pass, only [82] and [91] are strictly greater than [68.6] so the above-average count is [2].

<
 Previous

Next
 >

Your camera feed, audio and screen are being proctored.

i

Instructions

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

||

kalvium.community is sharing your screen.

Stop sharing

Hide

Example 2

Input

0

Output

No scores

Explanation

- The value `0` means no score lines follow.
- There is no first score that can initialise minimum or maximum, and calculating an average would divide by zero.
- The program therefore prints `No scores` and performs no statistical calculation.


Constraints

- `0 <= n <= 20`
- `-100 <= score <= 100`
- Scores may repeat and may be negative.
- A score equal to the average is not counted as above average.
- Use `/` for division and display the average with exactly two decimal places.
- Initialise minimum and maximum from an actual score, not from `0`, so all-negative input works correctly.
- Read each input using plain `input()` with no prompt text.

Do not use `sum()`, `min()`, `max()`, `sorted()`, list comprehensions, imports, or hardcoded outputs.

< Previous

Next >



kalvium.community is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 1 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18


A programmer writes `result = []` inside a loop before checking each item. What is the most likely consequence?

- ☐ Every matching item is permanently retained
- ☐ The list is repeatedly reset, so earlier matches are lost
- ☐ The list automatically sorts matching items
- ☐ Every item is appended regardless of the condition

 Clear Response

[< Previous](#)

[Next >](#)



kavium.community is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 2 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

A dataset contains five values, but only two satisfy a filtering condition. Which quantities should be accumulated to compute the average of only those two values?

- ☐ Total of all values and total count
- ☐ Total of matching values and count of matching values
- ☐ Maximum of matching values and total count
- ☐ Minimum of all values and count of all values

 Clear Response

[< Previous](#)

[Next >](#)

Your camera feed, audio and screen are being proctored.



kalvium.community is sharing your screen.

Stop sharing

Hide

 Mark for review

+1 0

Question 3 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18


Which operation adds one matching item to a list without replacing the existing items?

- ☐ `result = item`
- ☐ `result.append(item)`
- ☐ `result = [item]`
- ☐ `result + item`

 Clear Response

[< Previous](#)

[Next >](#)



kalvium.community is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 4 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

A program receives a list containing 5,000 customer records and must perform the same validation on every record. Which approach is most appropriate?

- ☐ Write the validation code separately for every record
- ☐ Use a loop so one validation action can process each record
- ☐ Validate only the first record and assume the rest match
- ☐ Create one conditional statement containing 5,000 separate cases

 Clear Response

[< Previous](#)

[Next >](#)

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Mark for review

+1 0

Question 5 of 18

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |

Given `nums = [1, 2, 3, 4, 5]`, what is produced by `doubled_evens` when the program keeps even numbers but appends twice their value?

- ☐ `[2, 4]`
- ☐ `[4, 8]`
- ☐ `[2, 4, 6, 8, 10]`
- ☐ `[1, 3, 5]`

Clear Response

< Previous

Next >

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Hide

Question 6 of 18

Mark for review

+1 0

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

A programmer wants both the matching items and their count. Which strategy avoids maintaining two separate accumulators?

- ☐ Use only a counter and reconstruct the items later
- ☐ Use only the original list and call `len()`
- ☐ Build the filtered list and obtain its count with `len()`
- ☐ Use two independent filtered lists

Clear Response

< Previous

Next >

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Mark for review

+1 0

Question 7 of 18

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |

A program calculates `total / count` after processing a collection, but the collection may be empty. Which change makes the calculation robust?

- ☐ Replace `/` with `//`
- ☐ Calculate the division inside the loop
- ☐ Perform the division only when `count > 0`
- ☐ Set `count` to `1` before processing

Clear Response

Previous

Next

Your camera feed, audio and screen are being proctored.



kalamandalam.com is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 8 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

Consider a program that needs to calculate the final grade for one student and then calculate grades for every student in a class. Which statement correctly distinguishes the two tasks?

- ☐ Both tasks require loops because grading always involves repetition
- ☐ The first task is one-time, while the second repeats the grading action
- ☐ The first task requires a loop, while the second is always one-time
- ☐ Both tasks should use separate copies of the grading logic

 Clear Response

[< Previous](#)

[Next >](#)

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Mark for review

+1 0

Question 9 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

A list contains `[12, 18, 25]`. A program uses `total = 0` and adds each value once. What value does `total` contain after the loop?

- ☐ 55
- ☐ 45
- ☐ 35
- ☐ 65

Clear Response

< Previous

Next >

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Mark for review

+1 0

Question 10 of 18

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |

A list is `[15, 22, 8, 40, 11, 30]`. To count values above the list's own average, why must the average be calculated before performing the filtering/counting comparison?

- ☐ The average depends on knowing which values pass
- ☐ The average can only be computed from filtered values
- ☐ The comparison condition cannot use numbers
- ☐ Counting always requires two passes

Clear Response

Previous

Next

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Mark for review

+1 0

Question 11 of 18

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |


A program uses `average = total // count` instead of `average = total / count`. What type of error can result?

- ☐ The loop may execute indefinitely
- ☐ The count may become negative
- ☐ The fractional part of the average may be lost
- ☐ The minimum value may be overwritten

Clear Response

< Previous

Next >



kalvium.community is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 12 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18


Which operation gives the average of accumulated values?

- ☐ `count / sum`
- ☐ `sum + count`
- ☐ `sum / count`
- ☐ `sum * count`

 Clear Response

[< Previous](#)

[Next >](#)



kalvium.community is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 13 of 18

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |


A programmer places `count = 0` inside a loop that processes five values. What is the main consequence?

- ☐ The count records only the current pass
- ☐ The count becomes the total number of values
- ☐ The count automatically becomes the average
- ☐ The count changes into the current data value

 Clear Response

[< Previous](#)

[Next >](#)



kalvium.community is sharing your screen.

Stop sharing

 Mark for review

+1 0

Question 14 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18


Which characteristic most directly distinguishes a loop from a one-time step?

- ☐ The action contains more than one line of code
- ☐ The action produces output on the screen
- ☐ The action is performed repeatedly under some control
- ☐ The action uses a value that changes during execution

 Clear Response

[< Previous](#)

[Next >](#)



 Mark for review

+1 0

 kavium.community is sharing your screen.

Stop sharing

 Hide Question 15 of 18

 Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

A conditional accumulator processes [20, 55, 70, 35] and adds only values at least [50]. Which pair of final values should it produce for the conditional sum and count?

- ☐ Sum 125, count 2
- ☐ Sum 90, count 2
- ☐ Sum 125, count 3
- ☐ Sum 160, count 4

 Clear Response

 Previous

Next 

Your camera feed, audio and screen are being proctored.

 Mark for review

 kavium.community is sharing your screen.

Stop sharing

 on 16 of 18

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

Read the code snippet below and answer the questions that follow.

A program processes a positive integer by repeatedly removing its last digit. During each pass, it adds the removed digit to . It also counts how many passes are performed.

```
n = 5832
total = 0
passes = 0

while n > 0:
    digit = n % 10


    if digit % 2 == 0:
        total = total + digit
    else:
        total = total - digit

    n = n // 10
    passes = passes + 1

print(total)
print(passes)
```

[< Previous](#)

[Next >](#)



kavium.community is sharing your screen.

Stop sharing

Hide

```
n = n // 16
passes = passes + 1

print(total)
print(passes)
```

Instructions

1	2	3
4	5	6
7	8	9
10	11	12
13	14	15
16	17	18

1/5

+1 0

What is the value of `total` when the program finishes?

- ☐ 2
- ☐ 4
- ☐ 6
- ☐ 8

 Clear Response

< Previous

Next >

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Clear Response

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |

2/5

+1 0

Which sequence shows the values of n immediately after each execution of $n = n // 10$?

☐ 582, 58, 5, 0

☐ 583, 58, 5, 1

☐ 583, 58, 5, 0

☐ 583, 59, 6, 0

Clear Response

3/5

+1 0

Previous

Next

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Clear Response

3/5

+1 0

Suppose the line `n = n // 10` is changed to `n = n - 10`. What happens to the loop for this starting value?

- ☐ It still processes exactly four digits and terminates.
- ☐ It terminates after processing the original four digits.
- ☐ It continues while `n` remains positive, but no longer extracts digits correctly.
- ☐ It immediately stops because subtracting `10` makes `n` negative.

Clear Response

< Previous

Next >

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |

Your camera feed, audio and screen are being proctored.



kavium.community is sharing your screen.

Stop sharing

Hide

Clear Response

Instructions

- | | | |
|----|----|----|
| 1 | 2 | 3 |
| 4 | 5 | 6 |
| 7 | 8 | 9 |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |

4/5

+1 0

If the initial value of `n` is changed from `5832` to `0`, how many times does the loop body execute?

☐ 0

☐ 1

☐ 4

☐ It keeps executing indefinitely.

 Clear Response

< Previous

Next >