

High Current, Power Inductors

MPCA-0518-XXX-M Power Choke



Description

- Halogen Free
- 125°C maximum total temperature operation
- 5.7 x 5.4 x 1.8mm maximum surface mount package
- Powder iron core material
- Magnetically shielded, low EMI
- High current carrying capacity, Low core losses
- Frequency range up to 5MHz
- RoHS compliant

Applications

- Voltage Regulator Module (VRM)
- Multi-phase regulators
- Point-of-load modules
- Smart phone POL modules
- SSD modules
- Notebook regulators
- Battery power systems
- Graphics cards
- Data networking and storage systems

Environmental Data

- Storage temperature range: -55°C to +125 °C
- Operating temperature range: -55°C to +125°C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020D compliant



Description												
MPCA-0518-1R0-M				1.0μH				±20 %				
Model				Inductance Value				Inductance Tolerance				
Global Part Number												
M	P	C	A	0	5	1	8	1	R	0	M	
Product Series				Dimensions				Inductance			ValueTol.	

Part No.	Inductance	DC Resistance		Heatin	Rating Current	Saturation Current
	L0 (μH)	DCR (mΩ)			Idc (A)	Isat (A)
	±20 %, 100 kHz, 1V	TYP.	MAX.		TYP.	TYP.
MPCA-0518-R47-M	0.47	7.7	9.0		10.5	15.5
MPCA-0518-R56-M	0.56	8.0	10.0		9.5	15.0
MPCA-0518-1R0-M	1.0	15.0	17.0		8.0	9.0
MPCA-0518-1R5-M	1.5	21.0	26.0		7.5	9.0
MPCA-0518-2R2-M	2.2	30.0	35.0		5.0	6.5
MPCA-0518-3R3-M	3.3	52.0	58.0		4.5	5.0
MPCA-0518-4R7-M	4.7	78.0	85.0		3.5	4.0
MPCA-0518-6R8-M	6.8	107.0	120.0		2.8	3.4
MPCA-0518-100-M	10.0	140.0	155.0		2.5	3.0

Notes

1. All test data is referenced to 25 °C ambient
2. Operating temperature range - 55 °C to + 125 °C
3. Idc(A):DC current (A) that will cause an approximate ΔT of 40 °C(reference ambient temperature is 25°C)
4. Isat(A):DC current (A) that will cause L0 to drop approximately 30 %
5. The part temperature (ambient + temp rise) should not exceed 125 °C under worst case operating conditions. Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

•Dimensions-mm



Recommend Land Pattern Dimensions



Marking

The inductor is marked with a 3-digit code

Example - -1.0→1R0

Note : Using Ink for marking





鴻達電能科技股份有限公司

