

ICECORE 15 (R290)

REMOTE COOLER CARBONATOR



FEATURES & BENEFITS

In a climate where ecology and economy are critical factors, it is important for the beverage industry to create more efficient products.

We are dedicated on addressing these issues directly and have developed market-leading cooling and dispense products that optimise performance and lower costs.

ICECORE™ offers dramatic improvements in energy consumption and reliability, with overall lower 'Total Cost of Ownership'.

- Significant improvements in insulation properties.
- Environmentally acceptable refrigerant (R290)
- Enhanced reliability via the use of high specification and 'designed for purpose' components.
- Smart electronic controls



ISO 9001
Quality
Management
Systems
CERTIFIED

ISO 14001
Environmental
Management
CERTIFIED

SPECIFICATIONS

PERFORMANCE

ICE BANK PULL DOWN	2hr 45min
ICE BANK WEIGHT	15kg Nominal
DISPENSE CAPACITY	459 x 340ml @2DPM
OPTIMISED AMBIENT TEMPERATURE	24°C
MAX OPERATING TEMPERATURE	40°C
RECOMMENDED LENGTH	40 meters max

HEAT REJECTION RATES

INTEGRAL (AVERAGE/PER HOUR)	0.50kWh
WATER COOLED (AVERAGE/PER HOUR)	0.46kWh

PHYSICAL DATA

HEIGHT	648mm (inc feet)
WIDTH	870mm (inc handles)
DEPTH	526mm
WATERBATH CAPACITY	43ltrs
DRY WEIGHT	77kg
OPERATING WEIGHT	120kg

ELECTRICAL

MAINS VOLTAGE	220-240V AC / 50Hz
RUN CURRENT	4.4 amps
FUSE RATING	10 amps

REFRIGERATION

COMPRESSOR SIZE	12.87cc
DUTY @ -10°C EVAPORATION	840W
REFRIGERANT	R290
INTEGRAL CHARGE	150g
WATER COOLED CHARGE	100g

CONTROLS

ICE BANK	3 pin resistive probe
CARBONATOR LIQUID LEVELS	Bi-level Resistive Probes

CARBONATION SYSTEM

BOWL RESERVE	1.8 ltr
FILL PUMP	125 gal/hr Brass Rotary
RECIRC PUMP	TMFR ST/ST

SYSTEM PROTECTION

COMPRESSOR	Thermal Switch (auto reset)
CARBONATOR PUMP	Programmable
RECIRC PUMP	Programmable

COILS

SYRUP	Qty 8
PRE-CHILL	Qty 1
SODA RECIRCULATION	Qty 1
STILL WATER	Qty 1
PRE-MIX	2

Also available ICECORE10 Water Cooled Model

Continuing product improvement may necessitate change of specifications without notice.