

# CENG 3549 – Functional Programming

## User-Defined Types & Trees & Input and Output

Burak Ekici

October 13, 2022

# Outline

① Intermediate Wrap-Up

② User-Defined Types

③ Trees

④ Input and Output

## Functions You Need to Know

- infix operators and special syntax  
(<=), (<), (==), (>=), (>), (||), (-), (,), (:), (/=), (.), (\*), (&&), (+), (++), [], [m..n]
- other `Prelude` functions  
abs, compare, concat, const, div, drop, error, even, filter, foldr, foldr1, fromInteger, fst, head, init, last, length, lines, map, max, min, mod, negate, not, null, product, putStr, putStrLn, read, replicate, reverse, show, showList, showsPrec, signum, snd, splitAt, sum, tail, take, unlines, unwords, words, zip, zipWith
- other `Prelude` constants  
False, otherwise, True
- other functions  
`Data.Char.isDigit`, `System.Environment.getArgs`

## Syntax You Need to Recognize

- **anonymous functions** / functions without names

`(\x -> 2 * x) -- an anonymous function for doubling`

## Syntax You Need to Recognize

- anonymous functions / functions without names

`(\x -> 2 * x)` -- an anonymous function for doubling

- infix operators and sections

`(+)` = `(\x y -> x + y)`

`x `f` y` = `f x y`

`(a >)` = `(\x -> a > x)`

`(> b)` = `(\x -> x > b)`

infix to prefix

prefix to infix

argument smaller than `a`?

argument greater than `b`?

## Syntax You Need to Recognize

- anonymous functions / functions without names

`(\x -> 2 * x)` -- an anonymous function for doubling

- infix operators and sections

`(+)` = `(\x y -> x + y)`

`x `f` y` = `f x y`

`(a >)` = `(\x -> a > x)`

`(> b)` = `(\x -> x > b)`

infix to prefix

prefix to infix

argument smaller than `a`?

argument greater than `b`?

- patterns and guards

```
headIfPositive xs = case xs of
  x:_ | x > 0 -> x
```

## Syntax You Need to Recognize

- anonymous functions / functions without names

`(\x -> 2 * x)` -- an anonymous function for doubling

- infix operators and sections

`(+)` = `(\x y -> x + y)`

`x `f` y` = `f x y`

`(a >)` = `(\x -> a > x)`

`(> b)` = `(\x -> x > b)`

infix to prefix

prefix to infix

argument smaller than `a`?

argument greater than `b`?

- patterns and guards

```
headIfPositive xs = case xs of
  x:_ | x > 0 -> x
```

- list comprehensions

```
filter p xs == [x | x <- xs, p x]
```

```
map f xs == [f x | x <- xs]
```

```
concat (map f xs) == [y | x <- xs, y <- f x]
```

```
concat $ map (\x -> map ((,)x) ys) xs == [(x, y) | x <- xs, y <- ys]
```

## Types and Type Classes

- **type signatures** – annotate functions by types

```
range :: Int -> Int -> [Int]
range m n | m > n      = []
          | otherwise = m : range (m + 1) n
```



## Types and Type Classes

- type signatures – annotate functions by types

```
range :: Int -> Int -> [Int]
range m n | m > n      = []
          | otherwise = m : range (m + 1) n
```

- type synonyms – mnemonic names for types

```
type Height = Int
type Width  = Int
```

## Types and Type Classes

- type signatures – annotate functions by types

```
range :: Int -> Int -> [Int]
range m n | m > n      = []
          | otherwise = m : range (m + 1) n
```

- type synonyms – mnemonic names for types

```
type Height = Int
type Width  = Int
```

- **type classes** and **class constraints** – for every function **f**, specific to class **C**, type inference adds a **C**-constraint to type

## Types and Type Classes

- type signatures – annotate functions by types

```
range :: Int -> Int -> [Int]
range m n | m > n      = []
          | otherwise = m : range (m + 1) n
```

- type synonyms – mnemonic names for types

```
type Height = Int
type Width  = Int
```

- type classes and class constraints – for every function `f`, specific to class `C`, type inference adds a `C`-constraint to type

## Example

- without type signature, we get

```
ghci> :t range
range :: (Ord a, Num a) => a -> a -> [a]
```

- `m > n`, hence `m` and `n` of class `Ord` and `m` and `n` of same type
- `m + 1`, hence `m` of class `Num`
- `m` and `n` of same type, hence `n` of class `Num`

## Equational Reasoning

- a function definition in Haskell is a (set of conditional) equation(s)
- if conditions are met, we may “replace equals by equals”
- in this way we may **evaluate** function calls by applying equations stepwise, until we reach final result

## Equational Reasoning

- a function definition in Haskell is a (set of conditional) equation(s)
- if conditions are met, we may “replace equals by equals”
- in this way we may evaluate function calls by applying equations stepwise, until we reach final result

## Kinds of Conditions

- “**if**  $b$  **then**  $t$  **else**  $e$ ” is  $t$ , when  $b$  is true; and  $e$ , otherwise
- “**case**  $e$  **of** {  $p_1 \rightarrow e_1$ ; ... ;  $p_n \rightarrow e_n$  }” is  $e_i$ , if  $e$  first matches  $p_i$

## Equational Reasoning

- a function definition in Haskell is a (set of conditional) equation(s)
- if conditions are met, we may “replace equals by equals”
- in this way we may evaluate function calls by applying equations stepwise, until we reach final result

## Kinds of Conditions

- “**if**  $b$  **then**  $t$  **else**  $e$ ” is  $t$ , when  $b$  is true; and  $e$ , otherwise
- “**case**  $e$  **of**  $\{ p_1 \rightarrow e_1; \dots; p_n \rightarrow e_n \}$ ” is  $e_i$ , if  $e$  first matches  $p_i$

## Primitive Operations

- for primitive operations (like  $(+)$ ,  $(*)$ ,  $\dots$ ), we assume predefined equations
- e.g.,  $1 + 2 = 3$ ,  $0 * 10 = 0$ ,  $\dots$

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`



## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`

- definition

```
factorial n | n <= 1 = 1
            | otherwise = n * factorial (n - 1)
```

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`

- definition

```
factorial n | n <= 1 = 1
            | otherwise = n * factorial (n - 1)
```

- evaluate `factorial 3`

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`

- definition

```
factorial n | n <= 1 = 1
            | otherwise = n * factorial (n - 1)
```

- evaluate `factorial 3`

- definition `head xs = case xs of x:_ -> x`

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`

- definition

```
factorial n | n <= 1 = 1
            | otherwise = n * factorial (n - 1)
```

- evaluate `factorial 3`

- definition `head xs = case xs of x:_ -> x`

- evaluate `head "ab"`

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`

- definition

```
factorial n | n <= 1 = 1
            | otherwise = n * factorial (n - 1)
```

- evaluate `factorial 3`

- definition `head xs = case xs of x:_ -> x`

- evaluate `head "ab"`

- definitions

```
null xs = case xs of { [] -> True; _ -> False }
tail xs = case xs of _:ys -> ys
prod xs = if null xs then 1
          else head xs * prod (tail xs)
```

## Examples (equational reasoning)

- definition

```
zip (x:xs) (y:ys) = (x, y) : zip xs ys
zip _      _      = []
```

- evaluate `zip [1,2,3] ['a','b']`

- definition

```
factorial n | n <= 1 = 1
            | otherwise = n * factorial (n - 1)
```

- evaluate `factorial 3`

- definition `head xs = case xs of x:_ -> x`

- evaluate `head "ab"`

- definitions

```
null xs = case xs of { [] -> True; _ -> False }
tail xs = case xs of _:ys -> ys
prod xs = if null xs then 1
          else head xs * prod (tail xs)
```

- evaluate `prod [5,6]`

# Outline

1 Intermediate Wrap-Up

2 User-Defined Types

3 Trees

4 Input and Output

## Data Declarations – Algebraic Data Types

- new types are introduced by

$$\begin{array}{rcl} \text{data } T \alpha_1 \cdots \alpha_n & = & C_1 \tau_{11} \cdots \tau_{1m_1} \\ & & \vdots \\ & & C_k \tau_{k1} \cdots \tau_{km_k} \end{array}$$



## Data Declarations – Algebraic Data Types

- new types are introduced by

$$\begin{array}{rcl} \text{data } T \, \alpha_1 \cdots \alpha_n & = & C_1 \, \tau_{11} \cdots \tau_{1m_1} \\ & & \vdots \\ & & C_k \, \tau_{k1} \cdots \tau_{km_k} \end{array}$$

- where  $T$  is name of new type (constructor) –starting with capital letter– taking  $n$  type parameters  $\alpha_1$  to  $\alpha_n$

## Data Declarations – Algebraic Data Types

- new types are introduced by

$$\begin{array}{rcl} \text{data } T \alpha_1 \cdots \alpha_n & = & C_1 \tau_{11} \cdots \tau_{1m_1} \\ & & \vdots \\ & & C_k \tau_{k1} \cdots \tau_{km_k} \end{array}$$

- where  $T$  is name of new type (constructor) –starting with capital letter– taking  $n$  type parameters  $\alpha_1$  to  $\alpha_n$
- and  $C_i$  is name of  $i$ th (data) **constructor**, taking  $m_i$  arguments of types  $\tau_{i1}$  to  $\tau_{im_i}$  (with type variables among  $\alpha_1$  to  $\alpha_n$ )

## Data Declarations – Algebraic Data Types

- new types are introduced by

$$\begin{array}{rcl} \text{data } T \alpha_1 \cdots \alpha_n & = & C_1 \tau_{11} \cdots \tau_{1m_1} \\ & & \vdots \\ & & C_k \tau_{k1} \cdots \tau_{km_k} \end{array}$$

- where  $T$  is name of new type (constructor) –starting with capital letter– taking  $n$  type parameters  $\alpha_1$  to  $\alpha_n$
- and  $C_i$  is name of  $i$ th (data) constructor, taking  $m_i$  arguments of types  $\tau_{i1}$  to  $\tau_{im_i}$  (with type variables among  $\alpha_1$  to  $\alpha_n$ )

## Examples

- `data Bool = False | True`
- `data List a = Nil | Cons a (List a)`
- `data Pair a b = Pair a b`

## Data Declarations – Algebraic Data Types

- new types are introduced by

$$\begin{array}{lcl} \text{data } T \alpha_1 \cdots \alpha_n & = & C_1 \tau_{11} \cdots \tau_{1m_1} \\ & & \vdots \\ & & C_k \tau_{k1} \cdots \tau_{km_k} \end{array}$$

- where  $T$  is name of new type (constructor) –starting with capital letter– taking  $n$  type parameters  $\alpha_1$  to  $\alpha_n$
- and  $C_i$  is name of  $i$ th (data) constructor, taking  $m_i$  arguments of types  $\tau_{i1}$  to  $\tau_{im_i}$  (with type variables among  $\alpha_1$  to  $\alpha_n$ )

## Examples

- `data Bool = False | True`
- `data List a = Nil | Cons a (List a)`
- `data Pair a b = Pair a b`

constructors and type names live in different name spaces

## Automatically Deriving Type Class Instances

- for some type classes it is possible to automatically derive instances for algebraic data types
- e.g.,  

```
data List a = Nil | Cons a (List a)  
  deriving (Eq, Show, Read)
```
- now, we are able to use `(==)`, `show`, and `read` for `Lists`

## Automatically Deriving Type Class Instances

- for some type classes it is possible to automatically derive instances for algebraic data types
- e.g.,  

```
data List a = Nil | Cons a (List a)  
  deriving (Eq, Show, Read)
```
- now, we are able to use (`==`), `show`, and `read` for `Lists`

## Examples

```
ghci> Nil == Cons 1 Nil  
False  
ghci> show (Cons 1 (Cons 2 Nil))  
"Cons_1_(Cons_2_Nil)"  
ghci> read it :: List Int  
Cons 1 (Cons 2 Nil)
```

# Outline

1 Intermediate Wrap-Up

2 User-Defined Types

3 Trees

4 Input and Output

## Definition (tree)

- (rooted) tree  $T = (N, E)$



## Definition (tree)

- (rooted) tree  $T = (N, E)$
- with set of nodes/vertices  $N$

## Definition (tree)

- (rooted) tree  $T = (N, E)$
- with set of nodes/vertices  $N$
- and set of edges  $E \subseteq N \times N$

## Definition (tree)

- (rooted) tree  $T = (N, E)$
- with set of nodes/vertices  $N$
- and set of edges  $E \subseteq N \times N$
- unique root of  $T$  ( $\text{root}(T) \in N$ ) without predecessor

## Definition (tree)


- (rooted) tree  $T = (N, E)$
- with set of nodes/vertices  $N$
- and set of edges  $E \subseteq N \times N$
- unique root of  $T$  ( $root(T) \in N$ ) without predecessor
- all other nodes have exactly one predecessor

## Definition (tree)

- (rooted) tree  $T = (N, E)$
- with set of nodes/vertices  $N$
- and set of edges  $E \subseteq N \times N$
- unique root of  $T$  ( $root(T) \in N$ ) without predecessor
- all other nodes have exactly one predecessor

## Example

- $N = \{A, B, C, D, E, F, G\}$
- $E = \{(A, B), (A, C), (A, E), (C, D), (E, F), (E, G)\}$
- $root(T) = A$
- $T =$



## Trees in Haskell

- possible type for trees with arbitrary nodes  
`data Tree a = Empty | Node a [Tree a]`
- a tree is either empty (0 nodes) or there is at least one node with content of type `a` and an arbitrary number of successor trees

## Examples

Empty

1  
Node 1 []

1  
|  
2  
Node 1 [Node 2 []]

1  
/ \  
2 3  
Node 1 [Node 2 [], Node 3 []]

## Binary Trees

- restrict number of successors (maximum 2)
- type

```
data BTree a = Empty | Node a (BTree a) (BTree a)
  deriving (Eq, Show, Read)
```

## Binary Trees

- restrict number of successors (maximum 2)
- type

```
data BTree a = Empty | Node a (BTree a) (BTree a)
  deriving (Eq, Show, Read)
```

## Functions on Binary Trees

- size – number of nodes

```
size :: BTree a -> Integer
size Empty      = 0
size (Node _ l r) = size l + size r + 1
```



## Binary Trees

- restrict number of successors (maximum 2)
- type

```
data BTree a = Empty | Node a (BTree a) (BTree a)
  deriving (Eq, Show, Read)
```

## Functions on Binary Trees

- size – number of nodes
- height – length of longest path from root to some leaf

```
size :: BTree a -> Integer
size Empty      = 0
size (Node _ l r) = size l + size r + 1

height :: BTree a -> Integer
height Empty    = 0
height (Node _ l r) = max (height l) (height r) + 1
```

## Creating Trees from Lists

- the easy way

```
fromList []      = Empty
fromList (x:xs) = Node x Empty (fromList xs)
```

## Creating Trees from Lists

- the easy way

```
fromList [] = Empty
fromList (x:xs) = Node x Empty (fromList xs)
```

- the balanced way

```
make [] = Empty
make xs = Node z (make ys) (make zs)
  where
    m      = length xs `div` 2
    (ys, z:zs) = splitAt m xs
```

## Creating Trees from Lists

- the easy way

```
fromList [] = Empty
fromList (x:xs) = Node x Empty (fromList xs)
```

- the balanced way

```
make [] = Empty
make xs = Node z (make ys) (make zs)
  where
    m = length xs `div` 2
    (ys, z:zs) = splitAt m xs
```

- the orderly way

```
searchTree = foldr insert Empty
  where
    insert x Empty = Node x Empty Empty
    insert x (Node y l r)
      | x < y = Node y (insert x l) r
      | otherwise = Node y l (insert x r)
```

## Transforming Trees into Lists

```
flatten Empty      = []  
flatten (Node x l r) = flatten l ++ [x] ++ flatten r
```

## Example (a sorting algorithm for lists)

```
sort = flatten . searchTree
```

# Outline

1 Intermediate Wrap-Up

2 User-Defined Types

3 Trees

4 Input and Output

## Example

- write the file `welcomeIO.hs`

```
main = do
  putStrLn "Greetings! What's your name?"
  name <- getLine
  putStrLn (
    "Welcome to Haskell's IO, " ++ name ++ "!"
```

- compile it with GHC via
- and run it

## Example

- write the file `welcomeIO.hs`

```
main = do
  putStrLn "Greetings! What's your name?"
  name <- getLine
  putStrLn (
    "Welcome to Haskell's IO, " ++ name ++ "!"
```

- compile it with GHC via
- and run it

## Remark

- `putStrLn` – prints string followed by newline
- `getLine` – reads line from standard input
- new syntax: `do` and `<-`



## IO and the Type System

- consider

```
ghci> :load welcomeIO.hs
ghci> :t putStrLn
putStrLn :: String -> IO ()
ghci> :t getLine
getLine :: IO String
ghci> :t main
main :: IO ()
```

## IO and the Type System

- consider

```
ghci> :load welcomeIO.hs
ghci> :t putStrLn
putStrLn :: String -> IO ()
ghci> :t getLine
getLine :: IO String
ghci> :t main
main :: IO ()
```

- IO** **a** is type of IO actions delivering results of type **a** (in addition to their IO operations)

## IO and the Type System

- consider

```
ghci> :load welcomeIO.hs
ghci> :t putStrLn
putStrLn :: String -> IO ()
ghci> :t getLine
getLine :: IO String
ghci> :t main
main :: IO ()
```
- IO a** is type of IO actions delivering results of type **a** (in addition to their IO operations)

## Examples

- String -> IO ()** – after supplying a string, we obtain an IO action (in case of **putStrLn**, “printing”)
- IO ()** – just IO (in case of **main**, run our program)
- IO String** – do some IO and deliver a string (in case of **getLine**, user-input)

## Further Notes

- IO actions (everything of type `IO a`) are just descriptions of what should be done; nothing is actually done at time of specification

## Further Notes

- IO actions (everything of type `IO a`) are just descriptions of what should be done; nothing is actually done at time of specification
- inside IO actions, order is important; IO actions are executed in order of appearance (once execution starts); result of sequence of IO actions is result of `last` action

## Further Notes

- IO actions (everything of type `IO a`) are just descriptions of what should be done; nothing is actually done at time of specification
- inside IO actions, order is important; IO actions are executed in order of appearance (once execution starts); result of sequence of IO actions is result of last action
- inside IO actions, `x <- action` (where `action :: IO a`) may be used to bind result of `action` (which has type `a`) to name `x` (but seriously, this is actually only done, once execution starts)

## Further Notes

- IO actions (everything of type `IO a`) are just descriptions of what should be done; nothing is actually done at time of specification
- inside IO actions, order is important; IO actions are executed in order of appearance (once execution starts); result of sequence of IO actions is result of last action
- inside IO actions, `x <- action` (where `action :: IO a`) may be used to bind result of `action` (which has type `a`) to name `x` (but seriously, this is actually only done, once execution starts)
- `x <- a` is not available outside IO actions

## Further Notes

- IO actions (everything of type `IO a`) are just descriptions of what should be done; nothing is actually done at time of specification
- inside IO actions, order is important; IO actions are executed in order of appearance (once execution starts); result of sequence of IO actions is result of last action
- inside IO actions, `x <- action` (where `action :: IO a`) may be used to bind result of `action` (which has type `a`) to name `x` (but seriously, this is actually only done, once execution starts)
- `x <- a` is not available outside IO actions

## Implications

- once we are inside an IO action, we cannot escape
- strict separation between purely functional code and IO
- when `IO a` does not appear inside type signature, we can be absolutely sure that no IO (“side-effect”) is performed



## Using Pure Code Inside IO Actions

- consider program `reply.hs`

```
reply :: String -> String
reply name =
  "Pleased to meet you, " ++ name ++ ".\n" ++
  "Your name contains " ++ n ++ " characters."
  where
    n = show $ length name

main :: IO ()
main = do
  putStrLn "Greetings again. What's your name?"
  name <- getLine
  let niceReply = reply name
  putStrLn niceReply
```

## Using Pure Code Inside IO Actions

- consider program `reply.hs`

```
reply :: String -> String
reply name =
  "Pleased to meet you, " ++ name ++ ".\n" ++
  "Your name contains " ++ n ++ " characters."
  where
    n = show $ length name

main :: IO ()
main = do
  putStrLn "Greetings again. What's your name?"
  name <- getLine
  let niceReply = reply name
  putStrLn niceReply
```

- that is, we may use `let x = e` (there is no `in` here!) to bind result of pure expression `e` to name `x`

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin



## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin
- `getLine :: IO String` – read line (excluding newline)

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin
- `getLine :: IO String` – read line (excluding newline)
- `interact :: (String -> String) -> IO ()` – use function that gets input as string and produces output as string

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin
- `getLine :: IO String` – read line (excluding newline)
- `interact :: (String -> String) -> IO ()` – use function that gets input as string and produces output as string
- `type FilePath = String`

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin
- `getLine :: IO String` – read line (excluding newline)
- `interact :: (String -> String) -> IO ()` – use function that gets input as string and produces output as string
- `type FilePath = String`
- `readFile :: FilePath -> IO String` – read file content

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin
- `getLine :: IO String` – read line (excluding newline)
- `interact :: (String -> String) -> IO ()` – use function that gets input as string and produces output as string
- `type FilePath = String`
- `readFile :: FilePath -> IO String` – read file content
- `writeFile :: FilePath -> String -> IO ()`

## Some Simple IO Functions

- `return :: a -> IO a` – turn anything into an IO action
- `System.Environment.getArgs :: IO [String]` – get command line arguments
- `putChar :: Char -> IO ()` – print character
- `putStr :: String -> IO ()` – print string
- `putStrLn :: String -> IO ()` – print string followed by newline
- `getChar :: IO Char` – read single character from stdin
- `getLine :: IO String` – read line (excluding newline)
- `interact :: (String -> String) -> IO ()` – use function that gets input as string and produces output as string
- `type FilePath = String`
- `readFile :: FilePath -> IO String` – read file content
- `writeFile :: FilePath -> String -> IO ()`
- `appendFile :: FilePath -> String -> IO ()`

## Examples (imitating some GNU commands)

- `cat.hs` – print file contents

```
main = do
  [file] <- getArgs
  s <- readFile file
  putStr s
```

## Examples (imitating some GNU commands)

- `cat.hs` – print file contents

```
main = do
  [file] <- getArgs
  s <- readFile file
  putStr s
```

- `wc.hs` – count newlines/words/characters in input

```
count s = ns ++ " " ++ ws ++ " " ++ bs ++ "\n"
  where ns = show $ length $ lines s
        ws = show $ length $ words s
        bs = show $ length s

main = interact count
```



## Examples (imitating some GNU commands)

- `cat.hs` – print file contents

```
main = do
  [file] <- getArgs
  s <- readFile file
  putStr s
```

- `wc.hs` – count newlines/words/characters in input

```
count s = ns ++ " " ++ ws ++ " " ++ bs ++ "\n"
  where ns = show $ length $ lines s
        ws = show $ length $ words s
        bs = show $ length s
```

```
main = interact count
```

- `uniq.hs` – omit repeated lines of input

```
main = interact (nub)
```

## Examples (imitating some GNU commands)

- `cat.hs` – print file contents

```
main = do
  [file] <- getArgs
  s <- readFile file
  putStr s
```

- `wc.hs` – count newlines/words/characters in input

```
count s = ns ++ " " ++ ws ++ " " ++ bs ++ "\n"
  where ns = show $ length $ lines s
        ws = show $ length $ words s
        bs = show $ length s
```

```
main = interact count
```

- `uniq.hs` – omit repeated lines of input

```
main = interact (nub)
```

- `sort.hs` – sort input lines

```
main = interact (sort)
```

## Remark

- `getArgs :: IO [String]` is in `System.Environment`
- `nub :: Eq a => [a] -> [a]` is in `Data.List`; eliminates duplicates
- `sort :: Ord a => [a] -> [a]` is in `Data.List`; sorts a list

## Remark

- `getArgs :: IO [String]` is in `System.Environment`
- `nub :: Eq a => [a] -> [a]` is in `Data.List`; eliminates duplicates
- `sort :: Ord a => [a] -> [a]` is in `Data.List`; sorts a list

## Remark

- `getArgs :: IO [String]` is in `System.Environment`
- `nub :: Eq a => [a] -> [a]` is in `Data.List`; eliminates duplicates
- `sort :: Ord a => [a] -> [a]` is in `Data.List`; sorts a list

## Examples (do some IO action for each argument)

- ```
foreach :: [a] -> (a -> IO ()) -> IO ()  
foreach []      io = return ()  
foreach (a:as) io = do { io a; foreach as io }
```

## Remark

- `getArgs :: IO [String]` is in `System.Environment`
- `nub :: Eq a => [a] -> [a]` is in `Data.List`; eliminates duplicates
- `sort :: Ord a => [a] -> [a]` is in `Data.List`; sorts a list

## Examples (do some IO action for each argument)

- ```
foreach :: [a] -> (a -> IO ()) -> IO ()  
foreach []      io = return ()  
foreach (a:as) io = do { io a; foreach as io }
```
- better `cat.hs`  

```
main = do  
  files <- getArgs  
  if null files then interact id else do  
    foreach files readAndPrint  
    where readAndPrint file = do  
      s <- readFile file  
      putStr s
```

Thanks! & Questions?